



FLOOR PLAN

SCALE: 1/4" = 1'-0" 2

KEY	DESCRIPTION	CODE	REF./SHT.	KEY	DESCRIPTION	CODE	REF./SHT.	KEY	DESCRIPTION	CODE	REF./SHT.
1	LEASE LINE			13	GC BUILT WALL WITH GC INSTALLED RECESSED 2X MTL STANDARDS SPACED AT 23.5" O.C. & WOOD SHELVING, CENTER BETWEEN FEATURE WALLS, U.N.O.	A6-0		25	(E) COLUMN TO REMAIN. PAINT [P19-SG]		
2	EXISTING DEMISING WALL, GC TO MAINTAIN EXISTING FIRE RATING			14	WB-8] WALL FINISH AT PASS THRU			26	GC TO ARDEX FLOOR AS REQUIRED TO CREATE LEVEL FLOOR		
3	(E) ENTRY DOORS TO REMAIN			15	EXISTING CONCRETE SLAB. BEAD BLAST & SEAL	CO-1		27	GC TO PROVIDE ATHLETA NAME AND SPACE NUMBER AT EXTERIOR SIDE OF REAR DOOR		
4	GC TO INFILL DEMISING WALL AS REQUIRED. MATCH FINISHES & FIRE RATING OF (E) DEMISING WALL			16	METAL TRANSITION STRIP BETWEEN VCT FLOORING & TILE FLOORING			28	GC TO PROVIDE (N) GYP. BOARD FINISHES BELOW STOREFRONT. PAINT [P1-EG]		
5	CLEAR UV/GRAFFITI FILM AT EXTERIOR OF STOREFRONT GLAZING	FLM-5		17	METAL TRANSITION STRIP BETWEEN VCT FLOORING & CORRIDOR MAT @ ENTRY	3/A0-1.1		29	2X4 STUD WALL. REFER TO 8-0.		
6	(E) STOREFRONT TO REMAIN.	2/A4-0		18	METAL TRANSITION STRIP BETWEEN VCT FLOORING & CONCRETE	1/A0-1.1		30	DOUBLE 2X4 STUD WALL. REFER TO A6-0 & 8-0		
7	EAS FINS; ONE ONE EACH SIDE OF ENTRY DOOR FRAME. SEE ELECTRICAL.	EAS-1	1/A4-0	19	WOOD BASE [B5] IN SALES PROVIDED BY VENDOR AND INSTALLED BY GC	B-5		31	GC TO POOR ARDEX TO LEVEL THE FLOOR FINISHES - 1/4" MIN. SLOPE		
8	FEATURE WALL WOOD FRAMES	4/A6-0		20	16" SHELF, PROVIDED BY OWNER			32	GC TO USE 1/2" ADA THRESHOLD	2/A0-1.1	
9	FITTING ROOM	A6-2		21	24" SHELF, PROVIDED BY OWNER			33	GC TO USE 1/2" ADA THRESHOLD	9/A0-1.1	
10	WOOD BASE [B2] BY GC WITH [B2] & 1X TRIM AT FITTING AREA (OUTER & INNER CONDITIONS) & CORRIDOR; GC TO SAND ALL TRIM & BASEBOARDS PRIOR TO PAINTING	B2		22	VERTICALLY MOUNTED TRACK LIGHT. INSTALL ON SIDE OF WINDOW OPENING ALONG FULL HEIGHT OF STOREFRONT GLAZING	A5-1 / A4-1		34	RECESSED 160X W/ FACE PLATE. REFER TO ELECTRICAL DWGS. CENTER WITH CASH WRAP		
11	FAUX WOOD SOFFIT ABOVE. [WB-3 CUSTOM] [WB-4 CUSTOM]			23	EXPOSED MASONRY AT (E) EXTERIOR WALL			35	GC TO USE 1/2" ADA THRESHOLD		
12	GC BUILT WALL WITHOUT STANDARDS	1/A6-0		24	(E) STAIRS, HANDRAILS & FINISHES TO REMAIN			36			

TYPE	DESCRIPTION
[Symbol]	EXISTING WALL
[Symbol]	GC BUILT WALL
[Symbol]	FURRED OUT WALL BY GC

WALL HATCH LEGEND

- SEE G0-2 FOR RESPONSIBILITY MATRIX AND FINISH SCHEDULE INFORMATION.
- ALL DIMENSIONS ARE FACE OF FINISH TO FACE OF FINISH UNLESS OTHERWISE NOTED.
- SEE G0-2.2 FOR WALL TYPE INFORMATION.

KEYNOTES 3 GENERAL NOTES 1