





**CONSTRUCTION KEY**

- SOFFIT OR CEILING FEATURE ABOVE PLAN LOCATION. SEE REFLECTED CLG PLAN
- NEW WALLS 3 5/8" MTL STUD W/ 5/8" GWB EACH SIDE. PROVIDE SOUND BATT INSULATION ALL WALLS. ALL WALLS TO BE FROM FLOOR TO FLOOR DECK ABOVE W/ ACOUSTICAL CAULK TOP AND BOTTOM
- WALL WITH INTERIOR HIGH GLAZING IN SHEETROCK OPENING. SEE WALL TYPE C ON SHEET A-401. DETERMINE LENGTHS IN FIELD TYP
- FEK FIRE EXTINGUISHER W/ CABINET
- WALL TYPE. SEE A-401 FOR SECTIONS
- WALL WITH NEW DOOR AND DOOR INFO TAG. SEE DOOR SCHEDULE
- KEY TO INTERIOR ELEVATIONS WITH DETAIL AND SHEET NO. NORTH IS PLAN NORTH (to top of sheet).
- OFFICE SPACE NAME TAG AND NUMBER SEE FINISH SCHEDULE
- CARPET TRANSITION TO OTHER MATERIAL OR CHANGES IN CARPET TYPE



1 SECOND FLOOR PLAN  
Scale: 1/8" = 1'-0"



**GENERAL NOTES:**

- 1.) ALL DIMENSIONS ARE TO FACE OF FINISH SURFACE. WALLS ARE 3 5/8" MTL STUD W/ 5/8" GWB EACH SIDE UNLESS NOTED OTHERWISE. SEE NOTE #3.
- 2.) PROVIDE NEW CARPET AND PAINT ALL WALLS WITHIN THE AREA OF WORK. SEE FINISH SCHEDULE FOR ADDITIONAL FINISH WORK IN NEW SPACES.
- 3.) WHERE REQUIRED, ALIGN ALL NEW WALLS SUCH THAT GWB IS FLUSH WITH EXISTING SURFACES. VERIFY EXISTING WALL THICKNESS AT ALL LOCATIONS WHERE NEW WALLS ALIGN WITH EXISTING. ADJUST NEW WALL THICKNESS TO MATCH EXISTING IF REQUIRED. CONFIRM ALL DOOR FRAME DIMENSIONS FOR DOORS WHERE EXISTING WALL THICKNESS IS TO BE MATCHED BY NEW WALL AND DOOR OR WHERE NEW DOORS ARE BEING INSTALLED IN EXISTING WALLS.
- 4.) ALL DOOR FRAMES ARE 4" FROM INSIDE CORNER OF ANY ADJACENT INTERSECTING WALL U.N.O.
- 5.) PROVIDE ALL NECESSARY POWER, LIGHTING, PLUMBING, HVAC, SPRINKLER AND LIFE SAFETY MODIFICATIONS REQUIRED FOR NEW CONSTRUCTION. MODIFY EXISTING SERVICE TO ACCOMMODATE NEW CONSTRUCTION. COORDINATE WITH BUILDING MANAGEMENT FOR MODIFICATIONS TO EXISTING BUILDING SYSTEMS. PROVIDE ALL NEW INSTALLATIONS TO BUILDING STANDARD UNLESS NOTED OTHERWISE. SEE ELEC PLAN FOR POWER REQUIREMENTS FOR EQUIPMENT AND COUNTER LOCATIONS.
- 6.) PROVIDE ALL NECESSARY ADA LIFE SAFETY DEVICES. PROVIDE OR RELOCATE FIRE PULL STATIONS AND FIRE EXTINGUISHERS PER CODE REQUIREMENTS.
- 7.) SECURE ALL NECESSARY CONSTRUCTION PERMITS FROM LOCAL AND STATE AGENCIES.
- 8.) COORDINATE WITH OWNER FOR ALL APPLIANCES SHOWN PRIOR TO CASEWORK FABRICATION. ALL APPLIANCES TO BE SELECTED AND PURCHASED BY OWNER AND INSTALLED BY CONTRACTOR.
- 9.) SEE IT, AVV AND SECURITY REQUIREMENTS FOR PLYWOOD BLOCKING REQUIREMENTS.
- 10.) SEE FINISH SCHEDULE FOR NEW FINISHES. ALL NEW AND EXISTING SPACES TO BE PAINTED.
- 11.) ALL COMPASS DIRECTIONS REFER TO PLAN NORTH (UP SHEET) NOT TRUE NORTH.



Date	4/2/14
Revision	
Project ID	2014003
Drawing Code	
Scale	100 middle st 2nd east
Plot Date	4-2-14

Designed By	rh
Drawn By	
Checked By	
Reviewed By	
Submitted By	
Project Manager	

Design Firm: **HKTA/architects**  
482 Congress Street  
Portland, Maine 04101

Project Title: **BERRY DUNN McNEIL PARKER**  
Second Floor  
100 Middle Street  
Portland, Maine

Drawing Title: **Floor Plan  
Second Floor Office Layout**

Scale: Sheet Scale

Drawing No.: **A-101**  
of  
8 Total Sheets

*HKTA / architects*  
482 Congress Street Suite 502  
Portland, Maine 04101  
phone: 207. 774. 6016  
fax: 207. 774. 9128  
email: hktain@maine.rr.com