Location of Construction: Owner: 100 Middle St Hiddle St Official		Phone			Permit Ng: 70952
Owner Address:	Lessee/Buyer's Name:	Phone:	Busines		PERMIT ISSUED
Contractor Name: Alliance Const	Address:	Bill McQue			Permit Issued:
Past Use:	Proposed Use:	COST OF WOR \$ 336,669		PERMIT FEE: \$ 1,700.00	CITY OF PORTLAND
Office	Samie	10	Denied	INSPECTION: Use Group: Type:	Zone: CBL: 029-E-026-
Proposed Project Description:		PEDESTRIAN A Action:	CTIVITII Approved	Signature: S DISTRICT (P.A.D.) with Conditions: E	□ Shoreland
Permit Taken By: Fary Greatk	Date Applied For:	Signature: 28 August 1997		Date:	□ Subdivision □ Site Plan maj □minor □mm □
 This permit application does not preclude the Building permits do not include plumbing, s Building permits are void if work is not start tion may invalidate a building permit and st RAIL: Liberty Management 100 Middle St (5th fl ear Portland, NR 04101 	eptic or electrical work. ed within six (6) months of the date of op all work	le State and Federal rules.	4000 325	PERMIT ISSUED REQUIRENTED	Zoning Appeal
I hereby certify that I am the owner of record of th authorized by the owner to make this application if a permit for work described in the application is areas covered by such permit at any reasonable h	as his authorized agent and I agree t s issued, I certify that the code offici our to enforce the provisions of the	to conform to all applicable al's authorized representati	e laws of th ve shall ha permit	is jurisdiction. In addition	, Denied
RESPONSIBLE PERSON IN CHARGE OF WOR			blic File	PHONE:	

City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

				4/25/48
				Completed
Type Foundation: Framing: Plumbing: Final: Other:				COMMENTS
Inspection Record Date			- Color	to office ,

BUILDING PERMIT REPORT

	DATE:	S[3]97] ADDRESS: 100 Middle St 5th EST
	REASC	NFOR PERMIT: renew tions
	BUILD	INGOWNER: Middle St OFFICE tour
	CONTI	Alliques Construction
	PERMI	TAPPLICANT: Beb Dickerico APPROVAL: *17×18 ×19×20×21×22 DENTED
		*26, +28, +29.
		CONDITION(S) OF APPROVAL
¥		This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
	2.	Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)

- Precaution must be taken to protect concrete from freezing.
- 4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 5. Private garages located <u>beneath habitable rooms</u> in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
- 6. All chinneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993) U.L. 103.
- 7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
- 8. Guardrail & Handrails A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, 11-4, 1-1, 1-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
- 9. Headroom in habitable space is a minimum of 7'6".
- Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread, 7" maximum rise.
- 11. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
- 12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a numinimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
- 13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
- 14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's.
- 15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
- 16. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC priman power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and

I-I shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

- A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- The Fire Alarm System shall be maintained to NFPA #72 Standard.
- The Sprinkler System shall maintained to NFPA #13 Standard.
- 17. 18/27/20. 21 All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- No construction or demolition work shall begin until you have obtained permits for dumpsters or containers. A work Stop Order shall be issued if this requirement is not met.
- 22. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 23. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Titles MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.

.

- This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office. 24.
- 25. (26.) (27.) Ventilation shall meet the requirements of Chapter 12 Sections 1210, of the City's Building Code,
 - All electrical and plumbing permits must be obtained by a Master Licensed holders of their trade.

3

- All requirements must be met before a finial Certificate of Occupancy is issued
- (28 Marshall terte 1-150 4 () () (rrall.
- 29 Mus or remane Cap 1201

Stat

01

- P. Samuel Hoffses, Chief of Code Enforcement
- cc: Lt. McDougall, PFD Marge Schmuckal



CITY OF PORTLAND, MAINE Department of Building Inspection **Certificate of Pecupancy**

LOCATION 100 Middle Street

Issued to Liberty Management

Date of Issue 4/28/98

This is to certify that the building, premises, or part thereof, at the above location, built — altered — changed as to use under Building Permit No.970952 , has had final inspection, has been found to conform substantially to requirements of Zoning Ordinance and Building Code of the City, and is hereby approved for occupancy or use, limited or otherwise, as indicated below.

PORTION OF BUILDING OR PREMISES

APPROVED OCCUPANCY

5th floor, east tower

office to office space

Limiting Conditions:

This certificate supersedes certificate issued

Approved:

(Date)

Inspector

Inspector of Buildings

Notice: This certificate identifies lawful use of building or premises, and ought to be transferred from owner to owner when property changes hands. Copy will be furnished to owner or lessee for one dollar.