City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction:	Owner:	L Assec.	Phone:	772-8896	Permit No: 9 81243
Owner Address:	Lessee/Buyer's Name:	Phone:	Business	Name:	PERMIT ISSUED
Contractor Name: Liberty Haragement Atta: Bill Past Use: Office	Address: **CHURE 100 Maddle 51 ** Proposed Use: Same	COST OF WOR FIRE DEPT.	K:	PERMIT FEE: \$ 250,00 INSPECTION: Use Group: Type:	Permit Issued: OCT 3 0 1998 CITY OF PORTLAND
Proposed Project Description: **Rake Interior Renovations** 2nd		Signature: PEDESTRIAN A Action:	CTIVITIES Approved	Signature: S DISTRICT (P.A.D.) ith Conditions: Date:	□ Special Zone or Reviews: □ Shoreland □ Wetland □ Flood Zone □ Subdivision
Permit Taken By: 1. This permit application does not preclude the A 2. Building permits do not include plumbing, se 3. Building permits are void if work is not started tion may invalidate a building permit and stop	ptic or electrical work. within six (6) months of the date of		1998		☐ Site Plan maj ☐minor ☐mm ☐ Zoning Appeal ☐ Variance ☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied
I hereby certify that I am the owner of record of the	CERTIFICATION			ISSUED JIREMENTS	Historic Preservation Not in District or Landmark Does Not Require Review Requires Review Action: Approved Approved With Conditions
authorized by the owner to make this application a if a permit for work described in the application is areas covered by such permit at any reasonable ho	s his authorized agent and I agree to issued, I certify that the code official	o conform to all applicable d's authorized representat	e laws of thi ive shall hav permit	s jurisdiction. In additi	on, Denied
RESPONSIBLE PERSON IN CHARGE OF WORK	K, TITLE			PHONE:	CEO DISTRICT

		113/99 Carplital and B. M. M.
Type Type Foundation: Framing: Plumbing: Final: Other:		McKust M

BUILDING PERMIT REPORT

BUILDING OWNER: Middle & Tower CONTRACTOR: Librity Mgt. PERMIT APPLICANT:	
PERMIT APPLICANT:	
PERMIT APPLICANT:	
	YPE / f)
HISE CROUP B ROCA 1996 CONSTRUCTION T	YPE / f)
BOCA 1770 CONSTRUCTION I	
CONDITION(S) OF APPROVAL	
This Permit is being issued with the understanding that the following conditions are	met:
Approved with the following conditions: */, */7 *18, *19, *20, * 30, *3	
1. This permit does not excuse the applicant from meeting applicable State and Fe	deral rules and laws.
 Before concrete for foundation is placed, approvals from the Development Reviewmust be obtained. (A 24 hour notice is required prior to inspection) 	ew Coordinator and Inspection Services
Foundation drain shall be placed around the perimeter of a foundation that cons	ists of gravel or crushed stone containing
not more than 10 percent material that passes through a No. 4 sieve. The drain	shall extend a minimum of 12 inches
beyond the outside edge of the footing. The thickness shall be such that the bott	
bottom of the base under the floor, and that the top of the drain is not less than 6 top of the drain shall be covered with an approved filter membrane material. W	
the invert of the pipe or tile shall not be higher than the floor elevation. The top	
protected with an approved filter membrane material. The pipe or tile shall be p	
crushed stone, and shall be covered with not less than 6" of the same material. S	
2.6 Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundar	tion wall, minimum of 12" from corners of
foundation and a maximum 6 'o.c. between bolts. (Section 2305.17)	
Precaution must be taken to protect concrete from freezing. Section 1908.0 It is strongly recommended that a registered land surveyor check all foundation	forms before concrete is placed. This is
 It is strongly recommended that a registered land surveyor check all foundation done to verify that the proper setbacks are maintained. 	forms before concrete is placed. This is
5. Private garages located <u>beneath habitable rooms</u> in occupancies in Use Group R-	-1, R-2, R-3 or I-1 shall be separated from
adjacent interior spaces by fire partitions and floor/ceiling assembly which are corresisting rating. Private garages attached side-by-side to rooms in the above occ the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 2)	onstructed with not less than 1-hour fire upancies shall be completely separated from μ uivalent applied to the garage means of $\frac{1}{2}$
All chimneys and vents shall be installed and maintained as per Chapter 12 of the National Mechanical Code/1993). Chapter 12 & NFPA 211	
 Sound transmission control in residential building shall be done in accordance we building code. 	with Chapter 12 section 1214.0 of the city's
3. Guardrails & Handrails: A guardrail system is a system of building components	
walking surfaces for the purpose of minimizing the possibility of an accidental fa	all from the walking surface to the lower
level. Minimum height all Use Groups 42", except Use Group R which is 36".	In occupancies in Use Group A, B, H-4, I-
I, I-2 M and R and public garages and open parking structures, open guards shat that a sphere with a diameter of 4" cannot pass through any opening. Guards sha	all not have an organizate pattern that
would provide a ladder effect. (Handrails shall be a minimum of 34" but not mo	re than 38". Use Group R-3 shall not be
less than 30", but not more than 38".) Handrail grip size shall have a circular cr	oss section with an outside diameter of at
least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall t	be on both sides of stairway. (Section
1014.7)	
Headroom in habitable space is a minimum of 7'6". (Section 1204.0) Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4"	maximum rise. All other Use group
 Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" minimum 11" tread. 7" maximum rise. (Section 1014.0) 	maximum rise. An other ose group
The minimum headroom in all parts of a stairway shall not be less than 80 inches	(6' 9") 1011 1

11.

- Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508min), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)
- 13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. Section 1010.1
- 14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) Section 710.0
- 15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment. Table 302.1.1
- All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Sinoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2

- A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. Section 921.0

 The Fire Alarm System shall be maintained to NFPA #72 Standard.
 - The Sprinkler System shall maintained to NFPA #13 Standard.
 All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
 - 21. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
 - 22. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
 - 23. Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code. (crawl spaces & attics)
 - 24. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
 - 25. All requirements must be met before a final Certificate of Occupancy is issued.
- All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
- 27. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
- 28. Please read and implement the attached Land Use-Zoning report requirements.
- 29. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.3. of the City's building code.

0.	Glass and glazing shall meet the requirements of Chapter 24 of the building code. This building is Type IA Construction NO Combustible can be
Ι.	This building is Type 1A Construction NO Combustible can be
	used in building materials
2	

P. Samuel Hoffses, Building Inspector

cc: Lt. McDougall, PFD

Marge Schniuckal, Zoning Administrator

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Attached Single Family Dwellings/Two-Family Dwelling Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Addressof Construction (include Portion of Building) :	100 MIDDLE ST. 2"D FLOOR	WEST TOWER B	
Total Square Footage of Proposed Structure 2,831	Square Footage of Lot		
Tax Assessor's Chart, Block & Lot Number Chart# 019 Block# £ Lot# 016 wi	OWNER: MIDDLE ST TOWER B A 100 MIDDLE STREET PURRIAND MAINE 04101	\$\$0C1478\$ Telephone#: 207 773 - 8886	
Owner's Address: MIDDLE ST. TOWLE B MISSEC. CO LIBERTY MANUACEMENT IN MIDDLE ST. PORTLAND, MAINE OYIOI	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee \$ 46,000 \$ 350	
Proposed Project Description:(Please be as specific as possible)	RENCIATION EXISTING OFFICES		
Contractor's Name, Address & Telephone LIBERTY MANAGEMENT - 41TW. BILL MILLUGH Rec'd By PUT LAND, ME 04101			
Current Use: Offict	Proposed Use: Offict		

Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation.

•All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II.
•All plumbing must be conducted in compliance with the State of Maine Plumbing Code.

All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III.
 HVAC(Heating, Ventililation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code.

You must Include the following with you application:

1) ACopy of Your Deed or Purchase and Sale Agreement 2) A Copy of your Construction Contract, if available

3) A Plot Plan/Site Plan

Minor or Major site plan review will be required for the above proposed projects. The attached checklist outlines the minimum standards for a site plan.

4) Building Plans
Unless exempted by State Law, construction documents must be designed by a registered design professional

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas
 equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant:	William 2 Mapl A	Date: 10/26/98

Building Permit Fee: \$25.00 for the 1st \$1000.cost plus \$5.00 per \$1,000.00 construction cost thereafter.

Additional Site review and related fees are attached on a separate addendum

BUILDING

OCT 2 6 1998