PLUMBING LEGEND	
SYMBOL	DESCRIPTION
WH	GAS FIRED VERTICAL TANK WATER HEATER
	OVAL UNDERCOUNTER MOUNTED LAVATORY MADE OF VITREOUS CHINA WITH CHROME-PLATED SINGLE LEVER ADA FAUCET WITH POP UP DRAIN
	INCOUNTER MOUNTED, SELF-RIMMING, SINGLE BOWL, STAINLESS STEEL BAR SINK WITH CHROME-PLATED BRASS, GOOSENECK SPOUT, SINGLE LEVER HANDLE FAUCET AND FITTINGS MEETING ADA REQUIREMENTS
	STAINLESS STEEL TRIPLE BOWL KITCHEN SINK WITH FAUCET, FITTINGS, DISPOSAL, AND DRAIN BOARDS.
	STAINLESS STEEL SINGLE BOWL WALL MOUNTED HAND WASH SINK WITH FAUCET AND FITTINGS.
	PRECAST TERRAZZO, FLOOR MOUNTED MOP SINK WITH WALL MOUNTED, SWIVEL SPOUT, LEVER HANDLE TYPE FAUCET WITH TOP BRACE AND INTEGRAL VACUUM BREAKER
	MOLDED POLYPROPYLENE, LEG MOUNTED UTILITY SINK WITH SWIVEL SPOUT, LEVER HANDLE TYPE FAUCET AND INTEGRAL VACUUM BREAKER
	1.6 GALLON TANK TYPE, FLOOR MOUNTED WATER CLOSET MADE OF VITREOUS CHINA WITH ELONGATED FRONT SIPHON JET BOWL AND SOLID PLASTIC SEAT WITH OPEN FRONT MEETING ADA REQUIREMENTS. PROVIDE LID AT GUESTROOMS. THE SEAT AND LID MUST REMAIN IN UPRIGHT POSITION WITHOUT BEING HELD.
	1.6 GALLON AUTO FLUSH VALVE TYPE, FLOOR MOUNTED WATER CLOSET MADE OF VITREOUS CHINA WITH ELONGATED FRONT SIPHON JET BOWL AND SOLID PLASTIC SEAT WITH OPEN FRONT MEETING ADA REQUIREMENTS
	DUAL HEIGHT, WALL MOUNTED STAINLESS STEEL WATER COOLER MEETING ADA REQUIREMENTS WITH CONCEALED COMPRESSOR UNIT
	30"x60" FIBERGLASS REINFORCED ACRYLIC RESIN ROLL-IN SHOWER STALL WITH A SLIP-RESISTANT, TEXTURED BOTTOM. PROVIDE SEAT, GRAB BARS AND SINGLE HANDLE MIXING VALVE AND SHOWER SPRAY UNIT WITH MIN. 60" LONG HOSE THAT CAN BE USED BOTH AS A FIXED HEAD AND AS A HAND-HELD SHOWER. SHOWER UNIT SHALL COMPLY WITH ICC/ANSI A117.1 AND ADA REQUIREMENTS.
	30"x60" FIBERGLASS REINFORCED ACRYLIC RESIN SHOWER BASE UNIT WITH SLIP-RESISTANT, TEXTURED BOTTOM, AND FULL HEIGHT GRANITE WALL SURROUND. PROVIDE SINGLE HANDLE MIXING VALVE AND ADJUSTABLE SHOWER HEAD.
	30"x60" ENAMELED STEEL, BATHTUB WITH SLIP-RESISTANT, TEXTURED BOTTOM AND FULL HEIGHT GRANITE WALL SURROUND. PROVIDE TUB SPOUT/SHOWER DIVERTER, SINGLE HANDLE MIXING VALVE AND ADJUSTABLE SHOWER HEAD.
	30"x60" ENAMELED STEEL, BATHTUB WITH SLIP-RESISTANT, TEXTURED BOTTOM AND FULL HEIGHT GRANITE WALL SURROUND. PROVIDE SEAT, GRAB BARS AND TUB SPOUT/SHOWER DIVERTER, SINGLE HANDLE MIXING VALVE AND SHOWER SPRAY UNIT WITH MIN. 60" LONG HOSE THAT CAN BE USED BOTH AS A FIXED HEAD AND AS A HAND-HELD SHOWER. BATHTUB UNIT SHALL COMPLY WITH ICC/ANSI A117.1 AND ADA REQUIREMENTS.

PLUMBING LEGEND	
SYMBOL	DESCRIPTION
	WASHER OUTLET BOX WITH DRAIN
HB	WALL HOSE BIBB (INTERIOR USE ONLY)
WH	FREEZE PROOF WALL KEYED WALL HYDRANT
G	GAS METER
W	WATER METER
	CLEANOUT. PROVIDE ACCESS COVER IN FINISHED AREAS
	SIAMESE FIRE DEPARTMENT HOSE CONNECTION
	SPRINKLER RISER
	SHUT-OFF VALVE
	SOIL WASTE (BELOW GRADE)
	SOIL WASTE (ABOVE GRADE)
	ROOF DRAIN LEADER (BELOW GRADE)
	ROOF DRAIN LEADER (ABOVE GRADE)
G	GAS PIPING

REVISION SCHEDULE

DATE	REVISION DESCRIPTION	BY

COPECHEE
CONSTRUCTION CORPORATION
11 CORPORATE DRIVE, BELMONT NH 03220
PHONE (603)527-9090 FAX (603)527-9191

SECOND FLOOR PLUMBING PLAN AND LEGEND

PROJECT:
Hotel, Restaurant, & Portside Residences
Portland ME

DATE: 06-15-10
SCALE: 1/8"=1'-0"
DRAWN BY: dwb
SHEET: P2

© COPYRIGHT 2010 BY O.C.C.