City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Location of Construction: Phone: Permit No Owner: 84 Middle St 80-90 Cerp Owner Address: Lessee/Buyer's Name: Phone: BusinessName: Granger Northern Permit issued: Address: Phone: Contractor Name: 774-3500 Granger Northern 51 Baxter Bivd Ptld. ME 04101 _ 4 1998 COST OF WORK: PERMIT FEE: Past Use: Proposed Use: \$ 75.000.00 395.00 FIRE DEPT. Approved INSPECTION: Office Same Use Group Type: 4 □ Denied CBL: 029-1-004 Zone: BUCHTUNI Signature: Signature: 🎢 🎶 Zoning Approval Proposed Project Description: IVITIES DISTRICT (PA.D.) PEDESTRIAN AC Approved Action: Approved with Conditions: ☐ Shoreland Interior Renovationes. 2nd floor Denied □ Wetland ☐ Flood Zone Signature: (4 □ Subdivision Date: ☐ Site Plan mai ☐minor ☐mm ☐ Permit Taken By: Date Applied For: Mary Gresik 25 February 1998 Zoning Appeal □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. 2. ☐ Conditional Use Building permits are void if work is not started within six (6) months of the date of issuance. False informa-□ Interpretation 3. □ Approved tion may invalidate a building permit and stop all work... □ Denied **Historic Preservation** □ Nøt in District or Landmark Does Not Require Review ☐ Requires Review Action: CERTIFICATION □ Appoved ☐ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been □ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit 25 February 1998 SIGNATURE OF APPLICANT DATE: PHONE: Bruce Eilfrank RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE: **CEO DISTRICT** White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

BUILDING PERMIT REPORT

DATE: 3/2/98 ADDRESS: 80-90 Middle DT	
REASON FOR PERMIT: renevition	
BUILDING OWNER: 86-90 ASSOCIATI	
CONTRACTOR: Granger Northern	
PERMIT APPLICANT: Box Hilbronk	
USE GROUP 13 BOCA 1996 CONSTRUCTION TYPE 3B	
CONDITION(S) OF APPROVAL	
This Permit is being Issued with the understanding that the following conditions are met:	
Approved with the following conditions: 4 × 17 18 19 30 24 26 27	
•	
 This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspecti 	ian Camilaaa muut ha
obtained. (A 24 hour notice is required prior to inspection)	on services musi be
3. Precaution must be taken to protect concrete from freezing.	
4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is place	ced. This is done to
verify that the proper setbacks are maintained.	
5. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be	
adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than	
rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separate	
spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of	½ inch gypsum
 board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. 	(The BOCA National
Mechanical Code/1993).	(The BOCA National
7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214	.0 of the city's
building code.	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
8. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides	
surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lo	
height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1,	
public garages and open parking structures, open guards shall have balusters or be of solid material such that	t a sphere with a
diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would pro (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but	not more than 38"
Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not great	
9. Headroom in habitable space is a minimum of 7'6".	
10. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other	Use group minimum
11" tread. 7" maximum rise.	
11. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8")	
12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one oper	
exterior door approved for emergency egress or rescue. The units must be operable from the inside without knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sil	
than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a n	
opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be	
and a minimum net clear opening of 5.7 sq. ft.	
13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is	s acceptable when it
exits directly from the apartment to the building exterior with no communications to other apartment units.	
14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including	fire doors with self
closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.)	

The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing

All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the

15.

16.

automatic extinguishment.

COMMENTS

	AMENTS			
3-17-98 Doing Demo wor's removing some in on 2nd Filor	K ()	John	Dweyer	
removing some in	terior	lv	ello de pa	titions.
on 2nd Filor				
		_		
3/15/2000 Completed. a. Nove				
<u> </u>	<u> </u>			-
				_
- 				
				
		_		
· · · · · · · · · · · · · · · · · · ·				
		<i>,</i>		
			Inspection Record	
		Туре	inspection Record	Date
	Foundation:			_
	Other:			

provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations): In the immediate vicinity of bedrooms In all bedrooms In each story within a dwelling unit, including basements In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. The Fire Alarm System shall be maintained to NFPA #72 Standard. The Sprinkler System shall maintained to NFPA #13 Standard. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996) Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year". The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services. Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. All requirements must be met before a final Certificate of Occupancy is issued. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996). Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). Please read and implement the attached Land Use-Zoning report requirements.

muel Houses, pade introcement

cc: Lt. McDougall, PFID Marge Schmuckal

21.

22.

23. **24.

25.

A26.

<u>J. 27.</u>

28.

29.

30.

31.

32.