City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction:	Owner:	Ph	ione:	Permit No:
Owner Address:	Lessee/Buyer's Name:		isinessName:	C00843
Contractions.	Lessee/Duyer's tvaille.	Thone.	isinessi vanie.	9900-0
Contractor Name:	Address:	Phone:		Permit Issued:
Raymond Dupuis		73	58-4001	A CONTRACTOR OF A CONTRACT
Past Use:	Proposed Use:	COST OF WORK: \$ 600.00 FIRE DEPT. Appro		29- N-2000 AUG-22000
				Zone: CBL:
Proposed Project Description:		Signature:	1	Zoning Approval:
Proposed Project Description:			TTIES DISTRICT (P.A.D.)	DI ton CHA
Stage for openil estertainmen	it.	Action: Appro Appro Denie	oved with Conditions:	□ Shoreland □ Wetland □ Flood Zone
And the second sec		Signature:	Date:	
Permit Taken By: Mike Nogent	Date Applied For:	July 27, 2000 66		
 This permit application does not preclude the A Building permits do not include plumbing, se Building permits are void if work is not started tion may invalidate a building permit and stop 	Zoning Appeal Variance Since S			
	CERTIFICATION			Action:
I hereby certify that I am the owner of record of the authorized by the owner to make this application a if a permit for work described in the application is areas covered by such permit at any reasonable ho	named property, or that the propose s his authorized agent and I agree t issued, I certify that the code officia	to conform to all applicable laws al's authorized representative sh	s of this jurisdiction. In addition, all have the authority to enter all	A ☐ Approved with Conditions ☐ Denied
		July 27, 2000		
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	PERMIT ISSUED
RESPONSIBLE PERSON IN CHARGE OF WORK	K. TITLE		PHONE: W	TH REQUIRENT
	rmit Desk Green-Assessor's	Canary–D.P.W. Pink–Public f		

	BUILDING PERMIT REPORT
DA	ATE: 27 July 2000 ADDRESS Cornor of Commercial Indig CBL:
RJ	EASON FOR PERMIT: Temp. STage
BI	JILDING OWNER: CITY OF For ILand
PF	RMIT APPLICANT: /CONTRACTOR Raymond Dupuis
US	SE GROUP: 4 CONSTRUCTION TYPE: 59 CONSTRUCTION COST: PERMIT FEES:
	e City's Adopted Building Code (The BOCA National Building code/1999 with City Amendments) e City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
	CONDITION(S) OF APPROVAL
Ть	is permit is being issued with the understanding that the following conditions are met: $\frac{\times 1}{27}$
1. 2. 3.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) " <u>ALL</u> LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING." Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and
4. 5.	shall be covered with not less than 6" of the same material. <u>Section 1813.5.2</u> Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. <u>Section 2305.17</u> Waterproofing and dampproofing shall be done in accordance with <u>Section 1813.0</u> of the building code.
6. 7.	Precaution must be taken to protect concrete from freezing. <u>Section 1908.0</u> It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
8.	Private garages located <u>beneath habitable rooms</u> in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. <u>Private garages attached side-by-side to rooms</u> in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)
	All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211
11.	Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", In occupancies in Use Group A,B.H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Exception: Handrails that form part of a guard shall have a height not less than 36" and not more than 42". Handrail grip size shall have a circular cross section with an outside diameter of at least 1 ¼" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7) Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
	Stair construction in <u>Use Group R-3 & R-4 is a minimum of 10" tread and 7 ½" maximum rise</u> . All other Use Group minimum 11" tread, 7' maximum rise. (Section 1014.0)
15.	The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4 Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as <u>means of egress or rescue</u> they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4) Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly
	from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1) All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's.
	(Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0) The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic

.

extinguishment. (Table 302.1.1)

- All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements
- 20. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- 21. The Fire Alarm System shall maintained to NFPA #72 Standard.
- 22. The Sprinkler System shall maintained to NFPA #13 Standard.
- 23. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1999)
- 24. Section 25 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- 26. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
- 27. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. <u>No closing in of walls until all</u> <u>electrical</u> (min. 72 hours notice) <u>and plumbing inspections have been done</u>.
- 28. All requirements must be met before a final Certificate of Occupancy is issued.
- 29. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building Code/1999).
- Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical Code/1993). (Chapter M-16)
- 31. Please read and implement the attached Land Use Zoning report requirements.
- 32. Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code.
- 33. Bridging shall comply with Section 2305.16.
- 34. Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2405.0)

All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1995 20 under ho DO ses, Building Inspector McDougall, PFD Marge Schmuckal, Zoning Administrator 4114 PSH 11/25/99

**This Permit is herewith issued, on the basis of plans submitted and conditions placed the plans, any deviations shall require a separate approval.

***THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD.

**** Certificate of Occupancy Fees: \$50.00 each

***** All PLANS THAT REQUIRE A PROFESSIONAL DESIGN'S SEAL,(AS PER SECTION 114.0 OF THE BUILDING CODE) SHALL ALSO BE PRESENTED TO THIS DIVISION ON AUTO CAD LT. 2000 OR REQUIVALENT.

Form # P 04	DISPLAY					FRONTAGE	OF	
Please Read Application And Notes, If Any,					IG INSPEC			000843
Attached			/		ERMIT			
This is to certify	that	/	/	City o	f Portland			
has permission	to			Stage	for entertainm	ent		AUG - 2 2000
AT				Corner	of Commercial	& India St.		

provided that the person or persons, firm or corporation accepting this permit shall comply with all of the provisions of the Statutes of Maine and of the Ordinances of the City of Portland regulating the construction, maintenance and use of buildings and structures, and of the application on file in this department.

Apply to Public Works for street line and grade if nature of work requires such information.	Notification of inspection must be given and written permission procured before this building or part thereof is lathed or otherwise closed-in. 24 HOUR NOTICE IS REQUIRED.	A certificate of occupancy must be procured by owner before this build- ing or part thereof is occupied.
OTHER REQUIRED APPROVALS		PRMIT ISSUED
Health Dept.		A HAV
-		Hampfel MAS
Other Department Name		Director - Building & Inspector Services
	ENALTY FOR REMOVING THIS CAR	AD A