
City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction:	Owner:		Phone:	Permit No:
15 Franklin St	A&M Partners		874-6959	
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName:	
Contractor Name:	Address:	Phone	<u></u>	Permit Issued:
Southpaw Design	253 Gray Road, Falmout	h 8	78–0678	
Past Use:	Proposed Use:	COST OF WORK	E PERMIT FEE:	
		\$	\$31.40	
Ofc Bldg	Same w/sign	FIRE DEPT. 🗖 A		
			enied Use Group: Type:	Zone: CBL: 29-N-44
		Signature:	Signature:	
Proposed Project Description:			CTIVITIES DISTRICT (P.A.D.)	Zoning Approval:
				Special Zone of Reviews:
				□ Special Zone or Reviews: □ □ Shoreland
Erect sign (4x8) as per plans				□ □ Wetland
				□ Flood Zone
		Signature:	Date:	
Permit Taken By:	Date Applied For:			Site Plan maj 🗆 minor 🗆 mm 🗆
Vicki Dover	2/	10/98	· · · · · · · · · · · · · · · · · · ·	Zoning Appeal
1. This permit application does not preclude the	Applicant(s) from meeting applicable	State and Federal rules.		□Variance
2. Building permits do not include plumbing, se				
	Conditional Use			
3. Building permits are void if work is not starte tion may invalidate a building permit and sto				
tion may invalidate a banding perime and ste	p un work.			Denied
				Historic Preservation
				□Not in District or Landmark
	D / 11			Does Not Require Review
Call Jenny Winslow 878-0678 for			Requires Review	
				Action:
	CERTIFICATION			
I hereby certify that I am the owner of record of th		I work is authorized by th	e owner of record and that I have be	n Appoved with Conditions
authorized by the owner to make this application				
if a permit for work described in the application is				
areas covered by such permit at)any reasonable h	-	-	•	Date:
				-
1 VIMMAN /~ In V.M	1 25	2/20/00		
SIGNATURE OF APPLICANT	ADDRESS:	<u>2/10/98</u> DATE:	PHONE:	—
Jenny Winsl Southpaw De	ow sign			
RESPONSIBLE PERSON IN CHARGE OF WOR			PHONE:	
White-P	ermit Desk Green–Assessor's C	anary-D.P.W. Pink-Pu	blic File Ivory Card-Inspector	

-



STANUD /11 NAIS WARN, 8x, hx, 1 , 12 **公**》 8 **BYAITION CREVIAE OLEICE**

SIGNAGE

~

.

.

PLEASE ANSWER ALL QUESTIONS

ADDRESS: 15 FRANKLIN ST, PURT ZONE: B-3
OWNER: A + M PACINERS
APPLICANT: JENNY WINSLOW, SOUTHPAN DESIGN
ASSESSOR NO.:
SINGLE TENANT LOT? YES NO
MULTI TENANT LOT? YESNO
FREESTANDING SIGN? YESNO DIMENSIONS (ex. pole sign)
MORE THAN ONE SIGN? YESNODIMENSIONS
BLDG. WALL SIGN? YES NO DIMENSIONS 4 × 8 7 327) (attached to bldg)
MORE THAN ONE SIGN? YES NODIMENSIONS
LIST ALL EXISTING SIGNAGE AND THEIR DIMENSIONS: 1011-
LOT FRONTAGE (FEET)
BLDG FRONTAGE (FEET) $125' \times 2 = 7250F$
AWNING YES NO IS AWNING BACKLIT? YES NO
HEIGHT OF AWNING:
IS THERE ANY COMMUNICATION, MESSAGE, TRADEMARK OR SYMBOL ON IT? $()$
A SITE SKETCH AND BUILDING SKETCH SHOWING EXACTLY WHERE EXISTING AND NEW
SIGNAGE IS LOCATED MUST BE PROVIDED. SKETCHES AND/OR PICTURES OF THE
PROPOSED SIGNS ARE ALSO REQUIRED.

BI	U	ILD	IN	G	P	ER	\mathbf{M}	[T]	RE	P	0	R	r
----	---	-----	----	---	---	----	--------------	-----	----	---	---	---	---

DATE: 1/ MAV 98	ADDRESS:	5 Franklin ST	(2q-N-4)	
REASON FOR PERMIT: TO Cro				
BUILDING OWNER: ASM F	arThers		· · · · · · · · · · · · · · · · · · ·	
CONTRACTOR: SenThpan	Design			
PERMIT APPLICANT: Jenny	Winslaw			
USE GROUP <u>SIGN</u>	BOCA 1996	CONSTRUCTION TYPE	23	_
,	CONDITION(S) OF APPROVAL		

This Permit is being issued with the understanding that the following conditions are met:

Approved with the following conditions: $\frac{1}{2}$

- This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
 Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Section Secti
 - Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
 - 3. Precaution must be taken to protect concrete from freezing.
 - 4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
 - 5. Private garages located <u>beneath habitable rooms</u> in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
 - 6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993).
 - 7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
 - 8. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2".
 - 9. Headroom in habitable space is a minimum of 7'6".
 - 10. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise.
 - 11. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8")
 - 12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as <u>means of egress or rescue</u> they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
 - 13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
 - 14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.)
 - 15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
 - 16. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the