


DRAWINGS PRIOR TO ROUGH-IN.

PARTIAL POWER PLAN

**POWER KEYED NOTES** 

 $\boxed{1}$  -  $\boxed{5}$  NOT USED.

- 6 DESIGN LAB STATION. CONCEAL RECEPTACLES AND ASSOCIATED CONDUIT AND CABLING WITHIN CASEWORK. COORDINATE RECEPTACLE LOCATIONS WITH CASEWORK SHOP DRAWINGS AND WITH DETAILS.
- (7) GENERAL PURPOSE DUPLEX RECEPTACLE MOUNTED AT 18"
- (8) JUNCTION BOXES FOR CONDUIT FROM DESIGN LAB DESK AND PRINTER STATION. SEE CONDUIT DETAIL ON SHEET E-202 FOR
- 9 NOT USED.
- (10) AIPHONE WALL MOUNT INTERCOM AT 48" A.F.F.
- (11) PROVIDE SURFACE-MOUNTED RECEPTACLE ABOVE TOP WINDOW MULLION, MAXIMUM 18" ABOVE TOP MULLION.
- (12) PROVIDE FLUSH FLOOR BOX, LEGRAND EVOLUTION PRODUCTS, #6ATCPNK (COORDINATE COVERPLATE COLOR WITH ARCHITECT) AND NEMA 5-20R RECEPTACLE. SEE ARCHITECTURAL PLANS FOR EXACT LOCATIONS. THE FLOOR BOX COVERS SHOULD ALL BE OPENING IN THE SAME DIRECTION.
- (13) FOR DEVICE SHOWN, RUN 1/2" CONDUIT IN FLOOR UNDERLAYMENT SPACE. DO NOT RUN CONDUIT PARALLEL WITH WOOD FLOORING, COORDINATE CONDUIT ROUTING WITH FLOORING CONTRACTOR AND ARCHITECT PRIOR TO LAYOUT TO ACCOMMODATE CONDUIT CUT-OUTS IN PLYWOOD. SEE SPECIFICATION SECTION 3.02.B.5.
- (14) CONDUIT UNDER FLOOR SLAB.
- 15) PROVIDE A 20A, 1P MOTOR RATED SWITCH FOR WATER
- (6) MOUNT 35" A.F.F. TO BOTTOM OF HAND DRYER. COORDINATE EXACT LOCATION WITH ARCHITECTURAL ELEVATIONS PRIOR TO ROUGH-IN.
- (17) NOT USED.
- (18) FIRE ALARM DEVICE.
- (19) (23) NOT USED.
- 24 CHIME MOUNTED AT 96" A.F.F.
- 25 J-BOX FOR MOTORIZED DAMPER. COORDINATE WITH MECHANICAL CONTRACTOR FOR EXACT LOCATION.
- (26) J-BOX FOR SECURITY KEYPAD. COORDINATE EXACT LOCATION WITH G.C. PRIOR TO ROUGH-IN.
- 27 NOT USED.
- (28) SOUND SYSTEM EQUIPMENT CABINET. REFER TO DETAIL FOR ADDITIONAL REQUIREMENTS INCLUDING LV CONDUIT.
- 29 NOT USED.
- (30) HVAC SENSOR LOCATIONS.
- (31) T-STAT LOCATIONS. COORDINATE PLACEMENT WITH ARCHITECT. REFER TO SHEET M-112 FOR T-STAT NUMBERS.
- (32) BURGLAR ALARM KEYPAD AT 44" A.F.F.
- (33) BURGLAR ALARM SOUNDER AT 96" A.F.F.
- (34) PROVIDE FLUSH FLOOR BOX, COMMERCIAL ROLL FORMED PRODUCTS 2000, #C2606-25-U (BOX) WITH #2606-A-SS STAINLESS STEEL COVERPLATE AND (2) NEMA 5-20R RECEPTACLES. SEE ARCHITECTURAL PLANS FOR EXACT LOCATIONS.
- 35 PROVIDE (2)FLUSH FLOOR BOXES, COMMERCIAL ROLL FORMED PRODUCTS 2000, #C2606-25-U (BOX) WITH #2606-A-SS STAINLESS STEEL COVERPLATE, (1) TELEPHONE OUTLET AND (3) DATA OUTLETS. SEE ARCHITECTURAL PLANS FOR EXACT LOCATIONS.
- 36 − 37 NOT USED.
- (38) EXISTING LANDLORD INSTALLED GFI WP RECEPTACLE AND DISCONNECT AT UNIT.



SCALE: 1/4" = 1'-0" @ FULL SIZE

PARTIAL POWER PLAN

E-112

Street E 0410

**≫** 

ISSUED / REVISED DATE

LL COORDINATION SET 11/08/16

PRELIMINARY SET

L/PERMIT SET

**EEA** 

EEA Consulting Engineers 6615 Vaught Ranch Road, Suite 200 Austin, Texas 78730-2314 USA

512.744.4400 main 512.744.4444 fax

State of Registration MAINE Firm Registration No. N/A EEA Project No. 20166538

SHOWN ON ELECTRICAL PLANS REMOVE ALL

CONDUIT AND CONDUCTOR PACK TO PANEL.

AND SHALL DISPLAY THE MANUFACTURER'S NAME

ON EACH COMPONENT. ACCEPTABLE MODELS (UNLESS LANDLORD REQUIRES DIFFERENT): SILENT KNIGHT 5204 OR 5207, ADEMCO 100, FIRELITE 9200 SERIES.