

### Section 1: Project Information

•

Energy Code: 2009 IECC Project Title: West Elm - Downtown Portland Project Type: New Construction

Construction Site: 164 Middle Street Portland, ME 04101 Designer/Contractor: Bryan Wilkerson EEA Consulting Engineers 6615 Vaught Ranch Road Austin, TX 78730 512-744-4400 bryanwilkerson@eeace.com

Report date: 11/17/16

# Section 2: Interior Lighting and Power Calculation

A Area Category	B Floor Area (ft2)	C Allowed Watts / ft2	D Allowed Watts (B x C)	
Retail	10100	1.5	15150	
Allowance: Furniture, clothing, cosmetics highlighting / Fix. ID: F1A / F1E	6100(a)	1.4	8540(b)	
The second of th	Supplemental Allowed Watts(c) =		1000	
		tal Allowed Watts =	24690	

(a) Area claimed must not exceed the illuminated area permitted for this allowance type. (b) Allowance is (B x C) or the actual wattage of the fixtures given in Section 2, whichever is less. (c) Supplemental watts must be associated with retail merchandise highlighting fixtures. Supplemental watts are not included calculation of lighting complaince percentage.

## Section 3: Interior Lighting Fixture Schedule

Fixture ID: Description / Lamp / Wattage Per Lamp / Ballast	Lamps/ Fixture	# of Fixtures	Fixture Watt.	(C X D
Retail (10100 sq.ft.)	TINUTE	Tixtures	wat.	
Track lighting 1: Lighting for Sale: Wattage based on circuit breaker capacity (40 amps x 120 volts)	0	0	4800	Exemp
Exemption:Lighting Sales or Education				
Track lighting 2: F1A / F1B: Track: Wattage based on circuit breaker capacity (120 amps x 120 volts)	0	0	14400	1440
LED 1: F11: 27w LED Downlight: LED Other Fixture Unit 28W:	1	8	27	21
Linear Fluorescent 1: F10: 8' Linear Fluor.: 48" T8 32W (Super T8): Electronic:	2	41	62	254
Linear Fluorescent 2: F10A: 4' Linear Fluor.: 48" T8 32W (Super T8): Electronic:	1	2	32	6
Incandescent 1: A2: 60w Incan Pendant: Incandescent 60W:	1	4	60	24
Incandescent 2: A1: 60w Incan Sconce: Incandescent 60W:	1	6	60	36
Linear Fluorescent 3; F13: 1'x4' Surface Mount Fluor.: 48" T8 32W (Super T8): Electronic:	2	1	62	6
Incandescent 3: A3: 150W Incan Pendant: Incandescent 150W:	1	2	150	30
	Total Proposed Watts =		1818	

## Section 4: Requirements Checklist

# Interior Lighting PASSES: Design 23% better than code.

Lighting Wattage:

1. Total proposed watts must be less than or equal to total allowed watts.

Project Title: West Elm - Downtown Portland

Data filename: I:\Project\20166538 WE Downtown Portland Maine\DWGS\ELEC\Visual-Energy\WE-Portland Maine-Lighting

Page 1 of 2 Project Title: West Elm - Downtown Portland

Allowed Watts	<b>Proposed Watts</b>	Cor
0.1000	40404	

# Controls, Switching, and Wiring:

2. Daylight zones under skylights more than 15 feet from the perimeter have lighting controls separate from daylight zones adjacent to vertical fenestration.

3. Daylight zones have individual lighting controls independent from that of the general area lighting.

Contiguous daylight zones spanning no more than two orientations are allowed to be controlled by a single controlling device. Daylight spaces enclosed by walls or ceiling height partitions and containing two or fewer light fixtures are not required to have a

separate switch for general area lighting. 4. Independent controls for each space (switch/occupancy sensor).

Areas designated as security or emergency areas that must be continuously illuminated.

Lighting in stairways or corridors that are elements of the means of egress.

5. Master switch at entry to hotel/motel guest room.

6. Individual dwelling units separately metered.

7. Medical task lighting or art/history display lighting claimed to be exempt from compliance has a control device independent of the control

a. Each space required to have a manual control also allows for reducing the connected lighting load by at least 50 percent by either controlling all luminaires, dual switching of alternate rows of luminaires, alternate luminaires, or alternate lamps, switching the middle lamp luminaires independently of other lamps, or switching each luminaire or each lamp.

Only one luminaire in space.

An occupant-sensing device controls the area.

The area is a corridor, storeroom, restroom, public lobby or sleeping unit. Areas that use less than 0.6 Watts/sq.ft.

9. Automatic lighting shutoff control in buildings larger than 5,000 sq.ft.

Sleeping units, patient care areas; and spaces where automatic shutoff would endanger safety or security.

☐ 10.Photocell/astronomical time switch on exterior lights.

 Lighting intended for 24 hour use. 11. Tandem wired one-lamp and three-lamp ballasted luminaires (No single-lamp ballasts).

☐ Electronic high-frequency ballasts; Luminaires on emergency circuits or with no available pair.

# Section 5: Compliance Statement

Compliance Statement: The proposed lighting design represented in this document is consistent with the building plans, specifications and other calculations submitted with this permit application. The proposed lighting system has been designed to meet the 2009 IECC requirements in COMcheck Version 4.0.4.0 and to comply with the mandatory requirements in the Requirements Checklist.

Project Title: West Elm - Downtown Portland Data filename: I:\Project\20166538 WE Downtown Portland Maine\DWGS\ELEC\Visual-Energy\WE-Portland Maine-Lighting

Report date: 11/17/16

10 10 5.00

WILLIAMS-SONOM
3250 Van Ness Aven
San Francisco, CA 9
T 415 616 8602
F 415 439 8164
www.williams-sonom

EEA Consulting Engineers 6615 Vaught Ranch Road, Suite 200 Austin, Texas 78730-2314 USA 512.744.4400 main 512.744.4444 fax

www.eeace.com

State of Registration MAINE Firm Registration No. N/A

DRAWN BY: BMW

CHECKED BY: SMR

EEA Project No. 20166538

ISSUED / REVISED DATE PRELIMINARY SET 09/08/16 LL COORDINATION SET 11/08/16 LL/PERMIT SET

ENERGY CODE CALCULATIONS

ComCheck.cck

I:\Project\20166538 WE Downtown Portland Maine\DWGS\Permit Drawings\ELEC\E-006.dwg