DOOR SCHEDULE

DOOR NUMBER	DESCRIPTION	SIZE	DOOR DATA				FRAME DATA					FIRE RATING	HARDWARE								REMARKS
			THICKNESS	MATERIAL	TYPE	FINISH	MATERIAL	FINISH	HEAD	JAMB	SILL		BUTTS	LOCKSET	EXIT DEVICES	CLOSER	STOP	PUSH/PULL BARS	WEATHERSTRIP THRESHOLD	MISC	
	FIRST FLOOR																				
1	ENTRY DOOR (EXISTING)	3'-0" X 8'-0" (PAIR)	1 3/4"	ALUM STILES TEMP GLASS	A-1	WE1-SG	ALUM	WE1-SG	--	--	--	--	P1	L1, L2	--	C1	--	PP1	W1, W2, T1	--	DOOR & DOOR HARDWARE BY LL. GC TO VERIFY IN FIELD
2	ELEVATOR VESTIBULE DOOR (EXISTING)	3'-0" X 7'-0" (PAIR)	1 3/4"	ALUM STILES TEMP GLASS	A-2	WE1-SG	ALUM	WE1-SG	--	--	--	--	P1	L1, L2	--	C1	--	PP1	W1, W2, T1	--	DOOR & DOOR HARDWARE BY LL. GC TO VERIFY IN FIELD
3	SIDE ENTRY DOOR (EXISTING)	3'-0" X 6'-10"	1 3/4"	ALUM STILES TEMP GLASS	A-3	WE1-SG	ALUM	WE1-SG	--	--	--	--	P1	L1, L2	--	C1	--	PP1	W1, W2, T1	--	DOOR & DOOR HARDWARE BY LL. GC TO VERIFY IN FIELD
4	DOOR TO BASEMENT STOCK ROOM(EXISTING)	3'-0" X 7'-0"	1 3/4"	HM	C	WE1-SG	WELD METAL	WE1-SG	E3/A-803	E1/A-803	--	--	B1	--	ED5	C2	--	--	S2, S4	M2, M6	DOOR & DOOR HARDWARE BY LL. GC TO VERIFY IN FIELD
5	SALES TO STOCKROOM	3'-0" X 7'-0"	1 3/4"	HM	C	WE1-SG	WELD METAL	WE1-SG	E3/A-803	E3/A-803	E7/A-803	--	B1	L13	--	C2	S1, S2	--	--	M2, M6	"PRIVATE" SIGN BY SIGN VENDOR
6	MEN'S TOILET ROOM	3'-0" X 7'-0"	1 3/4"	SCW	B-1	WE1-SG	WELD METAL	WE1-SG	E3/A-803	E3/A-803	C7/A-803	--	B1	L4	--	C2	S3	--	T4	M1, M6	UNDERCUT DOOR 1"
7	WOMEN'S TOILET ROOM	3'-0" X 7'-0"	1 3/4"	SCW	B-1	WE1-SG	WELD METAL	WE1-SG	E3/A-803	E3/A-803	C7/A-803	--	B1	L4	--	C2	S3	--	T4	M1, M6	UNDERCUT DOOR 1"
8	MANAGER'S OFFICE	3'-0" X 7'-0"	1 3/4"	HM	C	WE1-SG	WELD METAL	WE1-SG	E3/A-803	E3/A-803	E5/A-803	--	B1	L5	--	C2	S1, S2	--	W4	M1, M4, M7	
9	STOCK EXIT(EXISTING)	3'-0" X 7'-0"	1 3/4"	HM	C	WE1-SG	WELD METAL	WE1-SG	E3/A-803	E1/A-803	--	--	B1	--	ED3	C2	--	--	--	M1, M6	NEW HARDWARE ON EXISTING DOOR
10	ELEVATOR MACHINE ROOM(EXISTING)	3'-0" X 7'-0"	1 3/4"	HM	C	WE1-SG	WELD METAL	WE1-SG	E3/A-803	E1/A-803	--	--	B1	L11	--	C2	--	--	S2, S4	M1, M6	DOOR & DOOR HARDWARE BY LL. GC TO VERIFY IN FIELD

* GC TO PROVIDE CORRECT HARDWARE PACKAGE ON ALL LL PROVIDED DOORS AFTER VERIFING IN FIELD.

DOOR TYPE AND NOTES

1. EXIT DOORS AT STOREFRONT SHALL HAVE SIGN ABOVE STATING "THIS DOOR TO REMAIN UNLOCKED WHEN BUILDING IS OCCUPIED" IN 1" HIGH BLACK VINYL LETTERS ON A SILVER BACKGROUND. LOCKING DEVICE TO BE OF TYPE THAT IS READILY DISTINGUISHABLE AS LOCKED.
2. DOORS WITHIN THE PATH OF TRAVEL FOR HANDICAPPED TO BE OPENABLE WITH A SINGLE EFFORT BY LEVER, PANIC BAR OR PUSH / PULL HARDWARE.
3. EXIT DOORS TO BE OPENABLE FROM THE INSIDE WITHOUT USE OF A KEY OR ANY SPECIAL KNOWLEDGE OR EFFORT.
4. EXTERIOR DOOR CLOSERS TO BE ADJUSTED TO PROVIDE FOR A MAXIMUM EFFORT TO OPERATE OF 15 LBF (1008.1.3). AT FIRE DOOR, USE FORCE ACCEPTABLE BY FIRE MARSHAL.
5. INTERIOR DOOR CLOSERS TO BE ADJUSTED TO PROVIDE FOR A MAXIMUM EFFORT TO OPERATE OF 5.0 LBF.
6. THRESHOLDS SHALL NOT EXCEED 1/2" IN HEIGHT.
7. ALL WOOD AND HM DOORS TO HAVE 1-1/2" PAIR BUTTS PER LEAF.
8. BOTH SIDES OF DOOR LEAFS AND FRAMES SHALL BE FINISHED THE SAME, UNLESS OTHERWISE NOTED.
9. ALL WOOD DOOR FRAMES AND TRIM SHALL BE AWI OR WIC CUSTOM GRADE UON
10. DOORS AND CASED OPENINGS INDICATED ADJACENT TO WALL INTERSECTIONS SHALL BE LOCATED WITH THE EDGE OF FINISH OPENING SIX INCHES FROM THE ADJACENT WALL UNLESS OTHERWISE INDICATED; ALL OTHER DOORS AND CASED OPENINGS SHALL BE CENTERED BETWEEN NEAREST ADJACENT WALL INTERSECTIONS, UNLESS OTHERWISE DIMENSIONED.
11. ALL LEGAL EXITS SHALL BE PROVIDED WITH SELF-ILLUM. EXIT SIGNS HAVING 6" LETTERS WITH 3/4" STROKES IN CONTRASTING COLORS.
12. CAUTION: HM DOORS TAKE LARGER STRIKES THAN SOLID CORE DOORS.
13. HARDWARE CONTRACTOR TO COORDINATE ALL HARDWARE WITH DOORS AND FRAMES AS SPECIFIED, INCLUDING LOCKSETS AND STRIKES.
14. ALL MILLWORK IN THE SCOPE OF WORK SHALL BE DELIVERED ON SITE SHOP-PRIMED AND SANDED.
15. INSTALL ALL DOORS AND HARDWARE TO MEET ACCESSIBILITY REQUIREMENTS.

HARDWARE NOTES

1. ANY SUBSTITUTIONS TO BE SUBMITTED WITH CATALOG FOR ARCH APPROVAL.
2. GENERAL CONTRACTOR TO INSTALL LOCKSET WITH CONSTRUCTION CORES.
3. SUBMIT THREE (3) COPIES OF HARDWARE LIST AND CUT SHEETS. CUT SHEETS TO CLEARLY INDICATE HARDWARE TO BE USED.
4. CONTRACTOR TO ORDER ALL HARDWARE IMMEDIATELY UPON APPROVAL OF HARDWARE LIST.
5. GC IS RESPONSIBLE TO BID HARDWARE THAT CONFORMS TO REQUIREMENTS OF THE JURISDICTIONAL CODE AUTHORITIES.
6. WHERE OPENINGS ARE NOTED WITH AN HOURLY FIRE RESISTANCE RATING, PROVIDE HARDWARE COMPONENTS LABELED BY UNDERWRITERS LABORATORY, OR OTHER TESTING LABORATORY APPROVED BY THE LOCAL CODE AUTHORITIES, TO MEET THE HOURLY FIRE RATING NOTED.
7. HARDWARE SHALL CONFORM TO NFPA 80 FOR FIRE RATED CLASS INDICATED.

HARDWARE NOTES

ALL LOCKS AND CYLINDERS ARE TO BE COMPATIBLE WITH BEST 7-PIN KEY SYSTEM

BUTTS/PIVOTS

B1 HAGER HINGES BB1279 4 1/2" X 4 1/2" - US26D

B2 MCKINNEY HINGES TA2714-NRP 4 1/2" X 4 1/2" - US26D

B3 SOSS HINGES 218 - US26D

B4 CONTINUOUS GEARED HINGE (HURRICANE ZONE STORES)

P1 RIXSON 195 PIVOT SET W/ ONE M19 INTERMEDIATE PIVOT - FOR DOORS UP TO 10'-0" TALL TO PROVIDE 8.5 LB MAX OPENING FORCE (5.0 LB IN CALIFORNIA)

P2 RIXSON 195 PIVOT SET W/ TWO M19 INTERMEDIATE PIVOTS - FOR DOORS 10'-0" AND TALLER TO PROVIDE 8.5 LB MAX OPENING FORCE (5.0 LB IN CALIFORNIA)

LOCKET

L1 ADAMS RITE 3-POINT DEADLOCK - MS 1850/4015/4016 W/ EXIT INDICATOR 4089

L2 BEST CYLINDER - MORTISE TYPE WITH THUMBTURN AND STRIKE, TO BE COMPATIBLE WITH BEST 7-PIN, CORE -FINISH: 622

L3 SCHLAGE PASSAGE ND10S - RHO - 626

L4 SCHLAGE PRIVACY ND40S-RHO-626

L5 SCHLAGE LOCKSET ND53BD - RHO - 626

L6 BEST RIM CYLINDER 1E72 (AT OUTSIDE TRIM OF ACTIVE DOOR) - 626

L7 DETEX EAX500SK1 (FOR SINGLE DOOR), DETEX EAX500SK2 (FOR DOUBLE DOORS) BATTERY POWERED EXIT ALARM

L8 BEST MORTISE CYLINDER 1E74 - 62 (FOR USE W/ L7)

L9 IVES ROLLER LATCH 336 - 626

L10 PRECISION OUTSIDE LEVER TRIM 3903D -32D

L11 SCHLAGE LOCKSET ND80BD - RHO - 626

L12 IVES FLUSH BOLTS FB458 - 626

L13 SCHLAGE AL 10S X SATURN - 26D

L14 SCHLAGE LOCKSET ND25D - RHO - 626

L15 BEST CORE FOR COILING DOOR SWITCH

EXIT DEVICES

ED1 PRECISION FIRE RATED EXIT DEVICE (ACTIVE DOOR) FL2203 ALK X 1703A X RHR - 630 C

ED2 PRECISION FIRE RATED EXIT DEVICE (INACTIVE DOOR) FL2203 ALK X 1701 X LHR - 630

ED3 PRECISION EXIT DEVICE FL2101 ALK x 1701 (HANDED RHR OR LHR) - ALUM

ED4 PRECISION EXIT DEVICE FL2201 x 1701 (HANDED RHR OR LHR) - ALUM

ED5 PRECISION EXIT DEVICE FL2103 x 1703 (HANDED RHR OR LHR) - ALUM

ED6 PRECISION EXIT DEVICE FL2101 x 1701 (HANDED RHR OR LHR) - ALUM

ED7 PRECISION EXIT DEVICE FL2114 x 4914 (HANDED RHR OR LHR) - ALUM

ED8 PRECISION EXIT DEVICE FL2203 EXQ x 1703

CLOSER

C1 LCN 2034 X ALUM (MT FOR 180 DEGREES) OVERHEAD CLOSERS WITH HOLD OPEN

C2 NORTON CLOSER 8501 - ALUM

C3 NORTON ALUMINUM CLOSER 8501-BF X S/B - ALUM

C4 LCN CLOSER 4041PA - ALUM

C5 RIXSON FLOOR CLOSERS WITH HOLD OPEN - 40 x PH - TO PROVIDE 8.5 LB MAX OPENING FORCE (5.0 LB IN CALIFORNIA)

C6 KAWNEER HUSKY-II / SAM-II (FLORIDA STORES)

STOP

S1 ROCKWOOD DOOR STOP - 440 - US26D

S2 BALDWIN KICK DOWN DOOR STOP 4105- 626

S3 IVES DOME STOP X RISER FS13 X R14 - 626

S4 GLYNN-JOHNSON OVERHEAD STOP 100S - 626

S5 TICE RS2 FLOOR HOLDERS

S6 MAGNETIC HOLD OPEN

PUSH/PULL BARS

PP1 CUSTOM PULL, ON BOTH SIDES OF DOOR - 3D STUDIO
CONTACT: JOE FARAIS PH: 510.220.0220

PP2 HAFELE PULL 151.01.729 - 626

WEATHERSTRIP/THRESHOLDS

W1 BOTTOM SWEEPS BY STOREFRONT DOOR MANUFACTURER

W2 WEATHERSTRIP BY STOREFRONT DOOR MANUFACTURER

W3 DOOR SWEEP

W4 PEMKO SMOKE SEAL S88W-21' - WHITE

T1 PEMKO THRESHOLD - 176D 1/2" X 7"

T2 NGP THRESHOLD - 425A

T3 KAWNEER THRESHOLD STANDARD 1/2" X 4" ALUMINUM MILL FINISH (FLORIDA STORES)

T4 MARBLE THRESHOLD

T5 PEMKO THRESHOLD - 1716 1/2" X 6"

MISC

M1 ROCKWOOD KICKPLATE 10" X 2" LESS THAN TOTAL WIDTH OF DOOR - 630

M2 ROCKWOOD KICKPLATE 30" X 2" LESS THAN TOTAL WIDTH OF DOOR - 630

M3 VES LOCK GUARD LG1 - US32D

M4 IVES VIEWER U700B26D - 626

M5 PRECISION DOUBLE DOOR STRIKE

M6 IVES SILENCERS SR65/SR64

M7 COAT HOOK - LIBERTY 129849

DOOR TYPES



ENTRY DOOR — TYPE A-1

ENTRY DOOR — TYPE A-2

ENTRY DOOR — TYPE A-3



STOCKROOM /SALES /TOILET ROOMS — TYPE B-1



STOCKROOM/ MACHINE ROOM — TYPE C



SERVICE/ EXIT — TYPE D



EXIT — TYPE F



STOCKROOM /SALES - DOUBLE DOORS

OWNER:
WILLIAMS-SONOMA, INC.
3250 Van Ness Avenue
San Francisco, CA 94
T 415 616 8602
F 415 439 8164
www.williams-sonomainc

Reviewed for Code Compliance
Joseph Cotter Chief Building Inspector
Date: 04/26/17

LICENSED ARCHITECT
TODD K. HENOKI
STATE OF MAINE

CALLISONRTKL™
A DESIGN CONSULTANCY OF ARCADIS
CALLISONRTKL, INC.
www.callisonrtkl.com

west elm
Dowtown Portland
164 Middle Street
Portland, ME 04101
PROJECT #006-160335.00

ISSUED / REVISED	DATE
PRELIMINARY SET	09/08/16
LL COORDINATION SET	11/08/16
LL/PERMIT SET	11/21/16

DOOR SCHEDULE, NOTES, HARDWARE & DOOR TYPES

A-003

COPYRIGHT © 2016 CallisonRTKL Inc.