City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Owner: Phone: Location of Construction: Permit No: Znd floor Soley Whari LLC 207-775-2255 100 Commercial Street 991005 Lessee/Buyer's Name: Phone: BusinessName: Owner Address: Ill Commercial St. Ptland, ME Contractor Name: Address: Phone: Monaghan Woodworks 155 Falmouth St. Portland, ME 04097 *BradFinlay 775-2683 COST OF WORK: SFP | 5 1999 PERMIT FEE: Proposed Use: Past Use: \$ 5,000 54,00 Same Office FIRE DEPT. Approved INSPECTION: Use Group: B Type: 3B ☐ Denied CBL: 030-C-00 Zone: BOC4961 Signature: Zoning Approval Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) Amend Permit#990816 Action: Approved Special Zone or Reviews: Interior renovations for 2nd floor only. Approved with Conditions: ☐ Shoreland Denied □ Wetland □ Flood Zone ☐ Subdivision Signature: Date: ☐ Site Plan maj ☐minor ☐mm ☐ Permit Taken By: Date Applied For: UB Zoning Appeal ☐ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. satCall for Pick Up; ☐ Conditional Use Building permits are void if work is not started within six (6) months of the date of issuance. False informa-Brad Finley 775-2683 ☐ Interpretation 3. ☐ Approved tion may invalidate a building permit and stop all work... Honaghan Woodworks ☐ Denied Historic Preservation □ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review PERMIT ISSUED MITH REQUIREMENTS Action: CERTIFICATION □Appoved ☐ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, ☐ Denied if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit 9-5-99 ADDRESS: PHONE: SIGNATURE OF APPLICANT DATE:

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

PHONE:

CEO DISTRICT

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE

COMMENTS

		9/28/010 Work
Type Foundation: Framing: Plumbing: Final: Other		Comp kg
Inspection Record		lose in done 9/1/49
Date		40

BUILDING PERMIT REPORT : 9 SepT 99 **EASON FOR PERMIT:** PERMIT APPLICANT: **USE GROUP CONSTRUCTION TYPE** The City's Adopted Building Code (The BOCA National Building Code/1996 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993) CONDITION(S) OF APPROVAL This permit is being issued with the understanding that the following conditions are met: */ *// */2 */2

*27 *29 *30 *32 *33

Approved with the following conditions: ∡ 1. 2. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)"ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING." 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2 4. Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' o.c. between bolts. (Section 2305.17) 5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code. 6. Precaution must be taken to protect concrete from freezing. Section 1908.0 It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify 7. that the proper setbacks are maintained. 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National 9. Mechanical Code/1993). Chapter 12 & NFPA 211 Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building 10. Code. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces X11. for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of

Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
Stair construction in <u>Use Group R-3 & R-4is a minimum of 10" tread and 7 %" maximum rise</u>. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)

14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4

stairway. (Section 1014.7)

Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)

Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits
directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self
closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)
The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic
extinguishment. (Table 302.1.1)
All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of
the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke
detectors shall be installed and maintained at the following locations):
In the immediate vicinity of bedrooms
 In all bedrooms
 In each story within a dwelling unit, including basements
In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall
receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.
A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved
type. (Section 921.0)
The Fire Alarm System shall maintained to NFPA #72 Standard.
The Sprinkler System shall maintained to NFPA #13 Standard.
All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1996)
Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open
any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification
from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of
Inspection Services.
Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until
all electrical (min.72 hours notice) and plumbing inspections have been done.
All requirements must be met before a final Certificate of Occupancy is issued.
All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building
Code/1996).
Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
Please read and implement the attached Land Use Zoning report requirements.
Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.
Glass and glazing shall meet the requirements of Chapter 24 of the building code.
All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code
1996).
An Area of retuge shell be prosided
,

Muclification Building Inspector
Life McDougall, PFD
Marge Schmuckal, Zoning Administrator

PSH 7/24/99

38.

^{**}On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Attached Single Family Dwellings/Two-Family Dwelling Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Addressof Co	onstruction (include Portion of Building):	100 Commercial	ST (THOMAS BLOCK)
Total Square Footage	of Proposed Structure 2633	SQ F+ Square Footage of L	ot
Tax Assessor's Chart, 1 Chart# 030	Block & Lot Number Block# Lot# 00/	Soley WHARF	Telephone#: (207) 175-2252
	MERCIAL ST	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee \$ 5000.00 \$54
Proposed Project Desc Submitted 10	ription:(Please be as specific as possible) Work to Shalfoor (Amend permit # 990	2nd only
Contractor's Name, Ad	Idress & Telephone Non ACHA PORTLANO	ME 04097	55 FA/morth ST Rec'd By US
Current Use:	. Office	Proposed Use:	Same
You must Include t Minor or Major site checklist outlines th	he following with you application 1) ACopy of Y 2) A Copy of e plan review will be required for the minimum standards for a site p	(our Deed or Purchase and Sale f your Construction Contract, 3) A Plot Plan/Site Plan the above proposed projects. The plan. 4) Building Plans	e attached Monaghan Woodwork
			ned by a registered design professional INSPECTION
 Cross Se Floor Pla Window Foundati Electrica 		ng porches, decks w/ railings, and and dampproofing al drawings for any specialized ed	
I hereby certify that I ar owner to make this appl application is issued, I c enforce the provisions of Signature of applica	n the Owner of record of the named proper lication as his her authorized agent. I agreentify that the Code Official's authorized of the codes applicable to this permit.	Certification rty, or that the proposed work is authorize to conform to all applicable laws of this representative shall have the authority to e	by the owner of record and that I have been authorized by the spirisdiction. In addition, if a permit for work described in this anter all areas covered by this permit at any reasonable hour to Date: Date: 000.00 construction cost thereafter.
1301	Additional Site review	and related fees are attached on	a separate addendum

990816

030- 0-001

