Location of Construction: / Exchange Street Portland Mains	Owner: Kobert Goldy	Phone:		Permit No:	Λ.	
Owner Address:	Lessee/Buyer's Name: Subs unlimited INc.	Phone: Busine 879-0403	ssName:	99081		
Contractor Name:	Address:	Phone:			Permit Issued:	
Past Use:	Proposed Use:	COST OF WORK:	PERMIT FEE:	AUG 3 199	9	
sub shop	存寄期号	FIRE DEPT. □ Approved □ Denied	INSPECTION: Use Group: Type:	CITY OF PORT	LAND	
		Signature:	Signature:	Zone: CBL: 032-E-0	005	
Proposed Project Description:		PEDESTRIAN ACTIVITI		Zoning Approval:	. in	
Frame sigh		Action: Approved Approved Denied	with Conditions:	Special Zone of Shoreland Shoreland Wetland Flood Zone		
		Signature:	Date:	□Subdivision	,	
Permit Taken By:	Date Applied For:	ly 30, 1999 K.		☐ Site Plan maj	□minor □mm □	
 This permit application does not preclude the Building permits do not include plumbing, s Building permits are void if work is not started tion may invalidate a building permit and st 	peptic or electrical work. ed within six (6) months of the date of all work			□ Variance □ Miscellaneous □ Conditional Us □ Interpretation □ Approved □ Denied	e	
		47 Exchange Street		Historic Pre	servation	
	~ !	Protland Maine 04101 PER WITH R	MIT ISSUED EQUIREMENTS	□ Not in District of □ Does Not Requires Review	ire Review	
	CERTIFICATION	tine .		☐ Appoved		
I hereby certify that I am the owner of record of the authorized by the owner to make this application	as his authorized agent and I agree to	conform to all applicable laws of	this jurisdiction. In additi	ion, □ Denied	Conditions	
if a permit for work described in the application is areas covered by such permit at any reasonable h				Date:		
		July 30, 1999	9 ₁ .			
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:			
RESPONSIBLE PERSON IN CHARGE OF WOL	, SK TITLE		PHONE:			
MEDI OMBIDEE I EKBON IN CHARGE OF WOL	XIX, IIILL		I HONE.	CEO DISTRICT	1 * 1	

COMMENTS

	Inspection Record Type Foundation: Framing: Plumbing: Final: Other:O(Date
, ,		
•		

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Sign Permit Pre-Application Attached Single Family Dwellings/Two-Family Dwelling Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Addressof Construction (include Portion of Building): HT EXACUSES OF CONSTRUCTION (Include Portion of Building): OHIO
Total Square Footage of Proposed Structure Square Footage of Lot
Tax Assessor's Chart, Block & Lot Number Chart# 33 Block# E' Lot# 5 Owner: Subs Unlimited Fine Telephone#: 879 0403
Owner's Address: GT Exchange T Lessee/Buyer's Name (If Applicable) Total Sq. Ft. of Sign Fee \$ 265
Proposed Project Description:(Please be as specific as possible) A-Frame 5/5N
Contractor's Name, Address & Telephone Rec'd By
Current Use: Proposed Use:
Signature of applicant: Date: 7/30/29
Signage Permit Fee: \$30.00 plus .20 per square foot of signage





PLEASE ANSWER ALL QUESTIONS
ADDRESS: 47 Exhance ST Porture ZONE:
OWNER: Subs (Inlimited) Inc. Ken Longval
APPLICANT: Subs Iblimited Inc
ASSESSOR NO. 33 - 8-0045
PLEASE CIRCLE APPROPRIATE ANSWER
SINGLE TENANT LOT? YES NO FREESTANDING SIGN? (ex. Pole Sign) YES NO DIMENSIONS 3 + HEIGHT 4+ MORE THAN ONE SIGN? YES NO DIMENSIONS HEIGHT SIGN ATTACHED TO BLDG.? YES NO DIMENSIONS MORE THAN ONE SIGN? YES NO DIMENSIONS AWNING: YES NO IS AWNING BACKLIT? YES NO HEIGHT OFF SIDEWALK IS THERE ANY MESSAGE, TRADEMARK OR SYMBOL ON IT? BUFFOLO WINGS + THENS
LIST ALL EXISTING SIGNAGE AND THEIR DIMENSIONS:
*** TENANT BLDG. FRONTAGE (IN FEET): *** REQUIRED INFORMATION
AREA FOR COMPUTATION Double Faced A prame Size walk subset with painted + wings quapties AREA FOR COMPUTATION Double Faced A prame Size walk sign message AREA AREA Prame Size walk A prame Si
YOU SHALL PROVIDE:
A SITE SKETCH AND BUILDING SKETCH SHOWING EXACTLY WHERE EXISTING AND NEW SIGNAGE IS LOCATED MUST BE PROVIDED. SKETCHES AND/OR PICTURES OF PROPOSED ARE ALSO REQUIRED. SIGNATURE OF APPLICANT: DATE: 7 3 0 9

BUILDING PERMIT REPORT
DATE: 2Aug. 99 . ADDRESS: 47 Exchange ST. CBL: \$32-E-\$65 REASON FOR PERMIT: Side Walk Sign
REASON FOR PERMIT: Side Walk Sign
BUILDING OWNER: Robert Goldy
PERMIT APPLICANT: Sub - Unlimited Inc. 1Contractor
use group Signage construction type
The City's Adopted Building Code (The BOCA National Building Code/1996 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
CONDITION(S) OF APPROVAL
This permit is being issued with the understanding that the following conditions are met: 434
Approved with the following conditions:

- 1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

 Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained.

 (A 24 hour notice is required prior to inspection)
 - 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
 - 4. Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' o.c. between bolts. (Section 2305.17)
 - 5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.
- 6. Precaution must be taken to protect concrete from freezing. Section 1908.0
- 7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1996)
- All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211
- 10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
- Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 ¼" and not greater than 2". (Sections 1021 & 1022.0) Handrails shall be on both sides of stairway. (Section 1014.7)
- 12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
- 13. Stair construction in <u>Use Group R-3 & R-4is a minimum of 10" tread and 7 %" maximum rise</u>. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)
- 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
- Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)
- 16. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0) 18. The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling or by providing automatic extinguishment. (Table 302.1.1) All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of 19. the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be installed and maintained at the following locations): In the immediate vicinity of bedrooms In all bedrooms In each story within a dwelling unit, including basements In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2. 20. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0) The Fire Alarm System shall maintained to NFPA #72 Standard. 21. The Sprinkler System shall maintained to NFPA #13 Standard. 22. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 23. of the City's Building Code. (The BOCA National Building Code/1996) 24. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year". The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification 25. from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services. 26. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics). 27. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min.72 hours notice) and plumbing inspections have been done. 28. All requirements must be met before a final Certificate of Occupancy is issued. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building 29. Code/1996). Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical 30. Code/1993). (Chapter M-16) Please read and implement the attached Land Use Zoning report requirements. 32. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code. Glass and glazing shall meet the requirements of Chapter 24 of the building code.

31.

33.

X 34 All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code 1996). 35. 36.

38.

s, Building Inspector L. McDougall, PFD

Marge Schmuckal, Zoning Administrator

PSH 7/24/99

37.

**On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.