

FireFinder XLS and FS-250 Panels

Intelligent Device Interface Module

Model HTRI-M {HTRI-MC for Canada}

ARCHITECT AND ENGINEER SPECIFICATIONS

- Interfaces and supervises normally open (N.O.) contacts: [i.e. – fire detection] or normally closed (N.C.) contacts: [i.e. – security detection]
- Compact size allows mounting in single-gang box behind equipment
- Polarity Insensitive with *SureWire™* technology
 - Innovative technology supports comprehensive system and interface communication
- Operates with FireFinder XLS panel's Model DLC circuit
- Dynamic Supervision
- (2) Two-wire operation
- Device Program / Test Unit (Model DPU) programs and verifies address and test functionality
-  UL Listed,  ULC Listed; FM, CSFM and NYMEA Approved



Product Overview

The Intelligent Interface module (Model HTRI-M) is designed to provide the means of interfacing direct shorting devices to the Device Program / Test Unit (Model DPU) for the FireFinder XLS and FS-250 fire-alarm control panels (FACPs).

Model HTRI-M provides the most advanced method of address programming and supervision – including sophisticated FACP-communication – in the fire and life safety market. Each Model HTRI-M interface module incorporates microcomputer-chip technology, and advanced bi-directional communication capabilities with the respective FACP.

Model HTRI-M is designed to monitor a N.O. or N.C. dry contact, and reports the contact status to the FACP. The microcomputer chip for Model HTRI-M has the capacity of storing – in memory – identification information, as well as integral operating-status data.

Specifications

Each Model HTRI-M interface module is programmed, via Model DPU, which is a compact, portable and menu-driven accessory that makes programming and testing a given interface more accurately and efficiently than ever before.

Model DPU eliminates the need for mechanical-addressing mechanisms – such as program jumpers, DIP switches or rotary dials – since Model DPU sets the interface address of Model HTRI-M into its microcomputer-chip, non-volatile memory electronically.

Vibration, corrosion and other conditions that deteriorate mechanical-addressing mechanisms are no longer a cause for concern. Model HTRI-M is connected to Model DPU with the programming cable provided with the tester. This programming cable (P/N 110-694927) utilizes two (2) alligator clip connectors, to attach to the HTRI-M.

Specifications — (continued)

Model HTRI-M has five (5) leads [one (1) of the five (5) leads is for grounding], which are wired to the system with user-supplied wire nuts.

Model HTRI-M is fully compatible on the same Model DLC circuit with all intelligent H-series detectors; HMS-series addressable, manual stations; or any other H-series addressable intelligent modules, such as Model HZM or Model HCP.

Temperature and Humidity Range

Models are $\text{UL 864 9}^{\text{th}}$ Edition listed for indoor dry locations within a temperature range of $120\pm 3^{\circ}\text{F}$ ($49\pm 2^{\circ}\text{C}$) to $32\pm 3^{\circ}\text{F}$ ($0\pm 2^{\circ}\text{C}$) and at a relative humidity of $93\pm 2\%$ at a temperature of $90\pm 3^{\circ}\text{F}$ ($32\pm 2^{\circ}\text{C}$).

Electrical Rating

Current Draw (Active or Standby):	1.5mA
--------------------------------------	-------

Details for Ordering

Model Number	Part Number	Description
HTRI-M	500-034000	Single-input Intelligent Interface Module
HTRI-MC	500-034000C	Single-input Intelligent Interface Module, Canada

Note: Each HTRI-series model is 3.5 ounces (0.1 kilograms) for Shipping Weight.

Notice: This marketing catalog sheet is not intended to be used for system design or installation purposes. For the most up-to-date information, refer to each product's installation instructions.