ocation of Construction:	Owner: Jos Soley	. 2 1	Phone:		Permit No:		
wner Address:	Lessee/Buyer's Name:	Phone:	Phone: Business		990813		
ontractor Name;	Address:	Phor	ne:		Permit Issued:		
ist Use:	Proposed Use:	COST OF WOL	COST OF WORK: \$ FIRE DEPT. Approved Denied		AUG 3 1999		
Ketq&1	same				Zone: CBL: 032-F-005		
oposed Project Description:		PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) Action: Approved			Zoning Approval:		
Side Walk Sign					□ Special Zone or Reviews: □ Shoreland □ Wetland □ Flood Zone		
ermit Taken By:	Date Applied For: July	Signature:			☐ Subdivision ☐ Site Plan maj ☐minor ☐mm ☐		
Building permits do not include plu	not started within six (6) months of the date of is				☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied		
			PEI	RMIT ISSUED	Historic Preservation ☐ Not in District or Landmark ☐ Does Not Require Review		
			WITH	REQUIREMENTS	☐ Requires Review		
					Action:		
authorized by the owner to make this ap if a permit for work described in the app	CERTIFICATION cord of the named property, or that the proposed plication as his authorized agent and I agree to clication is issued, I certify that the code official's sonable hour to enforce the provisions of the code.	conform to all applicab s authorized representa	le laws of th	nis jurisdiction. In additio	n, Denied		
	*		- Pro-				
GNATURE OF APPLICANT	ADDRESS:	July 30, 1999 DATE:		PHONE:			
ESPONSIBLE PERSON IN CHARGE	OF WORK, TITLE			PHONE:	CEO DISTRICT		
	OF WORK, TITLE White-Permit Desk Green-Assessor's Ca	nary-D.P.W. Pink-P	ublic Fi	le			

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Sign Permit Pre-Application

Attached Single Family Dwellings/Two-Family Dwelling Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Addressof Construction (include Portion of Building) FRONT FRONT 363	FORT St
Total Square Footage of Proposed Structure 635.7	Square Footage of Lot
Tax Assessor's Chart, Block & Lot Number Chart# Block# Lot OoS	Owner: OSCAR BERNY: + TM: Telephone#: 173-73/4
Owner's Address:	Lessee/Buyer's Name (If Applicable) Control of September 1
Proposed Project Description:(Please be as specific as possible)	· .
Contractor's Name, Address & Telephone	Rec'd By
Current Use: Referr	Proposed Use: Sau
	- /2 /
Signature of applicant: J. Cens	
Signage Permit	it Fee: \$30.00 plus .20 per square foot of signage



ACORD. CERTIFICATE OF LIABILITY INSURANCE							
RODUCER		THIS CERT	IFICATE IS ISSI	JED AS A MATTER	OF IN		
Sedgwick of Main	e: Inc.			TRIGHTS UPON T			
Telephone: 207	774-5911	ALTER THE	E COVERAGE A	FFORDED BY THE P	OLIC	IES BELOW	
P. O. Box 9755			INSURERS A	AFFORDING COVERA	GE		
Portland, Maine	04104-5055	1		Insurance			
		INSURER A	MCGGTG	THEOLOGICE			
Oscar L. Benoit,	Tme	INSUREA B					
363 Fore Street	Zitt.	INSUPER C					
	ME 04101	INSURER D					
OVERAGES	11G 941G1	INSURER E					
THE POLICIES OF INSURANCE LISTED ANY REQUIREMENT, TERM OR CON MAY PERTAIN, THE INSURANCE AFFO POLICIES: AGGREGATE LIMITS SHOW	DITION OF ANY CONTRACT OR OTH ORDED BY THE POLICIES DESCRIBE	HER DOCUMENT WITH ED HEREIN IS SUBJECT PAID CLAYMS	HESPECT TO WH	HICH THIS CERTIFICATE	MAY	BE ISSUED OF	
TYPE OF INSURANCE	POLICY NUMBER	POLICY EFFECTIVE DATE (MM/DD/YY)	POLICY EXPIRATION CATE (MM/DDAY)	LIM	ITS		
A. GENERAL LIABILITY	BOA000531515	1/19/99	1/18/00	EACH OGGUPHENCE		1000000	
X CONMERCIAL GENERAL LIABILITY			1	FIRE DAMAGE (Any one fire)	5	50000	
CLAIMS NADE OCCUR				NED EXP (Any one person)	3	5000	
		Ţ	i	PERSONAL & ADV MUNEY	3	1000000	
			,	GENERAL AGGREGATE	3	2000000	
GEN'L AGGREGATE LIMIT APPLIES PER.			155	PRODUCTS COMPLOF AGG	4	2000000	
POUCY! PAO. LOC					1		
AUTOMOBILE LIABILITY				COMBINED SINGLE LIMIT	s		
SOTUA CALUDAHOS	Post Hy brand fax transmitta	The second secon	iges > /	ODILY INJURY	,		
EOTUA DANH	To Co	From Jacan		SLEDGENI!	3		
	Dept.	Phone #879-5	769	POPERTY DAMAGE	3		
GARAGE LIABILITY	Pax 773 7310	Fax #	7	JTO ONLY - EA ACCIDENT	3		
ANY AUTO	1			THER THAN	-		
				AGG	-		
EXCESS LIABILITY				EACH OCCURRENCE	5		
OCCUR CLAIMS MADE		1		AGGREGATE	S		
	T	1			5	in a Final	
DEDUCTIBLE	P.				S		
RETENTION \$	i			100	s		
WORKERS COMPENSATION AND	į.			WC STATU- STE			
EMPLOYERS' LIABILITY	1	1		E.L. EACH ACCIDENT	S		
r	i			E. L. DISEASE - SA EMPLOYE	E 3		
	1			E.L. DISEASE - POLICY LIMIT	3		
OTHER	1						
	<u>į</u>						
SCRIPTION OF OPERATIONS/LOCATIONS/VE EVIDENCE OF COVERA							
ERTIFICATE HOLDER AD	IDITIONAL INSURED; INSURER LETTER	CANCELLAT	TON			~	
CITY OF PORTLAND 389 CONGRESS STRE PORTLAND, ME 041	DATE THEREOF NOTICE TO THE IMPOSE NO OB	SHOULD ANY OF THE ABOVE DESCRIBED POLICIES BE CANCELLED BEFORE THE EXPIRATE DATE THEREOF, THE ISSUING INSURER WILL ENDEAVOR TO MAIL					
		REPRESENTATI		16 8.16			



032-F-005

BUILDING PERMIT REPORT

DATE: 2/Aug/99 ADDRESS: 363 Fore STreeT CBL: 32-F-\$5

REASON FOR PERMIT: Side Walk Sign

BUILDING OWNER: 'OSCAR BOOTT

PERMIT APPLICANT: 5AA. (Contractor)

USE GROUP SIJNAGL CONSTRUCTION TYPE

The City's Adopted Building Code (The BOCA National Building Code/1996 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)

CONDITION(S) OF APPROVAL

This permit is being issued with the understanding that the following conditions are met: 434

Approved with the following conditions:

1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)

- 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
- 4. Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' o.c. between bolts. (Section 2305.17)
- 5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.
- Precaution must be taken to protect concrete from freezing. Section 1908.0
- 7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or l-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than I-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1996)
- All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211
- Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
- Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A. B. H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 ¼" and not greater than 2". (Sections 1021 & 1022.0) Handrails shall be on both sides of stairway. (Section 1014.7)
- 12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
- 13. Stair construction in Use Group R-3 & R-4is a minimum of 10" tread and 7 3/4" maximum rise. All other Use Group minimum 11" tread. 7" maximum rise. (Section 1014.0)
- 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
- Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)
- 16. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

- 17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0) The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic 18. extinguishment. (Table 302.1.1) All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of 19. the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be installed and maintained at the following locations): In the immediate vicinity of bedrooms In all bedrooms In each story within a dwelling unit, including basements In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2. 20. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0) 21. The Fire Alarm System shall maintained to NFPA #72 Standard. 22. The Sprinkler System shall maintained to NFPA #13 Standard. 23. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1996) 24. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year". The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification 25. from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services. 26. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics). 27. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min.72 hours notice) and plumbing inspections have been done. 28. All requirements must be met before a final Certificate of Occupancy is issued. 29. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996). 30. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16) 31. Please read and implement the attached Land Use Zoning report requirements. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code. 32.

All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code

33. Glass and glazing shall meet the requirements of Chapter 24 of the building code.

35. 36. 37. 38.

Hoffses, Building Inspector McDougall, PFD

Marge Schmuckal, Zoning Administrator

PSIS 7/24/99

34.

1996).

**On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.