


# Ventless Hood

## Model FSH-6



- The compact and simple design of the ventless hood eliminates the need for expensive roof modifications and the hassle of dealing with multiple vendors for separate hood and electrical systems.
- The Giles Ventless Hood is a one-of-a-kind, Type 1, stainless steel unit, which features our proven Electrostatic Air Cleaning system, meeting vapor removal requirements for various appliances.
- Optional stand eliminates need for side clearances and makes installation much easier.
- The fire suppression system used in the Giles Ventless Hood is an Ansul R-102A fire suppression system. Our system includes internal piping, plenum nozzles, and conduit for routing the fusible link cable. Final installation, charging, and system testing must be performed by an authorized Ansul distributor or other fire protection agent, is the sole responsibility of the customer, and is **NOT** included with purchase.

### Design Features



### Ventless Hood System

This Ventless Hood consists of a Four-stage Air Purification System.

**Stage 1.** Two Stainless Steel Baffle Filters trap large grease particles. (Not Shown)

**Stage 2.** Two Disposable Pre-Filters trap smaller grease particles.

**Stage 3.** Two Electrostatic Air Cleaning Filters (EAC) use ionizers to charge particles of dirty air, allowing them to be collected by an electrostatic force.

**Stage 4.** Two Disposable Charcoal Filters help eliminate odor.

### Appliance Constraints

Equipment Type	Max. Input Power (kW)	Max. Cooking Temperature	Max. Shortening Capacity	Max. Cooking Area
Fryers	20 (per fryer) 40 (total)	400°F [204°C]	80 lbs [36kg] (per fryer) 160 lbs [72kg] (total)	380 in <sup>2</sup> [0.245m <sup>2</sup> ] single fryer, 760 in <sup>2</sup> [0.490m <sup>2</sup> ] any combination
Ovens	55	500°F [260°C]	N/A	72"[1829mm]L X 42"[1067mm]D (Ceiling) 68"[1727.2mm] X 42"[1067mm]D (Stand)
Griddles	25	400°F [204°C]	N/A	60"[1524mm]L X 26"[660mm]D (Ceiling) 68"[1727.2mm] X 42"[1067mm]D (Stand)
Ranges	25	400°F [204°C]	N/A	60"[1524mm]L X 26"[660mm]D (Ceiling) 68"[1727.2mm] X 42"[1067mm]D (Stand)

### Listings

### Giles Foodservice Equipment

An ISO 9001 Registered Company • Committed to Quality  
 2750 Gunter Park Drive West • Montgomery, AL 36109 USA  
 Phone 334.272.1457 • Fax 334.239.4117 • Phone Toll Free 800.554.4537  
 Web Site: www.gfse.com • Email: services@gfse.com




**Note: To be used with electric appliances only.**

# Ventless Hood

## Model FSH-6

Item No.: \_\_\_\_\_  
 Quantity: \_\_\_\_\_  
 Project Name: \_\_\_\_\_  
 SIS#: \_\_\_\_\_  
 AIA/CSI#: \_\_\_\_\_



Inches [millimeters]

### Specifications

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements additions or replacements for previously purchased equipment.

<p><b>Construction:</b> 20Ga to 18Ga Stainless Steel</p> <p><b>Dimensions:</b> Width: 72-11/16" [1846 mm] Depth: 49-5/8" [1260 mm] Height: 74" [1880 mm] w/72" stand 117-3/16" [2977 mm]</p> <p><b>Ventless Hood:</b> Exhaust CFM: 840-940 Approx. Decibel Level: 73 Uncrated Weight: 553 lbs [251 kg]</p>	<p><b>Electrical Specifications:</b> Available voltages: 208/220/240 1 phase - 208/220/240V - 8/8/8 AMPS (neutral wire required for lighting) (No service cord provided)</p> <p><b>Product Designation:</b> FSH-6 (see "How to Specify" below)</p> <p><b>Shipping Specifications:</b> Crated Weight: 733 lbs [333 kg] Crated Cube Size: 82" X 56" X 50" = 132.87 cu ft [2082mm X 1422mm X 1270mm = 3.762 cu meters]</p>
--	---

### Accessories Included

Unit is shipped with (2) Baffle Filters, (2) Pre-Filters, (2) EAC Filters, (2) Charcoal Filters, (1) EAC Soak Tank and (1) Manual.

### How To Specify

- Local Codes**  
Ensure your local codes permit Ventless Hoods.
- Appliance Constraints**  
Ensure the appliance is within the specified constraints of the hood. (See Appliance Constraints on the front page or contact Giles Enterprises)
- Location**  
Ensure the location you are installing the Ventless Hood meets the proper clearances specified above.
- Electrical Specifications**  
Determine the electrical specifications from the available Voltages, Hz., and Phase.
- ILS Option (Interlocking Start)**  
Specify if your county requires the hood to shut-down if the appliance underneath is not operating. Check with your local officials for this requirement.

### 6. Determine FSH-6 Part Number

Specify the part number from the following:

	Voltage	Hz.	Ph.	Mount	ILS	Part Number
<input type="checkbox"/>	208/240	60	1	Ceiling	No	78973
<input type="checkbox"/>	208/240	60	1	Ceiling	Yes	70591
<input type="checkbox"/>	208/240	60	1	72" Floor	No	71463
<input type="checkbox"/>	208/240	60	1	72" Floor	Yes	71471
<input type="checkbox"/>	220	50	1	Ceiling	No	70535
<input type="checkbox"/>	220	50	1	Ceiling	Yes	70536

### 7. Accessories (additional charges)

Specify the part number and quantity of the following accessory items needed:

	Qty	Description	Part Number
<input type="checkbox"/>		Pre-Filter	91707
<input type="checkbox"/>		EAC Filter (Left-side)	20521
<input type="checkbox"/>		EAC Filter (Right-side)	20520
<input type="checkbox"/>		Charcoal Filter	32056

### 8. Shipping

Specify the shipping method

### Giles Foodservice Equipment

2750 Gunter Park Drive West • Montgomery, AL 36109 USA  
 Phone 334.272.1457 • Fax 334.239.4117 • Phone Toll Free 800.554.4537  
 Web Site: www.gfse.com • Email: services@gfse.com