

## Kepware Technologies

Location			Door							Frame		
Mark	Serving Room Name	Number	Label	Drawing	Height	Width	Thickness	Material	Style	Label	Type	Material
201	Quiet Room	232	none	2-a4	8-6	3-0		Aluminum	Full Glass	none	Storefront	Aluminum
202	Meeting Room	230	none	4-a4	8-6	3-0		Aluminum	Full Glass	none	Storefront	Aluminum
203	Women's Toilet Room	225B	none	*	6-8	2-10	1.75	Wood Solid Core	Flush	none	Drywall KD	Steel
204	Men's Toilet Room	224B	none	*	6-8	2-10	1.75	Wood Solid Core	Flush	none	Drywall KD	Steel
205	Women's Showers	225	none	8-a5	TBD	TBD	TBD	TBD	TBD	none	TBD	TBD
206	Men's Showers	223	none	3-a5	6-8	2-10	1.75		Flush	none	Drywall KD	Steel
207	Device Room	219A	none	3-a3	8-6	3-0		Aluminum	Full Glass	none	Storefront	Aluminum
208	Stretching Studio	210	none	3-a2	7-0	3-0	1.75		Full Glass	none	TBD	TBD
209	Accessible Shower	204	none	*	6-8	3-0	1.75	Wood Solid Core	Flush	none	Drywall KD	Steel
210	Fitness Room	211	none	5-a2	6-Aug	Mar-00		Aluminum	Full Glass	none	Storefront	Aluminum
401	Cave/Meeting	401	none	8-a3	8-6	3-0		Aluminum	Full Glass	none	Storefront	Aluminum
402	Storage	402	none	*	6-8	3-0	1.75	Wood Solid Core	Flush	none	Drywall KD	Steel

### Notes:

1. All new doors and hardware shall be ADA compliant. Provide lever operated locksets.
2. Where used, door closers shall comply with ADA requirements

### Outline Specifications:

Wood Solid Core Doors: Graham GPD-PC 5-Ply Particleboard Core. Match finish to existing wood doors.

Flush Moulding for lites, Graham M6G 11/16" x 3/8" with 3/32" radius

Drywall Knockdown Frames: Curries C series 16 GA, Unequal Rabbet. Verify required throat depth

Aluminum Frames: Old Castle 2" x 4 1/2" series 3000

