City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Location of Construction: Owner: Phone: Permit No: 3rd Floor Songress Street 874-6959 Lessee/Buyer's Name: Phone: BusinessName: Owner Address: t. Prid. ME G4101 120 Exchange Permit Issued: Address: Contractor Name: Phone: COST OF WORK: Proposed Use: PERMIT FEE: Past Use: \$ 45,000 Same Office FIRE DEPT. Approved INSPECTION: Use Group: B Type; 2 4 ☐ Denied Zone: CBL BOCA 46 Signature: Zoning Approval: Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT (Action: Approved Special Zone or Reviews: Approved with Conditions: ☐ Shoreland Interior Resovations 3rd Floor Denied □Wetland ☐ Flood Zone Signature: Date: ☐ Subdivision ☐ Site Plan maj ☐minor ☐mm ☐ SP Permit Taken By: Date Applied For: 5-4-99 Zoning Appeal □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. 1. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. 2. □ Conditional Use Building permits are void if work is not started within six (6) months of the date of issuance. False informa-☐ Interpretation Dayoraga tion may invalidate a building permit and stop all work... ☐ Denied Historic Preservation □ Not in District or Landmark ☐ Does Not Require Review PERMIT ISSUED WITH REQUIREMENTS □ Requires Review Action: CERTIFICATION □ Appoved I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been ☐ Approved with Conditions authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, □ Denied if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit June 7, 1999 SIGNATURE OF APPLICANT ADDRESS: DATE: PHONE:

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE

PHONE: CEO DISTRICT



COMMENTS
2-23-00 Met uf Con Wood - walked Thru 3rd Floor - appears to be
2-23-00 Met uf Con Wood - walked Thru 3rd Floor - appears to be Completed per plans. Is requesting CO JB
3-2-00 left massage on Ready & 2
3-2-00 left message Co Ready &B

Inspection	Record
mspection	ICCOI (

Туре	Date
Foundation:	
Framing:	
Plumbing:	
Final:	
Other:	

	BUILDING PERMIT REPORT
DATE:	June 99 ADDRESS: 460 Congress ST- CBL: \$32-6-00/ FOR PERMIT: Interior renovations (Office) GOWNER: A & M Partner & Inc.
REASO	FOR PERMIT: InTerior renovations (Office)
BUILD	GOWNER: ASM Partners Inc.
PERMI	APPLICANT: /Contractor SAD
USE GF	UP_B BOCA 1996 CONSTRUCTION TYPE_2B
	CONDITION(S) OF APPROVAL
This per	it is being issued with the understanding that the following conditions are met:
Approve	with the following conditions: */ *20 ^{21,22} *23 *27 *34
51. 2. 3. 4. 5. 6. 7. 8.	his permit does not excuse the applicant from meeting applicable State and Federal rules and laws. efore concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained A 24 hour notice is required prior to inspection) oundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 0 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the voting. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the pof the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter embrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor evation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be acced on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2 boundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and maximum 6' o.c. between bolts. (Section 2305.17) //aterproofing and damp proofing shall be done in accordance with Section 1813.0 of the building code. recaution must be taken to protect concrete from freezing. Section 1908.0 is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify at the proper setbacks are maintained. rivate garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent terior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private trages attached side
9.	Il chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National echanical Code/1993). Chapter 12 & NFPA 211 pund transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building
10.	ode. uardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces of the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use roups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open arking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through my opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section than outside diameter of at least 1 ¼" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of airway. (Section 1014.7)
12.	eadroom in habitable space is a minimum of 7'6". (Section 1204.0) air construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 ½" maximum rise. All other Use Group minimum 11"
13.	ead, 7" maximum rise. (Section 1014.0)
14. 15.	ne minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4 The rery sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door proved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate loss. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above a floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches 10mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. ection 1018.6)
16.	ach apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits
17.	overtical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self open's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)

The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic 18. extinguishment. (Table 302.1.1) 19. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be installed and maintained at the following locations): In the immediate vicinity of bedrooms In all bedrooms In each story within a dwelling unit, including basements In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0) The Fire Alarm System shall maintained to NFPA #72 Standard. The Sprinkler System shall maintained to NFPA #13 Standard. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1996) Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year". 25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics). 26. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until 27. all electrical (min. 72 hours notice) and plumbing inspections have been done. All requirements must be met before a final Certificate of Occupancy is issued. 28. 29. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996). Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical 30. Code/1993). (Chapter M-16) Please read and implement the attached Land Use Zoning report requirements. 31. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code. 32.

35. 36._

Glass and glazing shall meet the requirements of Chapter 24 of the building code.

el Hogses Byilding Inspector V McDougall, PFD Marge Schmickal, Zoning Administrator

33. 34.

**On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Attached Single Family Dwellings/Two-Family Dwelling

Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Addressof Construction (include Portion of Building) 400 Congress St					
Total Square Footage of Proposed Structure 98.30	Square Footage of Lot /	7 acres			
Tax Assessor's Chart, Block & Lot Number Chart# 032 Block# Lot# 00/	Owner: HYM Extal	Telephone#: 874-6959			
Owner's Address: 120 Exchange 32 04/01	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee \$ 4500 \$ 245			
Proposed Project Description: (Please be as specific as possible)					
Contractor's Name, Address & Telephone		Rec'd By			
Current Use: OFFICE	Proposed Use: San	no			

Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation.

 All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II. All plumbing must be conducted in compliance with the State of Maine Plumbing Code.

All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III.

. HVAC(Heating, Ventililation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code. DING INSPECTION

You must Include the following with you application:

1) ACopy of Your Deed or Purchase and Sale Agreement 2) A Copy of your Construction Contract, if available

3) A Plot Plan/Site Plan

Minor or Major site plan review will be required for the above proposed projects. The attached checklist outlines the minimum standards for a site plan.

4) Building Plans

Unless exempted by State Law, construction documents must be designed by a registered design professional.

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to

enforce the provisions of the codes applicable to this permit.	
Signature of applicant:	Date: U G

Building Permit Fee: \$25.00 for the 1st \$1000.cost plus \$5.00 per \$1,000.00 construction cost thereafter.

Additional Site review and related fees are attached on a separate addendum



CITY OF PORTLAND, MAINE

Department of Building Inspection

Certificate of Occupancy

LOCATION

400 Congress St. CBL: 032-G-001

Issued to A&M Partners Date of Issue

2/29/00

This is to certify that the building, premises, or part thereof, at the above location, built - altered changed as to use under Building Permit No. 990599, has had final inspection, has been found to conform substantially to requirements of Zoning Ordinance and Building Code of the City, and is hereby approved for occupancy or use, limited or otherwise, as indicated below.

PORTION OF BUILDING OR PREMISES

APPROVED OCCUPANCY

3rd floor northwest corner of Congress & Exchange Streets

Limiting Conditions:

Office Use group B Type 2B BOCA 96

e supersedes

Inspector of Buildings

is certificate identifies lawful use of building or premises, and ought to be transferred from when property changes hands. Copy will be furnished to owner or lessee for one dollar.