#### City of Portland. Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Location of Construction: Owner: Phone: Permit No: 15 Temple Street 04101 City of Portland home Given Lessee/Buver's Name: Owner Address: Phone: BusinessName: 369 Congress Street 04103 Front Samearcha Fresh Samantha Permit Issued: Address: Phone: Contractor Name: Dunty Hagen Mone Given 878-9664 OCT 2 1 1999 COST OF WORK: Proposed Use: PERMIT FEE: Past Use: \$ \$ 36.40 Estail/Food CHESIA FIRE DEPT. Approved INSPECTION: □ Denied Use Group: Type: Zone: CBL: 032-H-004 Signature: Signature: Zoning Approval: Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) Action: Approved Special Zone or Reviews: I Building Sign 4' a 8' Rigid Four Carved Sign. Approved with Conditions: □Shoreland П Denied □ Wetland ☐ Flood Zone ☐ Subdivision Signature: Date: ☐ Site Plan mai ☐minor ☐mm ☐ Permit Taken By: Date Applied For: LA 10-7-99 Zoning Appeal □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. □ Miscellaneous Building permits do not include plumbing, septic or electrical work. □ Conditional Use 3. Building permits are void if work is not started within six (6) months of the date of issuance. False informa-☐ Interpretation ☐ Approved tion may invalidate a building permit and stop all work... □ Denied \*\*\*Call for Pick Up: Honty Hagen 828-9664 Historic Preservation □ Not in District or Landmark □ Does Not Require Review ☐ Requires Review PERMIT ISSUED WITH REQUIREMENTS Action: CERTIFICATION ☐ Appoved ☐ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been ☐ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit 10-7-99 SIGNATURE OF APPLICANT ADDRESS: DATE: PHONE: PERMIT ISSUED WITH REQUIREMENTS RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE:

CEO DISTRICT

# INFORMATION REQUIREMENTS FOR SIGN PERMIT APPLICATION

Applicants for a sign permit will be asked to submit the following information to the Code Enforcement Office:

- 1. Certificate of Liability listing the City as additional insured.
- 2. Letter of permission from the owner
- 3. A sketch plan of lot, indicating location of buildings, driveways and any abutting streets or right of ways. Lengths of building frontages and street frontages should be noted. (see attached)
- 4. Indicate on the plan all existing and proposed signs
- 5. Computation of the following:
  - A) Sign area of each existing and proposed building sign
  - B) Sign area height and setback of each existing and proposed freestanding sign
- 6. A sketch of any proposed sign(s), indicating dimensions, materials, source of illumination and construction method (see attached).
- 7. Certificate of flammability required for awning/canopy at time of application.
- 8. UL # required for lighted signs at the time of application.

Fee for permit - \$30.00 plus \$0.20 per square foot

Fee for awning based on cost of work - \$30.00 for the first \$1,000.00, \$6.00 for each additional \$1,000.000.

**NOTE:** Once a sketch plan has been filed for a property, the code enforcement office will keep a record of the plan so that a new sketch plan will not be required for later changes to signage on the property. In such an instance, applicants will only be required to submit information applicable to the new sign.

### SIGNAGE PRE-APPLICATION

### PLEASE ANSWER ALL QUESTIONS

ADDRESS: 15 TEMPLE STREET	ZONE: 3-3
OWNER: FREST GAMANTHA	
APPLICANT: HAGEN DESIGN	
ASSESSOR NO. 032 H 004	
SINGLE TENANT LOT? YES NO  MULTI TENANT LOT? YES NO  FREESTANDING SIGN? YES NO_X DIMENSIONS	
(ex. pole sign )  MORE THAN ONE SIGN? YES NO DIMENSIONS  BLDG. WALL SIGN? YES NO DIMENSIONS  (co. la	_
(attached to bldg)  MORE THAN ONE SIGN? YES NO DIMENSIONS	
LIST ALL EXISTING SIGNAGE AND THEIR DIMENSIONS:  LOT FRONTAGE (FEET): BLDG FRONTAGE (FEET): AWNING YES NO IS AWNING BACKLIT? YES NO HEIGHT OF AWNING:  IS THERE ANY COMMUNICATION, MESSAGE, TRADEMARK OR SYMBOL ON  **** TENANT BLDG. FRONTAGE (IN FEET)  **** REQUIRED INFORMATION	
BUILDING SIGN 4' x 8' = 32 SF	
A SITE SKETCH AND BUILDING SKETCH SHOWING EXACTI	Allowed)
EXISTING AND NEW SIGNAGE IS LOCATED MUST BE PROVI AND/OR PICTURES OF PROPOSED ARE ALSO REQUIRED.	
SIGNATURE OF APPLICANT:	DATE: 10 7 9

## THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

# Sign Permit Pre-Application Attached Single Family Dwellings/Two-Family Dwelling Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE\*\*If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Addressof Construction (include Portion of Building)	ID TEMPLE STREET	04101				
Total Square Footage of Proposed Structure	- Square Footage of Lot					
Tax Assessor's Chart, Block & Lot Number  Chart# 032 Block# H Lot# 004	Owner: CITY of PORTUAND Telephone#:					
Owner's Address: FREST SAMA STATES	Lessoe/Buyer's Name (If Applicable) FRESH SAMAWTHA	Total Sq. Ft. of Sign Fee 32 F \$36.40				
Proposed Project Description: (Please be as specific as possible)  BUILDING THE HUXBRUL 4'x 8' RIGID FRAM CARNED SIGN -  SPECIAL SIGN WORKS OF ART CENTAINED SIGNAGE "APPLE"						
Contractor's Name, Address & Telephone MCNTY : H		Rec'd By				
Current Use: PETAIL/FOOD Proposed Use: CAULE						
Signature of applicant:	Date: \O/	17/99				
Signage Permit Fee: \$30.00 plus .20 per square foot of signage						

DEPT. OF BUILDING INSPECTION
CITY OF PORTLAND, ME

OCT - 6 1999



MINER ALEN







Samantha

TOTAL GOBEFRANT

HAGEN DESIGN

299 Danforth Street Portland, Maine 04102 207.828.9664 207.828.8097 Fax

16-9"





PAINTED

· TOTAL 32 SF

## HAGEN DESIGN

299 Danforth Street Portland, Maine 04102 207.828.9664 207.828.8097 Fax Scale:

Date: 10/6/99

Job: 0

Samantha



BUILDING SIGN



### BUILDING PERMIT REPORT

DATE: <u>800T.99</u>	ADDRESS: 15 Temple	STE	CBL: 032-H-004
REASON FOR PERMIT:	Carved Sign		
BUILDING OWNER:	City of PorTLand	1	
PERMIT APPLICANT:	resh Saman Tha	/ _/Contractor_	Monty Hugen.
USE GROUP		UCTION TYPE	/
	Code (The BOCA National Building Code/I cal Code (The BOCA National Mechanical C	•	Amendments)
	CONDITION(S) OF	APPROVAL	
This permit is being issued w	ith the understanding that the following con	ditions are met	×1, *34
Approved with the following	conditions:		

\$1.

This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained.

(A 24 hour notice is required prior to inspection)"

ALL LOT LINES SHALL BE CLEARLY MARKED

BEFORE CALLING."

- 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
- 4. Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' o.c. between bolts. (Section 2305.17)
- 5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.
- 6. Precaution must be taken to protect concrete from freezing. Section 1908.0
- 7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1996)
- 9. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211
- 10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
- 11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 ¼" and not greater than 2". (Sections 1021 & 1022.0) Handrails shall be on both sides of stairway. (Section 1014.7)
- 12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
- 13. Stair construction in Use Group R-3 & R-4is a minimum of 10" tread and 7 3/4" maximum rise. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)
- 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
- 15. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)

Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits 16. directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1) 17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0) The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic 18. extinguishment. (Table 302.1.1) All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of 19. the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be installed and maintained at the following locations): In the immediate vicinity of bedrooms In all bedrooms In each story within a dwelling unit, including basements In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved 20. type. (Section 921.0) 21. The Fire Alarm System shall maintained to NFPA #72 Standard. 22. The Sprinkler System shall maintained to NFPA #13 Standard. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 23. of the City's Building Code. (The BOCA National Building Code/1996) 24. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year". 25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code, (Crawl spaces & attics). 26. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until 27. all electrical (min.72 hours notice) and plumbing inspections have been done. 28. All requirements must be met before a final Certificate of Occupancy is issued. All building elements shall meet the fastening schedule as per Table 2305,2 of the City's Building Code (the BOCA National Building 29. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical 30. Code/1993). (Chapter M-16) Please read and implement the attached Land Use Zoning report requirements. 31. 32. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.

- Glass and glazing shall meet the requirements of Chapter 24 of the building code. 33.

All signage, sh 1996).	all be done in accordance with Se	ction 3102.0 signs of the C	City's Building Code, (The B	OCA National Building Code

et Hoffses, Building Inspector Lt. McDougall, PFD

Marge Schmuckal, Zoning Administrator

PSH 7/24 99

38.

<sup>\*\*</sup>On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.