

<u>WALL TYPES</u> 1 1/2" = 1'-0"

- REMOVE EXISTING FLOORING AND SUBSTRATES DOWN TO ORIGINAL

FLOOR SHEATHING - NEW FINISHED FLOORING AS SCHEDULED

 3 /16" RUBBER ACOUSTIC MAT,
PLITEQ GENIEMAT RST05 (OR APPROVED EQUAL)

- NEW 5/8" SHEATHING SHIMMED LEVEL

- EXISTING BOARD FLOOR SHEATHING 1" THICK +/-

EXISTING 2" X 12" FLOOR JOISTS
@ 21-24" O.C. VIF. REFER TO
STRUCTURAL DRAWINGS FOR
REINFORCING REQUIREMENTS

 - 3 1/2" THICK MINERAL WOOL INSULATION, ROXUL COMFORTBATT OR APPROVED EQUAL)
- EXISTING 2X STRAPPING TO REMAIN

- REMOVE EXISTING PLASTER & LATH, REPLACE AND EXTEND AS REQUIRED CONTINUOUS 1/2" ACOUSTIC GWB

- NEW SUSPENDED CEILING ON METAL FRAMING, REFER TO CEILING PLANS FOR TYPE AND HEIGHT

— 8" STEEL CHANNEL FRAMING (SEE STRUCTURAL DRAWINGS)

— 3 1/2" THICK MINERAL WOOL INSULATION, ROXUL COMFORTBATT OR APPROVED EQUAL)

— 7/8" METAL HAT CHANNELS — 5/8" GYPSUM WALL BOARD CEILING

 NEW FINISHED FLOORING AS SCHEDULED
3 /16" RUBBER ACOUSTIC MAT.

PLITEQ GENIEMAT RST05 (OR APPROVED EQUAL)

 NEW 5/8" SHEATHING SHIMMED LEVEL
EXISTING BOARD FLOOR

SHEATHING 1" THICK +/-

— EXISTING 2" X 12" FLOOR JOISTS @ 16" O.C. VIF.

— 3 1/2" THICK MINERAL WOOL INSULATION, ROXUL COMFORTBATT OR APPROVED EQUAL)

— EXISTING 2X STRAPPING TO REMAIN

REMOVE EXISTING PLASTER & LATH, REPLACE AND EXTEND AS REQUIRED CONTINUOUS 1/2" ACOUSTIC GWB

 NEW SUSPENDED CEILING ON METAL FRAMING, REFER TO CEILING PLANS FOR TYPE AND HEIGHT

— 3 /16" RUBBER ACOUSTIC MAT, PLITEQ GENIEMAT RST05 (OR APPROVED EQUAL)

 NEW 5/8" SHEATHING SHIMMED LEVEL
EXISTING BOARD FLOOR

SHEATHING 1" THICK +/-

— EXISTING 2" X 12" FLOOR JOISTS
@ 16" O.C. VIF.

 EXISTING CEILINGS WITHIN FIRST FLOOR SPACES TO REMAIN IN PLACE

