## City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction: 195 Biddle Street 0410	Owner: George Burns 133 Middle Associate	s LLC	Phone:		Permit No:
Owner Address:	Lessee/Buyer's Name:	Phone:	Business	sName:	990867
Contractor Name:	Address:	Phone:			Permit Issued:
Past Use:	Proposed Use:	COST OF WORK	:	PERMIT FEE:	AUG 1 3 1999
Retail	Same	<pre>\$ ₽ FIRE DEPT. □ A □ De Signature:</pre>	nied	INSPECTION: SI 1999 Use Group: M Type: 322 BOCA 96 Signature: Hoff	Zone: CBL: 032-H-022 Zoning Approval:
Proposed Project Description:		PEDESTRIAN AC			N. 17-1
2x4 Sandwich Board Sign		A	pproved pproved w enied	vith Conditions:	Special Zone or Reviews:
Permit Taken By:	Date Applied For:		-12-99		Site Plan maj 🗆 Site Plan D
<ol> <li>This permit application does not preclude the A</li> <li>Building permits do not include plumbing, sep</li> <li>Building permits are void if work is not started tion may invalidate a building permit and stop</li> </ol>	ptic or electrical work. within six (6) months of the date of issua	nce. False informa-	Street E 041		□ Variance □ Miscellaneous □ Conditional Use □ Interpretation □ Approved □ Denied Historic Preservation □ Not in District or Landmark □ Does Not Require Review □ Requires Review Action:
I hereby certify that I am the owner of record of the authorized by the owner to make this application a if a permit for work described in the application is areas covered by such permit at any reasonable ho	named property, or that the proposed wor s his authorized agent and I agree to confi issued, I certify that the code official's aut ur to enforce the provisions of the code(s	orm to all applicable l horized representative applicable to such po Aug. 12, 19	laws of thi e shall hav ermit	is jurisdiction. In addition,	□ Appoved □ Approved with Conditions □ Denied Date:
SIGNATURE OF APPLICANT	ADDRESS:	DATE:		PHONE:	
RESPONSIBLE PERSON IN CHARGE OF WORK	K, TITLE rmit Desk Green–Assessor's Canary	-DPW Pink_Publ	ic File	PHONE:	

Ty Foundation: Framing: Plumbing: Final: Other:		5-5100 Argn mets lode Requirements MD	COMMENTS
Type Inspection Record Date			

	/ / BUILDING PERMIT REPORT
	DATE: 12/19/99 ADDRESS: 195 Middle ST. CBL: 032-H-022
	REASON FOR PERMIT: SIdewalk SIGN
	BUILDING OWNER: George Burts
	PERMITAPPLICANT: STeingass IContractor
	USE GROUP SIde walk Sign, construction type
	The City's Adopted Building Code (The BOCA National Building Code/1996 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
	CONDITION(S) OF APPROVAL
	This permit is being issued with the understanding that the following conditions are met: $\frac{\times}{1}$
	Approved with the following conditions:
Ł	<ol> <li>This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.</li> <li>Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)</li> </ol>
	Equipation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than

- 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
- 4. Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' o.c. between bolts. (Section 2305.17)
- 5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.
- 6. Precaution must be taken to protect concrete from freezing. Section 1908.0
- 7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 8. Private garages located <u>beneath habitable rooms</u> in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. <u>Private garages attached side-by-side to rooms</u> in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1996)
- All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211
- 10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
- 11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 ¼" and not greater than 2". (Sections 1021 & 1022.0) Handrails shall be on both sides of stairway. (Section 1014.7)
- 12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
- 13. Stair construction in <u>Use Group R-3 & R-4is a minimum of 10" tread and 7 ½" maximum rise</u>. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)
- 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
- 15. Every sleeping room below the fourth story in buildings of Use Groups R and 1-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)
- 16. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

- 17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)
- 18. The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)
- 19. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
  - In the immediate vicinity of bedrooms
  - In all bedrooms

.

- In each story within a dwelling unit, including basements
- In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.
- 20. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- 21. The Fire Alarm System shall maintained to NFPA #72 Standard.
- 22. The Sprinkler System shall maintained to NFPA #13 Standard.
- 23. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1996)
- 24. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- 26. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
- 27. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min.72 hours notice) and plumbing inspections have been done.
- 28. All requirements must be met before a final Certificate of Occupancy is issued.
- 29. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996).
- Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
- 31. Please read and implement the attached Land Use Zoning report requirements.
- 32. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.
- ,33. Glass and glazing shall meet the requirements of Chapter 24 of the building code.
- K34. All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code

1996). , accordance W TH X-35. 11 36. 37. 38. amuch Hollses, Building Inspector 80: McDougall, PFD Marge Schmuckal, Zoning Administrator PS117/24/92

\*\*On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

## THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

## Sign Permit Pre-Application Attached Single Family Dwellings/Two-Family Dwelling Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE\*\*If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Addressof Construction (include Portion of Building)	195	Middle ST	ö4	(01
Total Square Footage of Proposed Structure		Square Footage of Lot		
Tax Assessor's Chart, Block & Lot Number Chart# 32-Block# 1-4 Lot.# 01)	Owner: Geolg Mide	e Burns 193 the Associates L	Telephone#:	
Owner's Address: Michelle 1955 Michelle STEINGIASS Gallery	Lessee/Buyer's Na ATTAL: A	ame (If Applicable)	Total Sg. Ft. of Sign 2'× 4'	536.60
Proposed Project Description:(Please be as specific as possible)	Sandu	sich Board	d Sigr	)
Contractor's Name, Address & Telephone			Rec	c'd By UB
Current Use: Retai		Proposed Use: Sam	e	

Signature of applicant:	Date: \$10/99
Signage Permit Fee: \$30.00 plus .20 per	square foot of signage
SIDEWALK SANDWICH SIGN	DEPT. OF BUILDING INSPECTION CITY OF PORTLAND, ME
21	STORIE AND, ME
ZXY	ALIC 1 2 1000



	er Cast-Morse, Payson chool Street	& Ncyes	ONLY AND HOLDER, T	CONFERS NO RI HIS CERTIFICAT	ED AS A MATTER OF INF GHTS UPON THE CERT E DOES NOT AMEND, E FORDED BY THE POLIC	FICATE XTEND OR
	land ME 04841		1	The second se	AFFORDING COVERAG	Contraction of the local division of the loc
	007 504 0373	007 504 0147	COMPANY	TRAVELERS I	NSURANCE COMPAN	Y
ONG NO		0.207-594-9147	COMPANY			
			B	·		-1-
	The Stein Gallery,	Transac Inc	COMPANY			
	195 Middle St. Portland ME 04101		COMPANY			
	ICATED, NOTWITHSTANDING ANY RED RTIFICATE MAY BE ISSUED OR MAY PE	DE INSURANCE LISTED BR.Q'W HAVE BEEN UIREMENT, TERM OR CONDITION OF ANY I RTAIN, THE INSURANCE AFFORDED BY TH POLIC ES. LIMITS SHOWN MAY HAVE BEEN	CONTRACT OR OTHER DO	CUMENT WITH RESPE	CT TO WHICH THIS	
R	TYPE OF INSURANCE	POLICY NUMBER	POLICY EFFECTIVE DATE (MM/DD/YY)	POLICY EXPIRATION DATE (MM/DD/YY)	LINITS	
_	ENERAL LIABILITY				GENERAL AGGREGATE	\$ 2000000
	COMMERCIAL GENERAL LABILITY	I680348N8961	05/01/98	05/01/01		19
-	CLAIMS MADE CCCUR				PERSONAL & ADV INJURY	3 1000000
T	OWNER'S & CONTRACTOR'S PROT		1		EACH OCCURRENCE	\$ 1000000
X	BOP		Ł		FIRE DAMAGE (Any one fire)	\$ 300000
5					MED EXP (Any one parson)	\$ 5000
AL	ANY AUTO				COMBINED SINGLE LIMIT	5
I I	ALLOWNED AUTOS				BODILY INJURY (Par parson)	\$
	HIRED AUTOS				BODILY INJURY (Per accident)	\$
-	1				PROPERTY DAMAGE	\$
G	RAGE LIABILITY				AUTO ONLY - EA ACCIDENT	5
	ANY AUTO				OTHER THAN AUTO ONLY	
			1		EACH ACCIDENT	5
			1		AGGREGATE	ž
E)	CESS LIADUTY				EACH DCCURRENCE	\$
	UMBRELLA FORM		J		AGGREGATE	S
	OTHER THAN UMBRELLA FORM					s
	ORKERS SIDMPENSATION AND				TORY LIMITS	
E	PLOYERS' LIABILITY				EL EACH ACCIDENT	5
	E PROPRIETOR		i l		EL DISEASE - POLICY LIMIT	\$
0	RTNERS/EXECUTIVE				EL DISEASE - EA EMPLOYEE	3
0	HER					
	TION OF OPERATION SLOCATIONS VE iding proof of inst as an additional i	HICLESSPECIAL TEMS France for the certif: nsured in respects to	icate holder General Lia	listed and bility only	naming	
ERTI	FICATE HOLDER		CANCELLATI	ON		
CITPORT City of Portland 389 Congress Street Portland ME 04101			SHOULD ANY OF THE ABOVE DESCRIBED POLICIES & CANCELLED BEFORE THE EXPIRATION DATE THEREOF. THE ISSUING COMPANY WILL ENDEAVOR TO MAIL 10 DAYS WRITTEN NOTICE TO THE CERTIFICATE HOLDER NAMED TO THE LEFT BUT FAILURE TO MAIL SUCH NOTICE SHALL IMPOSE NO OBLIGATION OR LABILITY OF ANY KIND UPON THE COMPANY. ITS AGENTS OR REPRESENTATIVES. AUTHORIZED REPRESENTATIVE CLAUDER ACORD CORPORATION 1			
			ALTHORIZED RE	PRESENTATIVE		

TOTAL P.01



SIDEWALK SANDWICH SIGN