# City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction:	Owner:		Phone:	Permit No: 0 1 0
10 Exchange St 1st Fl. Suite			774-8300	761340
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName:	E PERMIT ISSUED
**P.O. Ediz 367 Ptd 04112	Address:	Die		Permit Issued:
Contractor Name:	Address:	? Phor	16:	
Past Use:	Proposed Use:	COST OF WOI	K: PERMIT FEE:	DEC - 2 1998
	a contraction of the second	\$ 780,00	\$ 25.00	
Retail	Semie	FIRE DEPT.		CITY OF PORTLAND
			Denied Use Group: Type	e:
			ed mostly	Zone: CBL:
		Signature:	Signature:	
Proposed Project Description:		PEDESTRIAN	ACTIVITIES DISTRICT (P.A.I	D.) Zoning Approval:
Tehned our Descentions Int. Floore		Action:	Approved	Special Zone or Reviews:
Interior Renovations 1st floor	oury		Approved with Conditions:	□ □ Shoreland
			Denied	U Wetland
		Signature:	Date:	□ Flood Zone □ Subdivision
Permit Taken By:	Date Applied For:	Signature,	Date.	Site Plan maj Dminor Dmm
	Dute Applied For.	November 12, 199	8	
				Zoning Appeal
1. This permit application does not preclude t		ble State and Federal rules		
2. Building permits do not include plumbing	, septic or electrical work.			Conditional Use
3. Building permits are void if work is not sta		of issuance. False informa-	-	□ Interpretation
tion may invalidate a building permit and	stop all work			
				□ Denied
				Historic Preservation
			PERMIT ISSUED TH REQUIREMENTS	□ Not in District or Landmark
		WI	TERMIT IS	Does Not Require Review
			H REDUUSSUED	Requires Review
			REMEAN	Action:
			icivis	8.
	CERTIFICATION			Appoved
I hereby certify that I am the owner of record of				
authorized by the owner to make this application if a permit for work described in the application				intion,
areas covered by such permit at any reasonable				Date:
areas covered by such permit at any reasonable	nour to emoree the provisions of the	code(s) applicable to such	1 permit	
		Margaret and A.	1000	
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	
SIGNALUKE OF AFFLICANT	ADDRESS:	DATE:	FROME:	
RESPONSIBLE PERSON IN CHARGE OF WO	ORK, TITLE		PHONE:	CEO DISTRICT
16/6-14-	Permit Desk Green-Assessor's	Capany D DW Disk D	ublic File Ivon: Card Instants	A construction of the second sec
vvnite-	Fernit Desk Green-Assessor's	Ganary-D.P.W. PINK-P	ublic File livery card-inspecto	

Date - plans min W. Kuyert, W. K. R. Carpon remove Desity apreced in permit. **Inspection Record** Q.S tor areas 12/17/98 ht Mac & PS hewis & Mike Jasen discuss pand return to Wall Storingy, cloor. Requester Davyer, 24 Type clock Sizing & distances required 100 Foundation: Plumbing: Framing: Other: Final: 2 rully 0 What up the the Issue, PJL w for holens 20 2 Norte deveral Wiscussed 661 12/11 GVICA 2/16d 221

COMMENTS

ADDRESS:	10 BXCHANGE ST.	
PERMIT APPLICATION	FOR: Inhun Renalchan	
BUILDING OWNER:		
PERMIT APPLICANT:	DAda	
REVIEWER:	D. MOVEWS	te of
DATE OF DECISION	V(/3) 199	

### HISTORIC PRESERVATION REVIEW

Note: Your property is an individually designated landmark structure or is located within a designated historic district. As such, alterations to the building exterior or site which are visible from a public way are subject to review and approval under Article IX (Historic Preservation) of the Land Use Code. Your building or sign permit application has been reviewed to determine whether the nature or scope of the project requires review, and if so, whether it meets the standards of the historic preservation ordinance.

### ACTION

	1		
V	Does no	<b>Require Review</b> (e.g. Interior work only alteration is not readily visible from a public way)	
×	propose or site a alteratio	is finding is based on the understanding that the application entails <u>interior work only or that the</u> <u>d exterior alteration(s) will not be readily visible</u> from a public way. If your project entails exterior lterations (including the installation of sign(s), <u>awnings</u> , or exterior lighting for such) these ns must be reviewed and approved prior to commencing with the work. Contact 874-8726 for formation.	or,
	Denied	Reason for Denial:	
	Approv	ed as submitted	
	Approv	ed with conditions (see below)	
	Conditio	ons of Approval:	
		Contact Historic Preservation Staff (874-8726 or 874-8728) prior to installation of sign(s) to confirm approved location.	
		Your sign permit includes no reference to exterior lighting; if lighting is included, please submit information on fixtures and specifications on installation.	
	Other co	onditions:	
	Ī.		
	2.		
	3.		

## THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

**Building or Use Permit Pre-Application** 

Attached Single Family Dwellings/Two-Family Dwelling

### Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE\*\*If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

Total Square Footag	ge of Proposed Structure	1,183 H	Sq Sq	uare Footage of Lot		ar garman and a second and	
Tax Assessor's Char Chart# 032	rt, Block & Lot Number Block# I	Lot# 012	Excha	nge Associates		Telephone#: 774-82	300
Owner's Address: 2 70.Boy Portland	Exchange 75 1367 8,04112 C10	Sociates L Joe Soley	essee/Buyer's Name			ost Of Work: 780.00	Fee 25 0
Proposed Project De	escription:(Please be as spe	cific as possible) //	vierior	renovations	- EXF	PANCIEXIST	ing
Retail SP existing	BALL & CLOSE B 510 S&F	T ENPA	ud to	1,183 SQ FT.	uu a F	All int	reno

Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation.

•All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II. •All plumbing must be conducted in compliance with the State of Maine Plumbing Code.

•All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III.

HVAC(Heating, Ventililation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code.
 You must Include the following with you application:

1) ACopy of Your Deed or Purchase and Sale Agreement

2) A Copy of your Construction Contract, if available

3) A Plot Plan/Site Plan

Minor or Major site plan review will be required for the above proposed projects. The attached checklist outlines the minimum standards for a site plan.

#### 4) Building Plans

Unless exempted by State Law, construction documents must be designed by a registered design professional. A complete set of construction drawings showing all of the following elements of construction:

Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)

- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas
  equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. Jagree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant: X le/100	Date: ~ 1/12/28
Building Permit Fee: \$25,00 for the 1st \$1000.cost plu	A DATE OF CARDING STREET, AND A STREET, AND A STREET, A DATE OF AN ADDRESS OF CARDING STREET, AND A ST
Additional Site review and related fees	are attached on a separate addendum

2 1998

	BUIL	DING	PERMIT	REPORT
--	------	------	--------	--------

BUILDING PERMIT REPORT
DATE: 17 NOV 98 ADDRESS: 10 Exchange ST- CBL 032-I-01
REASON FOR PERMIT: TO MAKE INTERIOR REMOVATIONS (ONLY)
BUILDING OWNER: Exchange ASSOC,
CONTRACTOR:
PERMIT APPLICANT:
USE GROUP M BOCA 1996 CONSTRUCTION TYPE 33
CONDITION(S) OF APPROVAL
This Permit is being issued with the understanding that the following conditions are met:
Approved with the following conditions: * (*8 * 9 *10 *18 *19 *20, *24 *26 *30 *31.
<ol> <li>This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.</li> <li>Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services</li> </ol>
<ul> <li>must be obtained. (A 24 hour notice is required prior to inspection)</li> <li>2.5 Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the footing. The</li> </ul>
bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be protected with an approved filter membrane material. The pipe or tile shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
2.6 Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6 'o.c. between bolts. (Section 2305.17)
3. Precaution must be taken to protect concrete from freezing. Section 1908.0
It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
5. Private garages located <u>beneath habitable rooms</u> in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the eQUIVALENT of the BOCA/1996)
<ol> <li>All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 &amp; NFPA 211</li> </ol>
7 Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's
<ul> <li>building code.</li> <li>Guardrails &amp; Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that</li> </ul>
would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of stairway. (Section 1014.7)
<ul> <li>Headroom in habitable space is a minimum of 7'6". (Section 1204.0)</li> <li>Stair construction in Use Group R-3 &amp; R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group</li> </ul>
minimum 11" tread. 7" maximum rise.( Section 1014.0 ) The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8") 1014 4

11. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6 0 ) 1

- Every sleeping room below the fourth story in buildings of use Groups R and 1-1 shall have at least one operable window or 12. exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508inm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)
- 13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. Section 1010.1
- All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with 14. self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) Section 710.0
- The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by 15 providing automatic extinguishment. Table 302.1.1
- All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the 16. provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996). and NFPA 101 Chapter 18 & 19. (Sinoke detectors shall be installed and maintained at the following locations):
  - In the immediate vicinity of bedrooms
  - In all bedrooms
  - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2

- A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. Section 921.0
- ×18. ×19. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- The Sprinkler System shall maintained to NFPA #13 Standard.
- ¥ 20. All exit signs. lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)

21. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".

22. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.

Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code. (crawl spaces & attics) 23.

- 24. All electrical. plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
- All requirements must be met before a final Certificate of Occupancy is issued. 25.
- All building elements shall meet the fastening schedule as per Table 2305,2 of the City's Building Code. (The BOCA X 26. National Building Code/1996).
  - Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National 27. Mechanical Code/1993). (Chapter M-16)
  - Please read and implement the attached Land Use-Zoning report requirements. 28.
  - Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.3. of the City's 29. building code.
- Glass and glazing shall meet the requirements of Chapter 24 of the building code. 30.

This permit does Not authorize The removal of any 31. any part of a bearing wall-Wa 32 33. Samuel Hollys, Buyding Inspector

11 ym cc: Lt. McDougall, PFD Marge Schmuckal, Zoning Administrator

17.