Owner Address:  Contractor Name:  Past Use:	Leasee/Buyer's Name:  Address:  21 Hill 84	1	Phys B1112 BusinessName:	PERMIT ISSUED
Earle Heagan	Address:	Di		THE ISSUED
Past Use:		No. Yermouth, HF 640	97 829-5661	Permit Issued: NOV - 8 1996
	Proposed Use:	\$ 70,000,00	A 470 MI	
Office	Sane		Approved INSPECTION: Use Group: Type Signature:	Zone: CBL: 632-X-001
Proposed Project Description:		Digitature.	CTIVITIES DISTRICT (P.C.)	Zoning Approval:
Make Interior Resovations	(5th f1)	1	Approved Approved with Conditions: Denied	Special Zone or Reviews: Shoreland Wetland Flood Zone
		Signature:	Date:	☐ Subdivision☐ Site Plan maj ☐ minor ☐ mm ☐
Permit Taken By: Hary Greek	Date Applied Fo	01 November 1996		Zoning Appeal
<ol> <li>Building permits do not include plumbing, sep</li> <li>Building permits are void if work is not started tion may invalidate a building permit and stop</li> <li>15218 - 15219 - 15220</li> <li>3 - Single Axle Trails</li> </ol>	within six (6) months of the all work		WITH REQUIREMENTS	☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied  Historic Preservation ☐ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review  Action:
I hereby certify that I am the owner of record of the authorized by the owner to make this application a if a permit for work described in the application is areas covered by such permit at any reasonable how	s his authorized agent and I sued, I certify that the code	proposed work is authorized by the agree to conform to all applicable official's authorized representativ	e laws of this jurisdiction. In addi- ve shall have the authority to ente	ition, Denied
and the stay		01 November	1994	-
SIGNATURE OF APPLICANT For le Reagant	ADDRESS:	DATE:	PHONE:	
RESPONSIBLE PERSON IN CHARGE OF WORK		or's Canary-D.P.W. Pink-Pul	PHONE:	CEO DISTRICT

Location of Construction:	Owner:		Phone:	Premitable:
2 Monument Sq.		Life Assurance	961112	PERWIT ISSUED
Owner Address:	Leasee/Buyer's Name:	Phone:	BusinessName:	
	McCandless & Hunt	(5th floor)		n MOV. 0 4000
Contractor Name:	Address:	Pho		Permit Issued
Earle Reagan			4097 829-5661	01
Past Use:	Proposed Use:	COST OF WO		CITY OF PORTLAND
		\$ 70,000.00	A STATE OF THE STA	CHILAND
Office	Same	FIRE DEPT.	Approved INSPECTION:	747-25
			Denied Use Group Ty	Zone: CBL:
		0	14.1v	Zone: CBL: 032-K-001
Proposed Project Description:		Signature:	ACTIVITIES DISTRICT (F.)	Zoning Approval:
Troposed Tojest Essempton				01 311/1/9
Make Interior Renovations	(5th f1)	Action:	Approved Approved with Conditions:	Special Zone or Reviews:
			Denied /	☐ Shoreland ☐ Wetland
			\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	☐ Flood Zone
		Signature:	1) Andre Boate: W/1	ML Subdivision
Permit Taken By:	Date Applied For:		y	☐ Site Plan maj ☐ minor ☐ mm ☐
Mary Gresik		01 November 1996	1	Zouline August
1. This permit application doesn't preclude the	Applicant(c) from meeting applica	ble State and Enderal rule	6	Zoning Appeal  Variance
	- 1	ble state and redetal fule	S.	☐ Miscellaneous
2. Building permits do not include plumbing, so	☐ Conditional Use			
3. Building permits are void if work is not starte		of issuance. False informa	a-	☐ Interpretation
tion may invalidate a building permit and sto	op all work			☐ Approved☐ Denied
15218 - 15219 - 15220			un Pan	Historic Preservation
			MARINIT	☑ Not in District or Landmark
3 - Single Axle Trail	ors		REO, ISS.	Does Not Require Review
			UIREUED	☐ Requires Review
			WITH REQUIREMENTS	Action:
			20	
7.75 B 9	CERTIFICATION			□ Appoved
I hereby certify that I am the owner of record of the				
authorized by the owner to make this application				dition,
if a permit for work described in the application i areas covered by such permit at any reasonable he				Date: 11/1/1/6
areas covered by such permit at any reasonable in	our to enforce the provisions of the	e code(s) applicable to suc	en permit	
( ) ( )				- h/
and eggi		01 Novembe		- Didu. R
SIGNATURE OF APPLICANT Larle Reaga	n ADDRESS:	DATE:	PHONE:	11 nonces
RESPONSIBLE PERSON IN CHARGE OF WOR	K, TITLE		PHONE:	CEO DISTRICT
enterna enterna artematica per proper de la companya del la companya de la compan				olo district

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

AROLL

#### **BUILDING PERMIT REPORT**

DATE: 31 DEC 96 ADDRESS: 2 Monument Sq.	474 floor
REASON FOR PERMIT: To MAKE INTERIOR renovations (4)Th Flo	or)
BUILDING OWNER: Equitable Life Assurance	
CONTRACTOR: Caron Building Corp.	
PERMIT APPLICANT: APPROVAL: */16 */78 DENIED: *34	×1921.

## CONDITION OF APPROVAL OF DENIAL

- X1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
  - 2. Before concrete for foundation is placed, approvals from the Development Review coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
  - 3. Precaution must be taken to protect concrete from freezing.
  - 4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
  - Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
  - 6. Guardrail & Handrails A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
  - 7. Headroom in habitable space is a minimum of 7'6".
  - 8. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise.
  - 9. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
  - 10. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
  - 11. Each apartment shall have access to two (20 separate, remote and approved means of egress. A single exit-is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
  - 12. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's.
  - 13. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
  - 14. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's building code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
    - In the immediate vicinity of bedrooms
    - In all bedrooms
    - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

15. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. The Fire Alarm System shall be maintained to NFPA #72 Standard. The Sprinkler System shall maintained to NFPA #13 Standard. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023, & 1024, Of the City's building code, (The BOCA National Building Code/1996) × 19. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted. 20. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year". **≯**21. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services. 22. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office. Ventilation shall meet the requirements of Chapter 12 Sections 1210. of the City's Building Code. 23. It more The 20 sprinkter heads are being relocated Fire Marshalls Office Must More Then 5 heads The STATE 29. ex Esproval 1 26.

P. Samuel Hoffses, Chief of Code Enforcement

cc: Lt. McDougall, PFD Marge Schmuckal

#### BUILDING PERMIT REPORT

<b>DATE:</b> 1	ADDRESS: A Michemat Sz.
REASON FOR PERMIT:	100-1
BUILDING OWNER:	
CONTRACTOR:	
PERMIT APPLICANT:	APPROVAL: */4/*//5*/6*/7*/8

### CONDITION OF APPROVAL OR DENIAL

- 1. Before concrete for foundation is placed, approvals from the Development Review coordinator and Inspection Services must be obtained. (A24 hour notice is required prior to inspection)
- 2. Precaution must be taken to protect concrete from freezing.
- It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 4. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4 section 407.0 of the BOCA/1996)
- 5. Guardrail & Handrails-A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface tot he loser level. Minimum height all Use Groups 42:, except Use Group R which is 36". In occupancies in Use Group A,B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
- 6. Headroom in habitable space is a minimum of 7'6".
- 7. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use Group minimum 11" tread, 7" maximum rise.
- 8. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
- 9. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue, they shall

have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. feet.

- 10. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
- 11. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with selfclosers.
- 12. The boiler shall be protected by enclosing with on (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
- 13. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's building code Chapter 9, Section 19, 919.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
  - 1. In the immediate vicinity of bedrooms
  - 2. In all bedrooms
  - 3. In each story within a swelling unit, including basements
    In addition to the required AC primary power source, required smoke detectors in
    occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the
    AC primary power source is interrupted. (Interconnection is required)
- A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- 15.) The Fire Alarm System shall be maintained to NFPA =72 Standard.
- (16) The Sprinkler System shall maintained to NFPA #13 Standard.
- All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. of the City's building code. (The BOCA National Building Code/1996)
- 18. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.
- 19. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 20. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act, Title 5 MRSA refers, shall obtain a certification from a design professional that the plans of the facility meet the standards of construction required by this section. Prior to commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- This permit does not excuse the applicant from obtaining any license which may be needed from the fry Clerk's Office.

Samuel Hoffses, Chief of Inspection Services c.c. Lt. McDougall P. F. D.



# CITY OF PORTLAND, MAINE

Department of Building Inspection

# Certificate of Occupancy

LOCATION

2 Monument Square 032-K-001

Inspector of Buildings

Issued to Compass Magant/Equitable Life As	sur. Date of Issue 02 January 1997
This is to certify that the building, premises, or	
<ul> <li>changed as to use under Building Permit No. 961112 substantic'ly to requirements of Zoning Ordinance and Buoccupancy or use, limited or otherwise, as indicated below.</li> </ul>	, has had final inspection, has been found to conform illding Code of the City, and is hereby approved for
PORTION OF BUILDING OR PREMISES	APPROVED OCCUPANCY
5th Floor	Office
Limiting Conditions:	McCandless & Hunt
This certificate supersedes certificate issued	
Approved:	
(Date) Inspector	Inspector of Buildings

