City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Location of Construction: Owner: Phone: Permit No: One City Center City Center Assoc. 871-1080 010099 Owner Address: Lessee/Buver's Name: BusinessName: Citadel Comm. Co., 1 City Center 3rd f1. Portland Permit Issued: Contractor Name: Payton Construction Corp. Address: 75 Market Street, Portland, ME 772-7222 Past Use: **COST OF WORK:** PERMIT FEE: Proposed Use: \$1,158.00 \$ 189,000.00 FIRE DEPT. Approved INSPECTION: Commercial Commercia1 Use Group: B Type://B ☐ Denied Zene: 7 CBL: 032-L-002 BOCA99 Signature: Signature: 74 Zoning, Approvat. Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT (P.M.D.) Action: Approved Special Zone or Reviews Approved with Conditions: □ Shoreland Tenant fit-up of 9,500 sf of space. Denied □ Wetland ☐ Flood Zone □ Subdivision Signature: Date: ☐ Site Plan mai ☐minor ☐mm ☐ Permit Taken By: Date Applied For: Gayle January 23, 2001 gg **Zoning Appeal** This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. □ Variance 1. ☐ Miscellaneous 2. Building permits do not include plumbing, septic or electrical work. ☐ Conditional Use Building permits are void if work is not started within six (6) months of the date of issuance. False informa-3. ☐ Interpretation □ Approved tion may invalidate a building permit and stop all work... □ Denied PERMIT ISSUED WITH REQUIREMENTS **Historic Preservation** □ Not in District or Landmark ☐ Does Not Require Review *** Call Adam @ 772-7222 ☐ Requires Review E-market Zrawing □ Appoved Set MATE **CERTIFICATION** I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been ☐ Approved with Conditions authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, ☐ Denied if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit Date: January 24, 2001 PERMIT ISSUED SIGNATURE OF APPLICANT ADDRESS: DATE: PHONE: WITH REQUIREMENTS 1 RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE: **CEO DISTRICT**

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Minor/Minor Site Review, Building or Use Permit Pre-Application Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

010,, pu,, 11101111 11.1111111111111111111111111	must be induce before permits of any mine are	····		
Location/Address of Construction: One City Center, Portland, ME				
Space Space 9,500 sf	Square Footage of Lot N/A			
Tax Assessor's Chart, Block & Lot Number Chart# 32 Block# L Lot# 2	Owner: City Center Assoc.	Telephone#: 871-1080		
Lessee Buyer's Name (If Applicable) Citadel Communication Cop.	Owner's/Purchaser/Lessee Address: 1 City Center, 3rd Floor Portland, ME	Cost Of Work: Fee: \$ 189,000.00 \$ 1,158.0		
Proposed Project Description:(Please be as specific as possible) Tenant Fit-Up of 9,500 sf space, work includes selective demolition, drywall, acoustical ceilings, flooring, paint & wall covering, flooring, plumbing & HVAC, and electrical systems.				
Contractor's Name. Address & Telephone Payton Construction Corp., 75 Mar	ket Street, Portland, ME (207)	772-7222 Rec'd By:		
Separate permits are required f	or Internal & External Plumbing, HVAC and Electrical instal	lation.		

•All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II.
•All plumbing must be conducted in compliance with the State of Maine Plumbing Code.

•All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III.
•HVAC(Heating, Ventilation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code.

You must Include the following with you application:

A Copy of Your Deed or Purchase and Sale Agreement
 A Copy of your Construction Contract, if available
 A Plot Plan (Sample Attached)

A "minor/minor" site plan review is required prior to permit issuance. The Site plan must be prepared and sealed by a registered land surveyor (2 copies are required). A complete plot plan (Site Plan)includes:

- The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the distance from the actual property lines. Structures include decks porches, a bow windows cantilever sections and roof overhangs, as well as, sheds, pools, garages and any other accessory structures.
- Scale and North arrow; Zoning District & Setbacks
- First Floor sill elevation (based on mean sea level datum):
- Location and dimensions of parking areas and driveways:
- Location and size of both existing utilities in the street and the proposed utilities serving the building:
- Location of areas on the site that will be used to dispose of surface water.
- Existing and proposed grade contours

4) Building Plans (Sample Attached)

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued. I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the godgs applicable to this permit.

Signature of applicant:	Date: 01-18-01
Site Review Fee: \$300.00/Building Permit Fee: \$25.00 for the	1st \$1000.cost plus \$5.00 per \$1.000.00 construction cost thereafter

BUILDING PERMIT REPORT

DATE: 6February 2001 ADDRESS: ONE CITY CONTEX CBL: \$32-1-002
REASON FOR PERMIT: Interior regovations 2nd Fl. C. Toda Comm. Co.
BUILDING OWNER: City Center ASSOC
PERMIT APPLICANT: 194709 GOST. COMMICONTRACTOR PAYTON GOST. COP
PERMIT APPLICANT: 19700 Cost. Corp. CONSTRUCTION COST: 189000 PERMIT FEES: 1158,69
The City's Adopted Building Code (The BOCA National Building Code/1999 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
CONDITION(S) OF ADDDOMAI

CONDITION(S) OF APPROVAL

This permit is being issued with the understandi	ng that the following conditions shall be met: 🔾 /	\$0 401 80x93
\$27, *34, *37, *39 ×39		

1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

 Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."

- 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
- 4. Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. Section 2305.17
- 5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.

6. Precaution must be taken to protect concrete and masonry. Concrete Sections 1908.9-19.8.10/ Masonry Sections 2111.3-2111.4.

- 7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)
- 9. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211
- 10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
- 11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42". In occupancies in Use Group A, B.H-4, I-1, I-2, M, R, public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. Handrails shall be a minimum of 34" but not more than 38". Exception: Handrails that form part of a guard shall have a height not less than 36 inches (914 mm) and not more than 42 inches (1067 mm). Handrail grip size shall have a circular cross section with an outside diameter of at least 1 ½" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7)
- 12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
- 13. Stair construction in <u>Use Group R-3 & R-4 is a minimum of 10" tread and 7 ½" maximum rise.</u> All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)
- 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
- 15. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)
- 16. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
- 17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closure's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)
- 18. The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)

- 19. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms

In each story within a dwelling unit, including basements

- ∠ 20. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- 21. The Fire Alarm System shall be installed and maintained to NFPA #72 Standard.
- 22. The Sprinkler System shall be installed and maintained to NFPA #13 Standard.
- All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1999)
 - 24. Section 25 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
 - 25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
 - 26. Ventilation and access shall meet the requirements of Chapter 12 Sections 1210.0 and 1211.0 of the City's Building Code. (Crawl spaces & attics).
- 427. All electrical, plumbing and HVAC permits must be obtained by Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.
 - 28. All requirements must be met before a final Certificate of Occupancy is issued.
 - 29. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building Code/1996).
 - 30. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical Code/1993). (Chapter M-16)
 - 31. Please read and implement the attached Land Use Zoning report requirements.
 - 32. Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code.
- 33. Bridging shall comply with Section 2305.16.
- 34. Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2406.0)
 - 35. All flashing shall comply with Section 1406.3.10.
- 36. All signage shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1999).

*37. Your plans did Not pear The seal date and signature of The design professional - Section 1/4,8 of the bldg. code. No world 15 to be started until 1/2se plans are submitted.

*38. Fenétrations of wall, cerling and Floor assemblies required to be fireres.

1stance rated in accordance will sections 767.0, 799, 714.1.1 Through

*39. Type I Const. does not allow wood study.

Santiel Hotises, Building Inspector Ce: McDougall, PFD

Marge Schmuckal, Zoning Administrator Michael Nugent, Inspection Service Manager

PSH 10/1/00

**This permit is herewith issued, on the basis of plans submitted and conditions placed on these plans, any deviations shall require a separate approval.

***THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD. (You Shall Call for Inspections)

****ALL PLANS THAT REQUIRE A PROFESSIONAL DESIGNER'S SEAL, (AS PER SECTION 114.0 OF THE BUILDING CODE) SHALL ALSO BE PRESENTED TO THIS DIVISION ON AUTO CAD LT. 2000, DXF FORMAT OR EQUIVALENT.

AutoCAD digital format Final plans depicting the as-built condition must be filed with this office prior to closure.