Location of Construction:	+ Akane	Phone:	Lenn	Permit No:9 9 0 26 5	
Owner Address: F.O. Box 1000 York Harbe	Lessee/Buver's Name:	Phone:	Busines		PERMIT ISSUED
Contractor Name:	Address:	Ph	one:	0877	Permit Issued:
Past Use:	Proposed Use:	COST OF WO		PERMIT FEE: \$ 55.00	MR 2,6 1999
Office	Same	FIRE DEPT.	☐ Approved ☐ Denied	INSPECTION: Use Group: 5 Type:	CITY OF PORTLAND
Proposed Project Description:		Signature.	H.Ya-	BOCA 96 Signature: Aff	Zone: CBL: 32-P-001 Zoning Approval:
Interior Renovations		Action:	Approved	S DISTRICT (P.A.D.) with Conditions:	Special Zone or Reviews: ☐ Shoreland
Permit Taken By:	Date Applied For:	Signature:		Date:	☐ Subdivision ☐ Site Plan maj ☐minor ☐mm ☐
 This permit application does not preclude the A Building permits do not include plumbing, se Building permits are void if work is not started tion may invalidate a building permit and sto 	Zoning Appeal Variance Miscellaneous Conditional Use Interpretation Approved Denied				
Call for p/u 967-0877			W	PERMIT ISSUED TH REQUIREMENTS	Historic Preservation □ Not in District or Landmark □ Does Not Require Review □ Requires Review Action:
I hereby certify that I am the owner of record of the authorized by the owner to make this application a if a permit for work described in the application is areas covered by such permit at any reasonable ho	as his authorized agent and I agree t issued, I certify that the code offici-	to conform to all application all applications authorized representations.	able laws of th stative shall ha ach permit	is jurisdiction. In addition,	☐ Approved ☐ Approved with Conditions ☐ Denied
SIGNATURE OF APPLICANT	ADDRESS:	DATE:		PHONE:	-
RESPONSIBLE PERSON IN CHARGE OF WORL	K, TITLE			PHONE:	CEO DISTRICT

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Attached Single Family Dwellings/Two-Family Dwelling Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

2 CITY	CENTER 150)					
Total Square Footage of Proposed Structure		Square Footage of Lot				
Lessee/Buyer's Name (If Applicable) OFFICE ENVIRONMENTS 17000 \$55 BOSTON, MA. 02210						
CONV		CONFERENCE				
	10000	967-0872 Rec'd By				
ance with the cted in compli vith the 1996 N itioning) insta n: vour Deed or f your Constr 3) A Plot P the above pro	emal Plumbing, HVAC and Electrical inst 1996 B.O.C.A. Building Code as ance with the State of Maine Pluational Electrical Code as ame illation must comply with the 19 Purchase and Sale Agreement auction Contract, if available lan/Site Plan	allation. s amended by Section 6-Art II. umbing Code. nded by Section 6-Art III.				
	Owner: GEODA ~ M Lessee/Buyer's N OFFICE 270 SO BOSTO CONV CES WO CON For Internal & Extance with the cted in complicity the 1996 N itioning) instant: our Deed or If your Constrant 3) A Plot P	Owner: GEORGE L. ROGERS DAA - MIDDLEDEER ASSOC. Lessee/Buyer's Name (If Applicable) OFFICE ENVIRONMENTS 250 SUMMER ST. BOSTON, MA. 09210 CONVERT ON E. CONVERT ON E. Proposed Use: Same for Internal & External Plumbing, HVAC and Electrical instance with the 1996 B.O.C.A. Building Code a cited in compliance with the State of Maine Plaith the 1996 National Electrical Code as a meditioning) installation must comply with the 1900 our Deed or Purchase and Sale Agreement f your Construction Contract, if available 3) A Plot Plan/Site Plan the above proposed projects. The attached				

4) Building Plans

Unless exempted by State Law, construction documents must be designed by a registered design professional. A complete set of construction drawings showing all of the following elements of construction:

Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)

- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued. I certify that he Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to

enforce the provisions of the ender approvality to this permit.	
Signature of applicant:	Date: 3/25/99

Building Permit Fee; \$25.00 for the 1st \$1000.cost plus \$5.00 per \$1,000.00 construction cost thereafter.

Additional Site review and related fees are attached on a separate addendum

Call for 1/1 967-0877

BUILDING PERMIT REPORT				
DATE: 3/25/99 ADDRESS: 2 C.Ty CeNTER 1ST FLOOR CBL: \$32-P-001				
REASON FOR PERMIT: InTerior Renova [1075.				
BUILDING OWNER: Aforthhand Co Middle Deer ASSOG				
PERMIT APPLICANT: NorThLand Const. Co.				
USE GROUP BOCA 1996 CONSTRUCTION TYPE 3#				
CONDITION(S) OF APPROVAL				
This permit is being issued with the understanding that the following conditions are met:				
Approved with the following conditions: \(\frac{\frac{\frac{\pi}{27}}{27}}{27}\frac{\frac{\pi}{29}}{29}\frac{\pi}{23}\frac{\pi}{21}\frac{\pi}{22}\frac{\pi}{23}}				
1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.				
 Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. 				
(A 24 hour notice is required prior to inspection)				
3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than				
10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the				
top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter				
membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor				
elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be				
placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2 4. Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and				
a maximum 6' o.c. between bolts. (Section 2305.17)				
5. Waterproofing and damp proofing shall be done in accordance with Section 1813.0 of the building code.				
6. Precaution must be taken to protect concrete from freezing. Section 1908.0				
7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.				
8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent				
interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private				
garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area				
by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the				
garage side. (Chapter 4, Section 407.0 of the BOCA/1996) 9. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National				
Mechanical Code/1993). Chapter 12 & NFPA 211				
10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building				
Code.				
Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces				
for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open				
parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through				
any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but				
not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section				
with an outside diameter of at least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of				
stairway. (Section 1014.7)				
Headroom in habitable space is a minimum of 7'6". (Section 1204.0) Stair construction in <u>Use Group R-3 & R-4is a minimum of 10" tread and 7 %" maximum rise</u> . All other Use Group minimum 11"				
tread, 7" maximum rise. (Section 1014.0)				
14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4				
Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door				
approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate				
tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches				

directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)

(Section 1018.6)

16.

(610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.

Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits

Inspection Record Type Foundation: Framing: Plumbing: Final: Other:			4/4/99 mos of Disk hiller ni gen-con. OK.M.	COMMENTS
Date				

- 18. The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)
- 19. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.

- A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- X 21. The Fire Alarm System shall maintained to NFPA #72 Standard.
- 22. The Sprinkler System shall maintained to NFPA #13 Standard.
- All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1996)
 - 24. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
 - 25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
 - 26. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
- All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.
- 28. All requirements must be met before a final Certificate of Occupancy is issued.
- All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996).
 - 30. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
 - 31. Please read and implement the attached Land Use Zoning report requirements.
- 32. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.
- Glass and glazing shall meet the requirements of Chapter 24 of the building code.

Samuel Hoffses, Building Inspector Lt. McDougall, PFD

Marge Schmuckal, Zoning Administrator

PSI 12-14-98 Thym

35.

36.

**On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.