

I:\gensler\Projects\Portland\21820\URS Portland\_CENTRAL\_21820.rvt



**SHEET NOTES**

- 01 GC TO RETROFIT STAIR DOOR TO ACCOMMODATE CARD READER. MAINTAIN FIRE RATING. COORDINATE W/ SECURITY VENDOR. REPLACE HARDWARE FOR ADA
- 02 PROVIDE GFRG. ACCESS PANEL FOR CABLING. COORDINATE SIZE W/ IT CONSULTANT
- 03 PATCH ALL AREAS AFFECTED BY DEMOLITION TO MATCH ADJACENT SURFACES
- 04 PROVIDE BLOCKING IN WALL FOR NEW TV LOCATION. COORDINATE LOCATION W/ AV VENDOR
- 05 NEW FIRE EXTINGUISHER LOCATION
- 06 PROVIDE FIRE STOPPING AT ALL PENETRATIONS THROUGH RATED ASSEMBLIES (SLAB AND FIRE RATED CEILING) MAINTAIN EXIST. RATING
- 07 MAY NEED TO RECONFIGURE ADJACENT TENANT HARDWARE TO ALLOW 180 DOOR SWING. GC TO COORD. WITH LANDLORD/TENANT.
- 08 NEW DOOR AT THIS LOCATION TO MAINTAIN OR RESTORE EXISTING FIRE RATING OF CORRIDOR. GC TO VERIFY



2 CITY CENTER, PORTLAND, ME 04101



214 North Tryon Street  
Suite 2320  
Charlotte, NC 28202  
United States  
Tel 704.377.2725  
Fax 704.377.2807

URS CORPORATION  
MEP ENGINEERS  
27777 FRANKLIN ROAD  
SUITE 2000  
SOUTHFIELD, MI 48034  
Tel 248.204.5900  
Fax 248.204.5901

MONAGHAN WOODWORKS  
100 COMMERCIAL STREET  
SUITE 212  
PORTLAND, ME 04101  
Tel 207.775.2683  
Fax 207.772.6726

**GENERAL NOTES**

- A. ALL PARTITION TYPES TO BE ASA U.O.N.
- B. REFER TO SHEET G00.20 FOR PARTITION TYPE INFORMATION
- C. GC SHALL RE-INSTATE THE INTEGRITY OF ALL RATED SYSTEMS.
- D. LOCATE DOORS WITH CLOSERS NO LESS THAN 1'-6" TO EDGE OF DOOR FROM INTERSECTING PARTITION ON PULL SIDE AND 1'-0" ON PUSH SIDE.
- E. ABANDONED POKE THROUGH TO BE FILLED IN, PATCHED AND SMOOTHED MEETING THE FLOORS REQUIRED FIRE RATINGS.
- F. PATCH/REPAIR GYP AT ALL AREAS AFFECTED BY DEMOLITION.
- G. ALL DIMENSIONS AND ALIGNMENTS ARE TO FACE OF FINISH, UNLESS NOTED OTHERWISE. CONTRACTOR TO COORDINATE FINISH AND APPLICATION THICKNESSES TO ACHIEVE DIMENSIONS PROVIDED.
- H. ALL DOOR FRAMES HINGE SIDE TO BE LOCATED 4" FROM ADJACENT PERPENDICULAR PARTITION UNLESS NOTED OTHERWISE.
- J. PROVIDE FIRE RETARDANT TREATED WOOD BLOCKING AS REQUIRED FOR: WALL HUNG MILLWORK AND EQUIPMENT, WALL HUNG FLAT SCREEN DISPLAYS (NOT LESS THAN 40" X 40" X 3/4" PLYWOOD), CENTERED ABOVE CREDENZAS FOR ARTWORK (4'-0" @ 6'-0" AFF), PRIVATE OFFICE FURNITURE OVERHEADS.
- K. DO NOT SCALE DRAWINGS. WRITTEN DIMENSIONS GOVERN. ALL PARTITION TYPES, LOCATION, AND DIMENSIONS AND DOOR AND WINDOW LOCATIONS SHALL BE AS SHOWN ON ARCHITECT'S DRAWINGS. IN CASE OF CONFLICT, NOTIFY ARCHITECT PRIOR TO PARTITION INSTALLATION. ARCHITECT'S PARTITION PLAN SUPERSEDES OTHER PLANS.
- L. SEE G00.03 FOR ALL OUTLET, STROBE, SWITCH, THERMOSTAT, FIRE ALARM PULL, PLACEMENT. NOTIFY ARCHITECT IMMEDIATELY IN EVENT OF DISCREPANCY.
- M. CENTERLINE OF ALL PARTITIONS MEETING THE PERIMETER TO ALIGN WITH CENTERLINE OF MULLION U.O.N.

Date	Description
08/08/14	ISSUED FOR CONSTRUCTION

Seal / Signature

**Project Name**  
URS - PORTLAND

**Project Number**  
59 6222.900

**Scale**  
As indicated

**Description**  
PARTITION PLAN - LEVEL 02

**A02.02**

- AREA NOT IN CONTRACT
- NEW NON-RATED PARTITION
- EXISTING PARTITION TO REMAIN



**1 PARTITION PLAN - LEVEL 02**  
SCALE: 1/4" = 1'-0"