

		PAINT NOTES	
1.)	XXXXX		
2.)			
3.)			

1	GWB - PAINTED
2	GWB MOISTURE RESISTANT - PAINTED
3	FRP PANELS
4	BRICK TILE
5	STAINLESS STEEL WALL PANELS
6	CLEAN EXISTING EXPOSED BRICK
7	
8	
9	
3AS	SE
10	4" VINYL
11	
12	
FLC	ORS
20	WOOD FLOORING
	WOOD FLOORING FINISHED CONCRETE
21	
21 22	FINISHED CONCRETE
<ul><li>20</li><li>21</li><li>22</li><li>23</li><li>24</li></ul>	FINISHED CONCRETE  BATHROOM TILE
21 22 23 24	FINISHED CONCRETE  BATHROOM TILE
21 22 23 24 25	FINISHED CONCRETE  BATHROOM TILE
21 22 23	FINISHED CONCRETE  BATHROOM TILE
21 22 23 24 25 26	FINISHED CONCRETE  BATHROOM TILE
21 22 23 24 25 26 27	FINISHED CONCRETE  BATHROOM TILE
21 22 23 24 25 26 27 28	FINISHED CONCRETE  BATHROOM TILE
21 22 23 24 25 26 27 28	FINISHED CONCRETE  BATHROOM TILE  QUARRY TILE
21 22 23 24 25 26 27 28 CEI	FINISHED CONCRETE  BATHROOM TILE  QUARRY TILE  LINGS
21 22 23 24 25 26 27 28 CEII 30 31	FINISHED CONCRETE  BATHROOM TILE  QUARRY TILE  LINGS  2X2 ACT CEILING
21 22 23 24 25 26 27 28 CEI	FINISHED CONCRETE  BATHROOM TILE  QUARRY TILE  LINGS  2X2 ACT CEILING  GWB MOISTURE RESISTANT - PAINTED

FINISH SCHEDULE KEY

## ROOM FINISH GENERAL NOTES

- ALSO SEE INTERIOR ELEVATIONS FOR GRAPHIC DEPICTION'S OF EXTENT OF FINISHES
- 2 INSTALL MOISTURE RESISTANT (MOLD AND MILDEW RESISTANT) GWB IN ALL AREAS WHERE PLUMBING FIXTURES EXIST (CEILING AND WALLS IN BATHROOMS)
- CLOSETS SHALL BE FINISHED AS THE ROOMS THEY SERVICE
- ALL SPACES DESIGNATED AS CLOSET OR 'CL.' ARE TO RECEIVE ONE CLOTHING ROD 5'-2" AFF AND ONE 12" SHELF ABOVE THE ROD ALONG THE WALL OPPOSITE THE DOOR UNLESS NOTED

ALL SPACES DESIGNATED AS LINEN CLOSETS (LIN) OR PANTRY (PAN) ARE TO RECEIVE FOUR 12" SHELVES SPACED AT 1'-6" OC STARTING AT FINISH FLOOR. UNLESS NOTED OTHERWISE.

- PROVIDE APPROPRIATE BLOCKING IN WALLS OF ALL BATHROOMS BEHIND FIXTURES, PARTITIONS AND ACCESSORIES. PROVIDE BLOCKING FOR GRAB BARS IN WALLS OF BATHROOMS
- PROVIDE APPROPRIATE BLOCKING IN WALLS FOR DOOR STOPS
- PROVIDE APPROPRIATE BLOCKING IN WALLS FOR WALL HUNG CABINETRY
- BOTTOM EDGE OF GWB ON WALL SURFACES TO BE HELD UP 1/2" FROM CONCRETE FLOOR SURFACES
- PROVIDE VINYL TRANSITIONS STRIPS AT ALL FLOOR TRANSITIONS UNLESS OTHERWISE NOTED
- 10 UNLESS OTHERWISE NOTED IN DRAWINGS THE TYPICALWALL TYPE IS 'NA'. ALL OTHER PARTITION TYPES WILL BE INDICATED.
- 11 VERIFY UNDERLAYMENT MEETS MANUFACTURERS SPECIFICATION AT RESILIENT FLOORING

## FINISHES NOTES

1.) PREHUNG SOLID CORE DOORS WITH INTEGRAL TRIM

2.) VINYL BASE THROUGHOUT

SENATORE No. 3322

© 2016 RYAN SENATORE

ARCHITECTURE

AND CENTER ND, MAINE STAURANT

R H

ARCHITECTURE 565 CONGRESS STREET PORTLAND, MAINE 04101 207-650-6414 senatorearchitecture.com

CONSULTANTS:

**REVISIONS:** 

DATE: 20 DECEMBER 2016

PROJECT No. DRAWN BY: RRT, RJS

CHECKED BY: AS NOTED

SCALE: SHEET TITLE:

FINISH SCHEDULE