City of Portland, Maine - Buildin	g or Use Permit Appli <mark>catio</mark>	in 38 ingress Street, (04101, Tel: (207) 87	74-8703, FAX: 874-8716
Location of Construction:	Owner:		839-4296	Permit No. 60709
Owner Address:	Leasee/Buyer's Name:	Phone: Business	sName:	PERMIT ISSUED
Contractor Name:	Address:	Phone:		Permit Issued:
Past Use:	Proposed Use:	COST OF WORK:	PERMIT FEE: \$ 170.00	JUL 2 3 1996
3-1.6m	Same	FIRE DEPT. □ Approved	INSPECTION:	CITY OF PORTLAND
		☐ Denied	Use Group 9 2 Type 5 B	Zone: CBL: 033-6-023
Proposed Project Description:		Signature: PEDESTRIAN ACTIVITIE	Signature:	Zoning Approval:
5.5 × 5.00 (1 × 5.5) (0.5 × 5.5)		Action: Approved		Special Zone or Reviews:
Papairs after fire - No	physical or structural changes	Approved v Denied Signature:	vith Conditions:	☐ Shoreland ☐ Wetland ☐ Flood Zone ☐ Subdivision
Permit Taken By:	Date Applied For:	17 July 1996 ()	men of Just	☐ Site Plan maj ☐ minor ☐ mm ☐
	eptic or electrical work. d within six (6) months of the date of is op all work	suance. False informa-	WITH REQUIREMENTS	Actions
	CERTIFICATION	Ψ,	SOLUSSI	☐ Appoved
I hereby certify that I am the owner of record of the authorized by the owner to make this application if a permit for work described in the application is areas covered by such permit at any reasonable has SIGNATURE OF APPLICANT	as his authorized agent and I agree to c ssued, I certify that the code official's	conform to all applicable laws of the authorized representative shall have	is jurisdiction. In addition,	☐ Approved with Conditions ☐ Denied Date:
Ace Duckaling	402111		139-4-96	
RESPONSIBLE PERSON IN CHARGE OF WOR	K, TITLE		PHONE:	CEO DISTRICT 5
White-Pe	ermit Desk Green-Assessor's Car	nary–D.P.W. Pink–Public File I	vory Card-Inspector	

BUILDING PERMIT REPORT

	DAT	E: 22 July 96 ADDRESS: 40 Hanover ST.
	REA	SON FOR PERMIT: MAKE repairs after fire -
	BUI	IDING OWNER: Oren Abjauist
	CON	TRACTOR: ACC Building Movers APPROVED: *4 *5 *7 ×9
		MIT APPLICANT: BEATS: *//X/3×/4/×/~×/6 *20
		CONDITION OF APPROVAL OR DESTAL
	1.	Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be
	2.	chained. (A 24 hour notice is required prior to inspection) Precaution must be taken to protect concrete from freezing. It is strongly recommended that a registered land surveyor check all
1		foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
X		All vertical openings shall be enclosed with construction having a fire rating of at least one(1) hour, including fire doors with selfclosers.
4	5.	Each apartment shall have access to two(2) separate, remote and approved means of egress. A single exit is acceptable when it exits
		directly from the apartment to the building exterior with no communications to other apartment units.
	6.	The boiler shall be protected by enclosing with one(1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment. Sprinkler piping serving not more than six sprinklers may be connected to a domestic water supply having a capacity sufficient to provide 0.15 callons per minute, per square foot of floor throughout the entire area. An INDITATING shut-off valve shall be installed in an accessible location between the sprinkler and the connection to the domestic water supply. Minimum pipe size shall be 3/4 inch copper or 1 inch steel. Maximum coverage area of a residential sprinkler is 144 sq. feet per sprinkler.
X	7.	Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of ecress or rescue, they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20
X.	8. 9.	inches (508 mm), and a minimum net clear opening of 5.7 sq. feet. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's building code Chapter 9, section 19, 919.3.2(BOCA National Building Code/1993), and NFPA 101 Chapter 18 i 19. (Smoke detectors shall be installed and maintained at the following locations):

- 1. In the immediate vicinity of bedrooms
- 2. In all bedrooms
- 3. In each story within a dwelling unit, including basements In addition to the required AC primary power source, required stoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted.
- 10. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4 section 407.0 of the BOCA/1993)
- All. Guardrail & Handrails-A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, E-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
 - 12. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10, section & subsections 1023. & 1024. of the City's building code. (The BOCA National Building Code/1993)
- 13. Stair construction in Use Group R-3 & R-4 is a minimum of 9" tread and 8-1/4" maximum rise.—All other Use Group minimum 11" tread, 7"-maximum rise.
- & 14. Beadroom in habitable space is a minimum of 7'6".
- 15. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
- *16. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.
 - 17. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
 - 18. The builder of a facility to which Section 4594—C of the Maine State Human Rights Act, Title 5 MRSA refers, shall obtain a certification from a design professional that the plans of the facility meet the standards of construction required by this section. Prior to commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.

19. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's Office.

P. Samuel Eoffses Thief of Inspection Services

/el 3/16/95 20. The outside five excupe shall be brought into Compliance with section 5-2,8 of The NSPA 101 21. Safely odi

033-13-023

ELECTRICAL PERMIT City of Portland, Me.



To the Chief Electrical Inspector, Portland Maine:

The undersigned hereby applies for a permit to make electrical installations in accordance with the laws of Maine, the City of Portland Electrical Ordinance,

National Electrical code and the following specification:

Date	05	August	1996
Permit #		17040	

WNED Oren Alhqu	ist								
WNEROren Alhqu	iist		ADDRESS	S			TOTAL	FACH	FFF
OUTLETS				_			TOTAL	EACH	FEE
OUILEIS	Receptacles		Switches		Smoke Detector	7	<i>c</i> =	.20	10 /0
FIXTURES	(number of)	40	Switches	20	Smoke Detector		67	.20	13.40
FIXTURES	incandescent		fluorescent				1.5	.20	2.00
	fluorescent strip		Huorescent				15	.20	3.00
SERVICES	nuorescent strip			-				.20	
SERVICES	Overhead				TTL AMPSTO	800		15.00	
	Underground	-			TILAMIFSTO	800		15.00	
TEMPORARY SERV.	Oriderground			-		000		15.00	
TEMPORARY SERV.	Overhead				AMPS OVER	800		25.00	
	Underground	-		-	AIVIFSOVER	800		25.00	
METERS /4	(number of)	-				000		1.00	7 00
MOTORS	(number of)						1	2.00	1.00
RESID/COM	Electric units							1.00	
HEATING	oil/gas units							5.00	
APPLIANCES			CookTone		Wall Ovens			2.00	
APPLIANCES	Ranges Water heaters		Cook Tops Fans		The state of the s			2.00	
Disposals	Dishwasher	-	Compactors		Others (denote)			2.00	-
MISC. (number of)	Air Cond/win	-	Compactors	_	Others (denote)			3.00	
MISC. (Humber of)	Air Cond/cent	-						10.00	
	Signs	-					-	5.00	
	Pools	-					-	10.00	
	Alarms/res	-						5.00	
	Alarms/com	-					-	15.00	
		-					-		
	Heavy Duty Outlets	-		-				2.00	
		-					49	05.00	
	Circus/Carnv	-					X	25.00	
	Alterations			-			1	5.00	5.00
	Fire Repairs							15.00	
	E Lights	-					-	1.00	
	E Generators						-	20.00	
TRANCFORMER	Panels	-						4.00	
TRANSFORMER	0-25 Kva	1						5.00	
	25-200 Kva							8.00	
	Over 200 Kva				TOTAL ALIQUINIT	DIE	1	10.00	
	ANNUALISA FEE (O.	01414	EDOLAL OF O		TOTAL AMOUNT	DUE	05.00		0.7
2000 L L L L L L L L L L L L L L L L L L	MINIMUM FEE/C	V-4-17-0-11			MINIMUM FEE	vvvv	25.00		25.0
INSPECTION:	Will be ready			O	will call XXXXXX	XXXX	CXXX		
CONTRACTORS NAME					0.1.0.7.0				
ADDRESS	4 Blueberry	Ave	Saco.	ME	04072			_	
TELEPHONE	284-8946				-		1		
MASTER LICENSE No.	17040				SIGNATURE OF	100	TOACT	rop	

	interior	Date
10-2-90- Had quant rail loose or stains 11-41 h. Led Fire has fitten who all to issue kit his compression of their	1/2/4 Worler in progress on contracte pilled up dumporte, states	Type Foundation: Framing: Plumbing: Final: Other:

DATE:	REMARKS:
£/5/90	Actoen & Helpen on site
111	Throllow boxes not legal (outors, was
11	need house (sendice)
9	show board in ceiling (Not / com)
	Revove old & defective wiedne
4149	o Tomo i wen 15+ Floor weter only miss.
9/19/9	a Helpen & Helpen on gite
2.7	