



KEYED NOTES:

- 1 EXISTING FIXTURE TO REMAIN.
- 2 TOILET RELOCATED TO HERE (SEE KEY NOTE 4).
- 3 REMOVE EXISTING TOILET, REPLACE WITH NEW P-1. CONFIRM EXISTING ROUGH-IN DIMENSIONS PRIOR TO SUBMITTAL.
- 4 RELOCATE EXISTING TOILET, REPLACE WITH NEW P-1.
- 5 ADD A TRUEBRO LAVGAURD 2 ADA TRIM KIT TO EXISTING LAVATORY.
- 6 RE-HANG EXISTING LAVATORY, HEIGHT CHANGE FROM 36" AFF TO 34" AFF.
- 7 REMOVE EXISTING FIXTURE AND PROVIDE NEW FIXTURE. CTE ADJACENT SANITARY WASTE, VENT, HOT AND COLD WATER PIPING. ASSUME AVG. PIPE RUNS OF 20 FEET.
- 8 PROVIDE COUNTER MOUNTED EYEWASH NEXT TO SINK, TEMPERING VALVE BELOW.
- 9 PROVIDE 2" INDIRECT FUNNEL DRAIN UNDER SINK, CTE WASTE PIPING ABOVE FLOOR, PROVIDE AIR GAP PER PLUMBING CODE.

GENERAL NOTES:

- 1. ALL WORK PER MAINE STATE PLUMBING CODE.
- 2. REMOVE UNUSED PIPING AND CAP AT MAINS.
- 3. PROVIDE NEW FLOOR FLANGE FOR RELOCATED OR REPLACED TOILETS.
- 4. REFER TO SHEET A201 AND A401 FOR PLUMBING FIXTURE LAYOUT INFORMATION.

TAG	DESCRIPTION	BRANCH SIZES				NOTES
		CW	HW	VENT	WASTE	
P-1	WATER CLOSET-FLUSH VALVE, FLOOR MOUNT	1"	---	1-1/2"	3"	TYP FOR NEW OR RELOCATED
P-2	LAVATORY, WALL MOUNT	1/2"	1/2"	1-1/2"	1-1/2"	TYP FOR NEW OR RELOCATED
P-3	3-BAY SINK	1/2"	1/2"	1-1/2"	2"	
EW-1	HAND HELD EYEWASH	1/2"	1/2"	---	---	TEMPERING VALVE WITH 1/2" INLETS AND OUTLET