



<b>W3</b>	<b>1 HR RATED NON-BEARING PARTITION</b>
<b>2 X 4</b>	

1	<b>STEEL FRAMING</b> — STEEL STUDS 2 IN BY 4 IN. DOUBLE TOP PLATE AND SINGLE BASE PLATE. 1FT BY 4 IN SPACING FOR STUD LAYOUT MAX.
2	<b>GYPSUM BOARD</b> —(1) LAYER OF 5/8" GYP BD. EACH SIDE, PAPER SURF-CED, APPLIED PERPENDICULAR TO FRAMING WITH 1" TYPE S STEEL SCREWS SPACED 8" O.C.
3	<b>BLOCKING</b> —WOOD BLOCKING AS NEEDED
4	<b>TAPE AND COMPOUND</b> — VINYL, DRY OR PREMIXED JOINT COMPOUND APPLIED IN TWO COATS TO SCREW HEADS, PAPER TAPE, 2 IN WIDE, EMBEDDED IN FIRST LAYER OF COMPOUND OVER ALL JOINTS.
5	<b>BASE</b> — 4" VINYL COVE BASE THROUGHOUT (SEE FINISH PLAN)
6	<b>UNDERSIDE OF STRUCTURE</b>
7	<b>TOP OF STRUCTURE</b>
8	<b>INSULATION</b> — Fill cavity with R11 un-faced batt insulation

Prepared For:	<b>Avesta Housing</b>	307 Cumberland Ave. Portland, ME
Architect:		
Project:	<b>307 Cumberland Ave.</b>	307 Cumberland Ave. Portland, ME
Revisions:		
Date:		
Scale:		
<b>WALL TYPE</b>		
<b>S1.04</b>		