



|              |   |
|--------------|---|
| <b>W-1</b>   | <b>1 HR RATED NON-BEARING PARTITION</b> |
| <b>2 X 4</b> |   |

|   |   |
|---|---|
| 1 | <b>STEEL FRAMING</b> — STEEL STUDS 2 IN BY 4 IN. SINGLE TOP PLATE AND SINGLE BASE PLATE. 1FT BY 4 IN SPACING FOR STUD LAYOUT MAX.   |
| 2 | <b>GYPSUM BOARD</b> —(1) LAYER OF 5/8" GYP BD. EACH SIDE, PAPER SURF-CED, APPLIED PERPENDICULAR TO FRAMING WITH 1" TYPE S STEEL SCREWS SPACED 8" O.C.                             |
| 3 | <b>BLOCKING</b> —WOOD BLOCKING AS NEEDED  |
| 4 | <b>TAPE AND COMPOUND</b> — VINYL, DRY OR PREMIXED JOINT COMPOUND APPLIED IN TWO COATS TO SCREW HEADS, PAPER TAPE, 2 IN WIDE, EMBEDDED IN FIRST LAYER OF COMPOUND OVER ALL JOINTS. |
| 5 | <b>BASE</b> — 4" VINYL COVE BASE THROUGHOUT (SEE FINISH PLAN)   |
| 6 | <b>UNDERSIDE OF STRUCTURE</b>   |
| 7 | <b>TOP &amp; BOTTOM OF WALL</b> —STEEL TOP CAP 2 IN BY 4 IN. SINGLE TOP PLATE AND SINGLE BASE PLATE.  |
| 8 | <b>INSULATION</b> — Fill cavity with R11 un-faced batt insulation   |

|                  |                                  |                                  |
|------------------|----------------------------------|----------------------------------|
| Prepared For:    | <b>Avesta Housing</b>            | 307 Cumberland Ave. Portland, ME |
| Architect:       | 307 Cumberland Ave. Portland, ME |                                  |
| Project:         | <b>307 Cumberland Ave.</b>       | 307 Cumberland Ave. Portland, ME |
| Revisions:       |                                  |                                  |
| Date:            |                                  |                                  |
| Scale:           |                                  |                                  |
| <b>WALL TYPE</b> |                                  |                                  |
| <b>A3.01</b>     |                                  |                                  |