City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction:	Owner:	d	Phone:	Permit No:
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName:	11920
Contractor Name:	Address:	Phone: 761-9465		PERMIT IS USSUED
Past Use:	Proposed Use:	COST OF WOF	PERMIT FEE: \$ 210.00	APR 1 5 1999
Public Works Garage	Some		Approved INSPECTION: Use Group: Typ  Signature: Fig.	
Proposed Project Description:			ACTIVITIES DISTRICT (P.A.	Zoning Approval:
Renovation to Public Works Ga	rage	Action:	Approved Approved with Conditions: Denied	Special Zone or Reviews: Shoreland Wetland Flood Zone
Permit Taken By:	Date Applied For:	Signature:	Date:	☐ Subdivision☐ Site Plan maj ☐minor ☐mm ☐
Permit Taken By:	Date Applied For:	7-73-43		Zoning Appeal
<ol> <li>Building permits do not include plumb</li> <li>Building permits are void if work is not tion may invalidate a building permit a</li> </ol>	t started within six (6) months of the date o	f issuance. False informa-		☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied
*		V	PERMIT ISSUED VITH REQUIREMENTS	Historic Preservation  ☐ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review  Action:
N.				
I hereby certify that I am the owner of recon- authorized by the owner to make this applic if a permit for work described in the applica- areas covered by such permit at any reason	cation as his authorized agent and I agree tation is issued, I certify that the code official	o conform to all applicab al's authorized representa	le laws of this jurisdiction. In additive shall have the authority to er	dition, Denied
		3-19-99		
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	

## THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

## Building or Use Permit Pre-Application Attached Single Family Dwellings/Two-Family Dwelling Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE\*\*If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

82 Ha	LOUR St. Pout	11200	MF	
Total Square Footage of Proposed Structure		Square Footage of Lot		
Owner:	of Portland		Telephone#:	
Lessee/Buyer's 1	Name (If Applicable)	-	39 000 \$2/	
	,		n	
Coost Co	utuactour PoBo	× 10792	Poutland Rec'd By 04/04	
	Proposed Use: Sa	me_		
iance with the letted in comple with the 1996 litioning) instant: Your Deed or of your Construction 3) A Plot Por the above proplan.	1996 B.O.C.A. Building iance with the State of M. National Electrical Code allation must comply with Purchase and Sale Agree ruction Contract, if availar Plan/Site Plan posed projects. The attacher	Code as am aine Plumb as amended the 1993 ment	nended by Section 6-Art bing Code. d by Section 6-Art III.	
	for Internal & Exance with the cted in comply with the 1996 litioning) instant:  Your Deed or of your Construction of your Construction of your construction of your construction.	Square Footage of Lot  Owner:  City of Postland  Lessee/Buyer's Name (If Applicable)  Lessee/Buyer's Name (If Applicable)  Proposed Use:  From Internal & External Plumbing, HVAC and Elecance with the 1996 B.O.C.A. Building cred in compliance with the State of Movith the 1996 National Electrical Code litioning) installation must comply with the 1996 National Electrical Code litioning) installation must comply with the 1996 National Electrical Code litioning) installation must comply with the 1996 National Electrical Code litioning installation must comply with the 1996 National Electrical Code litioning installation must comply with the 1996 National Electrical Code litioning installation must comply with the 1996 Plan/Site Plan the above proposed projects. The attacher plan.	Lessee/Buyer's Name (If Applicable)  Lessee/Buyer's Name (If Applicable)  Cos S  Lessee/Buyer's Name (If Applicable)  Cos S  Proposed Use:  P	

equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas

Floor Plans & Elevations Window and door schedules

Foundation plans with required drainage and dampproofing

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant:	Date: 3.29-99

Building Permit Fee: \$25.00 for the 1st \$1000.cost plus \$5.00 per \$1,000.00 construction cost thereafter.

Additional Site review and related fees are attached on a separate addendum

BUILDING PERMIT REPORT
DATE: 4/1/99 ADDRESS: 82 Hanover ST. CBL: \$34-6-601
REASON FOR PERMIT: RenovaTe Public Works Garage.
BUILDING OWNER: Ty of for land
PERMIT APPLICANT: # /Lan / 10 (oas/ (ons/,
USE GROUP S-( BOCA 1996 CONSTRUCTION TYPE 5 B
CONDITION(S) OF APPROVAL
This permit is being issued with the understanding that the following conditions are met:
Approved with the following conditions: \( \( \)
1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained.
(A 24 hour notice is required prior to inspection)
3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the
footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the
top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter
membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor
elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be
placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
4. Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and
a maximum 6' o.c. between bolts. (Section 2305.17)
5. Waterproofing and damp proofing shall be done in accordance with Section 1813.0 of the building code.
6. Precaution must be taken to protect concrete from freezing. Section 1908.0
7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify
that the proper setbacks are maintained.  8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent
interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private
garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area
by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the
garage side. (Chapter 4, Section 407.0 of the BOCA/1996)
9. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National
Mechanical Code/1993). Chapter 12 & NFPA 211
10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building
Code.
11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces
for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use
Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open
parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but
not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section
with an outside diameter of at least 1 ¼" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of
stairway. (Section 1014.7)
12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use Group minimum 11"
tread, 7" maximum rise. (Section 1014.0)
14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
15. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door
approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate

directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)

(Section 1018.6)

16.

tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.

Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits

- 18. The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)
- 19. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be installed and maintained at the following locations):
  - In the immediate vicinity of bedrooms
  - In all bedrooms
  - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.

- A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
  - (21) The Fire Alarm System shall maintained to NFPA #72 Standard.
- \*22. The Sprinkler System shall maintained to NFPA #13 Standard.
- (23. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1996)
- 24. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- 26. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
- All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.
- 28. All requirements must be met before a final Certificate of Occupancy is issued.
- 29. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996).
- Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
  - 31. Please read and implement the attached Land Use Zoning report requirements.
  - 32. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.

33. Glass and glazing shall meet the requirements of Chapter 24 of the building code.

The Mechanical Equipment 15 being hung from The roof a Structural analysis Should be made To very The roofs Loading Capability.

A mason my Construction Shall be done in accordance with Section.

35. A Maso'nny Construction shall be done in accordant chapter 21 of The City's building Code

Lt. McDougall, PFD

Marge Schmuckal, Zoning Administrator

PSH 12-14-98 HUMLS

\*\*On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.