

PLAN A

DETAIL FOR CURTAINWALL FRAMING

EXTERIOR SHEATHING IS 1" BOARDS w/ 3/8" PLYWOOD BRISTLING

WINDOWS TO BE INSTALLED, TESTED, FLASHED TO MANUFACTURER'S SPECIFICATIONS

EXISTING POST 8"x6" FULL DIMENSION

EXISTING BEAM 10"x6" FULL DIMENSION

NEW HEADER 2x10 KD

NEW POSTS (2) 2x6 KD

AW 1/2 39x19 PARADIGM

MULL

FC 1/2 39x80 PARADIGM

NEW POSTS (2) 2x6 KD

AW 1/2 39x19 PARADIGM

MULL

FC 1/2 39x80 PARADIGM

NEW POSTS (2) 2x6 KD

AW 1/2 39x19 PARADIGM

MULL

FC 1/2 39x80 PARADIGM

EXISTING POST 12"x6 FULL DIMENSION

NEW 2x6 KD

136 1/2

DRYWALL BY OTHERS

EXISTING 2"x10" FULL DIMENSION

- TEMPERED NOT REQUIRED -
- GLAZING EDGE WILL BE GREATER THAN 10" FROM STANDING SURFACE -

BOTTOM PLATE (2) 2x6 KD

HT. FROM FLOOR +/- 22 1/4"

SPACING = 3"