




GENERAL NOTES:

- A. RESILIENT BASE MEET ASTM F 1861 TYPE VT (VINYL THERMOPLASTIC) GROUP I (SOLID HOMOGENEOUS) COVE WITH TOE 4" HIGH WITH PREFORMED OUTSIDE CORNERS AND ENDS AS MANUFACTURED BY ARMSTRONG WORLD INDUSTRIES, INC; OR JOHNSONITE.
- B. PROVIDE CONCRETE SLAB PRIMER ARDEX P-51 PRIMER OR P-82 ULTRA PRIMER; UNDERLAYMENT ARDEX K-15; LEVELING AND PATCHING COMPOUND ARDEX SD-F FEATHER FINISH; WATER RESISTANT ADHESIVE WITH A VOC LIMIT OF 50 g/L.

KEY NOTES: REPRESENTED BY THIS SYMBOL: #

1. EXISTING SALES FLOOR VCT PATTERN TO REMAIN - FIELD VERIFY LOCATION OF TILE REPEAT
2. REMOVE EXISTING SALES FLOOR VCT AS NEEDED TO PERFORM NEW WORK - INFILL WITH NEW VCT FLOORING TO MATCH EXISTING SALES VCT FLOORING MANUFACTURER, COLORS, TEXTURE AND PATTERN REPEAT
3. EXISTING SHOT BLAST CONCRETE FINISHED FLOOR IN PRODUCE COOLER TO REMAIN
4. EXISTING QUARRY TILE FLOORING TO REMAIN
5. REMOVE EXISTING QUARRY TILE FLOORING AS NEEDED TO PERFORM NEW WORK - INFILL WITH NEW QUARRY TILE FLOORING TO MATCH EXISTING MANUFACTURER, COLOR AND TEXTURE
6. PROVIDE QUARRY TILE TO CONCRETE TRANSITION - SEE DETAIL A2 / A502
7. PROVIDE PORCELAIN TILE TO VCT TRANSITION - SEE DETAIL B2 / A502
8. CONCRETE TOPPING TO BE LEVEL AND FLUSH WITH EXISTING PRODUCE COOLER FINISHED FLOOR - SHOT BLAST AND SEAL
9. GRIND JOINT AT CONCRETE TOPPING AND EXISTING CONCRETE SLAB TO BE LEVEL AND FLUSH - SHOT BLAST DISTURBED AREA
10. EXISTING VCT FLOORING TO REMAIN
11. EXISTING CARPET TILE TO REMAIN
12. EXISTING CARPET TO QUARRY TILE TRANSITION TO REMAIN
13. THIN SET PORCELAIN TILE TO BE SET ON EXISTING PREPARED CONCRETE SLAB - SEE FLOOR FINISH SCHEDULE ON A102.1 FOR MATERIAL DESCRIPTION
14. PROVIDE SLANT BASE AT FLOOR / WALL TRANSITION - TYPICAL AT FULL PERIMETER OF RESTROOM FLOOR EXCEPT AT OPENING
15. EXISTING FLOOR DRAIN - DISH CONCRETE TOPPING TO DRAIN TO CREATE POSITIVE DRAINAGE TO DRAIN
16. NEW FLOOR DRAIN
17. EXISTING CONCRETE SLAB - FIELD VERIFY IF CONCRETE TOPPING IS NEEDED TO HAVE SLAB LEVEL AND FLUSH WITH EXISTING VESTIBULE FINISHED FLOOR - SHOT BLAST AND SEAL

GRAPHIC LEGEND:

-  EXISTING FLOOR TO REMAIN FIELD COORDINATE TRANSITIONS WITH NEW WORK
-  INFILL TO MATCH EXISTING VESTIBULE QUARRY TILE FLOORING - FIELD VERIFY - AMERICAN OLEAN COLOR N03 DESERT 6 x 6 UNGLAZED FLOOR TILE
-  INFILL TO MATCH EXISTING SALES FLOOR FINISH VCT FLOORING PATTERN - FIELD VERIFY JOHNSONITE AZROCK COLOR : V-225 MILKSHAKE (FIELD) AND V-218 MALT (ACCENT)

FLOOR FINISH SCHEDULE

| # | TAG | COLOR | REMARKS |
|----|-------|--------------------|---------------------------------------|
| 13 | FF209 | TERRAIN P541 | 13X13 TILE VERANDA SERIES BY DAL TILE |
| 18 | TG200 | SEE A206 FOR COLOR | RESTROOM FLOOR TILE GROUT |



| NO | REVISIONS | DATE | BY |
|----|-------------------------|----------|-----|
| 0 | ISSUED FOR REVIEW | 11-10-16 | MJW |
| 0 | ISSUED FOR CONSTRUCTION | 11-14-16 | MJW |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

HARRIMAN
© 2016
Project No. 16166

Auburn, ME 207.784.5100
Portland, ME 207.775.0053
Portsmouth, NH 603.626.1242
Boston, MA 617.426.5050

DWG TITLE: **FLOOR FINISH PLAN NOTES**
LOCATION: **PRODUCE COOLER AND RESTROOMS PORTLAND, ME**

SCALE 1/8" = 1'-0"
DRAWN MJW
DATE: 11-14-2016
DRAWING NO. **A102.1**
Store No. 8351