Location of Construction:	Owner:	HELD .	Phone:	Permit No:
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName:	DERMIT ISSUED
Contractor Name:	Address:	Phone:	1	Permit Issued:
Past Use:	Proposed Use:	COST OF WORK	PERMIT FEE: \$ 54.00	AUG 1 6 1999
Office	name	FIRE DEPT. A	approved INSPECTION:	OLTY OF PORTLAND
- hi		Signature:	Use Group: 13 Typ BOCA 96 Signature: Help	Zone: CBL:
Proposed Project Description:		PEDESTRIAN AC	CTIVITIES DISTRICT (P.Y.	D.) Zoning Approval:
Interior renovations - Const m create 2 new offices. Install su wall to complete enclosure		Aine to A	approved spproved with Conditions: Denied Date:	□ Special Zone or Reviews: □ Shoreland □ Wetland □ Flood Zone □ Subdivision
Permit Taken By:	Date Applied For:	ag. 12, 1999 K.	Dute.	☐ Site Plan maj ☐minor ☐mm ☐
 This permit application does not preclude the A Building permits do not include plumbing, sep Building permits are void if work is not started tion may invalidate a building permit and stop 	tic or electrical work. within six (6) months of the date of			☐ Variance ☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied
I hereby certify that I am the owner of record of the authorized by the owner to make this application as if a permit for work described in the application is i areas covered by such permit at any reasonable hou	his authorized agent and I agree ssued, I certify that the code offic	sed work is authorized by the to conform to all applicable ial's authorized representative code(s) applicable to such p	laws of this jurisdiction. In added to the shall have the authority to en	lition, Denied
SIGNATURE OF APPLICANT	ADDRESS:	Aug. 12, 1999 DATE:	PHONE:	
		400-400 F 12077		
RESPONSIBLE PERSON IN CHARGE OF WORK			PHONE:	CEO DISTRICT

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application

Attached Single Family Dwellings/Two-Family Dwelling

Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Addressof Construction (include Portion of Building):	537 Congress St.	5th floor (SCC)
Total Square Footage of Proposed Structure	Square Footage of Lot	
Tax Assessor's Chart, Block & Lot Number	Owner: Hega Poalty	Thust Telephone#:
Chart# 037 Block# C Lot# 014	Hampiteact Hap	207-871-1080
Owner's Address: CO Dirigo mannt. Co One City Center Portland, Me. 04101	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee 4 \$5,000.
Proposed Project Description (Please be as specific as possible)	Construct mars wa	as beneath measurine
to create Inew ollies In	rotale supponder	seilings from oners to
Proposed Project Description: (Please be as specific as possible) to create I new offices In outer wall to complete	enclosure.	(2)
Contractor's Name, Address & Telephone		Rec'd By
(1) + mght - Drigo Mo	amt Co One City C	enter-Port and Recally
Current Use:	Proposed Use:	AME
Separate permits are required	for Internal & External Plumbing, HVAC and	Electrical installation
•All construction must be conducted in compli		
	cted in compliance with the State of	
 All Electrical Installation must comply w 		
•HVAC(Heating, Ventililation and Air Cond	[[[마마마마마마마마마마마마마마마마마마마마마마마마마마마마마마마마마마	with the 1993 BOCA Mechanical Code.
You must Include the following with you application		CITY OF PORTCAST
	our Deed or Purchase and Sale As fyour Construction Contract, if as	vailable 1000
2) A Copy o	3) A Plot Plan/Site Plan	AUG 1 2 1999
Minor or Major site plan review will be required for		ached
checklist outlines the minimum standards for a site p	olan.	B N W E L
	4) Building Plans	
Unless exempted by State Law, construc		
A complete set of construction drawings showing al	of the following elements of constru	ction:

Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)

- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant: When Knight	Date: 8-12-1999

Building Permit Fee: \$25.00 for the 13\\$1000.cost plus \$5.00 per \$1,000.00 construction cost thereafter. Additional Site review and related fees are attached on a separate addendum

System Consulting Corporation New Offices Scope of Work

August 11, 1999

New walls, doors with locksets, sidelight windows, & vinyl cove base

Construct new walls using 3-1/2" metal studs and ½" drywall to construct two new private offices. Walls to be insulated for sound reduction and to include 3'HX4'W tempered sidelight windows in front walls. Doors to be 3/0 X6/8 metal jambs with flush oak slabs to match existing. Both doors to receive lockset hardware to match existing office hardware. All walls to receive vinyl cove base to match existing.

Suspended Ceilings

Install 2X2 ceilings to match existing. A second layer of tiles will be placed on tiles in gridwork with face showing upwards to give a finished look when viewing from mezzanine.

Painting

Paint all new walls to match existing. Paint metal door frames and poly door slabs.

Sprinkler Work

Drain entire system & install two new sprinkler heads to meet code.

Electrical

Install two new wrap around florescent lighting fixtures on suspended ceilings. Install new light switches for lighting control in offices. Remove gang switches on outside of new walls and relocate.

RITH DING PERMIT DEPORT

DOLEDING LEGITI KELOKI
DATE: 13 Aug. 99 · ADDRESS: 537. Congress ST. CBL: 037-C-014 REASON FOR PERMIT: InTerior renovations
REASON FOR PERMIT: InTerior renovaTions
BUILDING OWNER: Hega RealTy TrusT
PERMIT APPLICANT: 1Contractor 1/ Knight Dirigo man
use group B construction type 2B
The City's Adopted Building Code (The BOCA National Building Code/1996 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
CONDITION(S) OF APPROVAL
This permit is being issued with the understanding that the following conditions are met: *1 12,1422, *23 *27 *27 *28 *33
Approved with the following conditions:
This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than

- 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor clevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
- Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and 4. a maximum 6' o.c. between bolts. (Section 2305.17)
- 5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.
- 6. Precaution must be taken to protect concrete from freezing. Section 1908.0
- It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify 7. that the proper setbacks are maintained.
- Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent 8. interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1996)
- All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National 9. Mechanical Code/1993). Chapter 12 & NFPA 211
- Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building 10. Code.
- Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces 11. for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/2" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of stairway. (Section 1014.7)
- Headroom in habitable space is a minimum of 76". (Section 1204.0)
 - Stair construction in Use Group R-3 & R-4is a minimum of 10" tread and 7 1/2" maximum rise. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)
- The minimum headroom in all parts of a stainvay shall not be less than 80 inches. (6'8") 1014.4 14.
- Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door 15. approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of ceress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)
- Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits 16. directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

17.	All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self
	closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)
18.	The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic
	extinguishment. (Table 302.1.1)
9.	All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of
	the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke
	detectors shall be installed and maintained at the following locations):
	In the immediate vicinity of bedrooms
	In all bedrooms
	In each story within a dwelling unit, including basements
	In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall
	receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.
	A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved
	type. (Section 921.0)
	The Fire Alarm System shall maintained to NFPA #72 Standard.
	The Sprinkler System shall maintained to NFPA #13 Standard.
	All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0
	of the City's Building Code. (The BOCA National Building Code/1996)
	Section 25-135 of the Municipal Code for the City of Portland states, 'No person or utility shall be granted a permit to excavate or open
	any street or sidewalk from the time of November 15 of each year to April 15 of the following year.".
	The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification
	from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of
	Inspection Services.
	Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
	All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until
	all electrical (min.72 hours notice) and plumbing inspections have been done.
	All requirements must be met before a final Certificate of Occupancy is issued.
	All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building
	Code/1996).
	Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical
	Code/1993). (Chapter M-16)
	Please read and implement the attached Land Use Zoning report requirements.
	Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.
	Glass and glazing shall meet the requirements of Chapter 24 of the building code.
	All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code
	1996).
	1770].
	O_A
١.	

Indies Hopses, Building Inspector
Li McDougall, PFD
Marge Schmuckal, Zoning Administrator

**On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.