City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction:	Owner:	· · ·	Phone:		Permit No: 960942
511 Congress Street	October Corporation				900944
Owner Address:	Leasee/Buyer's Name:	Phone:	Business	Name:	PERIT ISSUED
Contractor Name:	Address:	Phon			Permit Issued:
Allied Construction	P. O. Box 1396, Portland		72-2888		
Past Use:	Proposed Use:	COST OF WOR	RK:	PERMIT FEE:	- SEP 2 6 1996
		\$500,000.00)	\$ 2,550.00	
Office	Same w/interior reno	FIRE DEPT. 🖬	Approved I	INSPECTION:	CITY OF PORTLAND
			1 m	Use Group: Type:	Zone: CBL: B-3 37-1 -2
Proposed Project Description:		Signature: 2		Signature: 1/2/9	Zoning Approval:
roposed roject Description.				DISTRICT (P.U.D.)	
			Approved	the Council Management of the Council Manage	Special Zone or Reviews:
Interior renov as per plan	c			th Conditions:	☐ Shoreland
incerior renov as per plan	.5	1744	Denied	ations approvable	│ □ Wetland □ Flood Zone
		Signature:			
Permit Teken Ru	Data Applied For	Signature.	U. Andri	Date: 9/24A	Site Plan maj 🗆 minor 🗆 mm 🗆
Permit Taken By: Vicki Dover	Date Applied For:	23/96	\sim		· · · · · · · · · · · · · · · · · · ·
			— <u> </u>	This primite	Zoning Appeal
1. This permit application doesn't preclude	de the Applicant(s) from meeting applicable S	State and Federal rules.	. 9	pacinico	
2. Building permits do not include plum	bing, septic or electrical work.		(J	 Miscellaneous Conditional Use
	of started within six (6) months of the date of is	suance False informa-	_		□ Interpretation
tion may invalidate a building permit		ssuance. Paise informa-	-		□ Approved
tion may invanduce a bunding permit	and stop an work				Denied
<i>#</i> 15080 - 30-3336					
15081 - 30-3335		PEHION	5		Historic Preservation
		WITH REQUI			Does Not Require Review
			n na ann an Christian an S		□ Requires Review
Call Allied for P/U					Action:
	CERTIFICATION				Appoved
I hereby certify that I am the owner of reco					
	ication as his authorized agent and I agree to c				
	cation issued, I certify that the code official's				alzi al
	hable hour to enforce the provisions of the co			· · · · · · · · · · · · · · · · · · ·	Date:
			1 -		
$-\dot{P}$	A	0/00/06			
CICNATURE OF A DRI ICANT	a White ADDRESS	9/23/96			- D Fridman S
	aliberte ADDRESS: d Construction	DATE:		PHONE:	
AIIIe					
RESPONSIBLE PERSON IN CHARGE OF	WORK, TITLE			PHONE:	
					5
W	hite–Permit Desk Green–Assessor's Ca	nary-D.P.W. Pink-P	ublic File Iv	ory Card-Inspector	Frontan
					P = - (ralar)

COMMENTS

31/OCT/96 - Inspection made Told general on Fireblocking of exit	walls
11/18/96 (10 for 2nd Flown, 3nd Flown, 4th gustiel, 1 Masement partial. Office space	Floor , A.Q
Inspection Record	
Type Foundation: \mathcal{N}/\mathcal{A} Framing: \mathcal{O}/\mathcal{K} Plumbing: \mathcal{O}/\mathcal{K} Final:	Date 10/15/90 10/15/96

Other:			
Outer.			



CITY OF PORTLAND, MAINE Department of Building Inspection **Certificate of Pccupancy**

Issued to

Date of Issue

APPROVED OCCUPANCY

and the second second

This is to certify that the building, premises, or part thereof, at the above location, built – altered

- changed as to use under Building Permit No. $_{\rm AMMED}$, has had final inspection, has been found to conform substantially to requirements of Zoning Ordinance and Building Code of the City, and is hereby approved for occupancy or use, limited or otherwise, as indicated below.

PORTION OF BUILDING OR PREMISES

·	,		t, est	· · ·

Limiting Conditions:

This certificate super certificate issued	sedes				
Approved:	for a second	a de la companya de l	•		
(Date)	Inspector	Inspector of Buildings			

Notice: This certificate identifies lawful use of building or premises, and ought to be transferred from owner to owner when property changes hands. Copy will be furnished to owner or lessee for one dollar.

BUILDING PERMIT REPORT

DATE: **ADDRESS:** menor **REASON FOR PERMIT: BUILDING OWNER:** rer. 001 **CONTRACTOR:** Jen APPROVAL: WU Cøn PERMIT APPLICANT: Con DENIED: #

CONDITION OF APPROVAL OR DENIAL

- 1. Before concrete for foundation is placed, approvals from the Development Review coordinator and Inspection Services must be obtained. (A24 hour notice is required prior to inspection)
- 2. Precaution must be taken to protect concrete from freezing.
- 3 It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 4. Private garages located <u>beneath habitable rooms</u> in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4 section 407.0 of the BOCA/1996)
- 5. Guardrail & Handrails-A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface tot he loser level. Minimum height all Use Groups 42:, except Use Group R which is 36". In occupancies in Use Group A,B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
- 6. Headroom in habitable space is a minimum of 7'6".
- 7. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use Group minimum 11" tread, 7" maximum rise.
- 8. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
- 9. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as <u>means of egress or rescue</u>, they shall

OVer

have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches(610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. feet.

10. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.

... ...

- 11. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with selfclosers.
- 12. The boiler shall be protected by enclosing with on (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
- All single and multiple station smoke detectors shall be of an approved type and shall be 13. installed in accordance with the provisions of the City's building code Chapter 9, Section 19, 919.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - 1. In the immediate vicinity of bedrooms
 - 2. In all bedrooms
 - 3. In each story within a pwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

- 14.) A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. 15
 - The Fire Alarm System shall be maintained to NFPA #72 Standard.
 - The Sprinkler System shall maintained to NFPA #13 Standard.
 - All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. of the City's building code. (The BOCA National Building Code/1996)
- 18. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.
- 19. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 20. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act, Title 5 MRSA refers, shall obtain a certification from a design professional that the plans of the facility meet the standards of construction required by this section. Prior to commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 21. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's Office.

P. Samuel Hoffses, Chief of Inspection Services c.c. Lt. McDougall P. F. D.

22.) Notexterior Alterstands Are Approved with This permit, Any Exterior Alteritans would require A separate permit.