

REFLECTED CEILING PLAN NOTES

RE ROOM FINISH SCHEDULE FOR CEILING HEIGHTS, TYPES, AND FINISHES, U.N.O.

2. FIRE SPRINKLERS SHALL BE LOCATED IN ALIGNMENT WITH OTHER CEILING ITEMS.

FIRE SPRINKLERS SHALL BE CENTERED IN CEILING TILE WHERE APPLICABLE.

4. FIRE SPRINKLERS SHALL BE PLACED TO COORDINATE WITH LIGHT FIXTURE POSITIONS INDICATED.

5. EXCEPT WHERE INDICATED, CENTER CEILING GRIDS IN ROOMS. USE HALF TILES OR GREATER @ PERIMETERS AS POSSIBLE.

6. RELOCATE EXISTING LIGHT FIXTURES TO LOCATIONS SHOWN. NEW LAYOUT TO BE AS SHOWN. RE: ELEC.

7. PATCH AND REPAIR DAMAGE TO EXISTING PLASTER BEAMS WHERE EXPOSED.

RCP SYMBOL LEGEND

0 2x4 LAY-IN LIGHT FIXTURE.

FINELITE PENDANT LIGHTING

CEILING MOUNTED EXIT LIGHT.

RETURN AIR GRILLE.

SUPPLY AIR GRILLE. EXHAUST AIR GRILLE.

CEILING MOUNTED SPEAKER.

CEILING MOUNTED SMOKE DETECTOR.

ISSUED FOR OWNER REVIEW 5-1-06 DESCRIPTION DATE

CURRENT ISSUE STATUS:

ARCHITECTURE ENGINEERING PLANNING

144 Fore Street/P.O. Box 618 Portland, Maine 04104 tel. (207) 772-3846 fax. (207) 772-1070

COMPASS CONSULTING 477 CONGRESS STREET 7TH FLOOR PORTLAND, MAINE

SEVENTH FLOOR

REFLECTED CEILING PLAN

AS NOTED GRAPHIC SCALE: 0" JOB CAP/DRAWN: A/E OF RECORD:

SMRT CAD FILE: AE102-06049

AE102

05-01-06

REFLECTED CEILING PLAN 1/4"=1'-0"