



CONCRETE  
 BREAST: 310"  
 FIRST: 310"  
 SECOND: 310"  
 THIRD: 310"  
 FOURTH: 310"

ALL THREE CAB WALLS  
 WILSONART  
 "STERLING ASA"  
 7995-38

NOTES:

- 1) CAB SHELL CONSTRUCTION COMPLETES WITH ALL REQUIREMENTS AS SET FORTH IN THE ASME/AWS A17.1 ELEVATOR SAFETY CODE. ALL LOCAL AND/OR HANDJOB REQUIREMENTS ARE THE RESPONSIBILITY OF THE INSTALLER.
- 2) ARCHITECTUALLY APPROVED MATERIALS MAY NOT MEET ASME/AWS A17.1 CODE REQUIREMENTS. IT IS THE RESPONSIBILITY OF THE INSTALLER TO OBTAIN APPROVALS FROM STATE AND/OR LOCAL AUTHORITIES FOR ANY MATERIALS THAT DO NOT COMPLY.
- 3) THE ELEVATOR INSTALLER MUST ADVISE IF WALL SCREWS SHOWN PROHIBIT INSTALLATION DUE TO HOISTWAY ENTRANCE SIZE OR OTHER ACCESS LIMITATIONS.

DATE	BY	CHKD	DESCRIPTION
3-08-17	ewd		ORIGINAL

THIS DRAWING REPRESENTS GENERAL DESIGN INTENT ONLY. ACTUAL AS-BUILT DETAILS MAY VARY FROM THAT SHOWN.

<b>CANTON ELEVATOR</b> 2-SPEED-FRONT OPENING-WOOD CORE ELEVATOR CAB SPRINGER'S JEWELRY FALMOUTH, ME	
CONTRACT NO.	18729
SHEET NO.	1 OF 2

ITEM	FINISH SPECIFICATIONS	MATERIAL / FINISH
SIDE WALL 'A'	REQUIRED	P.L. LAMIN - ADVISE COLOR
SIDE WALL 'B'	REQUIRED	P.L. LAMIN - ADVISE COLOR
REAR WALL	REQUIRED	P.L. LAMIN - ADVISE COLOR
DOOR PANELS	REQUIRED	SATIN STAINLESS STEEL
RETURN PANEL	REQUIRED	SATIN STAINLESS STEEL
STRIVE JAMB	REQUIRED	SATIN STAINLESS STEEL
TRANSOM	REQUIRED	SATIN STAINLESS STEEL
CANOPY	REQUIRED	12 GG. C.R.S. - WHITE ENAMEL
CEILING FRAME	REQUIRED	ANODIZED ALUMINUM TEE
BASE	REQUIRED	SATIN STAINLESS STEEL (20GG.)
CEILING TYPE	REQUIRED	PLASTIC THERMOGLASS
HANDRAIL(S)	REQUIRED	W/ LED LIGHTING
EXHAUST FAN	REQUIRED	2" x 5/8" SATIN STAINLESS STEEL
		SINGLE SPEED

REVIEWED 4-7-17  
 Brian E. Hoff BA