



- A) 20ga. "J" RUNNER
- B) GYPSUM LINER
- C) 1/2" TX SCREENS ON 6" CENTERS
- D) CODE "C" DRYWALL

**ADVISE**  
 ALL DOORS & FRAMES  
 TO BE FINISHED WITH  
 S.W. "ZEPHYR" SW4020

HORIZONTAL REACTIONS ON BUILDING  
 PER ASME A17.1 RULE 3.28.1(c) - SEE DIAGRAM

Ah	Bh	Ch	Dh	Fh	Gh
591.3	501.1	1.8	29.2	329.3	72.4

(ALL LOADS IN POUNDS)  
 (Calculations based on constant height above opening of 48")

- NOTES:
- ENTRANCE FRAMES ARE KNOCK-DOWN CONSTRUCTION.
  - ALL ENTRANCE DOORS AND FRAMES BEAR A 1 1/2 HOUR U.L. FIRE LABEL.
  - FASCIA PROVIDED IN ACCORDANCE WITH ASME/ANSI A17.1 ELEVATOR SAFETY CODE.
  - SUITABLE SILL RECESS AND SUPPORT TO BE PROVIDED BY AND GROUDED IN AFTER SILL INSTALLATION BY OTHERS.
  - ENTRANCE WALLS SHALL BE BUILT, OR ROUGH OPENING PROVIDED AS SHOWN AND FILLED IN, AFTER FRAMES ARE SET.

DATE	BY	CHKD	DESCRIPTION
3-09-17	ewd	ORIGINAL	

**DATA LEGEND**

OPERATOR TYPE & TEMPLATE NUMBER	GAL MOYER
OPERATOR:	
TEMPLATE No.:	82242
KEYWAYS @:	EACH ENTR. W/ ESCUTCHEON
COMPONENT MATERIAL & FINISH	
FRAMES	18 GA. PAINTED STEEL
DOOR PANELS	18 GA. PAINTED STEEL
SIGHT GUARDS	16 GA. PAINTED STEEL
TOE GUARDS	GALVANIZED STEEL
DUST COVERS	GALVANIZED STEEL
FASCIA	GALVANIZED STEEL
HEADERS	GALVANIZED STEEL
COLOR/FINISH SELECTIONS	
DOORS:	PANEL ADVISE COLOR
FRAMES:	PANEL ADVISE COLOR
SILLS	MILL FINISH EXTRUDED ALUMINUM



**ELEVATOR ENTRANCES**  
 2-SPEED SIDE-SLIDE

PROJECT  
 SPRINGER'S JEWELRY  
 FALMOUTH, ME

CONTRACT No.	18729	SHEET No.	2 OF 2
--------------	-------	-----------	--------

REVISIONED 4.7.17  
 DIMM & DUFFIN RA