City of Portland, Maine - Buildin	ng or Use Permit Applicatio	n 389 Congres	s Street, 0	4101, Tel: (207) 8	74-8703, FAX: 874-8716
Location of Construction:	Owner:		Phone:		Permit No: 9 7 1 3 0 7
522 Congress St	Maine College				7 1 1 0 0 1
Owner Address:	Lessee/Buyer's Name:	Phone:	Business	Name:	PERMIT ISSUED
Contractor Name:	Address:	Phor			Permit Issued:
				82-8494	DEC 1 6 1997
Past Use:	Proposed Use:	COST OF WOF \$48,000.00		PERMIT FEE: \$ 260.00	
College	Same	FIRE DEPT.	Approved	INSPECTION:	CITY OF PORTLAND
-			Denied	Use Group: Type:	Zone: 037-H-006
		Signature:	MIN	Signature: Hoffee	
Proposed Project Description:		PEDESTRIAN .		S DISTRICT (P.A.).)	Zoping Approval:
		Action:	Approved		Special Zone of Reviews:
Construct Glass Vitr	ine w/steel fire Escapes			ith Conditions:	[]] □ Shoreland
	all nithror		Denied		- - Welland
		Signature:		Date:	☐ Flood Zone ☐ Subdivision
Permit Taken By: Mary Gresik	Date Applied For:	05 December 199			☐ Site Plan maj ☐minor ☐mm ☐
					Zoning Appeal
1. This permit application does not preclude the	e Applicant(s) from meeting applicable S	tate and Federal rules	•		☐ Variance ☐ Miscellaneous
2. Building permits do not include plumbing,	septic or electrical work.				☐ Conditional Use
3. Building permits are void if work is not start	ed within six (6) months of the date of iss	suance. False informa	-		□ Interpretation
tion may invalidate a building permit and s					□Approved
					☐ Denied
		1	PERMIT WITH REQU	ISSUED IREMENTS	Historic Preservation Not in District or Landmark Discord Not Require Review Requires Review
					Action:
	CERTIFICATION				☑Appoved
I hereby certify that I am the owner of record of t					
authorized by the owner to make this application					
if a permit for work described in the application				e the authority to enter al	Date: 17/8/9
areas covered by such permit at any reasonable	hour to enforce the provisions of the cod	e(s) applicable to sucl	h permit		
5 10 de		05 D 1	1007		
SIGNATURE OF APPLICANT Stephen T	heodore ADDRESS:	05 December		PHONE:	- M-+
SIGNATURE OF APPLICANT Stephen T	neodore Appless.	DAIL.		110111.	
RESPONSIBLE PERSON IN CHARGE OF WO	RK, TITLE			PHONE:	- ceo district フノ
18/b:ta F	Pormit Dock Groon Assessor's Co-	and D.D.W. Bink D	ublic File 4	one Card-Inchestor	1 0 0
Winte-F	Permit Desk Green-Assessor's Can	iaiy~D.F.VV. FiliK-P	ublic file IV	ory caru-mspector	N (5

COMMENTS

·	
1/2/09-10:00 - Met Wed Sprawl on 5:7e-	told him five Dest, needed
2/2/99-10:00-Met Wed Sprawl on site- to inspect as well-	your in and a first
Windows dienhu built us la	lace purposere - Plans+
Window display built w/g, installation stamped by Appears to be done per f	She Theodore Achitect
11151ana 1010 Stanipea Ny	Steve Theory of Allowine .
Sprears to be asme per f) and
	
	Inspection Record
	Type Date
	dation:
	ning:
Final	bing::
	r:

BUILDING PERMIT REPORT

DATE: 12/16/97 ADDRESS: 522 (**) ress 57	
REASON FOR PERMIT: Construct Vitrine	
BUILDING OWNER: $M \in \mathcal{P}$	
CONTRACTOR: Theodor + Theodor -	
PERMIT APPLICANT: Stephen Theodor APPROVAL: 4/ 30.	ED_
USE GROUP (U) BOCA 1996 CONSTRUCTION TYPE 3B	
CONDITION(S) OF APPROVAL	
 This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Service must be obtained. (A 24 hour notice is required prior to inspection) Precaution must be taken to protect concrete from freezing. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This done to verify that the proper setbacks are maintained. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separate the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BONational Mechanical Code/1993). 	is is from fire ed from s of ½
7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the	city's
building code. 8. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of eleval walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, I I, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid mater that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern the would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not less than 30", but not more than 38".)	ower H-4, I- rial such hat
 Headroom in habitable space is a minimum of 7'6". Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use grouminimum 11" tread. 7" maximum rise. 	p
The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8") Every sleeping room below the fourth story in buildings of use Groups R and 1-1 shall have at least one operable wine exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use o special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimens shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.	f height
 Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptal when it exits directly from the apartment to the building exterior with no communications to other apartment units. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doc 	
 self closer's. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with provisions of the City's Building Code Chapter (1), Section 10, 920-7-2 (ROCA hardward Building Code Chapter (1), Section 10, 920-7-2 (ROCA hardward Building Code Chapter (1), 1920-7-2 (ROCA hardwar	the
provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NI 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):	'1'/\

In the immediate vicinity of bedrooms

In all bedrooms

In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and 1-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21. No construction or demolition work shall begin until you have obtained permits for dumpsters or containers. A work Stop Order shall be issued if this requirement is not met.
- 22. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 23. The builder of a facility to which Section 4594-C of the Maine State Fluman Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 24. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office.
- 25. Ventilation shall meet the requirements of Chapter 12 Sections 1210, of the City's Building Code.
- 26. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
- 27. All requirements must be met before a final Certificate of Occupancy is issued.
- 28. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
- 29. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993).

	, shill hit			
· · · · · · · · · · · · · · · · · · ·		 	· · · · · · · · · · · · · · · · · · ·	

Houses, Code Enforcement

cc: Lt. McDongatt, PFD Marge Schmickal