City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

				
Location of Construction:	Owner:	Phone:		Permit No:
516 Congress St Owner Address:	Pachios, Haro Lessee/Buyer's Name:	Phone: Business	Name:	-
owner reduces.	Levinsky's , Inc. Att			
Contractor Name:	Address:	Phone:Ptld, MI	E 04101	Permit Issued:
D U	D. J.I.	COST OF WORK:	774-6648 PERMIT FEE:	-
Past Use:	Proposed Use:	COST OF WORK:	\$ 48.60	
Retail	Same	FIRE DEPT. Approved INSPECTION:		4
		☐ Denied	Use Group: Type:	
			1 31	Zone: CBL: 037-H-009
Proposed Project Description:			Signature:	Zoning Approval:
Proposed Project Description.		PEDESTRIAN ACTIVITIES	` _	Lorming Approval.
		Action: Approved w	ith Conditions:	Special Zone or Reviews:
Erect Signage		Approved with Conditions:		☐ Shoreland ☐ Wetland
Liect Bighage		Semea	_	☐ Flood Zone
		Signature:	Date:	□Subdivision
Permit Taken By: Mary Gresik	Date Applied For:	0 May 1997		☐ Site Plan maj □minor□mm □
				Zoning Appeal
1. This permit application does not preclude the A	□ Variance			
2. Building permits do not include plumbing, sep	otic or electrical work.			☐ Miscellaneous ☐ Conditional Use
3. Building permits are void if work is not started	within six (6) months of the date of issu	iance. False informa-		☐ Interpretation
tion may invalidate a building permit and stop	□Approved			
				□ Denied
				Historic Preservation
	□ Not in District or Landmark			
	☐ Does Not Require Review☐ Requires Review			
				Action:
	CERTIFICATION			□Appoved
I hereby certify that I am the owner of record of the	☐ Approved with Conditions			
authorized by the owner to make this application a	□ Denied			
if a permit for work described in the application is	Date:			
areas covered by such permit at any reasonable ho	ur to enforce the provisions of the code	(s) applicable to such permit		
1 11 11-1121 11.	<i>j</i> '			
SIGNATURE OF APPLICANT	ADDRESS:	20_May_1997 DATE:	PHONE:	-
SIGNATURE OF APPLICANT Phil Levins	sky ADDRESS.	DAIL.	THORE.	
RESPONSIBLE PERSON IN CHARGE OF WORK	K, TITLE		PHONE:	CEO DISTRICT
White-Pe	rmit Desk Green-Assessor's Cana	ary-D.P.W. Pink-Public File I	vory Card-Inspector	

HANGING SIGN HANGING SIGN BY WALKERS & DRIVERS LIGHTED BE HUNG OM CON gress A. SIZE APPROXIMATELY
1/2 ft x 7 ft presently At 272 longues to be relocated on Free St, side

UNTAGE BLACK & ECLD BATIQUE LOUKING SIGN FOR STORE CUNGRESS TRUNT

to be relocated on The Front o 516 (orgness)

Presently mounted on 106 India St. 878 to be relocated on the 87 8id FOR I TORE FRONT UM: IN CAST ALUMINUM LETTERS, INDIVIDUAL FREE STROET

LOUIS OF BUILDING INCRECTION

Pland Godes

SIGNAGE

PLEASE ANSWER ALL QUESTIONS

PLEASE ANSWER ALL QUESTIONS	
Address: 5/t CONGRESS ST Zone: 84/0/	
owner: HAKAN PACHIOS Assessors #: 037-H-009)
Applicant: //V/NSKY'S T.NC.	
Single Tenant Lot?: Yes No	
Multi Tenant Lot?: Yes No	
Freestanding (Ext pole sign)? Yes No Dimensions	<i>†</i>
More than (1) one sign?: Yes No Dimensions See Attached	-
Bldg Wall Sign (att to bldg)? Yes No Dimensions 100 Co	<u>م</u>
List all existing signage and their dimensions: (mgess \$\frac{30''}{X} \frac{30'}{X} \frac{30'}{X} \frac{1}{30'} \frac{1}{X}	-
Lot Frontage(feet): Tenant Frontage(feet):	-
56' Along Free St. 55' Along Congress of Awnings	
Awning?: Yes No Is Awning Backlit?: Yes No	-
Is there any comunication, message, trademark or symbol on awning?	
Height of Awning?:	

PLEASE NOTE: Approvals for signs on the Public Sidewalk and temporary signs come under different requirements and regulations.

ALSO: See reverse side for additional information, requirements and materials needed for signage application submittal.

BUILDING PERMIT REPORT

DATE: 6/6/97	_ADDRESS: 516 Congress	57
REASON FOR PERMIT: To Croct	Signage	
BUILDING OWNER: Harold Pac	chios	
CONTRACTOR:		
PERMIT APPLICANT: Philip our sky	∕APPROVAL: <mark>'×</mark> /	DENIED
	<i>l</i>	

CONDITION(S) OF APPROVAL

- 1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
 - 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
 - 3. Precaution must be taken to protect concrete from freezing.
 - 4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
 - 5. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
 - 6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993) U.L. 103.
 - 7. Guardrail & Handrails A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1. I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
 - 8. Headroom in habitable space is a minimum of 7'6".
 - 9. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise.
 - 10. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
 - 11. Every sleeping room below the fourth story in buildings of use Groups R and 1-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 4-4 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
- 12. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
- 13. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's.
- 14. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
- All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

- 16. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- 17. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 18. The Sprinkler System shall maintained to NFPA #13 Standard.
- 19. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 20. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.
- 21. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 22. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 23. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office.
- 24. Ventilation shall meet the requirements of Chapter 12 Sections 1210, of the City's Building Code.
- 25. All electrical and plumbing permits must be obtained by a Master Licensed holders of their trade.

26. Please Submit The STructural plans For hanging signs befor approval

Defore work begings

27. (a) Large wood en 319n approved For Congress ST, (b) Indistribugh Letter 519n

On Free ST, approved subject to approval of Location and placement, (C) Projecting

28. Box 519n Not Approved.

Somble Holliers, Chief of Code Enforcement

x: Lt. McDougall, PFD
Marge Schmuckal
D. Audrew 5 SP







