

**1** Lighting Equipment Schedule

Type	Description	Lamp	Manufacturer	Catalog Number	Watts
<b>A</b>	Junction box mounted, incandescent, keyless, gazed porcelain lampholder with 3/8 inch black cord. Flat 5' dia. J-box cover plate required - paint black. 25 deg/narrow flood, short neck, 130v/olt lamp. Lamp to be significantly dimmed except during restourc	Philips 79P4R35/HAL/FR25 130v/olt NO SUBSTITUTE ALLOWED	By Contractor	utilizing Leviton 0045 lamp holder	75
<b>A-1</b>	Junction box mounted, incandescent, keyless, gazed porcelain lampholder with 3/8 inch black cord. Flat 5' dia. J-box cover plate required - paint black. 10 deg/narrow spot lamp, short neck, 130v/olt lamp. Lamp to be significantly dimmed except during gre	Philips 79P4R35/HAL/FR10 130v/olt NO SUBSTITUTE ALLOWED	By Contractor	utilizing Leviton 0045 lamp holder	75
<b>A-2</b>	Junction box mounted, incandescent, keyless, gazed porcelain lampholder with 1/2 inch black cord. Flat 5' dia. J-box cover plate required - paint black. 25 deg/narrow flood lamp, short neck, 130v/olt lamp. Lamp to be significantly dimmed except during gre	Philips 79P4R35/HAL/FR25 130v/olt NO SUBSTITUTE ALLOWED	By Contractor	utilizing Leviton 0045 lamp holder	75
<b>B</b>	Stem mounted low voltage, single circuit rail system, remotely located to cold q-tran transformer required. Dimmer for magnetic transformer read	N/A	M.P. Lighting SR-MC + CP101 -30"-M.C + SCP011-30"-M.C + TWO END001-H-C		
<b>B1</b>	Rail system mounted, low voltage, halogen, bar light. Dimmer for magnetic transformer read	Sylvania 50M/R16/R/R35C	M.P. Lighting X41SR-NS2M-W-C		55
<b>C</b>	Recessed, 18 fluorescent, linear wall grazing, bathroom light.	Philips F32B/TL320/AUCO	Day-3/ite Lighting N132JUNV		34
<b>D</b>	Recessed, low voltage, halogen, 3' round aperture adjustable down light, black reflector, black trim, integral magnetic transformer. Dimmer for magnetic transformer required.	Sylvania 50M/R16/R/R35C	Con-Tech Lighting LVR-316-CR3028-81K		55
<b>E</b>	Letter not used				
<b>F</b>	Surface mounted, 120 volt, 8 fluorescent, 1 foot by 4 foot wrap-around acrylic lens fixture, metal end caps.	(2) Philips F32B/TL320/AUCO	Day-3/ite Lighting CAN232-120		70 /ft
<b>G</b>	Recessed in wall, LED, step light, remotely occated driver required.	LED included	Con-Tech Lighting P3A-WW		3
<b>H</b>	Pendant mounted halogen up/down light. Fixture will be dimmed.		Allow \$320.00 each for this light.		100
<b>J</b>	Surface mounted, medium base porcelain socket on metal junction box with screw in PAR20 narrow spot warm white LED lamp. One socket every 12 inches.	Eco-Story ES-FAR20-30W/W www.eco-story.com 207.774.9889	By Contractor		5
<b>J1</b>	Surface mounted, medium base porcelain socket on metal junction box with screw in PAR16 narrow spot 130v/olt halogen lamp. One socket every 12 inches. Dimmed.	Philips 60P4R16/HAL/SP10-130v/olt	By Contractor		60
<b>K</b>	Recessed in 2 x 4 grid ceiling, 18 fluorescent, 2 foot x 4 foot, 4 lamp, gasketed kitchen light. Invert lens for easier cleaning.	(4) Philips F32B/TL320/AUCO	Day-3/ite Lighting 2DPW/C432-R501(U/NV/RED)- UNV-113EB-2N-P4F		130
<b>L</b>	Surface mounted in slot, medium base porcelain socket on metal junction box with screw in PAR16 narrow spot 130v/olt halogen lamp. One socket every 9 inches. Dimmed.	Philips 60P4R16/HAL/SP10-130v/olt	By Contractor		60
<b>M</b>	Counter mounted, incandescent, task light. Provide outlet for plugh in cord	---	By Owner		60
<b>N</b>	Bracket mounted, LED, exterior barnier light, with shroud. Aim straight down.	Narrow spot warm white LED	Becrazille TL4012DUV-SS-51K-W		12
<b>O</b>	Letter not used				
<b>P</b>	Surface mounted under bar, LED, strip light, 3000K shades 4'x6", continuous clear ribbed lens. Remotely occated 130V/24V 0-10v driver required. Dimmable - use compatible dimmer.	3000K LED's included	Tokistar Lighting AVM-CALLW-3000K-AVC		3
<b>Q</b>	Surface mounted under railing, color changing LED, strip light, RGB shades, 4'x6". Remotely located driver/light system transformer required.	RGB LED's included	Color Kinetics Color Flex SL 101-000021-01		3
	Dimming control to be Lutron Genie Eye				

