josef chalat



January 8, 2015

Jeanie Bourke, CEO/LPI/Plan Reviewer, Inspections Division, City of Portland, Maine Captain Chris Pirone, Portland Fire Department

I am pleased to submit documents in support of an application for a construction permit for a tenant improvement project of existing office space at 261 Commercial Street (19 Cross Street) on behalf of my client, MEMIC.

Project Description:

The proposed project calls for the renovation of 4991 square feet of existing office space on the 2nd floor of the building and renovation of 3125 square feet of existing office space on the 6th floor. The project is entirely within the boundaries of existing leased tenant space; there are no changes required or proposed to the egress stairs, or exits that serve the tenants in the building. The proposed work will demolish a small number of offices and provide open office area for demountable work stations. The scope of the project deals primarily with interior finishes. The project does not involve changes to the building structure or thermal envelope.

The tenant, MEMIC, is an insurance company specializing in Worker's Compensation The office environment is what you would typically find in an insurance company office and is unremarkable in terms of materials stored on site, occupant activities, and day to day business operations.

Code Reviews:

The documents include code reviews for both NFPA 101 and IBC 2009. It is important to note that there is no change proposed to the occupancy, occupant load, or extent of existing tenant space. This code review is for the Area of Work, as defined in the International Existing Building Code only. I have assumed that code requirements for items such as egress stairs, exit discharge, building type, building height and area limitations, fire ratings, separation of occupancies, and all other code issues that deal with the building beyond the work area have been addressed in earlier permits and are outside the scope of this project

The project has been designed to comply with the ADA technical guidelines for the Area of Work

Submission:

This project has been submitted to the City of Portland for a fast track review. It has also been submitted to the State Fire Marshal.

I look forward to answering any questions you have

Regards, Josef Chalat, Architect

architect



Project Description:

The building at 261 Commercial Street in Portland, Maine is a six (6) story office building owned by Casco View Holding LLC of Portland, Maine, and leased by MEMIC (Maine Employers' Mutual Insurance Company), a private mutual insurance company that opened in January 1993. The project involves reconfiguring office space on the 2nd and 6th floors. The work does not require changes to the structure of the building. This code summary demonstrates that the proposed work complies with applicable sections of NFPA 101, Life Safety Code Handbook, and the requirements of the specific occupancy, Existing Business.

Chapter 39: Existing Business Occupancies

39.1 General Requirements

- 39.1.1 Application. No change in occupancy is proposed.
- 39.1.2 Multiple Occupancies: Not applicable to this permit application
- 39.1.3 Special Definitions: Not applicable to this permit application
- 39.1.4 Classification of Occupancy: Business: See §6.1.11
 The Building Occupant, MEMIC, is a private mutual insurance company.
 The occupant's activities conform to the definition of a Business
 Occupancy in §6.1.11.1.
- 39.1.5 Classification of Hazard of Contents: see §6.2.2 The contents of this office comply with the Code's description of Ordinary Hazard Contents in §6.2.2.3* Ordinary Hazard Contents.
- 39.1.6 Minimum Construction Requirements: No requirements
- 39.1.7 Occupant Load:

The occupant load has been calculated according to Table 7.3.1.2. See drawings, sheet CR-1 calculations: 2^{nd} floor: 73 occupants 6^{th} floor: 136 occupants



39.2 Means of Egress Requirements

39.2.1 General

The existing stairs serve as the exits for each floor. The exit access on each floor has been designed in accordance with the means of egress requirements specified by Chapter 7 and Chapter 39.

- 39.2.2 Means of Egress Components.
 - 39.2.2.2 Doors. Doors complying with 7.2.1 shall be permitted

7.2.1.4.2 Door Leaf Swing Direction: A door can swing opposite direction of egress travel with room occupant load less than 50.

- 39.2.2.3 Stairs. No change to the existing stairs is proposed
- 39.2.3 Capacity of Means of Egress.

7.3.1.1.2: the loss of any means of egress leaves available 50% of egress capacity:

Stairs: The occupant load of the 6^{th} floor = 136. 50% =68 Occupants Stair width = .3 x 68 = 20.4 inches

Access ways = $.2 \times 68 = 13.6$ inches

Doors: All existing doors in the means of egress are 36" wide leaves 39.2.3.2 Clear width required

a clear width of at least 44" has been provided at new passageways serving an occupant load greater than 50

39.2.4 Number of Exits.

39.2.4.1 (2) 2 exits required

Two stair enclosures, labeled North Stair and South Stair on the plans, serve each floor

39.2.4.2 Exit access is allowed to be on a single path for up to the maximum common path of travel allowed

Maximum Common Path of travel = 100 feet (per 39.2.5.3.1). See drawing CR-1 for depiction of Common Paths of travel

39.2.5 Arrangement of Means of Egress.

39.2.5.2* Dead-end corridors shall not exceed 50 ft The proposed work does not include any corridors 39.2.5.3.1 Common path of travel shall not exceed 100 ft on a story protected throughout by an approved automatic sprinkler system in accordance with 9.7.1.1(1).See CR-1 for depiction of Common Paths of travel



- 39.2.6 Travel Distance to Exits. 39.2.6.3 Travel distance to an exit, measured in accordance with 7.6 shall not exceed 300 ft (91 m) in business occupancies protected throughout by an approved, supervised automatic sprinkler system in accordance with §9.7. See drawing cr-1
 - 39.2.7 Discharge from Exits.

Existing. No change proposed. Both exit stairs terminate at an exterior public way

39.2.8 Illumination of Means of Egress.

Lighting, with a combination of motion sensor-type lighting switches and dedicated circuits will be provided so that the illumination at all floor areas will be a minimum of 1 ft candle when occupants are present. See mechanical drawings

- 39.2.9 Emergency Lighting. See mechanical drawings for existing and new emergency lighting.
- 39.2.10 Marking of Means of Egress. See Life Safety Devices plans for existing and new exit signs
- 39.2.11 Special Means of Egress Features. Not applicable

39.3 Protection

39.3.1 Protection of Vertical Openings.

The existing exit stair enclosures appear to be enclosed by fire rated construction, and would have been required to be so enclosed when the building was constructed, however, this document does not represent that the existing fire stair enclosure meets code. The floor plan CR-1 shows the location of existing labeled doors.

39.3.2 Protection from Hazards.

Materials within this tenant space are routine office supplies that would be considered ordinary hazard materials, and therefore not required to be separated per 39.3.2.2. The appliances in the kitchenette area are used for food warming and are not flue connected appliances.



39.3.3 Interior Finish. Table A.10.2.2	
Business Occupancy, Sprinklered	
Exits	
Walls and Ceilings: A, B, or C permitted	Floors: no requirements
Exit Access Corridors	
Walls and Ceilings: A, B, or C permitted	Floors: no requirements
Other Spaces	
Walls and Ceilings: A, B, or C permitted	Floors: no requirements

39.3.4 Detection, Alarm, and Communications Systems. The existing alarm systems shall be modified as the work requires. See mechanical plans for specific details

39.3.5 Extinguishment Requirements.

In accordance with NFPA 10, Standards for Portable Fire Extinguishers, Table 6.2.1.1 Fire Extinguisher Size and Placement for Class A Hazards. See drawing CR-1 for maximum travel distance and fire extinguisher locations

- 39.3.6 Corridors. (No requirements.)
- 39.3.7 Subdivision of Building Spaces. (No special requirements.)

39.4 Special Provisions 39.

Not applicable to this permit application

39.5 Building Services

- 39.5.1 Utilities Not applicable to this permit application
- 39.5.2 Heating, Ventilating, and Air-Conditioning See mechanical drawings
- 39.5.3 Elevators, Escalators, and Conveyors Not applicable to this permit application
- 39.5.4 Rubbish Chutes, Incinerators, and Laundry Chutes. Not applicable to this permit application

39.6 Reserved

39.7.1 Emergency Plans.

Discussion: Tenant shall provide training to designated employees in the use of portable fire extinguishers. Tenant shall conduct drills in accordance with §4.7

Inspections Division 02/05/15

MEMIC, 261 Commercial Street, Portland Maine 2nd and 6th floor Renovation City of Portland Maine, Fire Department Requirements

Applicant

MEMIC 261 Commercial Street Portland Maine, 04101

Tenant Contact Catherine Lamson, Senior Vice President Chief Administrative Officer (207) 791 3304

Architect:

Josef Chalat, Architect 327 Ocean House Road Cape Elizabeth, Maine 04107 Phone: (207) 318-3234 Email: azimuth@maine.rr.com

Proposed Use of Structure (unchanged from existing)

IBC Business Occupancy B, Section 305, NFPA Chapter 39, Existing Business Occupancy

Floor Area (in square feet) 2nd floor Project area 4991 Gross floor area 8112 6th floor Project area 3125 Gross floor area 8171 Total Project Area 8116

Fire Protection of Structure:

The existing building appears to be fully sprinklered. The existing sprinkler system within the work area shall be modified on a design/build basis to accommodate revisions to the floor plan.



1. Provide acoustic sealant at bottom of wall, power outlets, switches 2. Offset outlets or other penetrations at least one stud bay so that no stud bay contains pentrations on both sides of wall

Provide moisture resistant cement backer 3. board board at tile installations



1½"= 1'-0"



WT-01 Wall Type (non-rated partition)

Wall Notes:









Architect: Josef Chalat, Architect 327 Ocean House Road Cape Elizabeth, Maine 04107 ph: (207) 318-3234 e: azimuth@maine.rr.com

Planning and Interior Design: Lisa Whited Whited Planning and Design ph: (2017) 329-2189 lwhited@maine.rr.com

Gretchen Boulos NCIDQ Boulos Commercial Design ph: (207) 749 1795 gretchen@bouloscommercialdesign.com

Mechanical Engineering: Bennet Engineering contact: Cat Tranberg ph (207) 865-9475 Cat@bennettengineering.net

General Contractor: Zachau Construction 1185 U.S. Route One Freeport, ME 04032 ph (207) 865-9925 (office) contact: Jon (207) 807-8980 (mobile) Jon@zachauconstruction.com

Project: MEMIC 261 Commercial Street 2nd & 6th floor Tenant Improvements

Tenant: MEMIC 261 Commercial Street (19 Cross Street) Portland Maine, 04101

Tenant Contact Catherine Lamson, Senior Vice President Chief Administrative Officer (207) 791 3304

Building Owner: Casco View Holdings II, LLC PO Box 1137 Portland, ME 04104

City of Portland Information: CBL 038 F019 Tax acct no. 51170

Date: 01-07-2015 Purpose:

Fast Track Construction Permit City of Portland, Maine

Revisions

Sheet Title

2nd floor plan

Sheet Number







Architect: Josef Chalat, Architect 327 Ocean House Road Cape Elizabeth, Maine 04107 ph: (207) 318-3234 e: azimuth@maine.rr.com

Planning and Interior Design: Lisa Whited Whited Planning and Design ph: (2017) 329-2189 lwhited@maine.rr.com

Gretchen Boulos NCIDQ Boulos Commercial Design ph: (207) 749 1795 gretchen@bouloscommercialdesign.com

Mechanical Engineering: Bennet Engineering contact: Cat Tranberg ph (207) 865-9475 Cat@bennettengineering.net

General Contractor: Zachau Construction 1185 U.S. Route One Freeport, ME 04032 ph (207) 865-9925 (office) contact: Jon (207) 807-8980 (mobile) Jon@zachauconstruction.com

Project:

MEMIC 261 Commercial Street 2nd & 6th floor Tenant Improvements

Tenant: MEMIC 261 Commercial Street (19 Cross Street) Portland Maine, 04101

Tenant Contact Catherine Lamson, Senior Vice President Chief Administrative Officer (207) 791 3304

Building Owner: Casco View Holdings II, LLC PO Box 1137 Portland, ME 04104

City of Portland Information: CBL 038 F019 Tax acct no. 51170

Date: 01-07-2015 Purpose:

Fast Track Construction Permit City of Portland, Maine

Revisions

Sheet Title

6th floor plan

Sheet Number



Ceiling Notes:

Sprinkler Heads:

- The existing sprinkler system shall be modified as required to accommodate the proposed ceiling plan and layout. The sprinkler work shall be designed and installed by a Maine licensed sprinkler contractor, under a separate permit as required by the City of Portland and State of Maine. Wherever possible, sprinkler heads shall be centered in ceiling tiles
 Life Safety Devices:
- Exit signs, alarms, strobe/alarms, emergency lighting, pull stations, smoke and heat detectors, motion sensors, and any other life safety device shall be provided as shown on the mechanical drawings.

Electrical and Mechanical Equipment:

 See machnical plans for electrical receptacles, switches light fixtures, switching and circuting, thermostats, louvers, motion sensors, and any other electrical or mechanical equipment
 Soffits

- 4. Provide gypsum board soffits on 3-5/8" metal framing metal framing with minimum 6" vertical face. Provide level 4 finish. Finished elevation of soffit to match finished elevation of ceiling tile unless other height is called out.
- Ceiling Grid and Ceiling Tile



Architect: Josef Chalat, Architect 327 Ocean House Road Cape Elizabeth, Maine 04107 ph: (207) 318-3234 e: azimuth@maine.rr.com

Planning and Interior Design: Lisa Whited Whited Planning and Design ph: (2017) 329-2189 Iwhited@maine.rr.com

Gretchen Boulos NCIDQ Boulos Commercial Design ph: (207) 749 1795 gretchen@bouloscommercialdesign.com

Mechanical Engineering: Bennet Engineering contact: Cat Tranberg ph (207) 865-9475 Cat@bennettengineering.net

General Contractor: Zachau Construction 1185 U.S. Route One Freeport, ME 04032 ph (207) 865-9925 (office) contact: Jon (207) 807-8980 (mobile) Jon@zachauconstruction.com

Project: MEMIC 261 Commercial Street 2nd & 6th floor Tenant Improvements

Tenant: MEMIC 261 Commercial Street (19 Cross Street) Portland Maine, 04101

Tenant Contact Catherine Lamson, Senior Vice President Chief Administrative Officer (207) 791 3304

Building Owner: Casco View Holdings II, LLC PO Box 1137 Portland, ME 04104

City of Portland Information: CBL 038 F019 Tax acct no. 51170

Date: 01-07-2015

Purpose: Fast Track Construction Permit City of Portland, Maine

Revisions

Sheet Title



Sheet Number

a3





Architect: Josef Chalat, Architect 327 Ocean House Road Cape Elizabeth, Maine 04107 ph: (207) 318-3234 e: azimuth@maine.rr.com

Planning and Interior Design: Lisa Whited Whited Planning and Design ph: (2017) 329-2189 lwhited@maine.rr.com

Gretchen Boulos NCIDQ Boulos Commercial Design ph: (207) 749 1795 gretchen@bouloscommercialdesign.com

Mechanical Engineering: Bennet Engineering contact: Cat Tranberg ph (207) 865-9475 Cat@bennettengineering.net

General Contractor: Zachau Construction 1185 U.S. Route One Freeport, ME 04032 ph (207) 865-9925 (office) contact: Jon (207) 807-8980 (mobile) Jon@zachauconstruction.com

Project: MEMIC 261 Commercial Street 2nd & 6th floor Tenant Improvements

Tenant: MEMIC 261 Commercial Street (19 Cross Street) Portland Maine, 04101

Tenant Contact Catherine Lamson, Senior Vice President Chief Administrative Officer (207) 791 3304

Building Owner: Casco View Holdings II, LLC PO Box 1137 Portland, ME 04104

City of Portland Information: CBL 038 F019 Tax acct no. 51170

Date: 01-07-2015 Purpose:

Fast Track Construction Permit City of Portland, Maine

Revisions

Sheet Title

6th floor ceiling plan

Sheet Number





Accessibility Building Code Certificate



4

Designer:	Josef Cr
Address of Project:	261 Comm
Nature of Project:	Tenant in
,	

Josef Chalat, Architect

261 Commercial Street, Portland, ME 04101

Tenant improvement of portions of 2nd and 6th floors

The technical submissions covering the proposed construction work as described above have been designed in compliance with applicable referenced standards found in the Maine Human Rights Law and Federal Americans with Disability Act. Residential Buildings with 4 units or more must conform to the Federal Fair Housing Accessibility Standards. Please provide proof of compliance if applicable.

	Signature:	Josef Chalat Digitally signed by Josef Chalat Di: cn=Josef Chalat, o=Azimuth LLC, ou=Architect, email=azimuth@maine.rr.com, ctus Date: 2015.01.09 15:21:52 -05'00'
CENSED ARCHIAE	Title:	Architect
JOSEF	Firm:	Azimuth LLC
AR2354	Address:	12 Channel View Road
THE OF MALL		261 Commercial Street
Frinst	Phone:	207 318 3234

For more information or to download this form and other permit applications visit the Inspections Division on our website at www.portlandmaine.gov







LEGEND

6th Floor Area of Project

gross project area 3125 sf

gross floor area 8171 sf

The project consists of demolishing selected existing walls

demountable work stations, and enclosed offices defined by

HVAC system will me modified as required. The locations of

existing life safety devices and sprinkler heads will also be

and ceilings and providing open office work area for

full height demountable partitions (DIRTT) walls. An electrical panel serving the floor will be relocated. The

adjusted and new items added where required

(work area per IEBC)

Project description:



.....

full height demountable partition

hatching indicates area of work

2nd Floor Area of Project (work area per IEBC)

gross project area 4991 sf gross floor area 8112 sf

Project description:

The project consists of demolishing selected existing walls and ceilings and providing open office work area for demountable work stations, and enclosed offices defined by full height demountable partitions (DIRTT) walls. An electrical panel serving the floor will be relocated. The HVAC system will me modified as required. The locations of existing life safety devices and sprinkler heads will also be adjusted and new items added where required

Total Area on two floors: 8116 square feet

DESCRIPTION OF EXISTING BUILDING:

The existing building is a 6 story steel and concrete framed building with a brick, aluminum and glass exterior. The original 5 story building had a 6th floor added to it.

note: phasing is shown schematically, exact extent of each phase to be field determined

General Notes:

- The general contractor shall perform the work of this project, as depicted on drawings, specifications, code reviews, revisions, and all other material submitted to the City of Portland in support of the building permit application for this project
- 2. The contractor shall maintain access to the existing means of egress, including exits, stairs, and elevators for all portions of the work
- 3. The project as designed does not require penetrations at any of the rated walls or floors in the building. However, if existing conditions are encountered that require penetrations of existing rated walls, floors, or ceilings, the contractor shall notify the architect immediately. The architect shall submit to The City of Portland details for firestopping to satisfy the requirements of IBC section 713, NFPA 1, section 12.7.5.1 and NFPA 101 Section 8.3.5, Penetrations
- 4. The Work shall be constructed in phases as depicted on the diagram at left. The General contractor shall submit a schedule indicating approximate start and finish dates of each phase
- 5. The existing sprinkler system within the work area shall be modified on a design/build basis to accommodate revisions to the floor plan. A licensed sprinkler contractor shall obtain all permits required for the work

LIST C	F DRAWINGS:
Cover c1	Cover Sheet
Demoli d1	ition: Demolition Floor Plans
Buildin cr	g Code: Code Review
Archite a1 a2 a3 a4	ectural: 2nd Floor Plan 6th Floor Plan 2nd Floor Ceiling Plan 6th Floor Ceiling Plan
Mecha DE-1 DE-2 DM-1 E-1 E-2 E-3 E-4 M-1 M-2 M-3	nical Lighting Demo Plan Lighting Demo Plan Mechanical Demo Plans 2nd Floor Lighting Plan 6th Floor Lighting Plan 2nd Floor Power Plan 6th Floor Power Plan 6th Floor Mechanical Plan 6th Floor Mechanical Plan Mechanical Legend, Schedules & Details



Architect: Josef Chalat, Architect 327 Ocean House Road Cape Elizabeth, Maine 04107 ph: (207) 318-3234 e: azimuth@maine.rr.com

Planning and Interior Design: Lisa Whited Whited Planning and Design ph: (2017) 329-2189 Iwhited@maine.rr.com

Gretchen Boulos NCIDQ Boulos Commercial Design ph: (207) 749 1795 gretchen@bouloscommercialdesign.com

Mechanical Engineering: Bennet Engineering contact: Cat Tranberg ph (207) 865-9475 Cat@bennettengineering.net

General Contractor: Zachau Construction 1185 U.S. Route One Freeport, ME 04032 ph (207) 865-9925 (office) contact: Jon (207) 807-8980 (mobile) Jon@zachauconstruction.com

Project:

MEMIC 261 Commercial Street 2nd & 6th floor Tenant Improvements

Tenant: MEMIC 261 Commercial Street (19 Cross Street) Portland Maine, 04101

Tenant Contact Catherine Lamson, Senior Vice President Chief Administrative Officer (207) 791 3304

Building Owner: Casco View Holdings II, LLC PO Box 1137 Portland, ME 04104

City of Portland Information: CBL 038 F019 Tax acct no. 51170

Date: 01-07-2015 Purpose:

Fast Track Construction Permit City of Portland, Maine

Revisions

Sheet Title

cover sheet project description general notes

Sheet Number

C1





From Designer:	Josef Chalat, Architect		
Date:			
Date:			
Job Name:	MEMIC, Tenant Improvements, 2nd a	nd 6th floors	
Address of Construction:	261 Commercial Street, Portland Mair	ne, 04101	
Cons	2009 International struction project was designed to the	Building Code e building code criteria listed below:	
Building Code & Year IBC 2009	L& IECC 2009 Use Group Classification	a (s) Business Group B Section 304	
Type of Construction IIIA (fi	re ratings to be verified as required)		
Will the Structure have a Fire su	ppression system in Accordance with S	ection 903.3.1 of the 2009 IRC NO, sprinkler per IBC	
Is the Structure mixed use? NO	If yes, separated or non sepa	arated or non separated (section 302.3)	
Supervisory alarm System? Yes	Geotechnical/Soils report re	equired? (See Section 1802.2) No	
	· · · · · · · · · · · · · · · ·	1	
Structural Design Calculation	s	Live load reduction	
Not Required	structural members (106.1 – 106.11)	Roof <i>live</i> loads (1603.1.2, 1607.11)	
		Roof snow loads (1603.7.3, 1608)	
Uniformly distributed floor live load	n Documents (1603) ds (7603.11, 1807)	Ground snow load, Pg (1608.2)	
Floor Area Use	Loads Shown	If $Pg > 10$ psf, flat-roof snow load p_f	
		If $Pg > 10$ psf, snow exposure factor, $_{Ce}$	
		If $Pg > 10$ psf, snow load importance factor, I_{k}	
		Roof thermal factor, $_G$ (1608.4)	
		Sloped roof snowload, _{Pt} (1608.4)	
Wind loads (1603.1.4, 1609)		Seismic design category (1616.3)	
Design option utili	zed (1609.1.1, 1609.6)	Basic seismic force resisting system (1617.6.2)	
Basic wind speed (1809.3)	Response modification coefficient, _{R/} and	
Building category a	and wind importance Factor, h_{p}	deflection amplification factor _{Cl} (1617.6.2)	
Wind exposure cat	regory (1609.4)	Analysis procedure (1616.6, 1617.5)	
Internal pressure coefficient (ASCE 7) Component and cladding pressures (1609.1.1, 1609.6.2.2) Main force wind pressures (7603.1.1, 1609.6.2.1)		Design base shear (1617.4, 16175.5.1)	
		Flood loads (1803.1.6, 1612)	
		Flood Hazard area (1612.3)	
		Elevation of structure	
Design option utili	2ca (1614.1)	Other loads	
Seismic use group	(category)	Concentrated loads (1607.4)	
Spectral response (1013.1)	Partition loads (1607.5)	
010 01033 (1013.1.3)		Misc. loads (Table 1607.8, 1607.6.1, 1607.7, 1607.12, 1607.13, 1610, 1611, 2404	



Certificate of Design



5

Date:

1/9/2015

From:

These plans and / or specifications covering construction work on:

MEMIC, Tenant Improvements on 2nd and 6th Floor 261 Commercial Street, Portland, ME 04101

Have been designed and drawn up by the undersigned, a Maine registered Architect / Engineer according to the **2009 International Building Code** and local amendments.

	Signature:	Josef Chalat Digitally signed by Josef Chalat DB: cm-Josef Chalat, o=Azimuth LLC, ou-Architect, email=azimuth@maine.rr.com, c=US Date: 2015.01.09 15:23:09-0500'
CENSED ARCHIIE	Title:	Architect
JOSEF	Firm:	Azimuth LLC
AR2354	Address:	12 Channel View Road
E OF NAT		Cape Elizabeth, ME 04107
//	Phone:	207 318 3234

For more information or to download this form and other permit applications visit the Inspections Division on our website at www.portlandmaine.gov





Existin	Existing Doors, both floors:		
mark	size	label	
a	3-0 x 7-0	$1\frac{1}{2}$ hours	
b	3-0 x 6-8	$1\frac{1}{2}$ hours	
c	3-0 x 7-0	$1\frac{1}{2}$ hours	
d	3-0 x 7-0	$1\frac{1}{2}$ hours	
e	3-0 x 6-8	$1\frac{1}{2}$ hours	
f	3-0 x 7-0	$1\frac{1}{2}$ hours	



4"x25" wired glass vision panel

emergency lighting

exit sign with direction of travel arrows indicated

NOTE: existing exit stair enclosure shafts are concrete block construction. The fire rating is a minimum of 1 hour and may be 2 hour, depending the thickness of block used.

flush 4"x25" wired glass vision panel

Applicable Building Codes:

Maine Uniform Energy and Building Code Portland City Code, Chapter 10 Fire Prevention and Protection NFPA 101 Life Safety Code IBC 2009 (International Building Code)

Existing Building: (6) story office building, single tenant

Sprinkler System: The existing building appears to be fully sprinklered. Modifications to the design of the existing system and installation shall be performed by a Maine Licensed Sprinkler Contractor as required by the State of Maine and the City of Portland

Code Highlights: Both NFPA and IBC referenced. Code cited is either most stringent or both codes agree. See attached code review for specific details

Occupancy (no change in existing occupancy) NFPA 1: Section 20.13, Business Occupancies NFPA 101: Existing Business Occupancy, Chapter 39 IBC: Business Group B Section 304

Classification of Work IEBC Section 404: Alteration-Level 2

NFPA Table A.7.6 Common Path, Dead-End, and Travel Distance Limits (by occupancy) Building is fully sprinklered Common Path of Travel: 100' maximum

300' maximum

050' maximum

Travel Distance to Exit: Dead End Corridor: (NA)

Occupant load NFPA Table 7.3.1.2

6th Floor: gross floor area 8171 sf net area at 1 per 15 = 975 sf = 65 occupants (assembly at lunch room and board room) gross area at 1 per 100 = 8171-975 =71 occupants (business) total 6th floor occupant load = 65+71 = 136 occupants

2nd Floor gross floor area 8112 sf gross floor area at 1 per 300 = 1028 sf = 3 occupants (mechanical) gross area at 1 per 100 = 8112-1028=70 occupants (business) total 2nd floor occupant load = 3+70 = 73 occupants

Widths required for egress passageways: 44" (IBC 1005.1)

occupant load < 220 aisles (IBC Group B) 36" (IBC 1017.2) occupant load < 180

8400 sf

2100 sf

2-A

Extinguishments Requirements. (NFPA 39.3.5)

NFPA 10 Table 6.2.1.1

Fire Extinguisher Size and Placement for Class A Hazards

Light (low) hazard occupancy	
Minimum rated extinguisher	2-A
Maximum floor area per unit A	3000sf
Maximum floor area per exitinguisher:	11,250 sf
maximum travel distance to an extinguisher:	75'
•	

floor area for calculation purpose: area per extinguisher minimum size extinguisher per location

Extinguishers provided at each station:

Dry Chemical Fire Exitnguisher Classification 4-A80-B:C tested to ANSI/UL 711 & ANSI/IUL 299 with bracket required by manufacturer



Architect: Josef Chalat, Architect 327 Ocean House Road Cape Elizabeth, Maine 04107 ph: (207) 318-3234 e: azimuth@maine.rr.com

Planning and Interior Design: Lisa Whited Whited Planning and Design ph: (2017) 329-2189 lwhited@maine.rr.com

Gretchen Boulos NCIDQ Boulos Commercial Design ph: (207) 749 1795 gretchen@bouloscommercialdesign.com

Mechanical Engineering: Bennet Engineering contact: Cat Tranberg ph (207) 865-9475 Cat@bennettengineering.net

General Contractor: Zachau Construction 1185 U.S. Route One Freeport, ME 04032 ph (207) 865-9925 (office) contact: Jon (207) 807-8980 (mobile) Jon@zachauconstruction.com

Project:

MEMIC 261 Commercial Street 2nd & 6th floor Tenant Improvements

Tenant: MEMIC 261 Commercial Street (19 Cross Street) Portland Maine, 04101

Tenant Contact Catherine Lamson, Senior Vice President Chief Administrative Officer (207) 791 3304

Building Owner: Casco View Holdings II, LLC PO Box 1137 Portland, ME 04104

City of Portland Information: CBL 038 F019 Tax acct no. 51170

Date: 01-07-2015 Purpose:

Fast Track Construction Permit City of Portland, Maine

Revisions

Sheet Title

code review

Sheet Number



Union E Cross project north

Demolition Notes

Submittals

 Provide owner with demolition schedule that minimize disturbances and interruptions to the owner's onsite operations. The schedule shall indicate interruptions of utility services, use and protection of elevator and stairs, locations of partitions for dust and noise control, and path of waste removal from building

Quality

 Comply with applicable EPA notification regulation before starting selective demolition. Comply with ANSI A10.6 Safety Requirements for Demolition Operations, and NFPA 241: Standard for Safeguarding Construction, Alteration, and Demolition Operations

Project Conditions and Requirements

- 3. The owner will occupy areas of the building adjacent to the areas of demolition. Conduct the work in a manner that provides minimal disruption to the owners operations
- The demolition plan is intended to be a schematic guide for removing existing assemblies, structures and materials as required for the new work to be installed. It is not intended to be exhaustive in detail. The contractor shall be familiar with the work of the project and remove all
- items as required by the work
 5. Remove all construction assemblies, materials, finishes, mechanical and electrical items necessary for the completion of the work as depicted on the drawings, specifications, and supplementary instructions. Refer to mechanical and electrical drawings for additional information on demolition of those items.
- 6. The removal disposal and associated fees of all demolished items shall be the responsibility of the General Contractor.
- 7. All removed items, debris and salvage shall be the property of the General contractor unless noted otherwise in the drawings or by the Owner.
- Demolition may uncover existing conditions, structures or assemblies that were not foreseen by the Architect or owner. The contractor shall bring to the attention of the Architect any existing conditions that are discovered that will affect the scope or design of the project
- 9. The Contractor shall restore any fire rated assemblies damaged by the demolition process to their required rating
- The contractor shall identify any pre-existing damage to fire rated walls, floors, ceilings and columns. The Architect will coordinate with the General Contractor to develop a plan to restore the continuity of rated assemblies
- 11. The Contractor shall protect finishes, assemblies and structures not required to be demolished or that are outside the area of work.
- 12. The contractor shall control dust, noise and vibration, to protect the
- 13. The contractor shall provide shoring and temporary support of existing structural members that the work requires.
- materials to be removed and reused, such as light fixtures and other electrical equipment, doors, and plumbing fixtures, shall be stored and protected from damage by ongoing construction activities
- 15. Maintain and ensure safe passage of building occupants around and trough areas of demolition.

Hazardous Materials

- 16. If the Contractor suspects that hazardous materials such asbestos containing materials (ACM), lead based paint, polychlorinated biphenyl, (PCB) and petroleum products are present he shall not disturb the material and notify the owner's representative.
- 17. Fluorescent lights shall be handled and disposed of properly to prevent the release of mercury vapor

Floor Specific Notes:

6TH FLOOR:

- The following existing items shall be reused
 1.1. light fixtures
- 1.2. door and hardware at existing telephone room
- 2. Existing carpet tiles in the existing open office area shall remain. Protect carpet with continuous panels taped at seams
- 3. The existing carpet tiles in the offices shall remain if they are on a continuous grid with the tiles in the open office area.

2ND FLOOR

1. All flooring, ceiling tiles, light fixtures within the work area shall be removed



Architect: Josef Chalat, Architect 327 Ocean House Road Cape Elizabeth, Maine 04107 ph: (207) 318-3234 e: azimuth@maine.rr.com

Planning and Interior Design: Lisa Whited Whited Planning and Design ph: (2017) 329-2189 Iwhited@maine.rr.com

Gretchen Boulos NCIDQ Boulos Commercial Design ph: (207) 749 1795 gretchen@bouloscommercialdesign.com

Mechanical Engineering: Bennet Engineering contact: Cat Tranberg ph (207) 865-9475 Cat@bennettengineering.net

General Contractor: Zachau Construction 1185 U.S. Route One Freeport, ME 04032 ph (207) 865-9925 (office) contact: Jon (207) 807-8980 (mobile) Jon@zachauconstruction.com

Project:

MEMIC 261 Commercial Street 2nd & 6th floor Tenant Improvements

Tenant: MEMIC

MEMIC 261 Commercial Street (19 Cross Street) Portland Maine, 04101

Tenant Contact Catherine Lamson, Senior Vice President Chief Administrative Officer (207) 791 3304

Building Owner: Casco View Holdings II, LLC PO Box 1137 Portland, ME 04104

City of Portland Information: CBL 038 F019 Tax acct no. 51170

Date: 01-07-2015 Purpose:

Fast Track Construction Permit City of Portland, Maine

Revisions

Sheet Title

demolition floor plans

Sheet Number

d1



FOR	PERMI	TTING

DE-1

PLAN

DEMO

LIGHTING

WP DENOTES WEATHERPROOF CONSTRUCTION RP DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REPLACED RM DENOTES EXISTING ELECTRICAL EQUIPMENT TO REMAIN RL DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE RELOCATED RV DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED GENERAL NOTES 1. ALL SIXTH FLOOR LIGHTING FIXTURES LOCATED WITHIN THE AREA OF WORK SHALL BE REMOVED AND SAFELY STORED FOR RE-INSTALLATION DURING CONSTRUCTION. DRAWING NO.



WP DENOTES WEATHERPROOF CONSTRUCTION

RP DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REPLACED RM DENOTES EXISTING ELECTRICAL EQUIPMENT TO REMAIN RL DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE RELOCATED RV DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED



PO BOX 297

FREEPORT, ME

261 COMMERCIAL STREET FLOOR 2 & FLOOR 6 PORTLAND, ME 04101

MEMIC







AN

Ц

EMO

 \square

WORK NOTES ○ CONTRACTOR SHALL REMOVE ALL EXISTING POWER DEVICES LOCATED ON WALLS BEING REMOVED DURING DEMOLITION.

RM DENOTES EXISTING ELECTRICAL EQUIPMENT TO REMAIN RL DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE RELOCATED RV DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED

2. CEILING MOUNTED SECURITY, TELCOMM AND SOUND MASKING SYSTEM DEVICES SHALL BE REMOVED AND STORED FOR REINSTALLATION DURING CONSTRUCTION.

RP DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REPLACED

GENERAL NOTES

1. CONTRACTOR SHALL VERIFY EXISTING CONDITIONS.

WP DENOTES WEATHERPROOF CONSTRUCTION



WORK NOTES ○ CONTRACTOR SHALL REMOVE ALL EXISTING POWER DEVICES LOCATED ON WALLS BEING REMOVED DURING DEMOLITION.

GENERAL NOTES 1. CONTRACTOR SHALL VERIFY EXISTING CONDITIONS. 2. CEILING MOUNTED SECURITY, TELCOMM AND SOUND MASKING SYSTEM DEVICES SHALL BE REMOVED AND STORED FOR REINSTALLATION DURING CONSTRUCTION.

WP DENOTES WEATHERPROOF CONSTRUCTION RP DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REPLACED RM DENOTES EXISTING ELECTRICAL EQUIPMENT TO REMAIN RL DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE RELOCATED RV DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED







7 BENNETT RD

PO BOX 297

FREEPORT, ME

A SURGAL AND AS











GENERAL NOTES

1. NOT ALL SYMBOLS INDICATED IN THE LEGEND APPEAR ON THE DRAWINGS. COORDINATE WORK ACCORDINGLY. COMPLY WITH SPECIFICATIONS AND NOTES BELOW AS APPLICABLE.

2. ALL RECEPTACLES SHALL BE INSTALLED 18" AFF TO CENTERLINE OF BOX UNLESS NOTED OTHERWISE.

3. ALL WIRING SHALL BE COPPER UNLESS DESIGNATED AS "AL". UNLESS OTHERWISE NOTED ALL WIRING SHALL BE 2*12 AWG AND 1*12 EQUIPMENT GROUNDING CONDUCTOR. HOMERUNS FED FROM A 20A-1P, 120V CIRCUIT IN EXCESS OF 70' SHALL BE *10 AWG.

4. CONNECT BATTERY BACKED EMERGENCY AND EXIT LIGHTING TO NEAREST LIGHTING CIRCUIT AHEAD OF ANY SWITCHING. CONNECT REMOTE HEADS WITH *10 AWG COPPER CONDUCTORS. AC EXIT FIXTURES SHALL BE CONNECTED TO NEAREST EMERGENCY CIRCUIT OR AS INDICATED.

5. TEST ALL EMERGENCY LIGHTING UNITS FOR PROPER OPERATION OF LAMPS AND BATTERIES.

6.SEE MECHANICAL PLAN FOR HVAC UNITS, PUMPS AND FANS CONTROLLED BY THERMOSTATS (PROVIDED BY ATC CONTRACTOR).

7. FUSES AND OVERLOAD UNITS FOR MOTORS SHALL BE SIZED BASED ON ACTUAL MOTOR NAMEPLATE DATA AND IN ACCORDANCE WITH NEC. CIRCUIT BREAKERS FOR MOTORS ARE SUPPLIED AT MAX VALUE PER NEC (2.5 × FLA). SIZE IN THE FIELD IN ACCORDANCE WITH MFGR RECOMMENDATION.

8. ALL WORK SHALL COMPLY WITH NFPA70, NFPA72, NFPA101 & ALL FEDERAL, STATE & LOCAL REGULATIONS.

9. ALL PENETRATIONS THROUGH FLOORS, RATED WALLS AND PARTITIONS SHALL BE SEALED WITH UL APPROVED FIRE SEALANT MATERIAL TO MAINTAIN FIRE RATING FOR THE SEPARATION.

10. ALL ENCLOSURES, CONDUIT BODIES AND THEIR COVERS CONTAINING FIRE ALARM SYSTEM CONDUCTORS SHALL BE PAINTED RED.

11. AN EQUIPMENT GROUNDING CONDUCTOR SHALL BE INSTALLED WITH ALL FEEDERS AND BRANCH CIRCUITS. SIZE IN ACCORDANCE WITH NFPA 70 ARTICLE 250.

12. PROVIDE TWO BALLASTS FOR EACH FIXTURE INDICATED AS REQUIRING DUAL LEVEL SWITCHING. ONE BALLAST TO CONTROL OUTER LAMPS AND THE SECOND BALLAST TO CONTROL INNER LAMP(S).

13. COORDINATE INSTALLATION OF VOICE/DATA OUTLETS WITH OWNER, MIS OR COMMUNICATIONS CONTRACTOR.

14. LOCATE DISCONNECTS AT EQUIPMENT AS REQUIRED BY MANUFACTURER. LOCATIONS ON DRAWINGS ARE APPROXIMATE.

15. PROVIDE RISER OR PLENUM RATED CABLES ABOVE SUSPENDED CEILINGS.16. ALL CONDUCTOR INSULATION FOR BUILDING WIRE SHALL BE THWN/THHN UNLESS NOTED OTHERWISE.

17. OUTLETS INSTALLED IN FIRE RATED WALLS BACK TO BACK SHALL BE SEPARATED BY 24" MINIMUM OR BE PROTECTED WITH "PUTTY PADS" PER 2009 INTERNATIONAL BUILDING CODE SECTION 713.3.2

18. MINIMUM WIRE SIZE ON ALL BRANCH CIRCUITS SHALL BE *12.

ABBREVIATIONS

А	AMP
AC	ALTERNATING CURRENT, ABOVE COUNTER
ADA	AMERICANS WITH DISABILITIES ACT
AF	AMP FRAME
AFCI	ARC FAULT CIRCUIT INTERRUPTER
AFF	ABOVE FINISHED FLOOR
AFG	ABOVE FINISHED GRADE
AIC	AMPERES INTERRUPTING CAPACITY
AI	
AT	AMP TRIP
ATC	AUTOMATIC TEMPERATURE CONTROL
ATS	AUTOMATIC TRANSFER SWITCH
AWG	AMERICAN WIRE GAUGE
BLDG	BUILDING
0200	CONDUIT
CB	
CL	CAST IRON
CKT	CIRCUIT
C C	
CMP	CENTRAL MAINE POWER (ELECTRIC UTILITY)
CMU	CONCRETE MASONRY LINIT
CIVIO	
	CARDON STEEL
СШН	CABINET LINIT HEATER
FC	
FF	FXHAUST FAN
ER	EXISTING REMAINS IN PLACE
ERL	EXISTING RELOCATE
ERM	EXISTING REMOVE
EUH	ELECTRIC UNIT HEATER
EWC	ELECTRICAL WATER COOLER
FACP	FIRE ALARM CONTROL PANEL
FAPS	FIRE ALARM PULL STATION
FRP	FIBER REINFORCED PLASTIC
FVNR	FULL VOLTAGE, NON-REVERSING
FWU	FURNISHED WITH UNIT
DC	DIRECT CURRENT
GFI	GROUND FAULT INTERRUPTER
GND	GROUND
HID	HIGH INTENSITY DISCHARGE
HOA	HAND-OFF-AUTOMATIC
HP	HORSEPOWER
HPS	HIGH PRESSURE SODIUM
ΗZ	HERTZ
ICB	INSULATED CASE CIRCUIT BREAKER
JB	JUNCTION BOX
KAIC	THOUSAND AMP INTERRUPTING CAPACITY
KCMIL	THOUSAND CIRCULAR MIL
ΚV	THOUSAND VOLTS
ΚVΑ	THOUSAND VOLT-AMPS
κw	INUUSANU WATTS (KILUWATT)
LCP	LATERAL CUNTRUL PH

LED LIGHT EMITTING DIODE

ΤΥΡΕ	MANUFACTURER AND MODEL NUMBER	LAMP INFO	REMARKS
А	FINELITE CAT No HPR-A-2x4-RCO-LED-SO-3500K-120-SC-C1	36W LED 3500K	GENERAL USE RECESSED 2'x4'
В	FINELITE CAT No HPR-A-2x2-RCO-LED-SO-3500K-120-SC-C1	36W LED 3500K	GENERAL USE RECESSED 2'x2'
С	PRESCOLITE CAT No LF4SQLEDG4/4SQLED5G435K/B24	14.4W LED 3500K	4" SQUARE, RECESSED DOWNLIGHT
D	FOCAL POINT SEEM 4 CAT No FSM4L-FL-1000LF-35K-1C-120V-LD1-G3-WH-4'	51W LED 3500K	CLOSED OFFICE AND MEETING ROOM RECESSED 1'x4'

NOTES:

1. FIXTURES SHALL BE ENERGY STAR RATED OR HAVE HIGH PERFORMANCE BALLASTS AND LAMPS TO MEET STATE EFFICIENCY CRITERIA.

2. CONTRACTOR SHALL APPLY FOR ALL STATE EFFICIENCY INCENTIVES ON OWNERS BEHALF.

3. CONTRACTOR SHALL COORDINATE TYPES AND QUANTITIES OF FIXTURES SUPPLIED BY OWNER.

SYMBOL LEGEND

John Min Teleschuld — RECESSED Mounted power Aval.get Part. Schulde Schuld — RECESSED Mounted power Aval.get Part. Schulde Schuld Just Dorm Christian — RECESSED Mounted power Aval.get Part. Schulde Schuld — RECESSED Mounted power Aval.get Part. Schulde Schuld Just Dorm Christian — RECESSED Mounted power Aval.get Part. Schulde Schuld — RECESSED Mounted power Aval.get Part. Schulde Schulde Just Dorm Christian — RECESSED Mounted power Aval.get Part. Schulde Schulde — RECESSED Mounted power Aval.get Part. Schulde Schulde Just Dorm Christian — RECESSED Mounted power Aval.get Part. Schulde Schulde Schulde — RECESSED Mounted power Aval.get Part. Schulde Schuld	LD			SURFACE MOUNTED POWER PANEL. SEE PANEL SCHEDULES FOR RATING
Liss Conc. The Host THE NEXT HE NEXT HE NEXT HE NEXT SUF CONTROL FOR LEVEL IN A CONTROL SO AND THE SUF CONTROL FOR THE NEXT SUF CONTROL SO AND THE SUF CONTROL FOR THE NEXT SUF CONTROL SO AND THE SUF CONTROL				RECESSED MOUNTED POWER PANEL SEE PANEL SCHEDULES FOR RATING
COULT BERVER THE THAT THAT TONS AS NOCATED COURD CONTRAL CONTRAL COURD CONTRAL CONTRAL COURD CONTRAL	LSIG	LONG TIME, SHORT TIME, INSTANTANEOUS, GROUND FAULT	(1/4)	ELECTRIC MOTOR DRIVEN EQUIPMENT. HP SHOWN
CC MUTCH CONTROL CENTER The USUND The USUND </td <td></td> <td>CIRCUIT BREAKER TRIP FUNCTIONS AS INDICATED</td> <td></td> <td>JUNCTION BOX. "H" DENOTES RANGE HOOD. "DS" DENOTES DISPOSAL</td>		CIRCUIT BREAKER TRIP FUNCTIONS AS INDICATED		JUNCTION BOX. "H" DENOTES RANGE HOOD. "DS" DENOTES DISPOSAL
LCC3 WALLEL CASE CREUT BREAKER WAR LOST BREAKER WAR LOST BREAKER PARL	MCC	MOTOR CONTROL CENTER	H, US, UW 🤤	"DW" DENOTES DISHWASHER
M.H. MAN DAR DUB PARKER MAN DAR DUB PARKER MAN DAR D	MCCB	MOLDED CASE CIRCUIT BREAKER	SM	MANUAL MOTOR STARTER SWITCH WITH THERMAL OVERLOAD DEVICE
Multic Structure Profile Barward Description Free Tuber Structure Multics ONY Multics ONY	MCB	MAIN CIRCUIT BREAKER		DISCONNECT SWITCH SIZE AND NUMBER OF POLES AS INDICATED ON
MAIL LUSS OK.Y MARKENSSON (************************************	MUP	MAIN DISTRUBITION PANEL MANHQI F	г <u> </u>	DRAWING. PROVIDED BY EC UNLESS NOTED OTHERWISE. PROVIDE FUSES
MSANAL TRANSTRANCT WAS TRANSTOCKED MANUAL TRANSTRANCT WAS TRANSTOCKED MSANAL TRANSTRANCT CODE MANUAL TRANSTRANCT WAS TRANSTOCKED MSANAL TRANSTRANCT CODE MATCHAL TRANSTOCKED MSANAL TRANSTRANCT TO CODE MATCHAL TREPT PROTECTION ASSOCIATION MSANAL TY CAPN MATCHAL TREPT PROTECTION ASSOCIATION P P. 202 MATCHAL TREPT PROTECTION ASSOCIATION P P. 202 MATCHAL TREPT PROTECTION ASSOCIATION P P. 202 MATCHAL TY CAPN ASSOCIATION P P. 202 MATCHAL TREPT PROTECTION ASSOCIATION P P. 202 MATCH	MLO	MAIN LUGS ONLY		WHERE RECOMMENDED BI MANOFACTORER.
NORMALLY CLOSED OF NURSE CALL AND INFLUED BY LC UNLESS. AND INFLUED BY LC UNLESS. NORMALLY CLOSED OF NURSE CALL AND INFLUED BY LC UNLESS. DUPLY RECEIVED CLO ADDRESS. NORMALLY OPEN DUPLY RECEIVED CLOSE CONS. SPEC CRADE CROUNDING TYPE, TAMPER PROOF AND BUDING PARTAL MONTH BY AFFUNCESS. NOTED OTHERWISE. NO WINKEE DUPLY RECEIVED CLOSE CONS. SPEC CRADE CROUNDING TYPE, TAMPER PROOF AND BUDING PARTAL MONTH BY AFFUNCESS. NO WINKEE DUPLY RECEIVED CLOSE CONS. SPEC CRADE CROUNDING TYPE, TAMPER PROOF AND TAMPER PROOF AND ADDRESS. POUSD CORPESS DUPLY RECEIVED CLOSE CONS. SPEC CRADE CROUNDING TYPE, TAMPER PROOF AND TAMPER PROOF AND ADDRESS PROOF ADDRESS PROOF AND ADDRESS PROOF ADDRESS PROOF AND ADDRESS PROOF ADDRESS PROOF ADDRESS PROOF AND	MTS	MANUAL TRANSFER SWITCH		COMBINATION MOTOR STARTER DISCONNECT SWITCH WITH AUXILART CONTACTS AND HAND-OFF-AUTO SWITCH AND RED RUN LIGHT. PROVIDED
NECK NATIONAL ELECTRICAL CODE DIES WARABLE FR. LOBUNT DIRK- HAUDENT DIRK- HAUDER BOOK AND NUMBER NO NORTLANT FR. PROTECTION ASSOCIATION N. MORTLANT DIRK- RECEPTACE 20A, 22V, SPC CARDE GROUNDED THE LARKER, TO'L BROTES SIDURED CROUNDED THE LARKER, TO'L BROTES NO NORMALLE TOTOM P. PORE PORE P. POR	NC	NORMALLY CLOSED OF NURSE CALL		AND INSTALLED BY EC UNLESS NOTED OTHERWISE.
NPFA NATIONAL FIRE PROJECTION ASSOCIATION NATIONAL FIRE PROJECTION ASSOCIATION CONTRACT ADDRESS NO MARKALY OPEN P DOLE DUPLY RECEPTACE, 20A, 239 SPEC, GRADE GROUNDING TYPE, TAMPER PROOF P DOLE ADDRESS DUPLY RECEPTACE, 20A, 239 SPEC, GRADE CROUNDING TYPE, TAMPER PROOF P HABLY ADDRESS DUPLY RECEPTACE, 20A, 239 SPEC, GRADE CROUNDING TYPE, TAMPER PROOF P HABLY ADDRESS DUPLY RECEPTACE, 20A, 239 SPEC, GRADE CROUNDING TYPE, TAMPER PROOF P HABLY ADDRESS DUPLY RECEPTACE, 20A, 239 SPEC, GRADE CROUNDING TYPE, TAMPER PROOF P HABLY ADDRESS DUPLY RECEPTACE, 20A, 239 SPEC, GRADE CROUNDING TYPE, TAMPER PROOF P HABLY ADDRESS DUPLY RECEPTACE, 20A, 239 SPEC, GRADE CROUNDING TYPE, TAMPER PROOF P HABLY ADDRESS DUPLY RECEPTACE, 20A, 239 SPEC, GRADE CROUNDING TYPE, TAMPER PROOF P HABLY ADDRESS DUPLY RECEPTACE, 20A, 239 SPEC, GRADE CROUNDING TYPE, TAMPER PROOF P HABLY ADDRESS DUPLY RECEPTACE, 20A, 239 SPEC, GRADE CROUNDING TYPE, TAMPER PROOF	NEC	NATIONAL ELECTRICAL CODE		VARIABLE FREQUENCY DRIVE, PROVIDED BY MC, INSTALLED AND WIRED BY EC
Norm Luth Schulz V OPEN Norm Construct Y OPEN Schulz D GRUMONG TYPE, LAMPER Norm Construct Y OPEN Schulz D GRUMONG TYPE, LAMPER Norm Construct Y OPEN Schulz D GRUMONG TYPE, LAMPER Norm Construct Y OPEN Schulz D GRUMONG TYPE, LAMPER Norm Construct Y OPEN Schulz D GRUMONG TYPE, LAMPER Norm Construct Y OPEN Schulz D GRUMONG TYPE, LAMPER Norm Construct Y OPEN Schulz D GRUMONG TYPE, LAMPER Pole Schulz D GRUMONG TYPE, LAMPER Prover Pole Schulz D GRUMONG TYPE, LAMPER Pole Schulz D GRUMONG TYPE, LAMPER Pole Schulz D GRUMONG TYPE, LAMPER Prover Pole Schulz D GRUMONG TYPE, LAMPER Pole Schulz D GRUMONG TYPE, LAMPER Pole Schulz D GRUMONG TYPE, L	NFPA	NATIONAL FIRE PROTECTION ASSOCIATION	Ĩ,	MATCHING PLATE. MOUNT 18" AFF UNLESS NOTED OTHERWISE. "IG" DENOTES
No. NUMBER Image: Second	NL			ISOLATED GROUNDING TYPE.
QL OVERLOAD P PQLE PA PUBLIC ADDRESS PA PUBLIC ADDRESS PD PUBLIC ADDRESS PD PUBLIC ADDRESS PH PUBLIC ADDRESS PD PUBLIC ADDRESS PH PUBLIC ADDRESS PD PUBLIC ADDRESS PUBLIC ADDRESS	NO.	NUMBER	\square	QUAD RECEPTACLE, 20A, 125V SPEC GRADE GROUNDING TYPE, TAMPER PROOF AND MATCHING PLATE. MOUNT 18" AFF UNLESS NOTED OTHERWISE.
P POLE P POLE P PULE ADDRESS PB PULE ADDRESS PF POWER FACTOR PF POWER FACTOR PHASE GROUND FROM PLATE TURNSHED #U.CLE 20A, 125V SPEC GRADE ENDING TYPE, ILMATENING PLATE TURNSHED #LOCK PHASE PAREL FARCENCY DUPLEX RECEPTACLE 20A, 125V SPEC GRADE ENDING TYPE, ILMATENING PLATE TURNSHED #LOCK PHASE PAREL FARCENCY DUPLEX RECEPTACLE 20A, 125V SPEC GRADE ENDING TYPE, ILMATENING PLATE TURNSHED #LOCK PHASE PAREL FARCENCY DUPLEX RECEPTACLE 20A, 125V SPEC GRADE ENDING TYPE, ILMATENING PLATE TURNSHED #LOCK PHASE PAREL AND CHARCH PLATE TURNSHEME (ELECTRIC UTILITY) PHASE PAREL AND CHARCH PLATE TURNSHEME (ELECTRIC UTILITY) PV POINT TO REMAYN PV POLYNWI, CHARGER PV POLYNWI, CHARGER PV POLYNWI, CHARGER PV POLYNWI, CHARGER PV POLYNWI, CHARGEN PV POLYNWI, CHARGER PV POLYNWI, CHARGER PV POLYNWI, CHARGER PV POLYNWI, CHARGEN PV POLYNWI, CHARGEN PV PARCENY & WRINN CRUE	OL	OVERLOAD	-	DUPLEX RECEPTACLE, 20A, 125V SPEC GRADE GROUNDING TYPE, TAMPER PROOF
PA PUBLIC ADDRESS PAH PUBLIC ADDRESS PUBLIC ADDRESS PUBLIC ADDRESS PUBLIC ADDRESS <td>Р</td> <td>POLE</td> <td>Ŭ</td> <td>AND MATCHING PLATE. MOUNT 18" AFF, BOTTOM RECEPTACLE SWITCHED.</td>	Р	POLE	Ŭ	AND MATCHING PLATE. MOUNT 18" AFF, BOTTOM RECEPTACLE SWITCHED.
PD POURT BUTION PF POURT FACTOR PH PHASE PH PHASE PH PAREL PSNH PRECEPTACLE 20A, 25V SPEC CRADE GROUNDING TYPE, ADOWE FINSTED TORR PSNH PRECEPTACLE 20A, 25V SPEC CRADE GROUNDING TYPE, ADOWE FINSTED TORR PSNH POURTIAL TRANSFORMER PVC POURTIAL TRANSFORMER <t< td=""><td>PA</td><td></td><td>Ę</td><td>GROUND FAULT DUPLEX RECEPTACLE 20A, 125V, TAMPER PROOF WITH MATCHING PLATE FURNISHED W/ OUTLET. FLUSH MOUNTED 45'' AFF EXCEPT AS NOTED.</td></t<>	PA		Ę	GROUND FAULT DUPLEX RECEPTACLE 20A, 125V, TAMPER PROOF WITH MATCHING PLATE FURNISHED W/ OUTLET. FLUSH MOUNTED 45'' AFF EXCEPT AS NOTED.
PH PHASE PH PHASE PNL PAREL PNL PAREL PNL POILS PNL PAREL PNL PAREL PNL PAREL PNL PAREL PNL POILS PRUERCOST POILS POILS Statistics PAREL POILS POILS Statistics POILS Statistics POILS Statistics POILS Statistics POILS Statistics POILS Statistics PAREL PARE POILS Statistics POILS Statis	PF	POWER FACTOR		REFRIGERATOR_DUPLEX_RECEPTACLE, 20A, 125V_SPEC_GRADE_GROUNDING_TYPE,
PNRL PH-2 PAREL PH-2 PAREL PL-2 PLUE MEDG PROVER POLE - POLE AND CROUT NUMBER AS INDICATED PT CL⊖ FLUEH FLOOR NUMBER DECEETACLE - 20A 125V SPEC GRADE GROUNDING PT PSH- PUBLIC SERVICE OF NEW HAMPSHRE (ELECTRC UTLITY) PT RANGE OUTLET 50 AMP, 250 VOLT, GROUNDING TYPE FLUEH MOUNTED 18" AF PC POLYNYL CHLORDE RL ELECTRICAL EOUPWENT TO BE RELOCATED RL RANGE OUTLET 50 AMP, 250 VOLT, GROUNDING TYPE FLUEH MOUNTED 18" AF RC ROD STEEL CONDUT RANGE OUTLET SO AMP, 250 VOLT, GROUNDING TYPE FLUEH MOUNTED 18" AF RC ROD STEEL CONDUT RANGE OUTLET SO AMP, 250 VOLT, GROUNDING TYPE FLUEH MOUNTED 18" AF RVM ELECTERCAL EOUPWENT TO REMAN RANGE WAY & WIRNG RUN EXPOSED BRANCH CREAT WERNE SHALL CONST OF RVM R ELECTRCAL EOUPWENT TO REMAN CONCEALED WINK SCHOOR RUN EXPOSED BRANCH CREAT WERNE SHALL CONST OF RVM R REDUCED VOLTARE, NON-REVESING XXX FLORM Y & WIRNG RUN EXPOSED SCHOOR WERNE SS SUPPLY FAN CABLE TV JUNCTION BOX "CTV", SIZE AS REQUIRED BY CABLE UTLITY STARS REMUTCH TO REMAN SS SUPPLY FAN CABLE TV JUNCTION BOX "CTV", SIZE AS REQUIRED BY CC DOOR FLUET LOCATION, CABLE MD JACKS BY EC SS SUPPLY FAN CONCEALED MARE, MERENTH CONCEALED MARE AS DESIGNATED DOOR FLUET TOO-ROORELL SS	PH	PHASE	-	TAMPER PROOF AND MATCHING PLATE. MOUNT RECEPTACLE AT 48 INCHES ABOVE FINISHED FLOOR.
IPI-2 THEL. FORMER POLE - POLE AND CRECUT INDIGHER AS INDICATED IPI-3 THEL. GLENDING CERVICE OF NEW HAMPSHIRE (ELECTRIC UTILITY) PSNH POLYNINYL CHLORDE PVC POLYNINYL CHLORDE RELECTRICAL EQUIPMENT TO BE RELOCATED RACEWAY & WIRNIC GRU EXSPECT RK ELECTRICAL EQUIPMENT TO REMAN RV RELECTRICAL EQUIPMENT TO REMANE RV RELECTRICAL EQUIPMENT TO REMANE RV RELECTRICAL EQUIPMENT TO REMANE RV REMAY & WIRNIG RIN EXPOSED RV RELECTRICAL EQUIPMENT TO REMANE RV RELECTRICAL EQUIPMENT TO REMANE SUB STELE CONDUT REMAY & WIRNIG RIN EXPOSED RV RELECTRICAL EQUIPMENT TO REMANE SUB STELE CONTROL YOL AGE REMAY & WIRNE RIN ENDER FLOOR SUB SOULD STATE SWICH (MARCE AGUE EXPONENCE) SWICH (MARCE AGUE EXPONENCE) REMAY & WIRNE RIN ENDER FLOOR SWICH (CHORADE MANUAL MOTOR STATE	PNL	PANEL	CL⊖	FLUSH FLOOR MOUNTED DUPLEX RECEPTACLE- 20A, 125V SPEC GRADE GROUNDING
OPTIONITAL TRANSFORMER PVC POLYWINTL CHLORDE PVC POLYWINTL CHLORDE RL ELECTRICAL EQUIPMENT TO BE RELOCATED RSC RIGD STEEL CONDUT RSC RIGD STEEL CONDUT RV ELECTRICAL EQUIPMENT TO REMAIN RV ELECTRICAL EQUIPMENT TO REMAIN RSC RIGD STEEL CONDUT RV ELECTRICAL EQUIPMENT TO REMAIN RV ELECTRICAL EQUIPMENT TO REMAIN RV ELECTRICAL EQUIPMENT TO REMAIN RV ELECTRICAL EQUIPMENT TO REMOVE RVR RZCWAY & WIRING RUN EXPOSED RVR EQUICED VOLTAGE, NON-REVESING SS SUPPLY FAN SLD SINCE LINE DAGRAM SM MANUAL MOTOR STAREER SWICH WITH THERMAL OVERDAD EVERGE WOUNED AT UNIT ET SWEDD SWITCHED FOLOR OR EXEMPTICAL TOOL PANEL PROVED BY ACCORDANCE SWEDD SWITCHED FOLOR OR EXEMPTICAL TOOL PANEL PROVED BY ACCORDANCE SWEDD SWITCH FOLOR OR EXEMPTICAL TOOL PANEL PROVED BY ACCORDANCE SWEDD SWITCH FOLOR OR EXEMPTICAL TOOL PANEL PROVED BY ACCORDANCE SWEDD SWITCH FOLOR OR EXEMPTICAL TOOL PANEL PROVED BY ACCORDANCE AND	TP1-2 PSNH	PUBLIC SERVICE OF NEW HAMPSHIRE (FLECTRIC LITUITY)	- 🔿	RANGE OUTLET 50 AMP. 250 VOLT GROUNDING TYPE FLUSH MOUNTED 18" AFF
PVC POLYYNYL CHCOROE RL ELECTRICAL EQUIPMENT TO BE RELOCATED RL ELECTRICAL EQUIPMENT TO REMAIN RCCWAY & WIRING OR MC CABLE BRANCH CIRCUIT WIRING SHALL CONSIST OF RTU ROOF TOP UNIT RV ELECTRICAL EQUIPMENT TO REMAIN RTU ROOF TOP UNIT RV ELECTRICAL EQUIPMENT TO REMOVE RVN RECEWAY & WIRING RUN EVOSED RVN RECEWAY & WIRING RUN EVOSED SUBJECTION TOP UNIT RACEWAY & WIRING RUN EVOSED RVN RECEWAY & WIRING RUN EVOSED SUBJECTION TOP UNIT RACEWAY & WIRING RUN EXOSED RVN RECEWAY & WIRING RUN EXOSED SUBJECTION TOP UNIT RECEWAY & WIRING RUN EXOSED SUBJECTION FOR ELECTRICALLY OPERATION FOR ELECTRICALLY OPERATION FOR ELECTRICALLY OPERATION CONTACTION SIN ACCORDANCE SUBJECTION FOR EXTENSION FOR TOP INFORMENT MICH LIGHTUN FOR ELECTRICALLY OPERATION CONTAC	PT	POTENTIAL TRANSFORMER	-₩	DRYER OUTLET 30 AMP 250 VOLT GROUNDING TYPE FLUSH MOUNTED 18" AFF
RL ELECTRICAL EQUIPMENT TO BE RELOCATED RM ELECTRICAL EQUIPMENT TO BE RELOCATED RM ELECTRICAL EQUIPMENT TO REMAN RC RIGD STEEL CONDUIT RTU ROF CARCIAL WARKS FUNCE RUN EXPOSED RV ELECTRICAL EQUIPMENT TO REMAN RV ELECTRICAL EQUIPMENT TO REMOVE RVN RACEWAY & WIRNE RUN EXPOSED RVN ENTRIE SUBJECT DURIT RV ELECTRICAL EQUIPMENT TO REMOVE RVN ELECTRICAL EQUIPMENT TO REMAN RV ELECTRICAL PONDOL RV ELECTRICAL PONDOL RV ELECTRICAL PONDOL RVN ELECTRICAL PONDOL SUPPLY FAN SUPPLY FAN SUPPLY FAN MANUAL MOTOR STAFTER SWITCH WITH THERMAL SWBO-1 SWITCHOAD DEVICE, MONTED AT UNIT EMERGENCY LOCAL PONDOL SWBO-1 SWITCHOAD DEVICE, MONTED AT UNIT EMERGENCY LOCAL PONDOL SWBO-1 SWITCHOAD DEVICE, MONTED AT UNIT EMERGENCUL CONCERCLAND CONCLETS, MODARD PONDOL </td <td>PVC</td> <td>POLYVINYL CHLORIDE</td> <td>¥</td> <td></td>	PVC	POLYVINYL CHLORIDE	¥	
RM ELECTRICAL EQUIPMENT TO REMAIN RSC Rigit STEEL CONDUIT RV ROOF TOP UNIT RV ROOF TOP UNIT RV RECENARY & WIRING RUN RV ELECTRICAL EQUIPMENT TO REMOVE RVNR REDUCED VOLTAGE, NON-REVESING SB SMART BOARD SF SUPLY FAN SLD SINGLE LINE DIAGRAM SM MANUAL MOTOR STARTER SWITCH WITH THERMAL OVERLOAD DEVICE, MOUNTED AT UNIT ET SW MANUAL MOTOR STARTER SWITCH WITH THERMAL OVERLOAD DEVICE, MOUNTED AT UNIT ET SW MANUAL MOTOR STARTER SWITCH SW MOND SITCH CONDER ALL EVERTICALLY OPERATED ET CT THE CLOCK SW MOND SITCH CONDER DOOR PAREL SW MICHAGAND NUMBER AS DESIGNATED ET TC THE CLOCK THE LOCK DOOR PAREL SW TOHAGAND NUMBER AS DESIGNATED Immediate Schedult TG UNDERGROUND V VOLT VA VOLT - AMPERE VFD VARIABLE FREQUENCY DRIVE VFD VARIABLE	RL	ELECTRICAL EQUIPMENT TO BE RELOCATED		RUN CONCEALED IN WALLS/CEILINGS BRANCH CIRCUIT WIRING SHALL CONSIST OF
NSL NRUD Site L CURUDI RTU RXOF TOP UNIT RXEWAY & WIRING RUN CONCELED UNDER FLOOR OR BUILDER FLOOR OR CONCELED UNDER FLOOR OR BUILDER JOB BELOW FINISH GRAD Concele Unit House RUN C*-JOBUBLE CONCELED UNDER FLOOR OR BUILDE JOB BELOW FINISH GRAD Concele Unit All the Concelest STESK DENTES (1)3/4'C-2*88WG:1*IOGND. RV REDUCED VOLTACE, NON-REVESING ************************************	RM	ELECTRICAL EQUIPMENT TO REMAIN		RACEWAY & WIRING RUN EXPOSED (1)1/2"C-2*12AWG+1*12GND UNLESS OTHER WISE
RV ELECTRICAL EQUIPMENT TO REMOVE RV ELECTRICAL EQUIPMENT TO REMOVE RV RELECTRICAL EQUIPMENT TO REMOVE RV REMOVE SUPPLY FAN SLD SINGLE LINE DIAGRAM SMBD-1 SWICH-GAD OVERE, WOUTH THERMAL OVERLOAD OVERCEADD NUMBER AS DESIGNATED TV OUTLET LOCATION, CABLE AND JACKS BY EC T V OUTLET LOCATION, CABLE CONTROL PANEL, PROVIDED BY MC WIRED BY CC SWBD-1 SWICHBOARD NUMBER AS DESIGNATED TV OUTLET LOCATION, CABLE CAND JACKS BY EC T TYP OUTLED AL UNIT DOOR PUSHBUTTON-DOORBELL TY PYPICAL DOOR PUSHBUTTON-DOORBELL DOOR PUSHBUTTON FOR ELECTRICALLY OPERATED DOOR, FURMENT V VOLT LIGHTING FIXTURE, SCHEDULE, LOWER CASE LETTRES DENOTE TYPE PER VFO VARIABLE FREQUENCY DRIVE <td>RSC</td> <td>RIGID STEEL CONDULT ROOF TOP LINIT</td> <td></td> <td>RACEWAY & WIRING RUN CONCEALED LINDER FLOOP OR</td>	RSC	RIGID STEEL CONDULT ROOF TOP LINIT		RACEWAY & WIRING RUN CONCEALED LINDER FLOOP OR
RVNR REDUCED VOLTAGE, NON-REVESING SK SMART BOARD SF SUPPLY FAN SLD SINGLE LINE DIAGRAM SM MANUAL MOTOR STARTER SWITCH WITH THERMAL OVERLOAD DEVICE, MOUNTED AT UNIT CABLE TV JUNCTION BOX "CTV", SIZE AS REQUIRED BY CABLE UTILITY SM MANUAL MOTOR STARTER SWITCH WITH THERMAL OVERLOAD DEVICE, MOUNTED AT UNIT CABLE TV JUNCTION BOX "CTV", SIZE AS REQUIRED BY CABLE UTILITY SWED-1 SWITCHBOARD NUMBER AS DESIGNATED C PUSHBUTTON FOR ELECTRICALLY OPERATED BY MC WIRED BY EC IS TRANSFER SWITCH DOOR PUSHBUITON FOR ELECTRICALLY OPERATED DOOR, FURN W/ DOOR OPERATOR, WIRED BY EC IS TRANSFER SWITCH DOOR PUSHBUITON FOR ELECTRICALLY OPERATED DOOR, FURN W/ DOOR OPERATOR, WIRED BY EC IS TRANSFER SWITCH DOOR CLECTRIC STRIKE IS TOP AND BOTTOM DOOR ELECTRIC STRIKE TYP TYPICAL DOOR CHIME WITH STROBE-ADA COMMUNICATIONS REQUIREMENT VOLT VOLT DOOR CHIME WITH STROBE-ADA COMMUNICATIONS REQUIREMENT VOLT VOLT SWITH SWITH VOLT VOLT SWITH SWITH VOLT VOLT SWITH SWITH SWITH W WITH	RV	ELECTRICAL EQUIPMENT TO REMOVE		BURIED 30" BELOW FINISH GRADE
SB SMART BOARD Index AND Curcon Homeler SF SUPPLY FAN SLD SINGLE LINE DIAGRAM SLD SINGLE LINE DIAGRAM SM MANUAL MOTOR STARTER SWITCH WITH THERMAL OVERLOAD DEVICE, MOUNTED AT UNIT SS SOLID STATE SWBD-1 SWITCHBOARD NUMBER AS DESIGNATED TC TIME CLOCK TS TRANSEER SWITCH TYP TYPICAL UG UNDERGROUND V VOLT W WATT W/W WATT W/P WEATHERROOF XFMR TRANSFORMER XFMR TRANSFORMER XFMR TRANSFORMER XFMR TRANSFORMER XFMR TRANSFORMER XFMR TRANSFORMER	RVNR	REDUCED VOLTAGE, NON-REVESING	<u>*</u> ► HP-XX	HOME RUN TO PANEL, WITH PROVIDE EQUIPMENT GROUNDS IN ACCORDANCE WITH NEPA 70, ATRICLE 250.
SF SUPPLY FAN SLD SINGLE LINE DIAGRAM SLD SINGLE LINE DIAGRAM SLD SINGLE LINE DIAGRAM M MANUAL MOTOR STARTER SWITCH WITH THERMAL OVERLOAD DEVICE, MOUNTED AT UNIT SWDD-1 SWITCHBOARD NUMBER AS DESIGNATED TC TIME CLOCK SWDD-1 SWITCHBOARD NUMBER AS DESIGNATED TC TIME CLOCK B TOP AND BOTTOM UG UNDERGROUND V VOLT UG UNDERGROUND V VOLT V VOLT V VOLT VFD VAIRABLE FREQUENCY DRIVE W WATT W/ WATT W/ WATT W/ WATH W/ WATT W/ WATT W/ EXPLOSION PROOF XFM FRANSFORMER XFM FRANSFORMER W/ WATT W/ WATT W/ WATT W/ WATH W/ WATH	SB	SMART BOARD	**	
SLD SINGLE LINE DIAGRAM SM MANUAL MOTOR STARTER SWITCH WITH THERMAL OVERLOAD DEVICE, MOUNTED AT UNIT TV OUTLET LOCATION, CABLE AND JACKS BY EC SS SOLID STATE TEMPERATURE CONTROL PANEL, PROVIDED BY MC WIRED BY EC SWBD-1 SWITCHBOARD NUMBER AS DESIGNATED PUSHBUTTON, FOR ELECTRICALLY OPERATED DOOR, FURN W/ DOOR OPERATOR, WIRED BY EC TC TIME CLOCK DOOR PUSHBUTTON-DOORBELL TS TRANSFER SWITCH DOOR ELECTRIC STRIKE TYP TYPICAL DOOR CHIME WITH STROBE-ADA COMMUNICATIONS REQUIREMENT UG UNDERGROUND ILIGHTING FIXTURES CAPITAL LETTERS DENOTE TYPE PER VA VOLT-AMPERE DHO VFD VARIABLE FREQUENCY DRIVE DHO W WATT SULF CONTAINCE CHIER SWITCHED W/W WITH SELF CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZ65I-03L, 65 WATTS FOR 90 MINUTES, COLOR BY ARCHITECT W WATT EMERGENCY LIGHTING BATTERY PACK DUAL-LITE NO LMI30-12VI-0 SELF-DIAGNOSTIC YP EXPLOSION PROOF ENT XFMR TRANSFORMER EXTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL LZ65I-03L, 65 WATTS FOR 90 MINUTES, COLOR BY ARCHITECT YP EXPLOSION PROOF EXTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL NO CORD 1203L, C	SF	SUPPLY FAN	CTV	CABLE TV JUNCTION BOX "CTV", SIZE AS REQUIRED BY CABLE UTILITY
SM OVERLOAD DUTY OF SUCCE, MOUNTED AT UNIT SN OVERLOAD DUTY OF SUCCE, MOUNTED AT UNIT SN SUED STATE SWBD-1 SWITCHBOARD NUMBER AS DESIGNATED TC TIME CLOCK TS TRANSFER SWITCH TS TRANSFER SWITCH TVP TYPICAL UG UNDERGROUND V VOLT V VIT W WATT W WATT V VOLT V VOLT VP VEATHEL FREQUENCY DROF V WITH W WEATHER VFD VARIABLE FREQUENCY DROF <td>SLD</td> <td>SINGLE LINE DIAGRAM</td> <td>ТV</td> <td>TV OUTLET LOCATION, CABLE AND JACKS BY EC</td>	SLD	SINGLE LINE DIAGRAM	ТV	TV OUTLET LOCATION, CABLE AND JACKS BY EC
SS SOLID STATE SWBD-1 SWITCHBOARD NUMBER AS DESIGNATED TC TIME CLOCK TS TRANSFER SWITCH TS TRANSFER SWITCH TVP TYPICAL UG UNDERGROUND V VOLT V VOLT VARIABLE FREQUENCY DRIVE VV VOLT-AMPERE VF VARIABLE FREQUENCY DRIVE VV WITH VV VARIABLE FREQUENCY DRIVE VV WITH VF EXECONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZESI-OJL, 65 WATTS FOR 90 MINUTES, COLOR BY ARCHITECT VF WAT VV WITH VF EXEL CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZESI-OJL, 65 WATTS FOR 90 MINUTES, COLOR BY ARCHITECT VF EXELF CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZESI-OJL, 65 WATTS FOR 90 MINUTES, COLOR BY ARCHITECT VF EXELF CONTAINED EMERGENCY LIGHTING BATTERY PACK DUAL-LITE (LED) MODEL NO CRP 1203L, COLOR BY ARCHITECT VF EXELF COLOR REMOTE HEAD DUAL-LITE (LED) MODEL NO CRP 1203L, COLOR BY ARCHITECT VF EXELF CONTAINED EMERGENCY LIGHTING BATTERY PACK DUAL-LITE NO LMI30-12VI-0 SELF-DIAGNOSTIC	SIM	OVERLOAD DEVICE, MOUNTED AT UNIT	TCP	TEMPERATURE CONTROL PANEL, PROVIDED BY MC WIRED BY EC
SWBD-1 SWITCHBOARD NUMBER AS DESIGNATED WIRED BY EC TC TIME CLOCK ● DOOR PUSHBUTTON-DOORBELL TS TRANSFER SWITCH □ TYP TYPICAL □ UG UNDERGROUND □ V VOLT □ VA VOLT-AMPERE □ VFD VARIABLE FREQUENCY DRIVE □ W WATT □ W/ WITH SELF CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZ65I-03L, WP WEATHERPROOF □ XFMR TRANSFORMER □ XFMR TRANSFORMER □ XFMR THREE PHASE □ 3W THREE WIRE □ 3W THREE WIRE □	SS	SOLID STATE	·	PUSHBUTTON FOR ELECTRICALLY OPERATED DOOR, FURN W/ DOOR OPERATOR,
Time octoor To book PoshBotton-bookBell Ts TRANSFER SWITCH TsB ToP AND BOTTOM TyP TyPicAL UG UNDERGROUND V VOLT VA VOLT-AMPERE VFD VARIABLE FREQUENCY DRIVE W WATT W/ WITH W WATT W/ WITH SELF CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZ65I-03L, 65 WATTS FOR 90 MINUTES, COLOR BY ARCHITECT W/ WITH W/ WEATHERPROOF SELF CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZ65I-03L, 65 WATTS FOR 90 MINUTES, COLOR BY ARCHITECT WP WEATHERPROOF STRANSFORMER XP EXPLOSION PROOF SPH THREE PHASE 4W FOUR WIRE 3W THREE WIRE	SWBD-1	SWITCHBOARD NUMBER AS DESIGNATED	0	WIRED BT EC
Two AND BOTTOM Typ Typical Idux Person UG UNDERGROUND A V Volt Volt VA VOLT-AMPERE DHO VFD VARIABLE FREQUENCY DRIVE DHO W WATT FO W/ WITH Self CONTROL W/ WITH Self CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZ65I-03L, W/ WITH Self CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZ65I-03L, W/ WITH Self CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZ65I-03L, W/ WITH Self CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZ65I-03L, W/ WITH Self CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZ65I-03L, W/ WITH Self CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZ65I-03L, W/ BY WEATHERPROOF Self CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZ65I-03L, W/ EXPLOSION PROOF INTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL No CPRD 1203L, COLOR BY ARCHITECT W/ FOUR WIRE EXTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL No OCRD 1203L, COLOR BY ARCHITECT	TS	TRANSFER SWITCH		
TYP TYPICAL UG UNDERGROUND V VOLT VA VOLT-AMPERE VFD VARIABLE FREQUENCY DRIVE W WATT W/ WITH W/ WITH SELF CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZ65I-03L, KP WEATHERPROOF XFMR TRANSFORMER XP EXPLOSION PROOF XP EXPLOSION PROOF XP FOUR WIRE 3W THREE PHASE 3W THREE WIRE	T&B	TOP AND BOTTOM		DOOR ELECTRIC STRIKE
UG UNDERGROUND A□ V VOLT LIGHTING FIXTURES, CAPITAL LETTERS DENOTE TYPE PER LIGHTING FIXTURES, CAPITAL LETTERS INDICATE VA VOLT-AMPERE D+O VFD VARIABLE FREQUENCY DRIVE FO W WATT W/ WITH WP WEATHERPROOF XFMR TRANSFORMER XFMR TRANSFORMER SPLOSION PROOF EMERGENCY LIGHTING BATTERY PACK DUAL-LITE No LM130-12VI-0 SELF-DIAGNOSTIC XP EXPLOSION PROOF XP EXPLOSION PROOF VP EXPLOSION PROOF VP EXPLOSION PROOF XP EXPLOSION PROOF XP EXPLOSION PROOF 3PH THREE PHASE 3PH THREE PHASE 3W THREE WIRE 3W THREE WIRE	TYP	TYPICAL	오▷얼	DOOR CHIME WITH STROBE-ADA COMMUNICATIONS REQUIREMENT
V VOLT VA VOLT-AMPERE VFD VARIABLE FREQUENCY DRIVE W WATT W WATT W/W WITH W WEATHERPROOF XFMR TRANSFORMER XFMR TRANSFORMER XP EXPLOSION PROOF XP FOUR WIRE 3W THREE PHASE 3W THREE WIRE	UG	UNDERGROUND		
VA VOL 1-AMPERE VFD VARIABLE FREQUENCY DRIVE W WATT W/ WITH WP WEATHERPROOF XFMR TRANSFORMER XP EXPLOSION PROOF XP EXPLOSION PROOF 3PH THREE PHASE 4W FOUR WIRE 3W THREE WIRE	V	VOLT		LIGHTING FIXTURE SCHEDULE. LOWER CASE LETTERS INDICATE
VFD VARIABLE FREQUENCY DRIVE W WATT W WATT W/ WITH WP WEATHERPROOF XFMR TRANSFORMER XP EXPLOSION PROOF XP EXPLOSION PROOF 3PH THREE PHASE 4W FOUR WIRE 3W THREE WIRE	VA		FO	BY OUTBOARD SWITCHED "" AND "" DIAGONAL INDICATED
W/ WITHSELF CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZ65I-03L, 65 WATTS FOR 90 MINUTES, COLOR BY ARCHITECTWPWEATHERPROOFEMERGENCY LIGHTING BATTERY PACK DUAL-LITE No LM130-12VI-0 SELF-DIAGNOSTICXFMRTRANSFORMEREMERGENCY LIGHTING BATTERY PACK DUAL-LITE No LM130-12VI-0 SELF-DIAGNOSTICXPEXPLOSION PROOFINTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL No CPRD 1203L, COLOR BY ARCHITECT3PHTHREE PHASEINTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL No OCRD 1203L COLOR BY ARCHITECT4WFOUR WIREINTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL No OCRD 1203L COLOR BY ARCHITECT3WTHREE WIREINTERIOR REMOTE HEAD DUAL-LITE LX-U-R-W-E OR APPROVED EQUAL	VFD W	VARIABLE FREQUENCY DRIVE WATT	0	NIGHT_LIGHT_(UNSWITCHED)
WPWEATHERPROOF65 WATTS FOR 90 MINUTES, COLOR BY ARCHITECTXFMRTRANSFORMEREMERGENCY LIGHTING BATTERY PACK DUAL-LITE No LM130-12VI-0 SELF-DIAGNOSTICXPEXPLOSION PROOFINTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL No CPRD 1203L, COLOR BY ARCHITECT3PHTHREE PHASEINTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL No OCRD 1203L COLOR BY ARCHITECT4WFOUR WIREINTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL No OCRD 1203L COLOR BY ARCHITECT3WTHREE WIREEXIT LIGHT FIXTURE, UNSWITCHED, DUAL-LITE LX-U-R-W-E OR APPROVED EQUAL	W/	WITH	22	SELF CONTAINED EMERGENCY LIGHT W/2 HEADS DUAL-LITE (LED) MODEL LZ65I-03L,
XFMR TRANSFORMER EMERGENCY LIGHTING BATTERY PACK DUAL-LITE No LM130-12VI-0 SELF-DIAGNOSTIC XP EXPLOSION PROOF INTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL No CPRD 1203L, COLOR BY ARCHITECT 3PH THREE PHASE INTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL No OCRD 1203L COLOR BY ARCHITECT 4W FOUR WIRE EXTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL No OCRD 1203L COLOR BY ARCHITECT 3W THREE WIRE EXIT LIGHT FIXTURE, UNSWITCHED, DUAL-LITE LX-U-R-W-E OR APPROVED EQUAL	WP	WEATHERPROOF		65 WAITS FOR 90 MINUTES, COLOR BY ARCHITECT
XP EXPLOSION PROOF 3PH THREE PHASE 4W FOUR WIRE 3W THREE WIRE	XFMR	TRANSFORMER	BATT	EMERGENCY LIGHTING BATTERY PACK DUAL-LITE No LM130-12VI-0 SELF-DIAGNOSTIC
4W FOUR WIRE 3W THREE WIRE WIRE Image: Construction of the second s	XР 3Du	LAPLUSIUN PRUUF	Ц° С	INTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL No CPRD 1203L, COLOR BY ARCHITECT
3W THREE WIRE EXIT LIGHT FIXTURE, UNSWITCHED, DUAL-LITE LX-U-R-W-E OR APPROVED EQUAL	3гп 4W	FOUR WIRE	R R	EXTERIOR REMOTE HEAD DUAL-LITE (LED) MODEL No OCRD 1203L COLOR BY ARCHITECT
	3W	THREE WIRE		EXIT LIGHT FIXTURE, UNSWITCHED, DUAL-LITE LX-U-R-W-E OR APPROVED EQUAL

LIGHT FIXTURE SCHEDULE

 Schutt Cowers Location Community and People Inducts Received Laboration Schutz Cowers and Schutz Cowers and		
DN GENERAL MOUNTED ADDIONAL SENSION AND LINEARE INFLATIONAL OPERATION CONTRACT ADDIONAL SENSION AND LINEARE INFLATIONAL OPERATIONAL DISCIPLINARY AND ADDIONAL SENSION AND ADDIONAL SENSITIC ADDIONAL SENSITICA ADDIONAL SENSITIC ADDIONAL SE	$\Box \forall$	SECURITY CAMERA LOCATION, COORDINATE AND PROVIDE DUPLEX RECEPTACLE, DATA AND CONDUIT PER MANUFACTURERS RECOMMENDATIONS
 PHE NUCLEUP PRAVE INFORCE STATUS CONTACT A 45" AFT LACESS OTHER WISE NOTED S. WALL POLE SWITCH (2007 ADA SEC CANAGE CONDUMENT THE NUCLET AT 3-3" MAY. S. SINGLE POLE SWITCH (2007 ADA SEC CANAGE CONDUMENT THE NUCLET ASS. S. SINGLE POLE SWITCH (2007 ADA SEC CANAGE CONDUMENT THE NUCLET ASS. S. PRENTE RANGE HOLD LIGHT SWITCH CONTACT TO HODD TAT THRU HODD JUNCTION BOX. BRUNER SHETT'S WITCH PROVE WITH RED PLATE MOUTHER 72" AFF S. SINGLE POLE SWITCH PROVE WITH RED PLATE MOUTHER 72" AFF S. SINGLE POLE DAWER SWITCH PROVE WITH RED PLATE MOUTHER 72" AFF S. SINGLE POLE DAWER SWITCH ROVE WITH RED PLATE MOUTHER 72" AFF S. SINGLE POLE MARKE SWITCH ROVE WITH RED PLATE MOUTHER 72" AFF S. SINGLE POLE MARKE SWITCH ROVE WITH RED PLATE MOUTHER 72" AFF S. SINGLE POLE MARKE SWITCH CASE LETTER NUCLESS TATUBLE OF CONTROLLED LOW. THELEPONE CASE LETTER NUCLEASES TATUBLE OF CONTROLLED LOW. THELEPONE AND AND ALL JACK MOUNT BY AFF UNLESS NOTED OTHERWISE, RUN ONE CAT SE CARLES THELEPONE PLACE MOUNT DY AFF UNLESS NOTED OTHERWISE, RUN ONE CAT SE CARLES THELEPONE PLACE MOUNT DY AFF UNLESS NOTED OTHERWISE, RUN ONE CAT SE CARLES THELEPONE PLACE MOUNT DY AFF UNLESS NOTED OTHERWISE, RUN ONE CAT SE CARLES THELEPONE PLACE MOUNT DY AFF UNLESS NOTED OTHERWISE, RUN ONE CAT SE CARLES THELEPONE PLACE MOUNT DY AFF AFF. MARKES DOTHER CARLES AND CONTROL TO THE AFF WIFFROOM PAREL AT RECEPTION THER ALAWA CONTROL PAREL THER ALAWA MAINGLARDER PART DE SALL PROVIDE WITH TO THE AFF THER ALAWA MAINGLARDER DATA SALL PROVIDE WITH TO THE AFF. THER ALAWA MAINGLARDER MOUNT OF SA	DT PIR MS	CEILING MOUNTED MOTION SENSOR (WATTSTOPPER OR EQUAL) CORRIDORS: WT-2255 SENSOR & B120E-P POWER PACK. OTHER COMMON SPACES: WT-605 SENSOR & B120E-P POWER PACK. SENSORS AND RELAYS TO CONTROL CIRCUITS IN SPACES INDICATED. DEVICES SHALL PROVIDE FULL COVERAGE IN AREAS INSTALLED. DT INDICATES DUAL TECHNOLOGY
 S. S. ANGLE POGE SWITCH, JON, JOA SPEC, GRANT, GROUNDEN, TYPE, MOUTT AF, AT, 3-3-WAY, A. S. WILDY, WITH PLOT LIGHT, SWITCH SHALL BE PROVOED WY ENGAVED NAMEPLATE BY THE CONDECT IN THE UNCENTRE DECOMPLICITION DOX. S. SWITCH, WITH RUDO FAN SWITCH, CONNECT TO HODO FAN THRU HODO JUNCTION BOX. S. BURKER SAFETY SWITCH, PROVIE WITH RED PLATE, MOUTTED 327-WF S. S. SWITCH, WITH WITH SWITCH, CONNECT TO HODO FAN THRU HODO JUNCTION BOX. SUBRER SAFETY SWITCH, PROVIE WITH RED PLATE, MOUTTED 327-WF S. S. SWITCH, WANT, LOWER CASS LETTER MODERIES TAXINGE OF CONTRELLED LIGA. S. S. WALL, AND HONDO FAN THRUTT, FUN TWO CAT SE CALLES BOX TO TBB THACLOOK WITHERDORE, JOAK MOUNT IN WAT, RUN THRUTT, RUN TWO CAT SE CALLES BOX TO TBB OTAL JUNC, RUN TWO CAT SE CALLES BOX TO TBB. THEERON PARL AT RECEIPTORY THRU HARD, JUNC, RUN TWO CAT SE CALLES BOX TO TBB OTAL JUNC, RUN TWO CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLE BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLE BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLE BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CAT SE CALLES BOX TO TBB OTHERWISE, RUN ONE CALLES BOX TO TBB OTHERWISE, RUN ONE CALLES BOX TO TBB OTHERWISE	Sms	PIR INDICATED PASSIVE INFRARED TECHNOLOGY WALL MOUNTED SWITCH MOTION SENSOR. MOUNT AT 48'' AFF UNLESS OTHER WISE NOTED
 USAN FYNE VOLD RENDER RADEL RODD LIGHT SWITCH, CONRECT TO HOOD LAN THRU HOOD JUNCTION BOX. BURKE RADE HOOD LIGHT SWITCH, CONRECT TO HOOD LIGHT THRU JUNCTION BOX. BURKE PASE DIMENT SWITCH, CONRECT TO HOOD LIGHT THRU JUNCTION BOX. BURKE PASE DIMENT SWITCH, CONRECT TO HOOD LIGHT THRU JUNCTION BOX. BURKE PASE DIMENT SWITCH, CONRECT TO HOOD LIGHT THRU JUNCTION BOX. BURKE PASE DIMENT SWITCH, CONRECT TO HOOD CATE COUNDING TYPE MOUNT 49" ATT. DIGTOCOLL TELEPHORE JOAN DUAL, JACK MOUNT IS/AFF, RUN TWO CAT SE CARLES BOX TO TBB OTATA JACK, RUN TWO CATE CARLE STATUBE OR CONTROLLED LIGA. FUER FLOOR MOUNTED TELEPHORY ATA DUAL JACK. RUN TWO CAT SE CARLES FUER FLOOR MOUNTED TELEPHORY ATA DUAL JACK. RUN TWO CAT SE CARLES TELEPHORE JOAN BOAD TELEPHORE JOAN MOUNT BY AFF UNLESS NOTED DIFFERMISE, RUN ONE CAT SE CARLES TELEPHORE JOAN MOUNT BY AFF UNLESS NOTED DIFFERMISE, RUN ONE CAT SE CARLES TELEPHORE JOAN MOUNT BY AFF UNLESS NOTED DIFFERMISE, RUN ONE CAT SE CARLES TELEPHORE JOAN MOUNT BY AFF UNLESS NOTED DIFFERMISE, RUN ONE CAT SE CARLES TELEPHORE JOAN MOUNT BY AFF UNLESS NOTED DIFFERMISE, RUN ONE CELLING, "W" DENOTES OCCUME ACCOUNT AND AND THE SECTION CONTROLLED. THERE ALAWI ADDINATED PAREL TELEPHORE JOAN MOUNT DIFFERE SECTION CONTROLLED. FERE ALAWI ADDINATED PAREL TELEPHORE JOAN MOUNT DIFFERE SECTION CONTROLLED. FERE ALAWI ADDINATED PAREL STATUM WIDELS STATUM ADDITER SECTION CONTROLLED. ATTIC DIFFERENCE AND THE DIFFERENCE AND AND ADDITES CELLING MOUNTED OF AFF. NUMBER BORDITES CONTROLLED ATTIC DIFFERENCE AND ADDITES CELLING MOUNTED OF AFF. NUMBER BORDITES CONTROLLED ATTIC DIFFERENCE AND ADDITES CELING MOUNTED OF AFF. NUMBER BORDITES CONTROLLED ATTIC DIFFERENCE AND ADDITES CELING MOUNTED OF AFF. NUMBER BORDITES CONTROLLED AT	S. S S4 S3	SINGLE POLE SWITCH, 120V, 20A, SPEC GRADE, GROUNDING TYPE, MOUNT 48" AFF, 3=3-WAY, 4=4-WAY, LOWER CASE LETTER INDICATES FIXTURE OR CONTROLLED LOAD. SWITCH WITH PILOT LIGHT, SWITCHE SHALL BE PROVIDED W/ ENGRAVED NAMEPLATE
S., BURKER SAFETY SWICH, RRAVIE WITH RED PLATE, MONTED 12" AFF B.O. SHARE ALL END EMBERS WITH AND ALL ALL THE STATURE OF CONTROLLED LOAD. S-SHARE ALL ALL ALL ALL ALL ALL ALL ALL ALL AL	Srf Srl	IDENTIFYING USE REMOTE RANGE HOOD FAN SWITCH, CONNECT TO HOOD FAN THRU HOOD JUNCTION BOX. REMOTE RANGE HOOD LIGHT SWITCH, CONNECT TO HOOD LIGHT THRU JUNCTION BOX.
 HADDOLLL LIGHER CONTACTOR TELEPHORE ALKA DUL, JACK, MOUNT 18"AFF, RUN TWO CAT SE CABLES BACK TO TBB DATA JACK, RUN TWO CAT SE CABLES BACK TO TBB. ELEM-RICK, RUN TWO CAT SE CABLE BACK TO TBB. ELEM-RICK, RUN TWO CAT SE CABLE BACK TO TBB. ELEM-RICK, MOUNT 18"AFF UNLESS NOTED OTHERWISE, RUN ONE CAT SE CABLES ELEM-RICK, MOUNT 18"AFF UNLESS NOTED OTHERWISE, RUN ONE CAT SE CABLE MICHERONE BACK BOARD WITERCOM PANEL AT RECEPTION INTERCOM PANEL AT RECEPTION FIRE ALARM ACUINTOR PANEL FIRE ALARM AUUL STATION, MOUNT 6"AFFF FIRE ALARM AUUL STATION, MOUNT 6"AFFF STATE AND AUXION CONTOLE FIRE THE MOUNT 6"AFF AFF, NUMBER DENOTES CAPADELLA RATING, "AFF FIRE ALARM AUUL STATION, MOUNT 6"AFFF STATE AND AUXION CONTOLE CONTOL TOTAL STATIC REVOLUTION AND ATF AFF STATE AND AUXION CONTOLE CONTOL TOTAL STATIC REVOLUTION AUXIONAL AND ATF AFF STATE ALARM AUUL STATION, MOUNT 6"AFFF STATE ANA AUXIONAL STATE PRODUCTION AND ATF AFF STATE ANA AUXIONAL STATE PRODUCTION AND AFF AFF STATE ANA AUXIONAL STATE PRODUCTION AND AFF AFF STATE ANA AUXIONAL STATE AND AUXIONAL ATF AFF AUXIONAL AUXIONAL AND AUXIONAL AUXI	S₅ D₀ D D₄D₃	BURNER SAFETY SWITCH, PROVIDE WITH RED PLATE, MOUNTED 72" AFF SINGLE POLE DIMMER SWITCH, 120V, 20A, SPEC GRADE, GROUNDING TYPE, MOUNT 48" AFF, 3=3-WAY, 4=4-WAY, LOWER CASE LETTER INDICATES FIXTURE OR CONTROLLED LOAD.
 THECLOCK TELEPHONE/DATA DUAL JACK, MOUNT 18"AFF, RUN TWO CAT SE CABLES BACK TO TBB DIATA JACK, RUN TWO CAT SE CARLES BACK TO TBB. FLEMEN FLOOR MOUNTED TELEPHONE/DATA DUAL JACK, RUN TWO CAT SE CABLES BACK TO TBB. "CLORENCES CELEME MOUNTED OTHERWISE, RUN ONE CAT SE CABLES BACK TO TBB." TELEPHONE JACK BOARD TELEPHONE JACK BOARD MATERCOM PAREL AL RECETION THERCOM PAREL AL RECETION THERCOM PAREL AL RECETION THERCOM PAREL AL RECETION THE COMPAREL AL RECETION ALL AL MARKED AND THE COMPAREMENT ON THE RECETION THE COMPAREL AND THE PAREL P		LIGHTING CONTACTOR
C. C. FLUSH IT DOE MUNITED TELEPROPERATURATION UNITE OF CR. RUN TWO CAT SE CABLES FELEPHONE ALX, MOUNT 18"-YFF UNLESS NOTED OTHERWISE, RUN ONE CAT SE CABLE DECEMBER ALX MOUNT 18"-YFF UNLESS NOTED OTHERWISE, RUN ONE CAT SE CABLE FELEPHONE BACK BOARD WY ROUTES VALL MOUNT DAT 72" AFF INTERCOM PAREL AT RECEPTION EXEMPTION FOR ALX AND CONTROL AT 72" AFF INTERCOM PAREL AT RECEPTION EXEMPTION FOR ALX AND MOUNT DAT 72" AFF INTERCOM PAREL AT RECEPTION EXEMPTION FOR ALX AND MOUNT PAREL FELEPHONE BACK MOUNT DAT 72" AFF INTERCOM PAREL AT RECEPTION EXEMPTION FOR AN ADDROVEMENT OF MALL FELEPHONE BACK MOUNT DAT 72" AFF INTERCOM PAREL AT RECEPTION EXEMPTION FOR AN ADDROVEMENT OF MALL FELEPHONE BACK MOUNT DAT 72" AFF INTERCOM PAREL AT RECEPTION EXEMPTION FOR AN ADDROVEMENT OF MALL FELEPHONE BACK MOUNT DAT 72" AFF INTERCOM PAREL AT RECEPTION EXEMPTION FOR AN ADDROVEMENT OF MALL FELEPHONE BACK MOUNT DAT 72" AFF INTERCOM PAREL FELEPHONE BACK BIEL INTERNAL FELEPHONE BACK BORD AT THE ADDROVE BACK BORD AND ADDROVE BACK FELEPHONE BACK BIELS INFORME OF CONTROL DAT 10" AFF AFF MANDER BACK FELEPHONE BACK BUTCE OF AN ADDROVE BETECTOR FELEPHONE BACK BUTCE OF AFF INTEN FELEPHONE BACK BUTCH AT AFF AFF INTERCOM PAREL FELEPHONE BACK BUTCH AFF AFF AFF AFF AFF AFF AFF AFF AFF AF	TC ▼ ▽	TIMECLOCK TELEPHONE/DATA DUAL JACK, MOUNT 18"AFF, RUN TWO CAT 5E CABLES BACK TO TBB DATA JACK, RUN TWO CAT 5E CABLES BACK TO TBB
 TELEPANGE LAKE, MOUNT INFAFF UNLESS NOTED OTHERWISS, RUN ONE CAT SE CAGLE MACK TO THE OR IT ROOM. MOUNT ABOVE CELING, WETROUTER, OLE CAT, SE CARLE BACK TO THE OR IT ROOM. MOUNT ABOVE CELING, INTERCOM PANEL AT RECEPTION FRE ALAM CONTROL PAREL FRE ALAM CONTROL PAREL FRE EXTINCUISES ALL COUNTERS AT 200 BATT TO THE OTHER OTHER OF THE CARD STATE TO THE ACCOUNT AND STATE TO THE OTHER OF THE CELING. FRE EXTINCUISES ALL COUNTERS AT 200 BATT TO THE OTHER OTHER OF THE CELING. FRE EXTINCUISES CELL COUNTERS AND STATE TO THE OTHER OTHER OF THE CELING. FRE EXTINCUISES CELL COUNTERS CELING MOUNTE OF THE THE OTHER OF THE CELING. FRE ALAM ANUNCIATOR PANEL FRE ALAM CONSCIED TO THE SECOND CELING. FRE ALAM CONSCIED TO THE SECOND CELING. FRE ALAM ANUNCIATOR MOUNT OF THE THE THE THE THE THE THE THE THE THE	CL 🐨	FLUSH FLOOR MOUNTED TELEPHONE/DATA DUAL JACK, RUN TWO CAT 5E CABLES BACK TO TBB. "CL" DENOTES CEILING MOUNTED
 WILL DUTTING OCC CALL SC CABLE BACK TO TBB OR IT ROOM. MOUNT ABOVE CELING, WI DENOTES WALL MOUNTED A 722" AFF INTERCOM PANEL AT RECEPTION FIRE ALARM CONTROL PANEL FIRE ALARM ANNUALTOR PANEL FIRE ALARM ANNUALTOR PANEL FIRE ALARM ANDERSKELE LECTRON WONTOR-SHALL BE ACCOMPLISHED THROUGH USE OF A ADDRESSAUE UNITERFACE DEVICE AND SHALL BE ACCOMPLISHED THROUGH USE FIRE ALARM ANDERSKELE CENTRON WONTOR-SHALL BE ACCOMPLISHED THROUGH USE FIRE ALARM ANNUAL STREPE ONLY FLUSH MOUNTED. NO DESIGNATION EDUX 5 15:00 FIRE ALARM VISUAL STROPE ONLY FLUSH MOUNTED. NO DESIGNATION EDUX 5 15:00 FIRE ALARM YOULS STROPE ONLY FLUSH MOUNTED. NO DESIGNATION EDUX 5 15:00 STREPE MANAGENY OCTOBOLISTIC TUPE, SYSTEM CONNECTED. SYSTEM CONNECTED FIRED TEMPERATURE HEAT DETECTOR STREPE DETECTOR, PHOTOELECTIC TYPE, SYSTEM CONNECTED. SYSTEM CONNECTED FIRED TEMPERATURE HEAT DETECTOR STREPE DETECTOR, PHOTOELECTIC TYPE, SYSTEM CONNECTED. SYSTEM CONNECTED SMOKE DETECTOR, PHOTOELECTRC TYPE, WITH SOUNDER BASE CARBON MONXORE DETECTOR, NOTION FALLED BY MECHANISM. CONTRACTOR. LARM DUCT SMOKE DETECTOR, ADDRESSAUE MOOILES AND PROGRAMMICE. SYSTEM CONNECTED SMOKE DETECTOR, ADDRESSAUE MOOILES AND PROGRAMMICE. SYSTEM CONNECTED SWITCH] SMPHNEL BY DECAMPERING. CONTRACTOR. LARM DUCT SWITCH FLOW SWITCH] SMPHNEL ME CONTRACTOR. STREME SYSTEM FLOW SWITCH] SMPHNEL BY DECAMPERING. CONTRACTOR. STREME SYSTEM FLOW SWITCH] SMPHNEL BY DECAMPERING. CONTRACTOR. STREME CALL MANUNCATOR UCHT WILE DUNCTES EXISTING ELECTRICAL EDUPMENT TO BE RELACED RM DENOTES EXISTING ELECTRICAL EDUPMENT TO BE RELACED RM DENOTES EXISTING ELECTRICAL EDUPMENT TO BE RELACED RM DENOTES EXISTING ELECTRICAL EDUPMENT TO BE RELACATED RV DENOTES EXISTING ELECTRICAL EDUPMENT TO BE RELACED RV DENOTES EXISTING ELECTRICAL EDUPMENT TO BE RELACED RV DENOTES EXISTING ELECTRICAL EDUPMENT TO BE RELACED RV DENOTES EXISTING ELECTRICAL EDUPMENT TO BE RELACATED RV DENOTES EXISTING	▼	TELEPHONE JACK, MOUNT 18"AFF UNLESS NOTED OTHERWISE, RUN ONE CAT 5E CABLE BACK TO TBB. TELEPHONE BACK BOARD
 INTERCOM PANEL IN UNIT INTERCOM PANEL AT RECEPTION INTERCOM PANEL AT REFACE DEVELON AND SHALL BE ACCOMPLIAND TO THE PARE INTERCOM PANEL AT MODIVISION, WOMTOR SHALL BE ACCOMPLIAND TO THE PARE INTERCOM PANEL AT MODIVISION, WOMTOR SHALL BE ACCOMPLIAND TO THE PARE INTERCOM PANEL AT MODIVISION, WOMTOR SHALL BE ACCOMPLIAND TO THE PARE INTERCOM PANEL AT MODIVISION, WOMTOR SHALL BE ACCOMPLIAND TO THE PARE INTERCOM PANEL AT MODIVISION OF PARE INTERCOM PANEL AT ATTORN WOMAND PARE INTERCOM PANEL AT ATTORN WOMAND PARE INTERCOMPARIATION OF PARE I	[₩] 《●》	WIFIROUTER, OCE CAT 5E CABLE BACK TO TBB OR IT ROOM. MOUNT ABOVE CEILING, "W" DENOTES WALL MOUNTED AT 72" AFF
HILENOW FARLAR I RELEFICION HILENOW FARLAR LAN RELEFICION HILENOW FARLAR LAN ROUTED PARL FIRE ALARM ANNUNCIATOR PANEL FIRE ALARM PULL STATION, MOUNT F:-B'AFF, MUMBER DENOTES, CAMDEL ARTING, "MH" FIRE ALARM YOULL STATION, MOUNT 48'AFF FIRE ALARM YOULL STATION, MOUNT 48'AFF STSTEM CONNECTED FIXED TEMPERATURE HEAT DETECTOR, STSTEM CONNECTED FIXED TEMPERATURE HEAT DETECTOR, SMOKE DETECTOR, PHOTOELECTRC TYPE, SYSTEM CONNECTED. SMOKE DETECTOR, PHOTOELECTRC TYPE, SYSTEM CONNECTED. SMOKE DETECTOR, PHOTOELECTRC TYPE, SYSTEM CONNECTED. SMOKE DETECTOR PHOTOELECTRC TYPE, SYSTEM CONNECTED.	P	INTERCOM PANEL IN UNIT
Image: Fire ALARM ANUMCATOR PANEL	FACP	FIRE ALARM CONTROL PANEL
OF AT JADDRESSABLE INTERFACE DEVICE AND SHALL PROVIDE NADI TO "THE PAGE Image: Provide and the automation of the analysis of		FIRE ALARM ANNUNCIATOR PANEL
Benotes Mukhow, "Act" Denotes Colling Mountee Not Designation Equations and the set of the	30	OF AN ADDRESSABLE INTERFACE DEVICE AND SHALL PROVIDE INPUT TO THE FACP
 THE ALARM YOLL STATION, MOUT 45 APT SH FRE ALARM YOLL STATIONS, STROBE ONLY FUSH MOUNTED SHETH CONNECTED SMOKE / CARBON MONORD DETECTOR, PHOTOELECTIC TYPE SKOKE DETECTOR, PHOTOELECTRIC TYPE, SYSTEM CONNECTED. SKOKE DETECTOR, PHOTOELECTRIC TYPE, SYSTEM CONNECTED. SKOKE DETECTOR, PHOTOELECTRIC TYPE, SYSTEM CONNECTED. SYSTEM CONNECTED SMOKE / STATION SYSTEM CONNECTED SMOKE DETECTOR, PHOTOELECTRIC TYPE, WITH SOUNDER BASE CARBON MONOXIDE DETECTOR, PHOTOELECTRIC TYPE, SYSTEM CONNECTED. SYSTEM CONNECTED SMOKE / STATION DUCT SMOKE DETECTOR & ISTS STATION STATION SMOKE DETECTOR & ISTS STATION SPRINKLER SYSTEM FLOW SWITCH SWPENED BY MECHANICAL CONTRACTOR: ALARM DUCT SMOKE DETECTOR, ADDITALLED BY MECHANICAL CONTRACTOR: ALARM DUCT SMOKE DETECTOR, ADDITALED BY MECHANICAL CONTRACTOR: ALARM DUCT SMOKE DETECTOR, ADDITALLED BY MECHANICAL CONTRACTOR: ALARM DUCT SMOKE DETECTOR, ADDITALLED BY MECHANICAL CONTRACTOR: ALARM DUCT SMOKE DETECTOR, ADDITALED BY SPRINKLER CONTRACTOR: ALARM DUCT SMOKE DETECTOR & USITCH SUPPLY LOCATIONS AND PROVIDE ALARM DUCT SMOKE DETECTOR & USITCH SUPPLY LOCATIONS AND PROVIDE ALARM DUCT SMOKE DETECTOR & USITCH SUPPLY DUCTIONS AND PROVIDE ALARM DUCT SMOKE DETECTOR, EQUIPMENT TO BE REPLACED RM DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED 		DENOTES MINIHORN, "CL" DENOTES CEILING MOUNTED. NO DESIGNATION EQUALS 15cd
CHARLEA KINNES: CLE DIVICES CLEARDN MONORIDE PHOTOCLECTRIC TYPE SMOKE DETECTOR, PHOTOELECTRIC TYPE, SYSTEM CONNECTED. SMOKE DETECTOR, PHOTOELECTRIC TYPE, SYSTEM CONNECTED. CHARLEA RANDONZIDE DETECTOR CARBON MONOXIDE DETECTOR DUCT SMOKE DETECTOR & TEST STATION CHARLEA RANDONZIDE DETECTOR, ADDRESSAGE MOULES AND FROGRAMMIC. CHARLEA RANDON HOLD NURSE CALL ANNUNCATOR LIGHT WP DENOTES KEATHERPROOF CONSTRUCTION RF DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REPLACED RM DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE RELOCATED RV DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED CHARLEA RANDONCES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED	15 CL SD	FIRE ALARM FULL STATION, MOUNT 48 AFF FIRE ALARM VISUAL STROBE ONLY, FLUSH MOUNT 6'-8'' AFF, NUMBER DENOTES
US* ● SYSTEM CONNECTED FIXED TEMPERATURE HEAT DETECTOR ● SMOKE DETECTOR, PHOTOELECTRIC TYPE, SYSTEM CONNECTED. ** ● SMOKE DETECTOR, PHOTOELECTRIC TYPE, SYSTEM CONNECTED. ** ● SYSTEM CONNECTED SMOKE DETECTOR, PHOTOELECTRIC TYPE, WITH SOUNDER BASE •• ● CARBON MONOXIDE DETECTOR •• CARBON MONOXIDE DETECTOR •• CARBON MONOXIDE DETECTOR •• SYSTEM CONNECTED SMOKE DETECTOR, SUPPLEO AND INSTALLED BY MECHANCAL CONTRACTOR: ALARM DUCT SMOKE DETECTORS, ADDRESSABLE MODULES AND PROGRAMMING. •• SPRINKLER SYSTEM FLOW SWITCH] SUPPLED BY SPRINKLER CONTRACTORS •• SPRINKLER SYSTEM TAMPER SWITCH] SPRINKLER CONTRACTOR. •• PHOMOSE CALL PULL STATION •• NURSE CALL PULL STATION •• DE	(28)	SYSTEM CONNECTED SMOKE / CARBON MONOXIDE DETECTOR, PHOTOELECTRIC TYPE
SMOKE DETECTOR, PHOTOELECTRIC TYPE, SYSTEM CONNECTED. ************************************	135°⊕D	SYSTEM CONNECTED FIXED TEMPERATURE HEAT DETECTOR
SPENDENCE SYSTEM CONNECTED SMOKE DETECTOR, PHOTOELECTRIC TYPE, WITH SOUNDER BASE G CARBON MONOXORD DETECTOR DUCT SMOKE DETECTOR & TEST STATION G2300 FIRE/SMOKE DAMPER, SUPPLIED AND INSTALLED BY MECHANICAL CONTRACTOR. ELECTRICAL CONTRACTOR TO PROVIDE ALL WIRNO CONNECTIONS AND FIRE ALARM DUCT SMOKE DETECTORS, ADDRESSABLE MODULES AND PROGRAMMING. G SPRINKLER SYSTEM FLOW SWITCH \SPRINKLER CVERTEX/EC CONTRACTOR WIRED BY EC, VERTY LOCATIONS WITH G MAINLER SYSTEM TAMPER SWITCH \SPRINKLER CONTRACTOR. G MAINLER SYSTEM TAMPER SWITCH \SPRINKLER CONTRACTOR MACNETIC DOOR HOLD M NURSE CALL BASE STATION MS NURSE CALL ANNUNCIATOR LIGHT WP DENOTES WEATHERPROOF CONSTRUCTION RP DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REPLACED RM DENOTES EXISTING ELECTRICAL EQUIPMENT TO REMAIN RL DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE RELOCATED RV DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED		SMOKE DETECTOR, PHOTOELECTRIC TYPE, SYSTEM CONNECTED.
 CARBON MONOXIDE DETECTOR DUCT SMOKE DETECTOR & TEST STATION FREXIMACE DEVATTACTOR TO PROVIDE ALL WIRING CONNECTIONS AND THE ALARM DUCT SMOKE DETECTORS, ADDRESSABLE MODULES AND PROREAMMING. SPRINKLER SYSTEM TAMPER SWITCH SUPPLIED BY SPRINKLER CONTRACTOR. MAGNETIC DOOR HOLD NURSE CALL BASE STATION NURSE CALL PULL STATION NURSE STATE CONTROL PULL NURSE STATION NURSE STATION NURSE STATION NURSE STATION NURSE STATIO	SB	SYSTEM CONNECTED SMOKE DETECTOR, PHOTOELECTRIC TYPE, WITH SOUNDER BASE
100011 SMARLE DELECTOR & TEST STATUTO 102000 102000 102000 102000 102000 102000 102000 102000 102000 102000 102000 102000 102000 102000 102000 1020000 1020000 1020000 10200000 102000000000 10200000000000000000000000000000000000	(CO)	CARBON MONOXIDE DETECTOR
ALARM DUCT SMOKE DETECTORS, ADDRESSABLE MODULES AND PROGRAMMING. IP SPRINKLER SYSTEM TAMPER SWITCH SUPPLIED BY SCRUMPT LOCATIONS WITH IP SPRINKLER SYSTEM TAMPER SWITCH SPRINKLER CONTRACTOR. IP MUSSE CALL BASE STATION IP DENOTES WEATHERPROOF CONSTRUCTION RP DENOTES WEATHERPROOF CONSTRUCTION RP DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REPLACED RM DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REPLACED RW DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED	FD/SD	FIRE/SMOKE DAMPER, SUPPLIED AND INSTALLED BY MECHANICAL CONTRACTOR.
↓ WIRED BY EC, VEREFY LOCATIONS WITH ↓ MAGNETIC DOOR HOLD NURSE CALL BASE STATION NURSE CALL PULL STATION NURSE CALL ANUNCIATOR LIGHT WP DENOTES WEATHERPROOF CONSTRUCTION RP DENOTES WEATHERPROOF CONSTRUCTION RP DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REPLACED RM DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE RELOCATED RV DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED Image: Provide and Provid	Ē	ALARM DUCT SMOKE DETECTORS, ADDRESSABLE MODULES AND PROGRAMMING. SPRINKLER SYSTEM FLOW SWITCH SUPPLIED BY SPRINKLER CONTRACTOR
H MAGNETIC DOOR HOLD NURSE CALL BASE STATION IM NURSE CALL PULL STATION IM NURSE CALL ANNUNCIATOR LIGHT WP DENOTES WEATHERPROOF CONSTRUCTION RP DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REPLACED RM DENOTES EXISTING ELECTRICAL EQUIPMENT TO REMAIN RL DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED	φ	SPRINKLER SYSTEM TAMPER SWITCH SPRINKLER CONTRACTOR.
Image: Solution of the second seco	HM N	MAGNETIC DOOR HOLD NURSE CALL BASE STATION
Image: Set and the set of the set o		NURSE CALL PULL STATION
RP DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REPLACED RM DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE RELOCATED RV DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED	₹ N	NURSE CALL ANNUNCIATOR LIGHT WP DENOTES WEATHERPROOF CONSTRUCTION
RM DENOTES EXISTING ELECTRICAL EQUIPMENT TO REMAN RL DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED RV DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED		RP DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REPLACED
		RM DENOTES EXISTING ELECTRICAL EQUIPMENT TO REMAIN RI DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE RELOCATED
		RV DENOTES EXISTING ELECTRICAL EQUIPMENT TO BE REMOVED

DRAWING NO.

FOR PERMITTING

Strengthening a Remarkable City, Building a Community for Life • www.portlandmaine.gov

Jeff Levine, AICP, Director Director of Planning and Urban Development Tammy Munson Director, Inspections Division

Electronic Signature and Fee Payment Confirmation

Notice: Your electronic signature is considered a legal signature per state law.

By digitally signing the attached document(s), you are signifying your understanding this is a legal document and your electronic signature is considered a *legal signature* per Maine state law. You are also signifying your intent on paying your fees by the opportunities below.

I, the undersigned, intend and acknowledge that no permit application can be reviewed until payment of appropriate permit fees are *paid in full* to the Inspections Office, City of Portland Maine by method noted below:

Within 24-48 hours, upon receipt of an e-mailed invoice from Building Inspections, which signifies that my electronic permit application and corresponding paperwork have been received, determined complete, entered by an administrative representative, and assigned a permit number, I then have the following four (4) payment options:

- to provide an on-line electronic check or credit/debit card (we now accept American Express, Discover, VISA, and MasterCard) payment (along with applicable fees beginning July 1, 2014),
- call the Inspections Office at (207) 874-8703 and speak to an administrative representative to provide a credit/debit card payment over the phone,

hand-deliver a payment method to the Inspections Office, Room 315, Portland City Hall,

or deliver a payment method through the U.S. Postal Service, at the following address:

City of Portland Inspections Division 389 Congress Street, Room 315 Portland, Maine 04101

Once my payment has been received, this then starts the review process of my permit. *After all approvals have been met and completed, I will then be issued my permit via e-mail.* No work shall be started until I have received my permit.

Applicant Signature:	Josef Chalat	Digitally signed by Josef Chalat DN: cn=Josef Chalat, o=Azimuth LLC, ou=Architect, email=azimuth@maine.rr.com, c=US Date: 2015.01.09 15:20:09 -05'00'	Date: 1/9/2015

I have provided digital copies and sent them on: Josef Chalat Discussion Chalat Disc

NOTE: All electronic paperwork must be delivered to <u>buildinginspections@portlandmaine.gov</u> or by physical means ie; a thumb drive or CD to the office.

Room 315 - 389 Congress Street- Portland, Maine 04101 (207) 874-8703 - Fax: 874-8716 - TTY: 874-8936

Acknowledgment of Code Compliance Responsibility- Fast Track Project

Josef Chalat, Architect am the owner or duly authorized owner's agent of the property listed below

MEMIC, 261 Commercial Street, Portland Maine 04101

Physical Address

I am seeking a permit for the construction or installation of:

Tenant Improvements at 2nd and 6th Floors

Proposed Project Description

I understand that the permits obtained pursuant to this acknowledgement of code compliance responsibility will be in my name and that I am acting as the general contractor for this project. I accept full responsibility for the work performed.

I am submitting for a permit authorized by the State of Maine Uniform Building and Energy Code (MUBEC), Fuel Board Laws and Rules and all locally adopted codes and standards applying to Plumbing, Electrical, Fire Prevention and Protection in anticipation of having it approved or approved with conditions. I have read the following statement and understand that failure to comply with all conditions once construction is begun may necessitate an immediate work stoppage until such time as compliance with the stipulated conditions is attained. I certify that I have made a diligent inquiry regarding the need for concurrent state or federal permits to engage in the work requested under this building permit, and no such permits are required or I will have obtained the required permits prior to issuance of this permit. I understand that the granting of this permit shall not be construed as satisfying the requirements of other applicable Federal, State or Local laws or regulations, including City of Portland historic preservation requirements, if applicable. I understand and agree that this permit does not authorize the violation of regulations.

In addition, I understand and agree that this building permit does not authorize the violation of the 12 M.R.S. § 12801 et seq. - Endangered Species.

I certify under penalty of perjury and under the laws of the State of Maine the foregoing is true and correct. I further certify that all easements, deed restrictions, or other encumbrances restricting the use of the property are shown on the site plans submitted with this application.

I hereby apply for a permit as a Owner's Agent Owner or Owner's Agent of the below listed property and by so doing will assume

responsibility for compliance with all applicable codes, bylaws, rules and regulations. the General Contractor's

I further understand that it is my responsibility to schedule inspections of the work as required and that the City's inspections will, at that time, check the work for code compliance. The City's inspectors may require modifications to the work completed if it does not meet applicable codes. <u>JC</u> _____ INITIAL HERE

Sign Here: 1- for Way

_{Date:} 1/8/2015

Acknowledgment of Code Compliance Responsibility- Fast Track Project

OFFICE USE ONLY

Permit #_____

CBL#_____

THIS PROJECT IS ELIGIBLE FOR FAST TRACK PERMITTING BECAUSE IT IS IN THE FOLLOWING CATEGORY / CATEGORIES (CHECK ALL THAT APPLY):

One/Two Family Swimming Pools, Spas or Hot Tubs
One/Two Family Decks, Stairs and Porches (attached or detached) First Floor Only
One/Two Family Detached One Story Accessory Structures (garages, sheds, etc.) not to exceed 600sq ft with no habitable space
Home Occupations (excluding day cares)
One/Two Family Renovation/Rehabilitation (within the existing shell)
Attached One /Two Family Garages /Additions/Dormers bearing the seal of a licensed design professional
New <i>Sprinklered</i> One and Two Family Homes (bearing the seal of a licensed design professional stating code compliance) – <i>MUST STILL RECEIVE LEVEL 1 SITE PLAN APPROVAL FROM PLANNING</i>
One/Two Family HVAC (including boilers, furnaces, heating appliances, pellet and wood stoves)
Interior office renovations with no change of use (no expansions; no site work; no load bearing structural changes are eligible)bearing the seal of a licensed design professional stating code compliance
✓ Interior Demolition with no load bearing demolition
Amendments to existing permits
Commercial HVAC systems (with structural and mechanical plans bearing the seal of a licensed design professional stating code compliance)
Commercial HVAC for Boilers/Furnaces/Heating Appliances
Commercial Signs or Awnings
Exterior Propane Tanks
Residential or Commercial Subsurface Waste Water Systems (No Rule Variance Only)
Renewal of Outdoor Dining Areas
Temporary Outdoor Tents and stages under 750 sq ft per tent or stage
Fire Suppression Systems (Both non-water and water based installations)
Fences over 6'-0" in height
Site work only
Retaining walls over 4ft in height with stamped plans (or approval from inspection staff)
I understand that if the property is located in a historic district this application will also be reviewed by Historic Preservation. I further understand that the Building Inspections Division reserves the right to deny a fast track

eligible pr Sign Here:

. - h

Date:_____

General Building Permit Application

If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Address/Location of Construction: 267	1 Commercial Street, Portland	l, ME 04101				
Total Square Footage of Proposed Struct 2nd floor 4991 sf 6th floor 3125 sf (renovatio	n) Josef Chalat					
Tax Assessor's Chart, Block & Lot	Applicant Name: Architect	Telephone:				
Chart# Block# Lot#	Address	(207) 865-9925				
038 F 019	327 Ocean House Road	Email				
	City, State & Zip					
	Cape Elizabeth, Maine 04107	Jon@zachauconstruction.com				
Lessee/Owner Name : MEMIC/Catherine Lamson	Contractor Name: Zachau Construction	Cost Of Work:				
(if different than applicant)	(if different from Applicant)	\$_286,160.00				
261 Commercial Street	1185 LLS Route One	C of O Fee: \$				
City. State & Zip:	City State & Zip:					
Portland Maine	Freeport ME, 04032	Historic Rev \$				
Telephone & E-mail:	Telephone & E-mail:	Total Econo . ¢				
207 791 3304 CatherineLamson@memic.com	207 865 9925	10tal Pees : \$				
Current use (i.e. single family) Business O	ffices	·				
If vacant, what was the previous use? <u>not</u>	previously vacant					
Proposed Specific use: same as previous use	, business offices					
Is property part of a subdivision? <u>no</u> If yes	s, please name					
Tenant Improvement of portions of 2nd floor and 6th floor of building.						
Who should we contact when the permit is ready: Jon Provost, Project Manager						
Address: 1185 U.S. Route One						
City, State & Zip: Freeport ME, 04032						
E-mail Address: Jon@zachauconstruction.com						
Telephone: (207) 807-8980						

Please submit all of the information outlined on the applicable checklist. Failure to do so causes an automatic permit denial.

In order to be sure the City fully understands the full scope of the project, the Planning and Development Department may request additional information prior to the issuance of a permit. For further information or to download copies of this form and other applications visit the Inspections Division on-line at <u>www.portlandmaine.gov</u>, or stop by the Inspections Division office, room 315 City Hall or call 874-8703.

I hereby certify that I am the Owner of record of the named property, or that the owner of record authorizes the proposed work and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature: Josef Chalat	Digitally signed by Josef Chalat DN: cn=Josef Chalat, o=Azimuth LLC, ou=Architect, email=azimuth@mains r.com, c=US Date: 2015.01.09 15:20:52 -05'00'	Date: 1/9/2015	
-------------------------	---	----------------	--

This is not a permit; you may not commence ANY work until the permit is issued.

SPECIFICATIONS

1.01 GENERAL MECHANICAL

- Furnish materials and labor necessary to deliver to the Owner a complete and operable system installed in accordance with the Α. contract documents.
- Submit shop drawings, manufacturers' data and certificates for equipment, materials and finish, and pertinent details for each system where specified in each individual section.
- C. Provide information sufficiently in advance of this work, so that work by the other trades may be coordinated and installed without delays. Furnish and locate sleeves, supports, anchors and necessary access panels.
- Obtain necessary permits and licenses, give notices and comply with laws, ordinances, rules, regulations or orders affecting the D. work, and pay fees and charges in connection therewith.
- Work and materials shall conform to the latest rules and regulations and these rules and regulations hereby are made part of this specification.
- Upon completion of the work and before applying for final payment, furnish a written guarantee, stating that the work complies with the provisions of codes and the local enforcing authorities, and that it will be free from defects of material and workmanship for not less than one (1) year. Guarantee shall further state that the Contractor will, at his own expense, repair or replace any of his material and work which may become defective during the time of guarantee, together with other work damaged as a consequence of such defects.
- Equipment schedules shall serve as the basis of design for the products used, or equal. G.
- 1.02 DUCTWORK AND ACCESSORIES
 - Ductwork shall be galvanized steel conforming to ASTM A527, weight of galvanized coating shall be not less than 1-1/4 ounces total for both sides of one sq.ft. of a sheet. Construction, metal gage, and reinforcements shall conform with SMACNA "Duct Construction Standards" and NFPA 90A for 2" W.G. pressure class. Fittings shall be constructed in accordance with SMACNA Standards and shall be of the types indicated (ONLY). Longitudinal joints shall be Pittsburgh lockseam (ONLY). Button punch snap locks are not acceptable. Joints shall be sealed to SMACNA seal class B with Hardcast Duct Seal 321 water based indoor/outdoor sealant. Α.
 - Volume dampers shall be Ruskin model MD-35 (rectangular) or model MDRS25 (round) with locking guadrant. Β.
 - Acoustical duct liner shall be 1" Type AP Armaflex SA elastomeric unicellular, no fiberglass. C.
- 1.03 INSULATION
 - A. Supply Air Ductwork: 1-1/2" fiberglass ductwrap with FSK.

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL
	DESCRIPTION COMPRESSED AIR PIPING (CA) CONDENSATE DRAIN PIPING (C) COOLING TOWER RETURN PIPING (CTR) COOLING TOWER SUPPLY PIPING (CTS) CHILLED WATER RETURN PIPING (CWR) CHILLED WATER SUPPLY PIPING (CWG) FUEL OIL RETURN PIPING (FOR) FUEL OIL SUPPLY PIPING (FOG) GAS PIPING (G) HOT WATER RETURN PIPING (HWR) HOT WATER SUPPLY PIPING (HWG) REFRIGERANT LIQUID PIPING (HWG) REFRIGERANT GAS PIPING (RG) SANITARY PIPING BELOW FLOOR (SAN) SANITARY PIPING ABOVE FLOOR (SAN) SANITARY VENT PIPING RAINWATER LEADER ABOVE SLAB (RWL) COLD WATER PIPING (HW) RECIRCULATED HOT WATER PIPING (RHW) PIPE CAP DIRECTION OF FLUID FLOW ELBOW UP ELBOW DOWN PIPE TEE UP PIPE TEE DOWN PIPE REDUCER PIPE WITH ANCHOR BUTTERFLY VALVE OS 4 Y GATE VALVE BACKFLOW PREVENTER (BFP)		DESCRIPTION BALL VALVE BALL VALVE BALL VALVE WITH 3/4" HOSE END GATE VALVE PRESSURE REDUCING VALVE FUSIBLE VALVE STRAINER WBLOUDOWN BALL VALVE 2-WAY CONTROL VALVE SOLENOID VALVE 3-WAY CONTROL VALVE 3-WAY CONTROL VALVE (TOP VIEW) 4-WAY CONTROL VALVE (TOP VIEW) 2 BUTTERFLY VALVES WSINGLE ACTUATOR BUTTERFLY VALVES WSINGLE ACTUATOR BUTTERFLY VALVE WACTUATOR TRIPLE-DUTY VALVE UNION PIPE FLANGE PUMP WITH FLANGES BASE MOUNTED PUMP VERTICAL INLINE PUMP VERTICAL INLINE PUMP FLEXIBLE PIPE CONNECTION (FC) PITCH DOWN PETCOCK FLOW METER PRESSURE GAGE WITH GAGE COCK THERMOMETER IN WELL WATER FLOW SWITCH PRESSURE SWITCH OR SENSOR IMMERSION TEMPERATURE SENSOR	SYMBOL TG Q Q Q Q Q Q Q Q Q Q Q Q Q
₽ © S	CHECK VALVE BALANCING VALVE (ADJUSTABLE) AUTOMATIC FLOW CONTROL VALVE RELIEF VALVE (RV)	€7-1 (R (T) (S)	DUCT MOUNTED SMOKE DETECTOR ROOM TEMPERATURE SENSOR THERMOSTAT OR SENSOR ON WALL	APD AS-* ATC

I	DESCRIPTION	ABBREVIATION	DESCRIPTION	ABBREVIATION	DESCRIPTION	ABBREVIATI
	TSTAT OR SENSOR W/ TAMPERPROOF GUARD	B- *	BOILER TAG	EWB	ENTERING WET BULB	LB
	MANUAL AIR VENT	BD-*	BYPASS DAMPER TAG	EWH-*	ELECTRIC WATER HEATER TAG	LD-*
	NOTE TAG (NUMBER)	BFP-*	BACKFLOW PREVENTER TAG	EWT	ENTERING WATER TEMPERATURE	LTHWS/R
	AIR DEVICE TAG (LETTER) WITH CFM	BHP	BRAKE HORSEPOWER	EXG	EXISTING	LRA
	ROOM NUMBER	втин	BRITISH THERMAL UNITS PER HOUR	E×H	EXHAUST	LWCO
	TURNING VANES	CBD	COUNTER BALANCED DAMPER	FC	FLEXIBLE CONNECTION	LWT
	DUCT W/MANUAL DAMPER	CC-*	COOLING COIL TAG	FCO	FLOOR CLEANOUT	MAX
	DUCT W/FLEXIBLE CONNECTION (FC)	CFM	CUBIC FEET PER MINUTE	FD	FIRE DAMPER	МВН
	LAGGED DUCT	CHLR-	CHILLER TAG	FD-*	FLOOR DRAIN TAG	MCA
	DUCT W/ACOUSTIC LINING	СО	CLEANOUT	FLA	FULL LOAD AMPS	MIN
	DUCT W/SQUARE-TO-ROUND TRANSITION	CONV-*	CONVECTOR TAG	FOR	FUEL OIL RETURN	NC
	FLEXIBLE DUCT	CUH-*	CABINET UNIT HEATER TAG	FOS	FUEL OIL SUPPLY	NIC
-	MOTOR OPERATED DAMPER	CP-*	CIRCULATING PUMP TAG	FPHB	FROST PROOF HOSE BIBB	NTS
	AIRFLOW OUT	CT-*	COOLING TOWER TAG	FPM	FEET PER MINUTE	ΟΑ
	AIRFLOW IN	Cv	VALVE COEFFICIENT	FS-*	FLOOR SINK TAG	OBD
	DIAMETER OR FLAT OVAL	CW	COLD WATER	FT	FEET	0.D.
	FIRE DAMPER	CHWS/R	CHILLED WATER SUPPLY AND RETURN	FTR-*	FINTUBE RADIATION TAG	OED
	ROUND OR FLAT OVAL DUCT DOWN	DB	DRY BULB	GA.	GAGE	OFRWL
_	ROUND OR FLAT OVAL DUCT UP	dB RE	DECIBELS RELATIVE TO	GAL	GALLONS	OFWH-*
	SUPPLY DIFFUSER	DC	DOUBLE CHECK	GFWH-*	GAS FIRED WATER HEATER TAG	OFRD
_	RETURN GRILLE	DCA	DOUBLE CHECK ATMOSPHERIC	GPH	GALLONS PER HOUR	OPD
	STEAM TRAP	DEG F	DEGREES FAHRENHEIT	GPM	GALLONS PER MINUTE	P-*
	WATER HAMMER ARRESTOR	DIA	DIAMETER	GUH-*	GAS UNIT HEATER TAG	PENET'N
		DIW	DOWN IN WALL	HC-*	HEATING COIL TAG	PF-*
TION	DESCRIPTION	DN	DOWN	HP	HORSEPOWER	PSIA
		EA	EXHAUST AIR	HRV-*	HEAT RECOVERY VENTILATOR TAG	PSIG
	AUTOMATIC AIR VENT	EAT	ENTERING AIR TEMPERATURE	ΗW	HOT WATER	PVC
	ACCESS DOOR	EDB	ENTERING DRY BULB	HWS/R	HOT WATER SUPPLY AND RETURN	RA
	ABOVE FINISHED FLOOR	EDC-*	ELECTRIC DUCT COIL TAG	I=B=R	INSTITUTE OF BOILER AND	RD
	AIR HANDLING UNIT TAG	EER	ENERGY EFFICIENCY RATIO		RADIATOR MANUFACTURERS	RDE
	AIRFLOW MONITORING STATION	EF-*	EXHAUST FAN TAG	IFWH-*	INDIRECT FIRED WATER HEATER TAG	RFM-
	AMPERES	EFF	EFFICIENCY	IN.	INCHES	RG-*
	ACCESS PANEL	EG-*	EXHAUST GRILLE TAG	I∨- *	INTAKE VENT TAG	RHW
	AIR PRESSURE DROP	ER-*	EXHAUST REGISTER TAG	I.W.	INDIRECT WASTE (AIR GAP)	RLA
	AIR SEPARATOR TAG	ESP	EXTERNAL STATIC PRESSURE	L-*	LOUVER TAG	RPM
	AUTOMATIC TEMPERATURE CONTROL	ET-*	EXPANSION TANK TAG	LAT	LEAVING AIR TEMPERATURE	RP9