Hammo
Swas
Quote Number:
Architectural Projec

Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 11/28/16

UNIT SUMMARY

The following is a schedule of the windows and doors for this project. For additional unit details, please see Line Item Quotes.
Additional charges, tax or Terms and Conditions may apply. Detail pricing is per unit.

NUMBER OF LINES: 4	TOTAL UNIT QTY: 6

LINE	MARK UNIT	BRAND	ITEM		QTY	
1	Unit 1, Unit 2	Marvin	Wood Ultimate Double Hung		2	
2	Unit 3	Marvin	Wood Ultimate Double Hung		1	
3	Unit 4, Unit 6	Marvin	Wood Ultimate Double Hung		2	
4	Unit 5	Marvin	Wood Ultimate Double Hung		1	

OLD

Hammo
Swas
Quote Number:
Architectural Projec

Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 11/28/16

LINE ITEM QUOTES

The following is a schedule of the windows and doors for this project. For additional unit details, please see Line Item Quotes. Additional charges, tax or Terms and Conditions may apply. Detail pricing is per unit.

Line #1 Qty: 2	Mark Unit: Unit 1, Unit 2			

As Viewed From The Exterior

Egress Information
Width: 31 13/16" Height: 26 49/64"
Net Clear Opening: 5.91 SqFt
Performance Information
U-Factor: 0.29
Solar Heat Gain Coefficient: 0.43
Visible Light Transmittance: 0.49
Condensation Resistance: 56
CPD Number: MAR-N-68-03405-00001
ENERGY STAR: N
Performance Grade
Licensee #739
AAMA/WDMA/CSA/101/ I.S.2/A440-08
LC-PG40 899X2059 mm (35.38X81.06 in)
LC-PG40 DP +40/-40
FL15162

Primed Pine Exterior
Bare Pine Interior
Back Prime
Wood Ultimate Double Hung
Glass Add For All Sash/Panels
Top Sash
Primed Pine Sash Exterior
Bare Pine Sash Interior
IG
Low E1 w/Argon
Black Perimeter and Spacer Bar
7/8" SDL - With Spacer Bar - Black
Rectangular - Special Cut 3W2H
Primed Pine Ext - Bare Pine Int
Putty Exterior Glazing Profile
Ovolo Interior Glazing Profile
Bottom Sash
Primed Pine Sash Exterior
Bare Pine Sash Interior
IG
Low E1 w/Argon
Black Perimeter and Spacer Bar
7/8" SDL - With Spacer Bar - Black
Rectangular - Special Cut 3W2H
Primed Pine Ext - Bare Pine Int
Putty Exterior Glazing Profile
Ovolo Interior Glazing Profile
Non Finger-Jointed Blindstop
Oil Rubbed Bronze Sash Lock
1 /Unit Oil Rubbed Bronze Sash Lift
Beige Jamb Hardware
Half Screen
Charcoal Fiberglass Mesh
Stone White Surround
4 9/16" Jambs
#** SHIP TOP CASING LOOSE
Primed Pine 6" 5/4 Flat Casing - Top
Primed Pine 2 1/2" 5/4 Flat Casing - Side
CASING REVEAL ON TOP 1 15/32" & ON SIDES 1 3/4" PER SKETCH
Primed Pine Simulated Thick Subsill
Non Finger-Jointed Subsill
Non Finger-Jointed Sill
No Installation Method
Non system generated Pricing

OLD

Line #2 Qty: 1	Mark Unit: Unit 3			

Primed Pine Exterior
Bare Pine Interior
Back Prime
Wood Ultimate Double Hung
Glass Add For All Sash/Panels
Top Sash
Primed Pine Sash Exterior
Bare Pine Sash Interior
IG

Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 11/28/16

As Viewed From The Exterior

Egress Information
Width: 32 1/16" Height: 26 57/64"
Net Clear Opening: 5.99 SqFt
Performance Information
U-Factor: 0.29
Solar Heat Gain Coefficient: 0.43
Visible Light Transmittance: 0.49
Condensation Resistance: 56
CPD Number: MAR-N-68-03405-00001
ENERGY STAR: N
Performance Grade
Licensee #1109
AAMA/WDMA/CSA/101/ I.S.2/A440-08
LC-PG40 1051X2464 mm (41.38X97 in)
LC-PG40 DP +40/-40
FL15206

Low E1 w/Argon
Black Perimeter and Spacer Bar
7/8" SDL - With Spacer Bar - Black
Rectangular - Special Cut 3W2H
Primed Pine Ext - Bare Pine Int
Putty Exterior Glazing Profile
Ovolo Interior Glazing Profile
Bottom Sash
Primed Pine Sash Exterior
Bare Pine Sash Interior
IG
Low E1 w/Argon
Black Perimeter and Spacer Bar
7/8" SDL - With Spacer Bar - Black
Rectangular - Special Cut 3W2H
Primed Pine Ext - Bare Pine Int
Putty Exterior Glazing Profile
Ovolo Interior Glazing Profile
Non Finger-Jointed Blindstop
Oil Rubbed Bronze Sash Lock
1 /Unit Oil Rubbed Bronze Sash Lift
Beige Jamb Hardware
Half Screen
Charcoal Fiberglass Mesh
Stone White Surround
4 9/16" Jambs
#** SHIP TOP CASING LOOSE
Primed Pine 6" 5/4 Flat Casing - Top
Primed Pine 2 1/2" 5/4 Flat Casing - Side
CASING REVEALL ON TOP 1 15/32" & ON SIDES 1 3/4" PER SKETCH
Primed Pine Simulated Thick Subsill
Non Finger-Jointed Subsill
Non Finger-Jointed Sill
No Installation Method
Non system generated Pricing

OLD

Line #3 Qty: 2	Mark Unit: Unit 4, Unit 6			

MARVIN Windows and Doors
Built around you.

As Viewed From The Exterior

Egress Information
Width: 32 1/16" Height: 28 41/64"
Net Clear Opening: 6.38 SqFt
Performance Information
U-Factor: 0.29
Solar Heat Gain Coefficient: 0.43
Visible Light Transmittance: 0.49
Condensation Resistance: 56
CPD Number: MAR-N-68-03405-00001

Primed Pine Exterior
Bare Pine Interior
Back Prime
Wood Ultimate Double Hung
Glass Add For All Sash/Panels
Top Sash
Primed Pine Sash Exterior
Bare Pine Sash Interior
IG
Low E1 w/Argon
Black Perimeter and Spacer Bar
7/8" SDL - With Spacer Bar - Black
Rectangular - Special Cut 3W2H
Primed Pine Ext - Bare Pine Int
Putty Exterior Glazing Profile
Ovolo Interior Glazing Profile
Bottom Sash
Primed Pine Sash Exterior
Bare Pine Sash Interior
IG
Low E1 w/Argon
Black Perimeter and Spacer Bar
7/8" SDL - With Spacer Bar - Black
Rectangular - Special Cut 3W2H
Primed Pine Ext - Bare Pine Int
Putty Exterior Glazing Profile
Ovolo Interior Glazing Profile
Non Finger-Jointed Blindstop
Oil Rubbed Bronze Sash Lock

Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 11/28/16

ENERGY STAR: N
Performance Grade
Licensee #1109
AAMA/WDMA/CSA/101/ I.S.2/A440-08
LC-PG40 1051X2464 mm (41.38X97 in)
LC-PG40 DP +40/-40
FL15206

1 /Unit Oil Rubbed Bronze Sash Lift
Beige Jamb Hardware
Half Screen
Charcoal Fiberglass Mesh
Stone White Surround
4 9/16" Jambs
Primed Pine 2 1/2" 5/4 Flat Casing
CASING REVEAL ON TOP 1 15/32" & ON SIDES 1 3/4" PER SKETCH
Primed Pine Simulated Thick Subsill
Non Finger-Jointed Subsill
Non Finger-Jointed Sill
No Installation Method
Non system generated Pricing

Line #4 Qty: 1	Mark Unit: Unit 5			

MARVIN Windows and Doors
Built around you.

As Viewed From The Exterior

Egress Information
Width: 32 1/16" Height: 28 37/64"
Net Clear Opening: 6.36 SqFt
Performance Information
U-Factor: 0.29
Solar Heat Gain Coefficient: 0.43
Visible Light Transmittance: 0.49
Condensation Resistance: 56
CPD Number: MAR-N-68-03405-00001
ENERGY STAR: N
Performance Grade
Licensee #1109
AAMA/WDMA/CSA/101/ I.S.2/A440-08
LC-PG40 1051X2464 mm (41.38X97 in)
LC-PG40 DP +40/-40
FL15206

Primed Pine Exterior
Bare Pine Interior
Back Prime
Wood Ultimate Double Hung
Glass Add For All Sash/Panels
Top Sash
Primed Pine Sash Exterior
Bare Pine Sash Interior
IG
Low E1 w/Argon
Black Perimeter and Spacer Bar
7/8" SDL - With Spacer Bar - Black
Rectangular - Special Cut 3W2H
Primed Pine Ext - Bare Pine Int
Putty Exterior Glazing Profile
Ovolo Interior Glazing Profile
Bottom Sash
Primed Pine Sash Exterior
Bare Pine Sash Interior
IG
Low E1 w/Argon
Black Perimeter and Spacer Bar
7/8" SDL - With Spacer Bar - Black
Rectangular - Special Cut 3W2H
Primed Pine Ext - Bare Pine Int
Putty Exterior Glazing Profile
Ovolo Interior Glazing Profile
Non Finger-Jointed Blindstop
Oil Rubbed Bronze Sash Lock
1 /Unit Oil Rubbed Bronze Sash Lift
Beige Jamb Hardware
Half Screen
Charcoal Fiberglass Mesh
Stone White Surround
4 9/16" Jambs
Primed Pine 2 1/2" 5/4 Flat Casing
CASING REVEAL ON TOP 1 15/32" & ON SIDES 1 3/4" PER SKETCH
Primed Pine Simulated Thick Subsill
Non Finger-Jointed Subsill
Non Finger-Jointed Sill
No Installation Method
Non system generated Pricing

OLD

Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 11/28/16

Product and Performance Information

NFRC energy ratings and values may vary depending on the exact configuration of glass thickness used on the unit. This data may change over time due to ongoing product changes or updated test results or requirements.

The National Fenestration Rating Council (NFRC) has developed and operates a uniform national rating system for the energy performance of fenestration products, including windows and doors. For additional information regarding this rating system, see www.nfrc.org/WindowRatings.

NFRC energy values and ratings may change over time due to ongoing product changes, updated test results or requirements.

OLD