Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 01/17/18

Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 07/22/15

Mini-Horns

The SpectrAlert® Advance series of mini-horn sounders are designed to simplify installations to provide primary and secondary signaling for fire and security applications.

Features

- 12 and 24V operation
- High and low volume settings
- Temporal and non-temporal tones
- Mounts to single gang back box
- Compatible with MDL sync module
- Mechanically and electrically compatible with PA400 series Mini-Alert™ sounders

The MHR and MHW mini-horns operate at 12 and 24 volts and are ideal for hotel, motel or residential fire system applications, where a smaller notification device is desired. The mini-horns offer high and low volume settings, and temporal or non-temporal tones. The horns can be mounted to single gang back boxes for aesthetically sensitive applications. Synchronization is also provided when using the MDL module.

The MHR and MHW mini-horns can operate between 32 and 120 degrees Fahrenheit from a regulated DC or full-wave rectified, unfiltered power supply. They are listed to Underwriter's Laboratories Standard UL 464 for fire protective signaling systems.

Agency Listings

UL LISTED S4011 | FM APPROVED 3028007 | MEA approved MEA7-07-E | 7135-1653:196

Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 01/17/18

Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 07/22/15

SpectrAlert® Advance Mini-Horn Specifications

Architectural/Engineering Specifications

Mini-horns shall be a System Sensor Model MHR or MHW capable of operating at nominal 12 or 24VDC and shall mount to a deep s horn shall be listed to Underwriter's Laboratories Standard UL464 for fire protective signaling systems. Mini-horns shall operate betw Fahrenheit from a regulated DC, or full-wave rectified, unfiltered power supply. When used with the Sync•Circuit™ Module, 12-volt rat circuit outputs shall operate between nine and 17.5 volts; 24-volt rated notification appliance circuit outputs shall operate between

Physical Specifications

Dimensions	4.6″L × 2.9″W × .45″D
Weight	2.67 oz.
Operating Temperature Range	32°F to 120°F (0°C to 49°C)
Mounting	Surface: deep single-gang back box (2¾″ deep) Flush: Standard 4″ × 4″ back box

Electrical Specifications

Input Terminals	12 to 18 AWG
Nominal Voltage	Regulated 12DC/FWR or regulated 24DC/FWR
Operating Voltage	8–33
Operating Voltage with MDL	9–33

UL Sound Output and Current Draw Data

Sounder Output (dBA)

Switch Setting	Pattern	Output Level	8–17.5VDC	8–17.5VFWR	Nominal 12 VDC	Nominal 12 VFWR	16–33VDC	16–33VFWR
1	Temporal	High	68	67	71	70	78	76
2	Temporal	Low	66	65	69	68	76	75
3	Non-temporal	High	72	71	75	74	80	79
4	Non-temporal	Low	70	69	73	72	78	77

Sounder Current Draw (mA RMS)

			8–17.5Volts		16–33Volts	
Switch Position	**Sound Pattern**	**Volume**	DC	FWR	DC	FWR
1	Temporal	High	12	10	17	15
2	Temporal	Low	10	9	14	13
3	Non-temporal	High	22	17	29	25
4	Non-temporal	Low	17	13	21	19

Ordering Information

Part No.	Description
MHR	Mini-Horn, Red
MHW	Mini-Horn, White

SYSTEM SENSOR®
3825 Ohio Avenue • St. Charles, IL 60174
Phone: 800-SENSOR2 • Fax: 630-377-6495

©2009 System Sensor.
Product specifications subject to change without notice. Visit systemsensor.com for current product information, including the latest version of this data sheet.
A05-0414-001 • 12/09 • #2266