DOOR SCHEDULE

DOOR SCHEDULE ABBREVIATIONS

CLO.	CLOSER	FR	FIRE RATED	HM	HOLLOW METAL	P	DOOR PULL	S.C.	SOLID CORE HARDBOARD	UC	UNDERCUT
DSI	DOOR SILENCERS	FRG	FIRE PROTECTION RATED GLAZING	INS	INSULATED	PS	PASSAGE SET	S.H.	SPRING HINGE	WD	WOOD (SOLID)
D.S.	DOOR SWEEP	HO	HOLD OPEN ARM	K	KICKPLATE (PUSH SIDE)	P.H.	FIRE EXIT PANIC HARDWARE (NOTE 3)	S.J.	SPLIT JAMB (WOOD)	WG	WIRE GLASS
DST	DOOR STOP	HA	HANDICAP ACCESSIBLE	KL	KEY LOCK	P.P.	PUSH PLATE	TEMP	TEMPERED	WS	WEATHERSTRIPPING
EHO	ELECTRO. HOLD OPENER	HC	HOLLOW CORE HARDBOARD	LC	FULL HEIGHT LOCKING CHANNEL	PVS	PRIVACY SET	TL	THUMB LATCH		VIEWER
ES	ELECTRIC STRIKE	HDWE	HARDWARE	MTL.	METAL	S.	STEEL	THK	THICKNESS	VIF	VERIFY IN FIELD
F.J.P.	FINGER JOINTED PRIMED			NO	NUMBER	SPF	SPRUCE, PINE, FIR			VL	VENT LOUVER (Lower)

NOTES:

1. TENANT SELECT; OWNER APPROVE
2. GC VERIFY 6'–8" DOOR HEIGHT/HEADER FOR BASEMENT DOORS

	DOORS											FRAME TYPES					THRESHOLD			
	MARK	ROOM	TYPE	SIZE	THK.	F.R.	HDWE SET	MAT.	GLASS SIZE	GLASS TYPE	REMARKS	TYPE	MAT.	F.R.	DETAILS HEAD	DETAILS JAMB	MAT.	DETAIL SILL	DETAIL HT.	REMARKS
BASEMENT	B.1	STAIR F	O	2'–8" x 6'–8"	–	1 HR	LEVER	STEEL	100 sq. in. Max.	FRG	FR, HA, CLO, K, DSI, DS, DST	FF	STEEL	1 HR	–	–	ALUMINUM	ALUM	–	1 HOUR FIRE RATED, SELF CLOSING AND SMOKE SEALED, W/ F.R. VISION LITE, NON–LOCKING FROM EGRESS SIDE. NOTE 1
	B.2	STAIR B	O	3'–0" x 6'–8"	–	1 HR	LEVER	STEEL	100 sq. in. Max.	FRG	FR, HA, CLO, K, DSI, DS, DST	FF	STEEL	1 HR	–	–			–	1 HOUR FIRE RATED, SELF CLOSING AND SMOKE SEALED, W/ F.R. VISION LITE, NON–LOCKING FROM EGRESS SIDE. GC VERIFY (E)OPENING
	B.3	ELECTRIC	R	3'–0" x 6'–8"	–	1 HR	LEVER	STEEL	–	–	FR, HA, CLO, KL, K, DSI, DS, DST	FF	STEEL	1 HR	–	–	–	–	–	RELOCATED EXISTING 1 1/2 HR STEEL DOOR AND FRAME, SMOKE SEALED (VIF) OWNER CONFIRM.
	B.4	TENANT STORAGE	K	3'–0" x 6'–8"	–	–	LEVER	STEEL	–	–	SH, P, KL	BB	WOOD	–	–	–	–	–	–	TENANT STORAGE ROOM DOOR (OWNER SELECT TYPE & STYLE & HARDWARE–TYP FOR 12)
	B.5	STORAGE	T	3'–0" x 6'–8"	–	–	LEVER	STEEL	–	–	CLO, P, DSI, DS, DST (Verify Existing Door Hardware)	EE	STEEL	–	–	–	–	–	–	EXISTING DOOR, REVERSE DOOR SWING (NON–LOCKING FROM EGRESS SIDE) OWNER OPTION:REMOVE DOOR; 36" WIDE MIN. OPENING
	B.6	ELEVATOR MACHINE	S	3'–0" x 6'–8"	–	1 1/2 HR	LEVER	STEEL	–	–	FR, CLO, KL, DSI, DS, DST	GG	STEEL	1 1/2 HR	–	–	–	–	–	SMOKE SEALED, SELF CLOSING, 1 1/2 HOUR FIRE RATED
	B.7	SPRINKLER	O	3'–0" x 6'–8"	–	1 HR	LEVER	STEEL	–	–	FR, HA, CLO, KL, DSI, DS, DST	FF	STEEL	1 HR	–	–	–	–	–	1 HOUR FIRE RATED, SELF CLOSING AND SMOKE SEALED
	B.8	MECHANICAL	T	3'–0" x 6'–8"	–	–	LEVER	STEEL	–	–	HA, CLO, KL, DS, DST	EE	STEEL	–	–	–	–	–	–	
	B.9	STAIR J	R	3'–0" x 6'–8"	–	1 HR	LEVER	STEEL	–	–	FR, HA, CLO, KL, DS, DST	FF	STEEL	1 HR	–	–	–	–	–	1 HOUR FIRE RATED, SELF CLOSING AND SMOKE SEALED, NON–LOCKING FROM EGRESS SIDE
	B.10	STAIR J	R	3'–0" x 6'–8"	–	1 HR	LEVER	STEEL	–	–	FR, HA, CLO, KL, DS, DST	FF	STEEL	1 HR	–	–	–	–	–	1 HOUR FIRE RATED, SELF CLOSING AND SMOKE SEALED, NON–LOCKING FROM EGRESS SIDE
	B.11	RESTROOM	K	2'–6" x 6'–8"			LEVER	S.C. WOOD	–	–	PVS, P, DST, (VL–Verify w/ MECH Dwgs)	BB	WOOD	–	–	–	–	–	–	VENTILATION LOUVER – GC CONFIRM W/MECH. ENGINEER
	B.12	ELECTRIC	R	3'–0" x 6'–8"		1 HR	LEVER	STEEL	–	–	FR, HA, CLO, KL, K, DSI, DS, DST	FF	STEEL	1 HR	–	–	–	–	–	1 HOUR FIRE RATED, SELF CLOSING AND SMOKE SEALED, NON–LOCKING FROM EGRESS SIDE
	B.13	ELEVATOR PIT	S	3'–0" x 7'–0"(VIF)		1 1/2 HR	KEYED	STEEL	–	–	FR, CLO, KL, P, PP, DSI, DS	GG	STEEL	1 1/2 HR						SMOKE SEALED, 1 1/2 HOUR FIRE RATED. GC VERIFY OPENING SIZE IN FIELD AND HARDWARE REQUIRED. NON–LOCKING FROM EGRESS SIDE
FIRST FLOOR	100.1	EXTERIOR ENTRY	W	3'–6" x 7'–0"	–	–	LEVER	FIBERGLASS	HALF	SAFETY	HA, INSUL, CLO, KL, PP, P, DSI, DS, WS	BB	WOOD	–	–	–	OAK	WOOD	–	EXTERIOR DOOR AND GLASS SIDELITE, GC CONFIRM OPENING IN FIELD, NON–LOCKING FROM EGRESS SIDE
	101.1	EXTERIOR ENTRY	A	3'–0" x 7'–0"	–	–	PANIC CROSS BAR NOTE 3	ALUM	FULL PANEL	SAFETY	HA, INSUL, PH, P, CLO, DSI, DS, DST, WS	AA	ALUM	–	–	–	MARBLE	ALUM	–	EXISTING EXTERIOR ALUMINUM GLASS ENTRY DOORS TO RESTAURANT, GC CONFIRM IN FIELD
	101.2	EXTERIOR ENTRY	A	(E)3'–0" x 7'–0" (NEW 6'–8"?)	–	–	PANIC CROSS BAR NOTE 3	ALUM	FULL PANEL	SAFETY	HA, INSUL, PH, P, CLO, DSI, DS, DST, WS	AA	ALUM	–	–	–	MARBLE	ALUM	1/2" MAX	EXISTING EXTERIOR ALUMINUM GLASS ENTRY DOOR (REPLACE W/ 6'–8" DOOR TO ACCOMODATE FLOOR SLOPE) GC CONFIRM IN FIELD
	101.3	MEN RESTROOM	Y	3'–0" x 7'–0"	–	–	LEVER	WOOD	–	–	HA, CLO, PP, KP, P, DS, DSI, DST	BB	WOOD	–	–	–	–	–	–	NOTE 1
	101.4	WOMEN RESTROOM	Y	3'–0" x 7'–0"	–	–	LEVER	WOOD	–	–	HA, CLO, PP, KP, P, DS, DSI, DST	BB	WOOD	–	–	–	–	–	–	NOTE 1
	102.1	EXTERIOR ENTRY	W	3'–0" x 7'–0"	–	–	LEVER	MAHOG	–	–	HA, INSUL, CLO, P, DS, DSI, DST, WS	BB	WOOD	–	–	–	MARBLE	–	1/2" MAX	REMOVE EXISTING EXTERIOR DOOR, INSTALL NEW MAHOG DOOR. GC CONFIRM IN FIELD
	102.2	EXTERIOR ENTRY	A	3'–0" x 7'–0"	–	–	LEVER	ALUM	FULL	SAFETY	HA, CLO, KL, P, DSI, DST, WS	AA	ALUM	–	–	–	ALUMINUM	ALUM	1/2" MAX	SOUTH ELEVATOR LOBBY ALUMINUM WIDE STILE DOOR, NON–LOCKING FROM EGRESS SIDE (RELOCATED DOOR? 101.2 3'–0" X 7'–0")GC CONFIRM
	102.3	STAIR F	P	3'–0" x 7'–0"	–	1 HR	LEVER	WOOD	100 sq. in. Max.	FRG	HA, PH, CLO, KL, PP, P, DS, DSI, DST	FF	STEEL	–	–	–	–	–	–	1 HOUR FIRE RATED, SELF CLOSING AND SMOKE SEALED–RESTAURANT TENANT SELECTION, OWNER APPROVE
	102.4	EXTERIOR ENTRY	F	3'–0" x 7'–0"	–	–	LEVER	FIBERGLASS	–	–	HA, PH, CLO, INSUL, KL, PP, P, DSI, WS	HH	STEEL	–	–	–	ALUMINUM	ALUM	–	NON–LOCKING FROM EGRESS SIDE, THERMALLY BROKEN METAL FRAME
	102.5	EXTERIOR ENTRY	B	3'–0" x 7'–0"	–	–	LEVER	FIBERGLASS	HALF	SAFETY	HA, CLO, INSUL, KL, PP, P, DSI, WS	HH	STEEL	–	–	–	OAK	WOOD	–	NON–LOCKING FROM EGRESS SIDE, THERMALLY BROKEN METAL FRAME (APARTMENTS EGRESS DOOR)
	104.1	EXTERIOR ENTRY	W	3'–0" x 7'–0"	–	–	LEVER	MAHOG	–	–	HA, CLO, INSUL, KL, P, DSI, WS	BB	WOOD	–	–	–	MARBLE	–	1/2" MAX	REMOVE EXISTING EXTERIOR DOOR, INSTALL NEW MAHOG DOOR. GC CONFIRM IN FIELD
	104.2	STAIR J	Q	2'–8" x 7'–0"	–	1 HR	LEVER	STEEL	–	–	HA, CLO, KL, DS, DSI, DST, WS	FF	STEEL	–	–	–	–	–	–	1 HOUR FIRE RATED, SELF CLOSING AND SMOKE SEALED
	104.3	EXTERIOR ENTRY	F	2'–8" x 7'–0"	–	–	LEVER	FIBERGLASS	–	–	HA, CLO, INSUL, KL, P, DS, DSI, WS	HH	STEEL	–	–	–	–	–	–	SELF CLOSING AND THERMALLY BROKEN METAL FRAME
	108.1	EXTERIOR METAL GATE	X	2'–6' X 9'–6"	–	–					MFGR STANDARD HARDWARE (NON–LOCKING FROM EGRESS SIDE)	–	–	–	–	–	–	–	–	CONTRACTOR VERIFY SIZE AND TYPE WITH OWNER
												–	–	–	–	–	–	–	–	GC REFER TO ELEVATION PROVIDED FROM JEREMY
SECOND FLOOR	200.1	STAIR A ENTRY	G	3'–0" x 6'–8"	–	1 HR	LEVER	WOOD	–	–	HA, FR, CLO, DS, DSI, DST	FF	STEEL	1 HR	–	–			–	LABELED DOOR AND FRAME, SMOKE SEALED, SELF CLOSING, AND EQUIPPED WITH POSITIVE LATCHING MECHANISM (FRAME DD ALSO ACCEPTABLE)
	200.2	STAIR A	G	2'–8" x 6'–8"	–	–	PLUG (E)BORED HOLE	WOOD	–	–	NONE	NONE	–	–	–	–	–	–	–	EXISTING DOOR (OR REHAB) OF HISTORICAL SIGNIFICANCE AND EXISTING CASING. GC CONFIRM AVAILABILITY
	200.3	STAIR A	G	2'–8" x 6'–8"	–	–	PLUG (E)BORED HOLE	WOOD	–	–	NONE	NONE	–	–	–	–	–	–	–	EXISTING DOOR (OR REHAB) OF HISTORICAL SIGNIFICANCE AND EXISTING CASING. GC CONFIRM AVAILABILITY
	200.4	STAIR A	G	2'–8" x 6'–8"	–	–	PLUG (E)BORED HOLE	WOOD	–	–	NONE	NONE	–	–	–	–	–	–	–	EXISTING DOOR (OR REHAB) OF HISTORICAL SIGNIFICANCE AND EXISTING CASING. GC CONFIRM AVAILABILITY
	201.1	APT ENTRY	G	3'–0" x 6'–8"	–	20 MIN.	LEVER	WOOD	–	–	HA, FR, CLO, KL, V, DSI, DS, DST, WS (SPRING HINGES OR CLOSER IS ACCEPTABLE)	CC	WOOD	20 MIN	–	–	MAPLE	HDWD	–	EXISTING DOOR (OR REHAB) OF HISTORICAL SIGNIFICANCE AND EXISTING CASING. GC CONFIRM AVAILABILITY SELF CLOSING, SMOKE SEALED AND EQUIPPED WITH POSITIVE LATCHING MECHANISM
	201.2	APT BATH	G	3'–0" x 6'–8"	–	–	LEVER	WOOD	–	–	HA, PVS DSI, DST	BB	WOOD	–	–	–	–	–	–	
	201.3	EXTERIOR TO DECK	B	3'–0" x 6'–8"	–	–	LEVER	WOOD	–	–	HA, PS, KL, DSI, DST, WS	BB	WOOD	–	–	–	–	–	–	DEADBOLT SECURITY
	202.1	APT ENTRY	G	3'–0" x 6'–8"	–	20 MIN.	LEVER	WOOD	–	–	HA, FR, CLO, KL, V, DSI, DS, DST, WS (SPRING HINGES OR CLOSER IS ACCEPTABLE)	CC	WOOD	20 MIN	–	–	MAPLE	HDWD	–	SELF CLOSING, SMOKE SEALED AND EQUIPPED WITH POSITIVE LATCHING MECHANISM
	202.2	APT BATH	G	3'–0" x 6'–8"	–	–	LEVER	WOOD	–	–	HA, PVS DSI, DST	BB	WOOD	–	–	–	–	–	–	
	202.3	APT CLOSET	L	(2) 2'–6" x 6'–8"	–	–	LEVER	WOOD	–	–	HA, PS DSI, DST	BB	WOOD	–	–	–	–	–	–	
	203.1	APT ENTRY	J	3'–0" x 6'–8"	–	20 MIN.	LEVER	WOOD	–	–	HA, FR, CLO, KL, V, DSI, DS, DST, WS (SPRING HINGES OR CLOSER IS ACCEPTABLE)	CC	WOOD	20 MIN	–	–	MAPLE	HDWD	–	SELF CLOSING, SMOKE SEALED AND EQUIPPED WITH POSITIVE LATCHING MECHANISM
	203.2	APT BATH	J	2'–8" x 6'–8"	–	–	LEVER	WOOD	–	–	HA, PVS DSI, DST	BB	WOOD	–	–	–	–	–	–	
	203.3	BEDROOM	J	2'–8" x 6'–8"	–	–	LEVER	WOOD	–	–	HA, PVS DSI, DST	BB	WOOD	–	–	–	–	–	–	
	203.4	APT CLOSET	L	(2) 2'–0" x 6'–8"	–	–	LEVER	WOOD	–	–	HA, PVS DSI, DST	BB	WOOD	–	–	–	–	–	–	
	203.5	BR CLOSET	J	(2) 2'–8" x 6'–8"	–	–	LEVER	WOOD	–	–	HA, PVS DSI, DST	BB	WOOD	–	–	–	–	–	–	
	204.1	APT ENTRY	J	3'–0" x 6'–8"	–	20 MIN.	LEVER	WOOD	–	–	HA, FR, CLO, KL, V, DSI, DS, DST, WS (SPRING HINGES OR CLOSER IS ACCEPTABLE)	CC	WOOD	20 MIN	–	–	MAPLE	HDWD	–	SELF CLOSING, SMOKE SEALED AND EQUIPPED WITH POSITIVE LATCHING MECHANISM
	204.2	BEDROOM	J	3'–0" x 6'–8"	–	–	LEVER	WOOD	–	–	HA, PVS DSI, DST	BB	WOOD	–	–	–	–	–	–	
	204.3	APT BATH	J	2'–8" x 6'–8"	–	–	LEVER	WOOD	–	–	HA, PVS DSI, DST	BB	WOOD	–	–	–	–	–		
	204.4	LAUNDRY	J	3'–0" x 6'–8"	–	–	LEVER	WOOD	–	–	HA, PS DSI, DST	BB	WOOD	–	–	–	–	–		
	204.5	BR CLOSET	J	2'–6" x 6'–8"	–	–	LEVER	WOOD	–	–	HA, PS DSI, DST	BB	WOOD							
	205.1	CORRIDOR	J	2'–8" x 6'–8"	–	–	PLUG (E)BORED HOLE	WOOD	–	–	NONE	NONE	–	–	–	–	—	—	–	EXISTING DOOR (OR REHAB) OF HISTORICAL SIGNIFICANCE AND EXISTING CASING. GC CONFIRM AVAILABILITY
	205.2	CORRIDOR	J	2'–8" x 6'–8"	–	–	PLUG (E)BORED HOLE	WOOD	–	–	NONE	NONE	–	–	–	–	—	—	–	EXISTING DOOR (OR REHAB) OF HISTORICAL SIGNIFICANCE AND EXISTING CASING. GC CONFIRM AVAILABILITY
	205.3	CORRIDOR	J	2'–8" x 6'–8"	–	–	PLUG (E)BORED HOLE	WOOD	–	–	NONE	NONE	–	–	–	–	—	—	–	EXISTING DOOR (OR REHAB) OF HISTORICAL SIGNIFICANCE AND EXISTING CASING. GC CONFIRM AVAILABILITY
	207.1	STAIR B ENTRY	G	3'–0" x 6'–8"	–	1 HR	LEVER	WOOD	–	–	HA, FR, CLO, DS, DSI, DST	FF	STEEL	1 HR	–	–			–	LABELED DOOR AND FRAME, SMOKE SEALED, SELF CLOSING, AND EQUIPPED WITH POSITIVE LATCHING MECHANISM (FRAME DD ALSO ACCEPTABLE)

REGISTERED ARCHITECT JOHN H. LEASURE No. 310 STATE OF MAINE

REV.	DATE	STATUS
.	3-30-17	STATE FIRE MARSHAL SUBMISSION
1	4-28-17	SUBMITTED FOR PERMITS

JOHN H. LEASURE ARCHITECT, INC.
6 Q STREET
SOUTH PORTLAND, MAINE 04106

SHWARTZ BUILDING RENOVATIONS
600–604 CONGRESS STREET
PORTLAND, MAINE

DOOR SCHEDULE

A25