Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 03/21/16

SIEMENS

Ca
Fire Safety &

FireFinder XLS and FS-250

HTRI Series Interface Modules
Models HTRI-D, HTRI-R and HTRI-S

ARCHITECT AND ENGINEER SPECIFICATIONS

- **Interfacing and supervising normally open (NO) or normally closed (NC) contacts**
- **Integral SPDT relay on Model HTRI-R (up to 4 amps)**
- **Dual input on Model HTRI-D, using a single address**
- **Polarity insensitive with *SureWire*™ technology**
- **Multi-color light-emitting diode (LED) indicates status [green / amber / red]**
- **Easy front access to programming port and wiring terminals**
- **Mounts 4-inch square, 2-¼"-deep box (or double-gang box)**
- **Dynamic supervision**
- **Comes with 5-x-5" faceplate**
- **Two-wire operation**
- **Model DPU programs and verifies address of the device and tests for proper functionality**
- **Electronic address programming is easy and dependable**
- **Ⓤ UL Listed & Ⓤ ULC Listed; FM, CSFM and NYMEA Approved**

Product Overview

The Siemens Industry, Inc. — Fire Safety HTRI Series Intelligent interface modules are designed to provide the means of interfacing direct shorting devices to the FireFinder XLS and FS-250 Fire Alarm Control Panel loop circuit.

The HTRI Series modules provide the most advanced method of address programming and supervision on the market — combined with sophisticated control panel communication. Each HTRI Series interface module incorporates a microcomputer chip. The HTRI Series microcomputer chip technology and its sophisticated bi-directional communication capabilities with the control panel, achieve the state of an 'intelligent device.'

Specifications

The HTRI Series intelligent interface modules are available in three (3) models. Models HTRI-S and HTRI-R are designed to monitor a (NO) or (NC) dry contact.

The interface module reports the status of the (NO) or (NC) contact to the control panel. Model HTRI-S can only monitor and report the status of the contact, while Model HTRI-R incorporates an addressable Form C relay.

The Model HTRI-R relay and contact device input are controlled at the same address. For the control panel system, the relay and input contact can be controlled as a separate function. The relay is typically used where control or shunting of external equipment is required.

The Model HTRI-D is a dual-input module that is designed to supervise and monitor two (2) sets of dry contacts. Model HTRI-D only requires one (1) address, but responds independently to each input. Model HTRI-D is ideal for monitoring a water-flow switch and its respective valve tamper switch.

Model HTRI has a multi-color LED that flashes 'green' when operating in *normal*; 'amber' if unit is in *trouble* condition, and 'red' to indicate a change of state.

SIEMENS Industry, Inc.
Building Technologies Division

Specifications (continued)

Model HTRI-D flashes twice — once for each address, and Model HTRI-R LED indicates a change of state in the relay. The device's microcomputer chip has the capacity of storing, in memory, identification information; as well as important operating-status information.

Siemens Industry, Inc., — Fire Safety innovative technology allows all HTRI Series intelligent interface modules to be programmed by using the Device Programming / Test Unit. Model DPU is a compact, portable and menu-driven accessory that makes programming and testing an interface device faster, easier and more dependable than previous methods.

Model DPU eliminates the need for mechanical addressing mechanisms, such as: program jumpers, DIP switches or rotary dials, since Model DPU electronically sets the HTRI Series interface address into the interface microcomputer-chip non-volatile memory. Vibration, corrosion and other conditions that deteriorate mechanical addressing mechanisms are no longer a cause for concern.

The HTRI Series is fitted with screw terminals for connection to an addressable circuit. The HTRI Series is fully compatible on the same FireFinder XLS and FS-250 circuits with all intelligent H-Series detectors, HMS Series addressable manual stations, or any other addressable intelligent modules, such as Model HZM or Model HCP.

All HTRI Series intelligent interface modules are ®UL listed. Environmental operating conditions for all HTRI Series modules are 32°F (°C) to 120°F (49°C) with a relative humidity of no greater than 93%, non-condensing.

Electrical Ratings

Current Draw
(Active or Standby) 1mA

Model HTRI-R Relay Ratings

Resistive:	4 Amps, 125 VAC 4 Amps, 30 VDC
Inductive:	3.5A, 120 VAC (0.6P.F.) 3.0A, 30 VDC (0.6P.F.) 2.0A, 120 VAC (0.4P.F.) 2.0A, 120 VAC (0.35P.F.) 2.0A, 30 VDC (0.35P.F.)

Mounting Diagram

Models HTRI-S, HTRI-D and HTRI
a 4-inch square, 2 ¼-deep box c
(user supplied). A 5-inch squar
is included with each HTRI Serie

Reviewed for Code Compliance
Inspections Division
Approved with Conditions

Date: 03/21/16

Details for Ordering

Model Number	Part Number	Description	Shipping Wgt. Lb.	Kg.
HTRI-S	500-033370	Single Input	7 oz.	2
HTRI-R	500-033300	Single Input w/Relay	7 oz.	2
HTRI-D	500-033360	Dual Input	7 oz.	2

Notice: This marketing catalog sheet is not intended to be used for system design or installation purposes. For the most up-to-date information, refer to each product's installation instructions.

SIEMENS Industry, Inc.
Building Technologies Division

Fire Safety
8 Fernwood Road
Florham Park, NJ 07932
Tel: (973) 593-2600
FAX: (908) 547-6877
URL: www.SBT.Siemens.com/FIS

Fire Safety
2 Kenview Boulevard
Brampton, Ontario
L6T 5E4 / Canada
Tel: (905) 799-9937
FAX: (905) 799-9858

(SII)
Printed in U.S.A.

June 2010
Supersedes sheet dated 12/04
(Rev. 1)