City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

A REAL PROPERTY OF THE OWNER OWNE

Location of Construction:	Owner: Baster Flace Asco	c l al un	Phone:		Permit No: 980298
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName: ST Pt10, HE 04101		PERMIT ISSUED
Contractor Name:	Address:	Phone: 772-5522			Permit Issued:
Past Use:	Proposed Use:	COST OF WORK:	•	PERMIT FEE: \$ 22.60	APR - 2 1998
Art Suphly	Gallery/Frame Shop	FIRE DEPT.		INSPECTION: Use Group: Type:	Zone: CBL: 040-P-009
Proposed Project Description: EDPREEINSEXE ETECT Signinge 18 Sq Ft		Signature: Signature: PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) Action: Approved Approved with Conditions: Implement Denied Implement Signature: Implement		Zoning Approval: Special Zone or Reviews: Shoreland Wetland Flood Zone Subdivision	
Permit Taken By: Herry Greath	Date Applied For: 27	Site Plan maj Eminor Emm			
 This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. Building permits do not include plumbing, septic or electrical work. Building permits are void if work is not started within six (6) months of the date of issuance. False information may invalidate a building permit and stop all work 					□ Miscellaneous □ Conditional Use □ Interpretation □ Approved □ Denied Historic Preservation □ Not in District or Landmark
A - 1			WITH	REQUIREMENTS	Does Not Require Review Requires Review
I hereby certify that I am the owner of record of the authorized by the owner to make this application a if a permit for work described in the application is areas covered by such permit at any reasonable ho	as his authorized agent and I agree to co issued, I certify that the code official's a	nform to all applicable l authorized representative	aws of the shall have	is jurisdiction. In addition,	Appoved Approved with Conditions Denied Date:
Sugaring .		27 March	3991		
SIGNATURE OF APPLICANT Martha GI	Isart La ADDRESS:	DATE:		PHONE:	
RESPONSIBLE PERSON IN CHARGE OF WORK			PHONE:		
White-Pe	rmit Desk Green-Assessor's Cana	ary-D.P.W. Pink-Publ	ic File I	vory Card-Inspector	1. 6. 6

305 COMMERCIAL ST. mm. BATTER PROPERTY MANAGEMENT JAMESON GALLERY & FRAME 57"H ×45"V EXISTING BRACKET T 17.82 2 36" × 36" 3 57" HIGH, 45" WIDTH, EXISTATE BRACKETT. 4 3 SIGNS ON BULDING FRONT. +- 180 +/- \$50 x2 - (300)

The self of

· ,

ł.

get the state of the state of the

Page 1 Stor





March 26, 1998

City of Portland

To Whom it may concern:

Baxter Property Management on behalf and as agent and manager of Baxter Place located at 305 Commercial Street in Portland, ME hereby grants permission to Jameson Gallery & Frame to install signage on front main hanging bracket in the front of the Baxter Place Building. As long as signage is in compliance with local ordinances.

Please call if you have any questions.

Sincerely,

Karen M. Walker General Manager



Peritine in R

a contract sector of


and FSC 4

*

INCURED TO ...

2 The attention of

1 de



	BUILDING PERMIT REPORT
DATE:	APri/98ADDRESS: 305 Commerical St. (040-F-009)
REASC	ON FOR PERMIT: TO Exect Signage
BUILD	UNGOWNER: BUXTER PLACE ASSOC.
CONTI	RACTOR: Jameson The Signery
PERMI	IT APPLICANT: MArTha FilmarTin
USE GI	4.6 12
	CONDITION(S) OF APPROVAL
This Po	ermit is being issued with the understanding that the following conditions are met:
Approv	ved with the following conditions: ×1, ×29
1	
×1.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
Ζ.	Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
3.	Precaution must be taken to protect concrete from freezing.
4.	It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to
	verify that the proper setbacks are maintained.
5.	Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from
	adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting
	rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior
	spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2 inch gypsum
	board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
6.	All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National
7.	Mechanical Code/1993).
7.	Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
8.	Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking
	surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum
	height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and
	public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a
	diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
	(Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".)
0	Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2".
9. 10.	Headroom in habitable space is a minimum of 7'6". Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum
10.	11" tread. 7" maximum rise.
11.	The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8")
12.	Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or
	exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special
	knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more
	than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear
	opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm),
10	and a minimum net clear opening of 5.7 sq. ft.
13.	Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it
14	exits directly from the apartment to the building exterior with no communications to other apartment units. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self
14.	closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.)
15.	The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing
1 <i>.</i>	automatic extinguishment.
16.	All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the

provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):

- In the immediate vicinity of bedrooms
- In all bedrooms
- In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

- 17 A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- 20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21 Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 22. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 23. Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code.
- 24. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
- 25. All requirements must be met before a final Certificate of Occupancy is issued.
- 26. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
- 27. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993).

Please read and implement the attached Land Use-Zoning report requirements. Defore This sign is pung a structural de Tail must be Submit and approved by This office 28. ★29. 30. 31. 32.

P Samue Hoffses, Gode Enforcement

cc: Lt. McDougall, RFD Marge Schmuckal