

## AIR HANDLER SCHEDULE

TAG	AREA SERVED	NOM. TONS	CFM	CFM O.A.	EXT. S.P.	FAN KW	ELECTRIC			COOLING *			HEATING **			REFRIGERANT			WEIGHT LBS	REMARKS
							POWER	MCA	BTU	KW	BTU	KW	BTU	KW	TYPE	LIQUID	GAS			
AH-101	113 LOBBY	1.50	600	0	0.60"	0.085	208V-60-1P	1.56	18,000	0.110	20,000	0.090	R410A	1/4	1/2	58	DUCTED, 10' HIGH			
AH-201	201, 202, 252, 245 & 246	1.25	440	105	0.60"	0.085	208V-60-1P	1.45	15,000	0.090	17,000	0.070	R410A	1/4	1/2	58	DUCTED, 10' HIGH			
AH-202	228, 229, 230, 231, 232, 233 & 242	2.00	670	128	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-203	223 OFFICE	1.25	380	16	0.20"	0.046	208V-60-1P	0.64	15,000	0.010	17,000	0.050	R410A	1/4	1/2	54	DUCTED, 8' HIGH			
AH-204	224 & 225 OFFICES	1.50	600	30	0.60"	0.085	208V-60-1P	1.56	18,000	0.110	20,000	0.090	R410A	1/4	1/2	58	DUCTED, 10' HIGH			
AH-205	226 OFFICE	1.25	380	16	0.20"	0.046	208V-60-1P	0.64	15,000	0.010	17,000	0.050	R410A	1/4	1/2	54	DUCTED, 8' HIGH			
AH-206	222, 221 & 222 OFFICES	2.00	670	45	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-207	218 & 219 OFFICES	1.00	370	27	0.60"	0.085	208V-60-1P	1.21	12,000	0.090	13,500	0.070	R410A	1/4	1/2	51	DUCTED, 10' HIGH			
AH-208	221, 235 & 236 OFFICES	2.00	670	31	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-209	231 & 236 OFFICES	1.25	380	25	0.20"	0.046	208V-60-1P	0.64	15,000	0.010	17,000	0.050	R410A	1/4	1/2	54	DUCTED, 8' HIGH			
AH-210	234, 240 & 241 OFFICES	2.00	670	31	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-211	216 & 217 OFFICES	1.25	440	30	0.60"	0.085	208V-60-1P	1.45	15,000	0.040	17,000	0.070	R410A	1/4	1/2	58	DUCTED, 10' HIGH			
AH-212	214 CONFERENCE	0.67	300	34	0.60"	0.015	208V-60-1P	1.05	8,000	0.060	9,000	0.040	R410A	1/4	1/2	51	DUCTED, 10' HIGH			
AH-214	211, 212 & 213 OFFICE	2.00	670	42	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-214	248 CONFERENCE	0.67	300	13	0.60"	0.015	208V-60-1P	1.05	8,000	0.060	9,000	0.040	R410A	1/4	1/2	51	DUCTED, 10' HIGH			
AH-215	204, 210, 249, 244, 251 & 251	0.50	300	36	0.60"	0.085	208V-60-1P	1.05	8,000	0.060	9,000	0.040	R410A	1/4	1/2	51	DUCTED, 10' HIGH			
AH-216	203 OFFICE	0.67	300	13	0.60"	0.015	208V-60-1P	1.05	8,000	0.060	9,000	0.040	R410A	1/4	1/2	51	DUCTED, 10' HIGH			
AH-217	207 PRODUCTION	2.00	670	35	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-218	208 TRAINING	2.00	670	85	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-301	322 & 323	2.00	670	103	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-302	301, 306, 307, 308 & 331	1.00	370	104	0.60"	0.085	208V-60-1P	1.21	12,000	0.090	13,500	0.070	R410A	1/4	1/2	51	DUCTED, 10' HIGH			
AH-303	302, 334, 331 & 338	1.25	380	67	0.20"	0.046	208V-60-1P	0.64	15,000	0.010	17,000	0.050	R410A	1/4	1/2	54	DUCTED, 8' HIGH			
AH-304	303 FILES & 304 OFFICE	1.25	380	21	0.20"	0.046	208V-60-1P	0.64	15,000	0.010	17,000	0.050	R410A	1/4	1/2	54	DUCTED, 8' HIGH			
AH-305	385 OFFICE	1.00	370	12	0.20"	0.046	208V-60-1P	0.64	12,000	0.010	13,500	0.050	R410A	1/4	1/2	46	DUCTED, 8' HIGH			
AH-306	304, 310 & 311	2.00	670	37	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-307	312, 313 & 314 OFFICES	2.50	740	45	0.60"	0.012	208V-60-1P	2.50	30,000	0.140	34,000	0.120	R410A	3/8	5/8	71	DUCTED, 10' HIGH			
AH-308	315 OFFICE	1.25	380	17	0.20"	0.046	208V-60-1P	0.64	15,000	0.010	17,000	0.050	R410A	1/4	1/2	54	DUCTED, 8' HIGH			
AH-309	316 & 317 OFFICES	1.50	600	17	0.60"	0.085	208V-60-1P	1.64	18,000	0.110	20,000	0.090	R410A	1/4	1/2	58	DUCTED, 10' HIGH			
AH-310	318 OFFICE	1.25	380	17	0.20"	0.046	208V-60-1P	0.64	15,000	0.010	17,000	0.050	R410A	1/4	1/2	54	DUCTED, 8' HIGH			
AH-311	319, 320 & 321 OFFICES	2.00	670	45	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-312	326, 327 & 328	1.50	600	42	0.60"	0.085	208V-60-1P	1.56	18,000	0.110	20,000	0.090	R410A	1/4	1/2	58	DUCTED, 10' HIGH			
AH-313	324 CONFERENCE	1.25	380	66	0.20"	0.046	208V-60-1P	0.64	15,000	0.010	17,000	0.050	R410A	1/4	1/2	54	DUCTED, 8' HIGH			
AH-314	330, 332 & 333 OFFICES	2.00	670	45	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-315	340 & 348 OFFICES	1.25	440	28	0.60"	0.085	208V-60-1P	1.45	15,000	0.090	17,000	0.070	R410A	1/4	1/2	58	DUCTED, 10' HIGH			
AH-316	382 OFFICE	1.00	370	15	0.20"	0.046	208V-60-1P	0.64	12,000	0.010	13,500	0.050	R410A	1/4	1/2	46	DUCTED, 8' HIGH			
AH-317	384 OPEN OFFICE	2.00	670	51	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-318	341, 342 & 343	1.00	370	51	0.60"	0.085	208V-60-1P	1.21	12,000	0.090	13,500	0.070	R410A	1/4	1/2	51	DUCTED, 10' HIGH			
AH-319	344, 350 & 351 OFFICES	2.00	670	48	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-320	380 & 381 OFFICES	2.00	670	31	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-321	376, 377 & 378	3.00	1060	53	0.60"	0.040	208V-60-1P	3.33	36,000	0.240	40,000	0.220	R410A	3/8	5/8	43	DUCTED, 10' HIGH			
AH-322	354, 356, 376 & 378A	1.25	440	61	0.60"	0.085	208V-60-1P	1.45	15,000	0.090	17,000	0.070	R410A	1/4	1/2	58	DUCTED, 10' HIGH			
AH-323	373, 374 & 375 OFFICES	3.00	940	46	0.60"	0.044	208V-60-1P	3.33	36,000	0.240	40,000	0.220	R410A	3/8	5/8	43	DUCTED, 10' HIGH			
AH-324	351, 362, 371 & 386	1.25	440	41	0.60"	0.085	208V-60-1P	1.45	15,000	0.090	17,000	0.070	R410A	1/4	1/2	58	DUCTED, 10' HIGH			
AH-325	364 & 371	1.00	370	17	0.60"	0.085	208V-60-1P	1.21	12,000	0.090	13,500	0.070	R410A	1/4	1/2	51	DUCTED, 10' HIGH			
AH-326	372 OFFICE	1.00	370	15	0.20"	0.046	208V-60-1P	0.64	12,000	0.010	13,500	0.050	R410A	1/4	1/2	46	DUCTED, 8' HIGH			
AH-327	352, 353 & 358 OFFICES	2.00	670	48	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-328	354, 360 & 361 OFFICES	2.00	670	42	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-329	364, 365 & 366 OFFICES	2.00	670	45	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-330	367 OFFICE	0.67	300	17	0.60"	0.015	208V-60-1P	1.05	8,000	0.060	9,000	0.040	R410A	1/4	1/2	51	DUCTED, 10' HIGH			
AH-331	368 OFFICE	1.00	370	17	0.60"	0.085	208V-60-1P	1.21	12,000	0.090	13,500	0.070	R410A	1/4	1/2	51	DUCTED, 10' HIGH			
AH-332	363 OFFICE	2.50	740	45	0.60"	0.012	208V-60-1P	2.50	30,000	0.140	34,000	0.120	R410A	3/8	5/8	71	DUCTED, 10' HIGH			
AH-401	401, 408 & 407	0.67	300	45	0.60"	0.015	208V-60-1P	1.05	8,000	0.060	9,000	0.040	R410A	1/4	1/2	51	DUCTED, 10' HIGH			
AH-402	422 OPEN OFFICE & 423	2.00	670	116	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-403	403 OFFICE	1.00	370	16	0.60"	0.085	208V-60-1P	1.21	12,000	0.090	13,500	0.070	R410A	1/4	1/2	51	DUCTED, 10' HIGH			
AH-404	404 CONFERENCE	1.25	440	66	0.60"	0.085	208V-60-1P	1.45	15,000	0.090	17,000	0.070	R410A	1/4	1/2	58	DUCTED, 10' HIGH			
AH-405	404, 410 & 411	2.00	670	42	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-406	412, 413 & 414 OFFICES	2.50	740	42	0.60"	0.012	208V-60-1P	2.50	30,000	0.140	34,000	0.120	R410A	3/8	5/8	71	DUCTED, 10' HIGH			
AH-407	415 OFFICE	1.25	380	17	0.20"	0.046	208V-60-1P	0.64	15,000	0.010	17,000	0.050	R410A	1/4	1/2	54	DUCTED, 8' HIGH			
AH-408	416 & 417 OFFICES	1.50	600	30	0.60"	0.085	208V-60-1P	1.64	18,000	0.110	20,000	0.090	R410A	1/4	1/2	58	DUCTED, 10' HIGH			
AH-409	418 OFFICE	1.25	380	17	0.20"	0.046	208V-60-1P	0.64	15,000	0.010	17,000	0.050	R410A	1/4	1/2	54	DUCTED, 8' HIGH			
AH-410	419, 420 & 421 OFFICES	2.00	670	45	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-411	424, 428 & 427	1.50	600	42	0.60"	0.085	208V-60-1P	1.56	18,000	0.110	20,000	0.090	R410A	1/4	1/2	58	DUCTED, 10' HIGH			
AH-412	430, 431 & 432 OFFICES	2.00	670	45	0.60"	0.070	208V-60-1P	2.25	24,000	0.040	27,000	0.050	R410A	3/8	5/8	51	DUCTED, 10' HIGH			
AH-413	433 STOR. & 434 OFFICE	1.00	370																	