

DRAWINGS DEPICT ONLY THE GENERAL EXISTING CONDITION. THE

ALL COAT CLOSETS SHALL HAVE ROD AND SHELF. REFER TO DETAIL DRAWING.

GENERAL CONTRACTOR SHALL COORDINATE THE LOCATION OF REQUIRED FIRE PROOF BLOCKING IN WALLS TO RECEIVE CABINETS, SHELVING, MAJOR ART

CONTRACTOR SHALL FIELD VERIFY EXISTING CONDITIONS AND SHALL NOTIFY

THE ARCHITECT IN WRITING OF ANY DISCREPANCIES AND/OR DAMAGED EXISTING

BASE BUILDING WORK WHICH MAY INTERFERE WITH THE PROPER EXECUTION OF

STRUCTURAL MEMBERS, DUSTWORK, PIPING, AND CONDUIT, THE GYPSUM BOARD

CONTRACTOR SHALL BE RESPONSIBLE FOR EXACT QUANTITY

ALL PLAN DIMENSIONS INDICATED ARE TO FINISHED FACE OF

WHERE CONCEALED WOOD BLOCKING OR FRAMING IS REQUIRED,

CONTRACTOR SHALL USE ONLY FIRE-RETARDANT TREATED WOOD.

WHERE FIRE—RATED AND FULL HEIGHT PARTITIONS ARE PENETRATED BY

SHALL BE SCRIBED TO FIT TIGHT AGAINST THE PENETRATING ITEM AND CAULKED WITH THE APPROPRIATE SEALANT. COORDINATE WITH MECHANICAL

TAKE-OFFS BASED ON FIELD OBSERVATIONS.

WORK, COAT ROD AND SHELVES.

AND ELECTRICAL WORK AND DETAILS.

PARTITION; U.O.N.

NEW TENANT WORK.

INDICATES NEW LOW HEIGHT WALL CONSTRUCTION AT 5'-6" AFF.

- DOOR SWING AND NO.

SEE ELEVATIONS AND DETAILS

WALL TYPE DESIGNATION - (TYPE 1 U.O.N.)

REFER TO DETAILS ON SHEET A-7.2

SEE DOOR SCHEDULE A-9 SERIES

INTERIOR ELEVATION SYMBOLS, e.g.

FIRE EXTINGUISHER CABINET: FULLY RECESSED

THE G.C. SHALL FURR-OUT PARTITIONS AS NEEDED FOR

SEE ELEVATION 1 ON DWG. A-6

HATCH INDICATES MILLWORK SCOPE

DEPTH OF CABINET

- BOXES, PULL STATIONS, EXTINGUISHERS, FIRE HOSE VALVE CABINETS, STROBES, ETC. AND SHALL RELOCATE AS REQUIRED WHERE IN CONFLICT WITH PARTITIONS AND/OR WHERE DEMOLITION OCCURS AND TO ACCOMMODATE NEW LAYOUT. SEE ENGINEERING DOCUMENTS.
- 15. THE G.C. SHALL COORDINATE WITH THE DRYWALL SUB FOR PATCHING OF EXISTING PARTITIONS, SOFFITS, COLUMNS, CORE AND PERIMETER. REPLACE DRYWALL AS NEEDED WHERE OLD WALL COVERING EXISTS, FINISH AS PER
- 16. THE G.C. SHALL COORDINATE WITH DOOR AND GWB SUBS FOR FIT OF NEW FRAMES AT PARTITIONS SO NO GAPS OCCUR. SEE DOOR SCHEDULE FOR FRAME SPECIFICATION FOLLOW ALL MANUFACTURER GUIDLINES FOR
- INSTALLATION AND TOLLERANCE. 17. THE G.C. SHALL PROVIDE IN WALL BLOCKING AS NEEDED PER DETAIL DRAWINGS. ALSO PROVIDE AT SERVER ROOM FIRE RATED 3/4" PLYWOOD ON 2'
- X 4" BLOCKING TO MOUNT FROM 18" AFF TO ABOVE CEILING GRID TO CREATE WIRING CHASE. SEE ENGINEERING DRAWINGS FOR REQUIREMENTS.
- 18. THE G.C. SHALL PROVIDE IN WALL BLOCKING FOR ALL OFFICES WHERE MILLWORK SHELF IS LOCATED. G.C. SHALL ALSO PROVIDE BLOCKING FOR ALL WALLS TO RECEIVE ARTWORK AND PLASMAS.
- 19. THE G.C. SHALL PREP EXISTING DEMISING OFFICE SIDE WALLS TO BE SAME AS

23. PAINT ALL EXPOSED COLUMNS P1 FINISH.

DRAWING NO.